

SPECIFICATIONS PURSUANT TO CT6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Whole Tree Yarding (WTY), Units: 3, 5, 7, 17, 18, 19, 32, and 33.

Within units requiring whole tree yarding, accumulations of slash at the base of residual trees shall be removed and lop and scattered to a depth less than 24 inches in height.

Scatter Slash (SCAT), Units: All

Purchaser shall scatter all limbs cut from Included Timber, which remains in entire unit, so as to avoid concentrations around leave trees and to lie within 36 inches of the ground.

Pile Landing Slash (PL) Units: All

A landing is considered a place where any logs or products are gathered for loading. Slash and other debris resulting from Purchaser's operations that has accumulated on landings that is greater than 1 inch in diameter or greater than 8 feet in length shall be piled for burning by the Forest Service.

Construction of landing piles: Piles shall contain little or no soil. Accumulations of soil that remain after Forest Service Burning will be leveled to normal ground contour. Slash piling operations shall not unnecessarily damage young growth or other trees to be reserved. Slash piles shall be located away from residual trees and young growth to prevent damage during pile burning. All objects which extend more than 4 feet in any direction from the windrow or pile profile will be cut off and returned to the windrow or pile.