

**LEAD BASED PAINT SCRAPING/SANDING SAFETY MEASURES AND WORK DESCRIPTION:**

- 1) LAY PROTECTIVE SHEETING 15 FEET FROM WORK SURFACE. TAPE OR STAPLE THE PROTECTIVE SHEETING TO WOOD SIDING AND CONSTRUCT CURBING ON OUTSIDE OF SHEETING TO KEEP WASTE FROM GETTING ON GROUND
- 2) KEEP WINDOWS AND DOORS CLOSED DURING SANDING AND SCRAPING WORK
- 3) ALWAYS WEAR SAFETY GOGGLES WHEN SCRAPING
- 4) WEAR DISPOSABLE PROTECTIVE CLOTHING COVERS
- 5) WEAR NIOSH-APPROVED RESPIRATOR WHEN WORK CREATES DUST OR PAINT CHIPS
- 6) POST "NO EATING, DRINKING OR SMOKING" WARNING SIGN ON SITE
- 7) CONTRACTOR SHALL CLEAN ALL EXPOSED EXTERIOR SURFACES WITH A DETERGENT (OR LEAD-SPECIFIC CLEANER) AND SCRUB BRUSH TO REMOVE DIRT AND/OR LOOSE PAINT CHIPS PRIOR TO PAINTING
- 8) CONTRACTOR SHALL MATCH PAINT COLOR TO THE MOAB OFFICE
- 9) CONTRACTOR SHALL APPLY SUFFICIENT COATS OF SOFT GLOSS, 100% ACRYLIC EXTERIOR HOUSE PAINT AND EXTERIOR LATEX ACRYLIC PRIMER AS MANUFACTURED BY MOORGLO OR APPROVED EQUAL ON ALL EXPOSED EXTERIOR WOOD SURFACES SUCH THAT THE BUILDINGS WILL HAVE A UNIFORM EVEN COLOR
- 10) STORE ALL WASTE IN A SECURE CONTAINER OR DUMPSTER UNTIL FINAL DISPOSAL. CONTRACTOR IS RESPONSIBLE FOR DISPOSING OF WASTE AT AN EPA APPROVED DISPOSAL SITE.

**NOTE**

CONTRACTOR IS RESPONSIBLE TO VERIFY DIMENSIONS OF BUILDING; NUMBER AND SIZES OF WINDOWS, DOORS, AND APPURTENANCES ON BUILDINGS; LOCATION OF TRIM, WINDOWS AND DOORS; LOCATION AND SIZE OF SURFACE MOUNTED UTILITIES; ETC. PRIOR TO BIDDING THIS CONTRACT.

ALL EXPOSED WOOD SURFACES SHALL BE PAINTED INCLUDING: EXTERIOR SIDING, WINDOW/DOOR TRIM, AND EXPOSED ROOF RAFTERS ETC.

CONTRACTOR SHALL REQUEST WRITTEN APPROVAL PRIOR TO PAINTING FROM THE COR.

U. S. Department of Agriculture  
**FOREST SERVICE**  
 Intermountain Region 4  
 Engineering  
 MANTH-LA SAL NATIONAL FOREST



DESIGN	BY: B. WILDE	DATE
DRAWING	CHECK: C. CHRISTENSEN	
	BY: B. WILDE	
	CHECK: C. CHRISTENSEN	
APPROVED:	DIRECTOR, ENGINEERING	

**MOAB OFFICE PAINTING PROJECT**  
 LEAD BASED PAINT NOTES