

**REGION 6 VIPR PRE-AWARD
 FIRE EQUIPMENT INSPECTION CHECKLIST
 VEHICLE WITH DRIVER**

COMPANY NAME: _____ **DATE:** _____
(On VIPR Agreement)

EQUIPMENT MAKE: _____ **MODEL:** _____

VIN#: _____ **EQUIPMENT/Unit I.D.** _____

EQUIPMENT REQUIREMENTS – VEHICLE W/DRIVER

- Pickup, Type 1 – GVWR ≥ 8,501 lbs., min. 6 ½ ft. bed length 2WD 4WD
- Pickup, Type 2 – GVWR 6,001 to 8,500 lbs., min. 6 ft. bed length 2WD 4WD
- Pickup, Type 3 – GVWR ≤ 6,001 lbs., min. 5 ft. bed length 2WD 4WD
-
- Stakeside, Type 1 – GVWR ≥ 14,001 lbs. dump/tilt box lift gate 2WD 4WD
- Stakeside, Type 2 – GVWR ≥ 10,001 to 14,000 lbs. dump/tilt box lift gate 2WD 4WD
- Sport Utility Vehicle: (min. 5 passenger) 2WD 4WD > 6 passengers
- Passenger Van: 7 to 9 passenger. 2WD 4WD

*NOTE: Passenger or passenger-carrying capacity minimums stated above includes the driver.
 Vans larger than 9 passengers will not be awarded an agreement.*

Minimum Requirements

Yes No

	Minimum Requirements		Yes	No
1	VIN # on Equipment matches VIPR			
2	OF-296 Vehicle/Heavy Equipment Safety Inspection completed			
3	Vehicles with GVWR 10,001 lbs. or greater: Annual DOT inspection or Commercial Vehicle Safety Alliance Inspection (49 CFR 396.23)	(D.2.2)		
4	The full bed of the truck available for incident use	(D.2.1.1)		
5	Vehicles configured to the manufacturers original specifications *lift kits, aftermarket exhaust (i.e., glass packs) and other such modifications that would compromise the integrity of the vehicle are not allowed.	(D.2.1.1)		
6	Tires: Must have load ratings in accordance with the vehicle Gross Vehicle Weight Ratings (GVWR). All tires shall have sound sidewalls, body and tire tread depth of a minimum of 2/32 inch for rear tires and 4/32 inch for steering axle tires.			
7	Spare Tire, wheel wrench, jack	(D.2.1.1)		
8	Fire Extinguisher: 2A 10BC	(D.2.1.1)		
9	STAKESIDES: Flatbed truck with railings that are, at a minimum, the same height of the cab and firmly attached on all 4 sides. The railing on the sides and the rear of the bed must be removable for loading/unloading cargo.	(D.2.1.1)		

