



NOTES:

1. INCISE AND TREAT ALL LUMBER AFTER FABRICATION IN ACCORDANCE WITH AWPA U1 USING PENTACHLOROPHENOL IN HEAVY OIL (TYPE A SOLVENT).
2. TREAT TO USE CATEGORY UC4B.
3. TREATMENT - PRESERVATIVE TREATMENT WILL BE IN ACCORDANCE WITH CURRENT AWPA STANDARDS AND WILL COMPLY WITH THE REQUIREMENTS OF THE CURRENT ADDITION OF WWPIS BEST MANAGEMENT PRACTICES FOR THE USE OF TREATED WOOD IN AQUATIC ENVIRONMENTS.
4. ALL GLU-LAM WILL BE COASTAL DOUG. FIR, COMBINATION 3, 4, OR 5. WET CONDITION USE AND INDUSTRIAL APPEARANCE.

QUANTITY:

CONTRACTOR SHALL SUPPLY THE FOLLOWING CURBS:
 2 CURBS AT 26' OVERALL LENGTH - DRILLED FOR INSTALLATION WITH 4 CURB BLOCKS
 2 CURBS AT 40' LENGTH WITH ONE SPLICE IN THE CENTER - DRILLED FOR INSTALLATION WITH 5 CURB BLOCKS