

TABLE PURSUANT TO C6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

<u>YARDING/SKIDDING REQUIREMENTS</u>	<u>CUTTING UNITS</u>
Except during winching, the leading ends of logs must be suspended above the ground during skidding operations.	All
Equipment shall be restricted to slopes of 35% or less.	All
Ground based skidding equipment is restricted to designated skid trails.	All
Existing skid trails should be used when possible. Skid trails shall not be located down draws, Streamcourses, or swales. Skid trails should be located approximately 120 feet apart.	All
Avoid skidding or forwarding uphill for more than 40 feet on slopes steeper than 35%.	All
No heavy equipment shall be allowed in inclusions of highly erodible soil.	2,12
On coarse textured soils, there shall be no downhill skidding or forwarding on slopes steeper than 35%, or uphill skidding on slopes steeper than 25%, to avoid displacing topsoil from coarse textured soil.	170
Shall be logged over on snow covered or frozen soil or it shall be logged on dry soil and not have biomass removal, except at the time of logging, with the same equipment.	2
Shall not have biomass removal, except at the time of logging, with the same equipment.	14,42,46
Shall not have biomass removal, except at the time of logging, with the same equipment or it shall be logged when dry.	238,240