

TABLE PURSUANT TO CT6.42# - YARDING/SKIDDING REQUIREMENTS (06/2010)

<u>YARDING/SKIDDING REQUIREMENTS</u>	<u>PAYMENT UNITS</u>
Skid trails and skyline corridors will be approved in advance by the Forest Service. Trails will avoid wet areas and dry draw bottoms, except at approved crossings.	All
Tractor skidtrails will be an average of 100 feet apart except where converging.	01, 02, 03, 05, 06, 07, 08, 09, 10, 12, 13, 14, and 99
Ground based equipment is limited to a maximum of 35% sustained slope.	01, 02, 03, 05, 06, 07, 08, 09, 10, 12, 13, 14, and 99
Ground-based skid trails shall be no wider than 12 feet.	01, 02, 03, 05, 06, 07, 08, 09, 10, 12, 13, 14, and 99
Corridor spacing will be a minimum of 150 feet at point of maximum lateral yarding.	04 and 11
Corridor width will be a maximum of 12 feet.	04 and 11
Cable yarding systems will have 75 feet of lateral yarding capability. One-end suspension during inhaul is required, excluding inhaul and yarding within 100 feet of landings.	04 and 11
Full suspension is required over streamcourses and buffers.	04 and 11
One end suspension is required for all yarding methods.	All
Whole tree yarding is required.	All