

TABLE PURSUANT TO CP5.31# - ROAD MAINTENANCE REQUIREMENTS (01/2003)

Contract Road Maintenance Requirements Summary

Road	Termini		Miles	Applicable Prehaul Road Maintenance Specifications								
	From	To		T-836	T-838	T-851	T-854					
46	0.00	3.64	3.64	-	-	D	D					
63	0.00	0.19	0.19	-	-	D	D					
6310	0.00	14.75	14.75	D	-	P	D					
4670	9.74	10.78	1.04	-	D	P	D					

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

Road	Termini		Miles	Applicable During Haul Road Maintenance Specifications								
	From	To		T-813	T-831	T-834	T-836	T-838	T-842	T-851	T-854	T-892
46	0.00	3.64	3.64	-	D	D	-	-	D	P	D	D
63	0.00	0.19	0.19	-	D	D	-	-	D	P	D	D
6310	0.00	14.75	14.75	D	-	-	D	-	-	P	D	-
4670	9.74	10.78	1.04	D	-	-	-	D	-	P	D	-

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

Road	Termini		Miles	Applicable Post Haul Road Maintenance Specifications								
	From	To		T-836	T-838							
46	0.00	3.64	3.64	-	-							
63	0.00	0.19	0.19	-	-							
6310	0.00	14.75	14.75	D	-							
4670	9.74	10.78	1.04	-	D							

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

See Mt. Hood National Forest Road Rules Policy dated 1-01-1992.

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO
CP5.31# - ROAD MAINTENANCE REQUIREMENTS (01/2003)

1	2	3			4	5	6			7	8	9	
Road No. and Termini	Special Project Specifi- cation	Travel Way			Brush And Log Out	Surfacing	Dust Abatement			Seasonal Mainte- nance	Snow Removal	Post Haul	
		Width	X Slope	Comp			Product	Applic Rate	Width			Block	Treat
4600 0.00 - 3.64	T831,T834 T842,T851 T854,T892	-	-	-	8' From Shoulder	-	-	-	-	-		-	-
6300 0.00 - 0.19	T831,T834 T842,T851 T854,T892	-	-	-	8' From Shoulder	-	-	-	-	-		-	-
6310 0.00 - 14.75	T813,T836 T851,T854	-	-	-	4' From Shoulder	-	-	-	-	-		-	-
4670 9.74 - 10.78	T813,T838 T851,T854	-	-	-	4' From Shoulder	-	-	-	-	-		-	-

DT = Removal of Danger Trees as marked in the field by Forest Service.
 * Surfacing - Roads & Landings that require spot rocking shall be approved by the Contracting Officer.
 NOTE: Forest Service approved erosion control devises will be required during road maintenance activities (including Blading, Shaping, Ditch Cleaning, and Slide and Slough Removal) and Landing Construction. These devises may include but are not limited to check dams, silt fencing, straw bales, wattles, staked bio bags, etc.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO
CP5.31# - ROAD MAINTENANCE REQUIREMENTS (01/2003)

Column No.	Heading	Entry	Explanation
	Any	Blank	Except as otherwise described, no entry indicates Purchaser is not authorized or required to perform the work item(s).
	Any	RC	This work requirement applies only when haul of sale related construction materials occurs.
2	Special Project Specification	Number	Entry indicates Special Project Specification which applies.
3	Travel Way	EX	Purchaser shall maintain the traveled way to the width existing upon entry, or at the completion of Specified Road work.
		Numbers	Purchaser shall maintain the traveled way to the standard width indicated by the entry, plus curve widening, in accordance with Section T-811. If required, the road template shall be shaped to this width and to the designated cross slope before haul and during recurring maintenance.
		IS, C, OS, F, or AI	Cross slopes are designated as: IS (Inslope), C (Crown), OS (Outslope), F (Flat), AI (As Is).
		A or B	If compaction is required.
4	Brush and Log Out	Numeric & R and or L	Purchaser shall remove brush for specified width on either or both the right (R) side or left (L) side of road.
		As Staked	Limits of brushing are as staked or marked in the field.
		OPT	Purchaser may use hand or mechanical means of brushing.
		H	Only hand brushing may be used.
		DT	Purchaser shall fall & leave Danger Trees that will reach the road prism at approximately 1.5 times the tree height. Clear all Danger Tree debris from road prism.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO
CP5.31# - ROAD MAINTENANCE REQUIREMENTS (01/2003)

Sale Name: Lowe Creek Bough

Column No.	Heading	Entry	Explanation
5	Surfacing	Aggregate Grading	Purchaser shall place surfacing on roads listed according to the grading indicated. Surfacing Shall be obtained from a Certified Weed-Free commercial source.
		D	Purchaser is to make deposits for listed road maintenance, including surface rock replacement.
6	Dust Abatement	OPT	Product selection is Purchaser's choice from those listed in Section T-812.
		Product Abbr.	Unless otherwise agreed, Purchaser is restricted to product listed corresponding to the abbreviation shown in Section T-812; (i.e., LigS = Lignon Sulfonate) Application rates are estimated amounts.
		EX	Purchaser shall abate dust on the existing width
		Numbers	Purchaser shall abate dust to the width indicated by entry.
7	Seasonal Maintenance	W	Waterbars and/or crossditching shall be required prior to expected seasonal precipitation.
		B	Entrance barriers shall be installed by Purchaser prior to nonuse periods.
8	Snow Removal	TS	Snowplowing authorized for Purchaser's Operations without recreation access being provided per Section T-803 requirements.
		JU	Snowplowing authorized, but must provide for recreation joint use per Section T-803 requirements.
		Blank	Snowplowing is not authorized. Forest Service may authorize plowing by permit when not in conflict with other uses.
9	Post Haul	P	P denotes that work is Purchaser's Responsibility to perform.