

TABLE PURSUANT TO CT6.42# - YARDING/SKIDDING REQUIREMENTS (06/2010)

<p>All logs yarded within designated skyline areas shall have one-end suspended at all times except during lateral inhaul or within 100 feet of the landing.</p>	<p>4A, 5, 41, 48A</p>
<p>Carriage must provide a means for pulling 75 feet of slackline and be able to maintain a fixed position on the skyline during lateral yarding to minimize leave tree damage.</p>	<p>4A, 5, 41, 48A</p>
<p>Skyline corridor locations shall be spaced minimum of 150 feet apart and shall not exceed 10 feet wide.</p>	<p>4A, 5, 41, 48A</p>
<p>Tractor/forwarder trails shall be spaced 60 feet apart except where trails converge or unless approved otherwise by the FS.</p>	<p>All cutting units designated as tractor or forwarder on sale area map.</p>
<p>Skidding tractors/forwarders shall be no more than 12 feet wide, including the blade</p>	<p>All cutting units designated as tractor or forwarder on sale area map.</p>
<p>All logs/trees shall have one end suspended during skidding or forwarding</p>	<p>All cutting units designated as tractor or forwarder on sale area map.</p>
<p>Utilize existing skid trails and landings where practicable.</p>	<p>All cutting units designated as tractor or forwarder on sale area map.</p>
<p>Forwarder required. Equipment must provide full suspension of logs and operation is restricted to approved trail locations.</p>	<p>2, 4, 6, 6A, 7, 7A, 10, 18, 21, 31, 32, 33, 36, 38, 40, 40A, 44, 46 and 46A.</p>
<p>Winchline required on slopes > 35% for trees/logs beyond the reach of the harvester operating on designated and approved trails.</p>	<p>2</p>

