

Sale Name: Bailey Salvage

C2.11# - TIMBER SUBJECT TO AGREEMENT (02/1971)

In addition, there is within Sale Area an unestimated quantity of:

Species	Product
All Species	Non-Saw
DF & Other Coniferous Species	Sawtimber
Ponderosa Pine	Sawtimber

that shall be Included Timber upon written agreement.

C2.3# - RESERVE TREES (04/2004)

Notwithstanding the designations for cutting under B2.31, B2.32, B2.33, or B2.34, live or dead genetic reserve trees or groups of reserve trees within such cutting units or clearings shall be left uncut. Reserve trees are identified by a metal tag and orange paint above stump height and shall be protected in accordance with C6.32#. Units with reserve trees are shown on Sale Area Map.

C2.35# (OPTION 1) - INDIVIDUAL TREE DESIGNATION (06/2008)

All trees meeting the attached designation description which meet the minimum tree diameter stated in A2 are designated for cutting. Additional timber to be cut, if any, will be designated for cutting in accordance with B2.37.

Leave trees, Marked with orange paint, or identified by blue tags are not to be cut, unless designated by the Forest Service.

C3.47# - ABNORMAL DELAY (09/2004)

Unless otherwise agreed, felled timber meeting Utilization Standards shall be removed by Purchaser pursuant to B2.2 and shall be presented for Scaling within the time period indicated in the following removal schedule. The number of days shown are consecutive calendar days.

Failure to remove and present such timber for Scaling within the required time limits will be considered abnormal delay, subject to B3.47.

See attached removal schedule.

DESCRIPTION PURSUANT TO C2.35# (Option 1) - INDIVIDUAL TREE DESIGNATION
(06/2008)

For subdivisions: 1, 2, 4, 5, 6, 9, 10 & 11

Trees that are designated for cutting must meet the utilization standards stated in A2 and shall meet the following requirements.

- a. Standing dead Ponderosa Pine with no visible green needles.
- b. Standing live or dead Douglas-Fir, Western larch, White Fir and other coniferous species.
- c. Leave trees marked with orange paint or identified by blue tags are not to be cut unless designated by the Forest Service.

For subdivisions: 12-30

Trees that are designated for cutting must meet the utilization standards stated in A2 and shall meet the following requirements.

- a. All conifers marked with blue paint are designated for cutting.
- b. Leave trees marked with orange paint or identified by blue tags are not to be cut unless designated by the Forest Service.

Additional timber to be cut, if any will be designated for in accordance with B2.37.

REMOVAL SCHEDULE PURSUANT TO C3.47# - ABNORMAL DELAY (09/2004)

Included Timber

Time Limits

ALL.

30

days after felling has started as to
minimize deterioration and value
loss.

Sale Name: Bailey Salvage

C4.211 - DOWNPAYMENT (06/2007)

The downpayment amount shown in A18 may not be applied toward any other payment required under the provisions of this contract, except damages determined pursuant to B9.4, transferred to other timber sales, or refunded until (a) stumpage value representing 25 percent of the total bid value of the timber sale has been charged and paid for, or (b) the estimated value of the unscaled timber is equal to or less than the amount of the downpayment, or (c) if 36 CFR 223.49(e) is applicable, the estimated value of the unscaled timber is equal to or less than the amount of the downpayment.

If Forest Service makes a determination that this contract should not have been included under increased downpayment requirements (36 CFR 223.49(e)), the downpayment shall be revised and applied in accordance with 36 CFR 223.49(f).

C4.212 - TEMPORARY REDUCTION OF DOWNPAYMENT (08/2009)

Notwithstanding B4.211 or C4.211, upon the Purchaser's written request Forest Service may temporarily reduce the downpayment when Purchaser's scheduled operations are delayed or interrupted for 30 or more consecutive days, or the contract term is extended for 30 or more consecutive days for any of the following reasons:

- (1) Forest Service requests or orders Purchaser to delay or interrupt operations for reasons other than breach;
- (2) Purchaser interrupts or delays scheduled operations to work on a sale designated by the Forest Service as in urgent need of harvesting; or
- (3) An adjustment of the contract term authorized upon a determination of substantial overriding public interest, including a market-related contract term addition, or an urgent removal contract term extension under 36 CFR 223.53.

When Purchaser is not cutting or removing timber under contract during a qualifying period of delay, interruption, or extension listed above the downpayment may be reduced to \$1000 or 2 percent of the downpayment amount stated in the contract, whichever is greater. The Purchaser must restore the downpayment to the full amount stated in the contract within 15 days from receipt of the bill for collection and written notice from the Contracting Officer that the basis for temporarily reducing the downpayment no longer exists. Purchaser shall not cut or remove timber on a contract where the downpayment has been temporarily reduced until the downpayment amount stated in the contract is fully restored.

Sale Name: Bailey Salvage

C4.4 - PAYMENTS NOT RECEIVED (08/2012)

(a) Payments are due and payable on the date of issue indicated on the bill for collection. When a payment for timber cut and other charges is not received at the location designated by Forest Service by the date specified in the bill for collection for, Contracting Officer will suspend all or any part of Purchaser's Operations until payment or acceptable payment guarantee is received. Other charges include, but are not limited to:

- (i) Slash disposal, road maintenance, and contract Scaling deposits;
- (ii) Cooperative work at rates established by specific agreement under B4.218;
- (iii) Damages pursuant to B9.4;
- (iv) Road use fees;
- (v) Restoration of downpayment pursuant to B4.22;
- (vi) Periodic payments pursuant to B4.213;
- (vii) Extension Deposits pursuant to B4.217; and
- (viii) Other mandatory deposits.

(b) Failure to pay amounts due by the date specified in the bill for collection shall be considered a breach under B9.3. The 30-day notice period prescribed therein shall begin to run as of the end of business on the date specified for receipt of payments. If the performance or payment is guaranteed by surety bond, the surety will receive a copy of the written notification of breach. Demand will be made on the surety or other institution providing the guarantee or bond instrument for immediate payment 10 days after issuance of written notification of the breach.

(c) Pursuant to the Debt Collection Improvement Act of 1996, as amended, if payment is not received by Forest Service within 15 days after the date of issue indicated on the bill for collection:

(i) Simple interest shall be assessed at the Current Value of Funds Rate as established by the Secretary of the Treasury. Interest will begin to accrue as of the date of issue indicated on the initial bill for collection.

(ii) Debtors will be assessed administrative charges, in addition to the delinquent amount due. Administrative charges are those additional costs incurred by the Government in processing, handling, and collecting delinquent debts.

(iii) A penalty charge of six (6) percent per annum will be assessed on any portion of a debt delinquent more than 90 days. This penalty charge is in addition to interest and administrative charges under paragraphs (c)(i) and (c)(ii). The penalty charge shall accrue from the date of issue indicated on the bill for collection and shall be assessed on all outstanding amounts, including interest and administrative costs assessed under paragraphs (c)(i) and (c)(ii).

(iv) Payments will be credited on the date received by the Federal Depository or Collection Officer designated on the bill for collection.

(d) Forest Service remedies for Purchaser's failure to make payment for timber cut and other charges when due, except for accrual of interest, suspension of all or any part of Purchaser's Operations, and administrative offset, shall be stayed for so long as:

- (i) A bona fide dispute exists as to Purchaser's obligation to make such payment and
- (ii) Purchaser files and prosecutes a timely Claim.

Sale Name: Bailey Salvage

C5.12# - USE OF ROADS BY PURCHASER (06/1999)

Purchaser's use of existing roads identified on Sale Area Map by the following codes is prohibited or subject to restrictive limitations, unless agreed otherwise:

Code	Use Limitations
X	Hauling prohibited
R	Hauling restricted
U	Unsuitable for hauling prior to completion of agreed reconstruction
P	Use prohibited
A	Public use restriction
W	Regulation waiver

Roads coded A will be signed by the Forest Service to inform the public of use restrictions. Purchaser's use of roads coded R, A, or W shall be in accordance with the following restrictions:

See Restricted Road List Table.

TABLE PURSUANT TO C5.12# - USE OF ROADS BY PURCHASER (06/1999)

Restricted Road List					
Road Number	Road Name	Termini		Map Legend	Description of Restrictions
		From	To		
All Roads				N/A	Restrict commercial timber haul on the following holidays: Memorial Day, 4 th of July, Labor Day and during the weekends of deer rifle hunting season. Restriction applies on the holiday date and/or the week-end from Friday noon through Monday noon.
All Native Surface Roads				N/A	Dry season/frozen haul conditions required on native surface roads to reduce road damage. If road surface is rutted 2 inches or deeper or ditch water is muddy, commercial timber haul will be suspended.
27		Hwy 26	Grant Springs	R	Commercial use is prohibited on weekends from the end of rifle hunting season to April 1. A parking area shall be snowplowed at the junction with Rd. 2700650, as designated on the ground, each time the road is plowed.
2630		Hwy 26	2210	R	Inadequate turnouts and curve widening. Maximum safe capacity in any one day is 50 loaded vehicles having three (3) or more axles. New permits or agreements to use this road as alternative haul routes will be subject to Forest Service approval with number of loads.

Title and Date of Governing Road Rules Document:

Ochoco National Forest
Commercial Road Rules

June 2009

Effective Date

Sale Name: Bailey Salvage

C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Purchaser shall maintain roads in accordance with the following Contract Road Maintenance Requirements Summary:

See Contract Road Maintenance Requirements Summary Table.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO
 C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Road	Termini		Miles	Maint. Level	Applicable Pre-Haul Road Maintenance Specifications										
	From	To			T-803	T-811	T-831	T-832	T-834	T-838	T-839	T-842	T-851	T-854	T-891
2210	FS Bdy	EOU	4.3	3	P	P	P		P			P	P	P	P
2600450	Hwy. 26	2600630	0.7	2	P		P	P	P	P				P	P
2600452	2600450	EOU	0.2	2	P		P	P	P	P				P	P
2600600	Hwy 26	EOU	2.9	1	P	P	P		P			P	P	P	P
2600604	2600600	End	0.4	1	P		P		P		P			P	P
2600607	2600600	End	1.4	1	P		P		P		P			P	P
2600608	2600600	EOU	0.3	1	P		P		P		P			P	P
2600610	2600600	End	1.3	1	P	P	P		P			P	P	P	P
2600622	2600630	End	0.4	1	P		P		P		P			P	P
2600623	2600630	EOU	0.9	1	P		P		P		P			P	P
2600630	2600600	2600450	2.7	1	P		P		P		P			P	P
2600633	2600600	EOU	0.1	1	P		P		P		P			P	P
2600636	2600600	EOU	0.1	1	P		P		P		P			P	P
2600650	Hwy 26	EOU	0.2	2	P		P	P	P	P				P	P
2600700	Hwy 26	End	2.0	2	P		P	P	P	P				P	P
2630	Hwy 26	2630013	0.6	3	P	P	P		P			P	P	P	P
2630013	2630	End	0.9	1	P		P		P		P			P	P
2630016	2630013	End	0.5	1	P		P		P		P			P	P
27	Hwy 26	2730	1.4	5	P		P		P			P	P	P	
2730	27	2730550	0.8	2	P	P	P		P			P	P	P	P
2730550	2730	EOU	1.8	1	P		P		P		P			P	P

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,

OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO
C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Road	Termini		Miles	Maint. Level	Applicable During-Haul Road Maintenance Specifications										
	From	To			T-803	T-811	T-812	T-831	T-832	T-834	T-838	T-839	T-851	T-854	T-891
2210	FS Bdy	EOU	4.3	3	P	p	p	P		P			p	p	P
2600450	Hwy 26	2600630	0.7	2	P		p	P	P	P	P			p	P
2600452	2600450	EOU	0.2	2	P		p	P	P	P	P			p	P
2600600	Hwy 26	EOU	2.9	1	P	p	p	P		P			p	p	P
2600604	2600600	End	0.4	1	P		p	P		P		p		p	P
2600607	2600600	End	1.4	1	P		p	P		P		p		p	P
2600608	2600600	EOU	0.3	1	P		p	P		P		p		p	P
2600610	2600600	End	1.3	1	P	p	p	P		P			p	p	P
2600622	2600630	End	0.4	1	P		p	P		P		p		p	P
2600623	2600630	EOU	0.9	1	P		p	P		P		p		p	P
2600630	2600600	2600450	2.7	1	P		p	P		P		p		p	P
2600633	2600600	EOU	0.1	1	P		p	P		P		p		p	P
2600636	2600600	EOU	0.1	1	P		p	P		P		p		p	P
2600650	Hwy 26	EOU	0.2	2	P		p	P	P	P	P			p	P
2600700	Hwy 26	End	2	2	P		p	P	P	P	P			p	P
2630	Hwy 26	2630013	0.6	3	P	p	p	P		P			p	p	P
2630013	2630	End	0.9	1	P		p	P		P		p		p	P
2630016	2630013	End	0.5	1	P		p	P		P		p		p	P
27	Hwy 26	2730	1.4	5	P			P		P			p	p	
2730	27	2730550	0.8	2	P	p	p	P		P			p	p	P
2730550	2730	EOU	1.8	1	P		p	P		P		p		p	P

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,
OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO
 C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Road	Termini		Miles	Maint. Level	Applicable Post-Haul Road Maintenance Specifications												
	From	To			T-811	T-831	T-834	T-835	T-838	T-839	T-891						
2210	FS Bdy	EOU	4.3	3	p	p	p										
2600450	Hwy 26	2600630	0.7	2		p	p			p							
2600452	2600450	EOU	0.2	2		p	p			p							
2600600	Hwy 26	EOU	2.9	1	p	p	p										
2600604	2600600	End	0.4	1		p	p	p			p	p					
2600607	2600600	End	1.4	1		p	p	p			p	p					
2600608	2600600	EOU	0.3	1		p	p	p			p	p					
2600610	2600600	End	1.3	1	p	p	p										
2600622	2600630	End	0.4	1		p	p	p			p	p					
2600623	2600630	EOU	0.9	1		p	p	p			p	p					
2600630	2600600	2600450	2.7	1		p	p	p			p	p					
2600633	2600600	EOU	0.1	1		p	p	p			p	p					
2600636	2600600	EOU	0.1	1		p	p	p			p	p					
2600650	Hwy 26	EOU	0.2	2		p	p			p							
2600700	Hwy 26	End	2	2		p	p			p							
2630	Hwy 26	2630013	0.6	3	p	p	p										
2630013	2630	End	0.9	1		p	p	p			p	p					
2630016	2630013	End	0.5	1		p	p	p			p	p					
27	Hwy 26	2730	1.4	5		p	p										
2730	27	2730550	0.8	2	p	p	p										
2730550	2730	EOU	1.8	1		p	p	p			p	p					

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO
 C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

1 Road No. and Termini	2 Special Project Specification	3 Travel Way			4 Brushing and Log Out	5 Surfacing	6 Dust Abatement			7 Seasonal Mainte nance	8 Snow Removal	9 Post Haul	
		Width	X Slope	Comp			Application					Block	Treat
							Product	Rate	Width				
2210 FS Bdy to EOU	T-803-01F T-812-01F T-834-01F T-891-01F	EX	AI	A	2' Lt & Rt	SRR Deposit See CT5.32#	OPT		EX		JU		
2600450 Hwy 26 to 2600630	T-803-01F T-812-01F T-832-01F T-834-01F T-891-01F				T-838		OPT		EX	W	TS		PR
2600452 2600450 to EOU	T-803-01F T-812-01F T-832-01F T-834-01F T-891-01F				T-838		OPT		EX	W	TS		PR
2600600 Hwy 26 to EOU	T-803-01F T-812-01F T-834-01F T-891-01F	EX	AI	A	2' Lt & Rt	SRR Deposit See CT5.32#	OPT		EX		JU		
2600604 2600600 to End	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600607 2600600 to End	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600608 2600600 to EOU	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600610 2600600 to End	T-803-01F T-812-01F T-834-01F T-891-01F	EX	AI	A	2' Lt & Rt	SRR Deposit See CT5.32#	OPT		EX		JU		
2600622 2600630 to End	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600623 2600630 to EOU	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600630 2600600 to 2600450	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS		PR

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO
C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

1 Road No. and Termini	2 Special Project Specification	3 Travel Way			4 Brushing and Log Out	5 Surfacing	6 Dust Abatement Application			7 Seasonal Mainte nance	8 Snow Removal	9 Post Haul	
		Width	X Slope	Comp			Product	Rate	Width			Block	Treat
2600633 2600600 to EOU	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600636 2600600 to EOU	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2600650 Hwy 26 to EOU	T-803-01F T-812-01F T-832-01F T-834-01F T-891-01F				T-838		OPT		EX	W	TS		PR
2600700 Hwy 26 to End	T-803-01F T-812-01F T-832-01F T-834-01F T-891-01F				T-838		OPT		EX	W	TS		PR
2630 Hwy 26 to 2630013	T-803-01F T-812-01F T-834-01F T-891-01F	EX	AI	A	2' Lt & Rt	SRR Deposit See CT5.32#	OPT		EX		JU		
2630013 2630 to End	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
2630016 2630013 to End	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS	PR	PR
27 Hwy 26 to 2730	T-803-01F T-812-01F T-834-01F T-891-01F				2' Lt & Rt	Ashpalt Deposit See CT5.32#					JU		
2730 27 to 2730550	T-803-01F T-812-01F T-834-01F T-891-01F	EX	AI	A	2' Lt & Rt	SRR Deposit See CT5.32#	OPT		EX		JU		
2730550 2730 to EOU	T-803-01F T-812-01F T-834-01F T-835-01F T-891-01F				T-839		OPT		EX	W & B	TS		PR

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO
C5.31# - ROAD MAINTENANCE REQUIREMENTS (7/01)

Column No.	Heading	Entry	Explanation
	Any	Blank	Except as otherwise described, no entry indicates Purchaser is not authorized or required to perform the work item(s).
	Any	RC	This work requirement applies only when haul of sale related construction materials occurs.
2	Special Project Specification	Number	Entry indicates Special Project Specification which applies.
3	Travel Way	EX Numbers IS, C, OS, F, or AI A or B	Purchaser shall maintain the traveled way to the width existing upon entry, or at the completion of Specified Road work. Purchaser shall maintain the traveled way to the standard width indicated by the entry, plus curve widening, in accordance with Section T-811. If required, the road template shall be shaped to this width and to the designated cross slope before haul and during recurring maintenance. Cross slopes are designated as: IS (Inslope), C (Crown), OS (Outslope), F (Flat), AI (As Is). If compaction is required.
4	Brush and Log Out	Numeric & R and or L As Staked OPT H	Purchaser shall remove brush for specified width on either or both the right (R) side or left (L) side of road. Limits of brushing are as staked or marked in the field. Purchaser may use hand or mechanical means of brushing. Only hand brushing may be used.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO
C5.31# - ROAD MAINTENANCE REQUIREMENTS (7/01)

Column No.	Heading	Entry	Explanation
5	Surfacing	Aggregate Grading	Purchaser shall place surfacing on roads listed according to the grading indicated.
6	Dust Abatement	OPT	Product selection is Purchaser's choice from those listed in Section T-812.
		Product Abbr.	Unless otherwise agreed, Purchaser is restricted to product listed corresponding to the abbreviation shown in Section T-812; (i.e., LigS = Lignon Sulfonate) Application rates are estimated amounts.
		EX	Purchaser shall abate dust on the existing width
		Numbers	Purchaser shall abate dust to the width indicated by entry.
7	Seasonal Maintenance	W	Waterbars and/or crossditching shall be required prior to expected seasonal precipitation.
		B	Entrance barriers shall be installed by Purchaser prior to nonuse periods.
8	Snow Removal	TS	Snowplowing authorized for Purchaser's Operations without recreation access being provided per Section T-803 requirements.
		JU	Snowplowing authorized, but must provide for recreation joint use per Section T-803 requirements.
		Blank	Snowplowing is not authorized. Forest Service may authorize plowing by permit when not in conflict with other uses.
9	Post Haul	PR	PR denotes that work is Purchaser's Responsibility to perform.

Sale Name: Bailey Salvage

C5.32# - ROAD MAINTENANCE DEPOSIT SCHEDULE (07/2001)

Other provisions herein notwithstanding, when Forest Service requests payment in lieu of Purchaser's performance of road maintenance, Purchaser shall make Required Deposits (16 USC 537) for current and/or deferred road maintenance. Such deposits are based on the estimated volume and distance hauled and Purchaser's commensurate use of each road listed in the Road Maintenance Plan in C5.31#.

Purchaser and Forest Service may agree in writing on adjustment of such rates. If Purchaser uses roads under jurisdiction of Forest Service other than those listed in the Road Maintenance Plan, Forest Service shall establish rates commensurate with Purchaser's use of such roads.

The Required Deposits for Forest Service work in lieu of Purchaser performance and for deferred maintenance is: \$.39 per MBF.

The following table lists who Purchaser will make deposits for road maintenance to, and the rate per unit of measure of the deposit. The Road Maintenance Agreement is available for inspection at the Forest Supervisor's office.

Deposit Made To	Rate	Unit of Measure
N/A		

C6.22# - PROTECTION OF IMPROVEMENTS (07/2001)

Unless otherwise agreed to in writing, Purchaser shall move or relocate the improvements listed in the following table to locations in a manner as specified in drawings or in specifications attached hereto. Improvements shall be returned to their original locations following Purchaser's operations.

See attached table of improvements to be moved.

TABLE PURSUANT TO C6.22# - PROTECTION OF IMPROVEMENTS (07/2001)

Type of Improvement	Move or Relocate to
Wire fence in Cutting Units 2, 11, and 24.	Fence may be cut for operations where agreed to by Forest Service. Fence shall be repaired by Purchaser following operations in each Cutting Unit.
Historic Summit Trail 2630 RD	Log hauling shall stay within the existing prism and no new vehicle staging areas will be permitted along the historic road; vehicles may park within existing landings or existing pull-offs or spur roads
Trails as shown on Sale Area Map	Trail markers, such as diamonds, on trees designated for removal shall be moved to a nearby tree that is not designated for removal.

Sale Name: Bailey Salvage

C6.315# - SALE OPERATION SCHEDULE (06/1994)

Unless otherwise agreed to between Purchaser and Forest Service, Purchaser's Operations shall be performed in accordance with the following schedule.

See attached schedule.

SCHEDULE PURSUANT TO C6.315# - SALE OPERATION SCHEDULE (06/1994)

Item	Operating Conditions	Purpose
Cutting Units 11	Priority 1: Harvest and removal of timber from this unit shall occur first.	Public and employee personnel safety and fence protection
All roadside cutting units	Priority 2: Harvest and removal of timber from roadside up to any cutting unit.	Public Safety
2730-550 2600-600 2600-450-630	Gates shall be opened in the morning and closed/locked when operations are done for the day.	Protect closed roads

Sale Name: Bailey Salvage

C6.32# - PROTECTION OF RESERVE TREES (04/2004)

Purchaser's damage or destruction of reserve trees described in C2.3# will cause serious and substantial silvicultural or other damage to the National Forest. It will be difficult if not impossible to determine the amount of such damage. Therefore, Purchaser shall pay as fixed, agreed, and liquidated damages \$ 500 for each genetic reserve tree and \$ N/A for each N/A reserve tree damaged or destroyed by Purchaser's Operations, in addition to amounts payable under B3.45 and B3.46.

Damage, as used herein, includes any injury to the living crown, bole, or roots of reserve trees. If areas are marked on the ground around such reserve trees, operation of heavy equipment or skidding of products within the area shall be considered to be damage to the tree.

C6.405 - ALTERNATE REMOVAL OF INCLUDED TIMBER (05/2005)

Purchaser and Forest Service may agree to alternate removal requirements of Included Timber contained in A2. Alternate removal requirements are to be set forth in an agreement signed by both Purchaser and Contracting Officer. The terms of the agreement binds both parties and becomes part of the timber sale contract.

The development and execution of the agreement is based upon the determination by the Contracting Officer that removal of Included Timber is economically impractical if Purchaser has no ready market for such logs in the tributary area. A tributary area is defined as the area in which the Purchaser and competitors regularly deliver saw logs, or 200 miles from the Sale Area, whichever distance is greater.

The agreement for alternate removal requirements shall be executed prior to removing any timber from the Subdivisions included in the agreement. Alternate removal requirements shall apply only to whole units and not to portions of units. All material meeting alternate removal specifications shall be cut and removed to locations designed in the agreement.

Volumes of material with alternate removal requirements will be determined from the National Cruise report for the sale. Purchaser will be charged for the following:

- a) stumpage value at current contract rates of the alternatively removed timber;
- b) plus the cost of other work required by the Forest Service to dispose of alternatively removed material;
- c) plus the difference between the appraised transportation cost of the Sawtimber and/or Nonsawtimber material involved and the appraised transportation cost of the alternative.
- d) Minus any work required to be completed by the Purchaser associated with alternate removal requirements.

Charges will be debited to the Purchaser's timber sale account.

Upon acceptance of the alternate removal requirements, the Subdivision will be removed from the Sale Area under B6.36.

Title to material included in the alternate removal agreement shall remain with the Forest Service.

Sale Name: Bailey Salvage

C6.41# - SPECIFIC REQUIREMENTS (01/2000)

Notwithstanding B6.41, B6.411, B6.5 and B6.61, felling objectives shall be accomplished by the type of felling methods and equipment listed herein. Methods or equipment other than those specified may be approved. For Subdivisions shown in the following table, Purchaser shall submit a cutting plan for Forest Service acceptance, prior to the start of felling operations.

See attached table.

TABLE PURSUANT TO C6.41# - SPECIFIC REQUIREMENTS (01/2000)

<u>FELLING METHODS</u>	<u>Cutting Unit</u>
Trees shall be felled away from designated streamcourses and wet areas. Direction of felled trees shall also be to the lead to facilitate the yarding operation and minimize soil impact. Exceptions to these objectives apply only where safety, or protecting improvements, terrain features or felling within subdivision boundaries preclude felling to the lead.	All
If timber felling is completed other than handfelling, the following mechanized felling methods shall apply.	All
Mechanized felling equipment shall operate in a manner which will minimize detrimental soil disturbance and residual stand damage.	
Mechanized Felling equipment is allowed off the skid trails for a single round trip only except in the streamcourse buffers.	All
Mechanized felling equipment is prohibited on slopes greater than 35 percent.	All
No equipment operation within 50 feet of any seeps, springs, bogs, or ponds.	All
Metal tracks and cleats are prohibited on paved roads.	All
During winter months, ground-based equipment shall operate only when there is a continuous snow pack or when soils are frozen to a depth of 6 inches or greater.	All
Vehicles and equipment are prohibited off road in locations of invasive species and ATP on the Sale Area Map.	All
8" stump height required 75 feet from the edge of FS roads 2600 and 2630 unless visibility of stumps is hidden by topographic features.	2, 11, 26

FELLING EQUIPMENT

Mechanized felling equipment shall be limited to a boom-mounted shear/saw with a minimum reach of 17 feet from equipment center point or as agreed to by Forest Service. When snow and/or frozen ground conditions exist, other felling methods or equipment may be agreed to.	All
--	-----

Sale Name: Bailey Salvage

C6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

Purchaser shall submit for Forest Service approval a Yarding/Skidding Plan prior to the start of felling operations. Requirements other than those specified in the following table may be approved. When appropriate, such approval shall include adjustments in Current Contract Rates and revision of the Sale Area Map. In no such case shall the adjustments result in Current Contract Rates less than Base Rates.

Location of all skid roads and trails, tractor roads, skyline corridors, mechanized harvester trails, forwarder roads, and other log skidding facilities, shall be approved prior to their use or construction.

See attached table for requirements.

TABLE PURSUANT TO C6.42# - YARDING/SKIDDING REQUIREMENTS
(06/2010)

<u>YARDING/SKIDDING REQUIREMENTS</u>	<u>CUTTING UNIT</u>
Ground based skidding equipment is required. Rubber tired skidders/tractors shall have integral arch/grapple.	All
Mechanized skidding equipment is prohibited on slopes greater than 35%.	All
Spacing between skid trails shall be an average of 100 feet.	All
Leading end of all logs must be suspended above the ground during tractor skidding.	All
All ground based equipment shall be confined to designated skid trails and landings.	All
No equipment operation within 50 feet of any seeps, springs, bogs, or ponds.	All
Metal tracks and cleats are prohibited on paved roads.	All
During winter months, ground-based equipment shall operate only when there is a continuous snow pack or when soils are frozen to a depth of 6 inches or greater.	All
Vehicles and equipment are prohibited off road in locations of invasive species, wetlands and meadows on the Sale Area Map.	All
Landings shall not be located on system trails.	
Skidding across trails is permitted with Forest Service approval.	9, 22, 24, 25, 27, 30

Sale Name: Bailey Salvage

C6.6# - EROSION CONTROL AND SOIL TREATMENT BY PURCHASER (04/2014)

Erosion prevention and control work required by B6.6, shall be completed within 15 calendar days after yarding/skidding operations related to each landing are substantially completed or after Forest Service designation on the ground of work where such designation is required hereunder. Said time limit shall be exclusive of full days lost in Purchaser's Operations due to causes beyond Purchaser's control. Such on the ground designation shall be done as promptly as feasible unless it is agreed that the location of such work can be established without marking on the ground. After September 15, and as long thereafter as operations continue, the work shall be done as promptly as practicable. Damage resulting from Purchaser's Operations due to failure to perform required work shall be repaired by Purchaser.

On slopes greater than 35 percent, erosion control measures will be done with methods other than mechanized equipment, unless otherwise agreed.

Where soil has been disturbed or displaced on Sale Area by Purchaser's Operations and where measures described in B6.6 will not result in satisfactory erosion control or where subsoiling is shown on Sale Area Map, the following shall be performed. If applicable, timing of the work shall be coordinated with required scarification or subsoiling.

(a) Where staked or otherwise marked on the ground by Forest Service, seed, fertilizer, and mulch will be applied as indicated below in the seeding, fertilizing, and mulching schedule. All applications shall be current and done during the period from October 1 to November 15, unless otherwise agreed to. Applications shall be done only during favorable conditions. If Purchaser and Forest Service agree, seed can be applied and covered within 10 days of ground disturbance, and may be done outside the required periods.

(b) Where shown on Sale Area Map, landings, Temporary Roads and/or skidtrails/roads shall be scarified to a depth of 20 inches to provide a seedbed for grass seed, fertilizer, and mulch. Seed, fertilizer, and mulch shall be spread evenly at the rates shown in the table. When the seed, fertilizer, and mulch are applied in separate operations, the second or third operations shall be within 10 days of the first or second.

(c) Where shown on Sale Area Map, landings, Temporary Roads, and skid trails/roads used by Purchaser shall be subsoiled to a minimum depth of 20 inches, except that Forest Service may agree to lesser depths. Each subsoiler shank shall be equipped with a shoe and wings which has a total width of at least 18 inches. The design of the shank and wings will be such that the treated, compacted soil is slightly lifted and well-fractured rather than plowed, mixed, or displaced. The distance between subsoiler shank passes shall not exceed 36 inches. Treated areas shall span the total width of compaction. Subsoiling shall be kept reasonably current and shall be done during Normal Operating Season unless otherwise agreed.

(d) When agreed to, Purchaser may use alternate methods of erosion control.

Seed shall meet current Forest Service requirements, with the additional requirement that no seed containing any noxious weed seed in excess of established state limitations as listed in the current "State Noxious Weed Requirements Recognized in the Administration of the Federal Seed Act" publication will be used (commonly referred to as the "all states" noxious weed seed list). Seed shall be furnished separately or in mixture in standard containers clearly marked with: (1) seed name; (2) lot number; (3) net weight; (4) percentages of purity and of germination (in case of legumes, percentage of germination to include hard seed); (5) percentage of weed seed content; and (6) certification that no noxious weed seeds in excess of established state standards are present. The contractor shall furnish the Government duplicate signed copies of a certificate, signed by a Registered Seed Technologist or Seed Analyst (certified through either the Association of Official Seed Analysis or the Society of Commercial Seed Technologists), certifying that each lot of seed has been tested in accordance with the Association of Official Seed Analysts Standards within 12 months prior to date of application. This certificate shall include (1) name and address of laboratory, (2) date of test, (3) lot number for each kind of seed, (4) name of seed, (5) percentage of

Sale Name: Bailey Salvage

germination, (6) percentage of purity, (7) percentage of weed seed content, and (8) certification that no noxious weed seeds in excess of established state limitations are present in any kind of seed.

Legume seed shall be inoculated with approved cultures in accordance with the instructions of the manufacturer.

No seed may be applied without prior written approval by the government.

(e) Purchaser may be required to seed areas disturbed by harvest activities to prevent the spread of noxious weeds, or the establishment of new areas.

See attached application schedule.

APPLICATION SCHEDULE PURSUANT TO C6.6# - EROSION CONTROL AND SOIL TREATMENT BY PURCHASER (04/2014)

SUBDIVISION OR UNIT NUMBER	AREAS A) SKID TRAILS B) FIRELINES C) TEMP. ROADS D) LANDINGS E) OTHER	SEED		FERTILIZER		MULCH	
		APPLICATION		APPLICATION		APPLICATION	
		SPECIES <u>1/</u> MIXTURE	LBS/AC	TYPE <u>2/</u>	LBS/A C	TYPE <u>3/</u>	LBS/A C
All	A*,C,D	Blue Wild Rye	15 lbs + 10%	N/A	N/A	N/A	N/A
All	A*,C,D	Idaho Fescue	15 lbs + 10%	N/A	N/A	N/A	N/A
All	A*,C,D	Sandbergs Bluegrass	15 lbs + 10%	N/A	N/A	N/A	N/A
All	A*,C,D	Prairie Junegrass	15 lbs + 10%	N/A	N/A	N/A	N/A
All	A*,C,D	Bottlebrush Squirrel Tail	15 lbs + 10%	N/A	N/A	N/A	N/A

*300 feet of the skid trails from the landings will be seeded.

Scarification is required on landings, temporary roads, and 300' of the skid trails from the landings. Scarification depth shall be 6" - 12". This supersedes (b) on page 159.

The Purchaser will be required to pay a co-op deposit of \$0.04/CCF (\$0.02/MBF) for the cultivation and harvest of replacement seed of native species for use on future contracts.

1/ For sales in Oregon, the seed shall meet the State certification specifications. Seed must be packaged in containers carrying official certification labels sewn in, glued to, or printed upon the container, with the following information:

1. Variety (if certified as to variety) and kind.
2. Quantity of seed (pounds or bushels).
3. Class of certified seed (blue tags for certified seed).
4. Inspection or lot number traceable to the certifying agency's records.

For sales in Washington, the seed shall be labeled as "Prohibited and Restricted Noxious Weed Free for the State of Washington." The purchaser shall furnish a copy of the seed analysis.

For state of California lands in Region 6, seed must be certified by the state of California, or by an independent agency or company that is approved by the state of California for "prohibited and restricted noxious weed free for the state of California."

For mixtures of seed, each ingredient in excess of 5 percent must be listed with its percentage by weight and its germination percentage.

Legumes must be inoculated with nitrogen fixing bacteria before planting. The label must show the expiration date of the inoculant.

All seed treated with a fungicide or pesticide must be labeled that it is "treated" giving the name of the chemical used, and an appropriate warning or a caution statement.

2/ Fertilizer shall be a standard commercial fertilizer with guaranteed analysis of contents clearly marked on containers.

3/ Mulch shall meet the appropriate State's certification specifications, with evidence of its certification traceable to the certifying agency's records.

Sale Name: Bailey Salvage

C6.7 - SLASH DISPOSAL (06/2008)

As used in the following Subsections, the term "slash" is vegetative debris including, but not limited to, cull logs, blasted or pushed-out stumps, chunks, broken tops, limbs, branches, rotten wood, damaged brush, damaged or destroyed reproduction, saplings or poles, resulting from Purchaser's Operations.

Any burning of slash or refuse by Purchaser is subject to C7.201.

Forest Service may agree to substitute methods of slash disposal if such substitute methods will give equally satisfactory results.

Forest Service may waive specific slash treatment requirements. Purchaser's Timber Sale Account will be charged for any slash treatment requirements waived or for work taken over by Forest Service. The amount of such charges will be determined by Forest Service if Purchaser has not begun felling operations. If felling operations have begun, charges will be determined by mutual agreement.

Forest Service may enter into a written agreement with the Purchaser for the Purchaser to complete slash disposal work originally scheduled to be done by the Forest Service. The agreement will describe the work to be completed by the Purchaser, and the value of such work. Value of the work to be done will be based upon the slash disposal plan in which the cooperative deposits were calculated, and will include Forest Service overhead. Any deposits paid by the Purchaser for this work will be credited to the Purchaser's timber sale account. This work is in addition to that required by C6.74#.

Forest Service may also enter into a written agreement with Purchaser for the Purchaser to remove slash from landings, subject to B3.41. Brush disposal deposits paid by the Purchaser for the Forest Service to burn landing piles will be credited to the Purchaser's timber sale account in the amount shown in the brush disposal plan, less the amount needed by the Forest Service for final cleanup of the landings following removal of the landing slash piles by the Purchaser. The credit will be made following the final removal by the Purchaser of all Included Timber, and slash piles, from the Sale Area.

C6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Purchaser shall pile, burn, yard, construct firelines or otherwise treat slash defined in C6.7, within designated areas. Work required of Purchaser shall be in accordance with the attached slash plan, specifications, and Sale Area Map.

Unless otherwise agreed, or shown in the attached slash plan or specifications, when Included Timber is removed during Normal Operating Season, required slash work shall be completed within 30 days of removal of approximately three-quarters of the volume in the unit. When Included Timber is removed outside Normal Operating Season, required work will be completed within 30 days of the beginning of the next Normal Operating Season.

See attached specifications.

SPECIFICATIONS PURSUANT TO C6.74# - SLASH TREATMENT REQUIREMENTS (02/02)

Slash Treatment within Harvest Units.

1. Slash to be Treated

- a. In Harvest Units: ALL.
- b. All slash meeting the definition in C6.7 remaining in cutting units, shall not exceed 18 inches from the ground.
- c. Slash treatment shall be kept current with logging operations.
- d. Activity-generated slash will be cleared from all trails within harvest units for a minimum of four feet on each side. This slash treatment does not include trails that exist on system roads where post-haul road maintenance requirements are included in C5.31#.

Slash Treatment for Machine Piling on Landings, Adjacent to System Roads and Temporary Roads.

1. Slash to be Piled

- a. Slash resulting from the construction of landings and temporary roads, and slash accumulated on the landings from the logging operation shall be piled.

2. Construction and Location of Piles

- a. Slash piles shall be located at least 25 feet from the crown or drip line of any dead or live tree or equal distance between standing dead or live trees, whichever is greater. These piles shall be minimum of 6 feet in height and 12 feet in diameter, if sufficient slash is available.
- b. All piles shall be compact and free of dirt and rocks.
- c. All material extending beyond the general contour of the piled slash shall be trimmed off and added to the pile.

3. Equipment Requirements

- a. Machines used for piling slash shall be equipped with brush blades, detachable rake fronts, or grapples.

Sale Name: Bailey Salvage

C6.815 - THIRD PARTY SCALING SERVICES (04/2004)

Notwithstanding the requirement for Forest Service or parties under contract to Forest Service to provide Scaling services under B6.81, Scaling designated in A10 shall be conducted by a third party Scaling organization approved by Forest Service. Scaling shall be done in accordance with A9 and Purchaser shall bear costs for Scaling service.

In the event third party Scaling service is suspended for causes such as strikes, termination of third party's approval to Scale National Forest logs by Forest Service, or Purchaser's failure to pay third party Scaling costs, hauling operations shall be suspended until agreed alternate Scaling services are provided or service by third party is resumed.

When an approved alternate Scaling location pursuant to B6.811 does not have an approved third party scaling organization as a commonly used Scaling services provider, Forest Service or parties under contract to Forest Service shall provide Scaling services at the approved alternate location. In such an event, the cost of waived third party Scaling listed in A10 shall be charged to Timber Sale Account.

If Forest Service and Purchaser agree in writing that another party under contract to Forest Service will perform Scaling, the contract will be modified to include C6.816 and Timber Sale Account will be charged for such Scaling.

C6.84 (OPTION 1) - USE OF PAINT BY PURCHASER (05/2005)

Notwithstanding B6.842, use of paint by the Purchaser within the Sale Area in the color(s) used by the Forest Service in the preparation of the sale and administration of the contract will be by written approval of the Forest Service.

C6.851 - WEIGHT OF LOST LOADS (04/2014)

Purchaser shall present all loads for weighing and shall furnish a weight ticket for each load pursuant to a weighing services agreement. Any load for which a weight ticket is not provided, or the weight ticket is incomplete or unreadable, or does not include the Forest Service load receipt number, shall be considered a lost sample load with a net weight equal to the load with the heaviest net weight presented during the billing period, as established by the Forest Service.

Sale Name: Bailey Salvage

C7.1 - PLANS (09/2004)

The plan shall state how Purchaser's representative or alternates will be contacted in a fire emergency, both during periods of operation and at other times such as evenings or weekends. Purchaser shall certify compliance with specific fire precautionary measures included as Subsections under C7.2 - Specific Fire Precautions, before beginning operations during Fire Precautionary Period (closed season) and shall update such certification when operations change.

If helicopter yarding is required, the plan shall include a schedule of rates mutually agreed to for computing Purchaser costs incurred toward meeting Purchaser's obligations under A14, or for paying for helicopters controlled by Purchaser and used under Forest Service direction for suppressing Operations Fires or other fires on Sale Area, excluding Negligent Fires.

Sale Name: Bailey Salvage

C7.2 - SPECIFIC FIRE PRECAUTIONS (09/2002)

When the industrial fire precautions level is I or higher, unless waiver is granted under C7.22, specific required fire precautionary measures are as follows:

A. Fire Security.

Purchaser will designate in writing a person or persons who shall perform fire security services listed below on Sale Area and vicinity. The designated person will be capable of operating Purchaser's communications and fire fighting equipment specified in the contract, excluding helicopters, and of directing the activities of Purchaser's personnel on Forest fires. Such person must report any fire detected to Forest Service within 15 minutes of detection. In lieu of having the designated person perform the required supervisory duties, Purchaser may provide another person meeting the qualifications stated above to direct the activities of Purchaser's personnel and equipment during all fire fighting activities.

Services described shall be for at least 1 hour from the time Purchaser's Operations are shut down. For the purposes of this provision, personnel servicing equipment, and their vehicles, who are not engaged in cutting or welding metal are excluded.

Fire security services shall consist of moving throughout the operation area or areas constantly looking, reporting, and taking suppression action on any fires detected. Where possible, the designated person shall observe inaccessible portions of helicopter operating areas from vantage points within or adjacent to Sale Area.

Purchaser shall furnish fire security services based on the predicted industrial precaution level, obtained by Purchaser from the appropriate Ranger District Headquarters. If predictions made after 6:00 p.m. local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in fire security services are indicated.

B. Fire Extinguisher and Equipment (on Trucks, Tractors, Power Saws, etc.).

(a) Each yarder or loader equipped with an internal combustion engine or other spark emitting source shall be equipped with a readily accessible fire extinguisher, with an Underwriter's Laboratory (UL) Rating of at least 5 B,C.

(b) All power-driven equipment operated by Purchaser on National Forest land, except portable fire pumps, shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C and one "D" handled or long handled round point shovel, size O or larger. In addition, each motor patrol, truck and passenger-carrying vehicle shall be equipped with a double-bit axe or Pulaski, 3-1/2 pounds or larger.

(c) Equipment required in (a) and (b) shall be kept in a serviceable condition and shall be readily available.

(d) Each gasoline power saw operator shall be equipped with a pressurized chemical fire extinguisher of not less than 8-ounce capacity by weight, and one long handled round point shovel, size O or larger, except at a landing where a suitable fire extinguisher and shovel are immediately available. The extinguisher will be kept in possession of the saw operator at all times. The shovel shall be accessible to the operator within 1 minute.

(e) Each helicopter shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C mounted inside the aircraft within reach of the pilot's operating position.

(f) One refill for each type or one extra extinguisher sufficient to replace each size extinguisher required on equipment shall be safely stored in the fire tool box or other agreed upon place on Sale Area that is protected and readily available.

Sale Name: Bailey Salvage

(g) At each area where helicopters are being serviced or supplied, a carbon dioxide fire extinguisher with a UL rating of at least 20 B,C will be provided on the site and placed where it is available for immediate use.

C. Spark Arrestors and Mufflers.

Each internal combustion engine shall be equipped with a spark arrester qualified and rated under USDA Forest Service Standard 5100-1a as shown in the National Wildfire Coordination Group Spark Arrester Guide, unless it is:

(a) Equipped with a turbine-driven exhaust supercharger such as the turbocharger. There shall be no exhaust bypass.

(b) A multi-position engine, such as on power saws which must meet the performance levels set forth in the Society of Automotive Engineers (SAE) "multi-positioned small engine exhaust fire ignition standard, SAE recommended practice J335B" as now or hereafter amended.

(c) A passenger carrying vehicle or light truck, or medium truck up to 40,000 GVW, used on roads and equipped with a factory designed muffler complete with baffles and an exhaust system in good working condition.

(d) A heavy duty truck, such as a dump or log truck, or other vehicle used for commercial hauling, used only on roads and equipped with a factory designed muffler and with a vertical stack exhaust system extending above the cab.

Exhaust equipment described in this Subsection, including spark arresters and mufflers, shall be properly installed and constantly maintained in serviceable condition.

D. Fire Tools.

Purchaser shall furnish serviceable fire fighting tools in a readily accessible fire tool box or compartment of sound construction with a hinged lid and hasp so arranged that the box can be secured or sealed. The box shall be red and marked "Fire Tools" in letters at least 1 inch high. It shall contain a minimum of:

(a) Two axes or Pulaskis with a 32 inch handle.

(b) Three adze eye hoes. One Pulaski may be substituted for one adze eye hoe.

(c) Three long handled, round point shovels, size 0 or larger.

E. Tank Truck.

Purchaser shall provide a tank truck or trailer, containing not less than 300 gallons of water, during yarding, skidding, loading, land clearing, right-of-way clearing, mechanical falling, and mechanical treatment of slash. Such tank truck or trailer shall be maintained in a serviceable condition and located within 10 minutes, round trip, from each operating side during Fire Precautionary Period (closed season), except as provided under B7.21.

The tank truck or trailer shall be equipped with a pump capable of discharging 20 gallons of water per minute, using a 1/4 inch nozzle tip, through a 50 foot length of poly or rubber lined hose. In addition, 500 feet of serviceable hard rubber poly or rubber lined or FJRL hose of not less than 1 inch outside diameter, fitted with a nozzle capable of discharging a straight stream of 1/4 inch diameter and a spray pattern shall be immediately available for use. The tank, pump, nozzle and at least 250 feet, of the total 500 feet of hose, shall be connected and ready for use at all times. Synthetic hose may be used by

Sale Name: Bailey Salvage

agreement.

If a trailer is used, it shall be equipped with a hitch to facilitate prompt movement. A serviceable tow vehicle shall be immediately available for attachment to the trailer and must meet the time requirements stated above. Such truck or trailer shall be equipped to operate for a minimum of 8 hours.

Where designated on Sale Area Map, Purchaser shall provide a tank trailer or water source and pumping equipment, including accessories, which can be lifted and transported by the yarding system. The component parts shall meet all specifications above. The tank trailer or water supply and pumping accessories shall be deliverable to a fire, in area of operations, within 15 minutes of detection.

In lieu of the above tank trailer or water supply for helicopter operations, Purchaser may provide a suitable helicopter water bucket with a 300 gallon capacity. When Purchaser provides a water bucket, a water source shall be provided within 5 minutes round trip flight time from operating side.

F. Communications.

During Purchaser's Operations, excluding powersaw falling and bucking, Purchaser shall provide adequate two-way communication facilities to report a fire to Forest Service within 15 minutes of detection. Citizen Band radios (CB's) are not considered adequate two-way communications because FCC Regulations prohibit commercial use.

G. Smoking and Open Fire Restrictions.

Smoking and fires shall be permitted only at the option of Purchaser. Purchaser shall not permit open fires on Sale Area without advance permission in writing from Forest Service.

H. Blasting.

Blasting shall be permitted only for road construction purposes unless advance permission is obtained from Forest Service.

Whenever the Industrial Fire Precaution Level is II or greater, a fire security person equipped with a long handled round point No. 0 or larger shovel and a 5 gallon backpack pump can filled with water, will stay at location of blast for 1 hour after blasting is done. Blasting may be suspended by Forest Service, in areas of high rate of spread and resistance to control.

Fuses shall not be used for blasting. Explosive cords shall not be used without permission of Forest Service, which may specify conditions under which such explosives may be used and precautions to be taken.

I. Compliance with State Fire Laws.

Listing of specific fire precautionary measures in the foregoing Subsections is not intended to relieve Purchaser in any way from compliance with State fire laws covering fire prevention and suppression equipment, applicable to Purchaser's Operations.

J. Aircraft Communications.

Every aircraft used in conjunction with Purchaser's Operations shall be equipped with an operable radio system. The radio system shall be capable of transmitting and receiving on VHF frequency 122.85 Megahertz (MHz) with a minimum output of 5 watts at the transmitter. The system shall be located and installed so that the pilot can operate it while flying. A shielded all-weather broad-band antenna shall be part of the system. Radio and antenna shall be properly installed and maintained.

Upon discovery or notification of a fire on Sale Area, all aircraft pilots controlled by Purchaser shall

Sale Name: Bailey Salvage

monitor VHF frequency 122.85 MHz when within 5 miles of a fire and broadcast their intentions.

K. Logging Block Equipment.

Purchaser shall provide a serviceable 5 gallon backpack pump full of water, one axe, and one long handled round point shovel, size 0 or larger, at each haulback block through which a running line passes.

The area below such blocks must be kept clear of all flammable debris under 4 inches in diameter for a distance of 6 feet in all directions. Material larger than 4 inches that poses a fire risk, such as punky logs, must also be removed.

Purchaser shall avoid line-rub on rocks or woody material which may result in sparks or sufficient heat to cause ignition of fire.

C7.201 - BURNING BY PURCHASER (01/1993)

Notwithstanding the Fire Precautionary Period limitation of B7.2, Purchaser is required to obtain written permission from Forest Service prior to any burning on the National Forest Lands.

Sale Name: Bailey Salvage

C7.22 - EMERGENCY FIRE PRECAUTIONS (09/2004)

Purchaser shall restrict operations in accordance with the Industrial Fire Precaution Levels attached. Forest Service may change the Industrial Fire Precaution Levels to other values upon revision of the National Fire Danger Rating System and may change the specific Industrial Fire Precaution Levels when such changes are necessary for the protection of the National Forest. When sent to Purchaser, the revised Industrial Fire Precaution Levels will supersede the attached levels.

INDUSTRIAL FIRE PRECAUTIONS SCHEDULE

LEVEL INDUSTRIAL FIRE PRECAUTION

I. Closed Season - Fire precaution requirements are in effect. A Fire Watch/Fire Security is required at this and all higher levels unless otherwise waived.

II. Partial Hootowl - The following may operate only between The hours of 8 p.m. and 1 p.m. local time:

power saws, except at loading sites;
cable yarding;
blasting;
welding or cutting of metal.

III. Partial shutdown - The following are prohibited:

cable yarding - except that gravity operated logging systems employing non-motorized carriages may be operated between the hours of 8 p.m. and 1 p.m. local time when all blocks and moving lines are 10 feet or more above the ground, excluding the line between the carriage and the choker.

power saws - except at loading sites and on tractor/skidder operations between the hours of 8 p.m. and 1 p.m. local time.

In addition, the following are permitted between the hours of 8 p.m. and 1 p.m. local time:

tractor, skidder, feller-buncher, forwarder, or shovel logging operations where tractors, skidders or other equipment with a blade capable of constructing fireline are immediately available to quickly reach and effectively attack a fire start;
mechanized loading and hauling;
blasting;
welding or cutting of metal;
any other spark-emitting operation not specifically mentioned.

IV. General shutdown - All operations are prohibited.

The following definitions shall apply to these Industrial Fire Precaution Levels:

Cable yarding systems: A yarding system employing cables and winches in a fixed position.

Closed Season (Fire Precautionary Period): That time period each year when a fire hazard exists as

Sale Name: Bailey Salvage

described in A12.

Hauling: Where hauling involves transit through more than one shutdown zone/regulated use area, the precaution level at the woods site shall govern the level of haul restrictions, unless prohibited by other than the Industrial Fire Precaution Level system.

Loading sites/woods site: A place where any product or material (including but not limited to logs, firewood, slash, soil, rock, poles, posts, etc.) is placed in or upon a truck or other vehicle.

Advance written waiver of the above precautions may be issued by the Contracting Officer or Forest Service Representative.

Such waiver, or substitute precautions under B7.21, shall prescribe measures to be taken by Purchaser to reduce the risk of ignition, and/or the spread of fire. The Contracting Officer or Forest Service Representative shall consider site specific weather factors, fuel conditions, and specific operations that result in less risk of fire ignition and/or spread than contemplated when precaution level was predicted. Consideration shall also be given to measures that reduce the precaution levels above. Purchaser shall assure that all conditions of such waivers or substitute precautions are met.

Purchaser shall obtain the predicted Industrial Fire Precaution Level from the appropriate Ranger District headquarters. If predictions made after 6:00 p.m., local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in restrictions or industrial precautions are indicated.

C8.13 - DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTY (09/2004)

Purchaser and Forest Service hereby agree, acknowledge, and accept that there is no expressed or implied warranty provided by the Forest Service that guarantees the Purchaser will be allowed to complete the removal of products sold under the terms of the contract. Upon execution of the contract, Purchaser hereby acknowledges the acceptance of the risk that this contract is subject to interruption or termination as a result of litigation associated with the environmental analysis process used by the Forest Service in the planning of this timber sale. If such interruption or termination occurs due to litigation, Purchaser agrees to accept as full compensation for such interruption remedies pursuant to B8.33, or for termination remedies pursuant to B8.34.

Sale Name: Bailey Salvage

CB.66# (Option 1) - USE OF TIMBER (04/2004)

(a) This contract is subject to the Forest Resources Conservation and Shortage Relief Act of 1990, as amended (16 USC 620, et seq.).

(b) Except for None determined pursuant to public hearing to be surplus, unprocessed Included Timber shall not be exported from the United States nor used in direct or indirect substitution for unprocessed timber exported from private lands by Purchaser or any person as defined in the Act (16 USC 620e).

(c) Timber in the following form will be considered unprocessed:

(i) Trees or portions of trees or other roundwood not processed to standards and specifications suitable for end product use;

(ii) Lumber, construction timbers, or cants intended for remanufacturing not meeting standards defined in the Act (16 USC 620e); and

(iii) Aspen or other pulpwood bolts exceeding 100 inches in length.

(d) Unless otherwise agreed in writing, unprocessed Included Timber shall be delivered to a domestic processing facility and shall not be mixed with logs intended for export.

(e) Prior to award, during the life of this contract, and for a period of 3 years from Termination Date, Purchaser shall furnish to Forest Service, upon request, records showing the volume and geographic origin of unprocessed timber from private lands exported or sold for export by Purchaser or affiliates.

(f) Prior to delivering unprocessed Included Timber to another party, Purchaser shall require each buyer, exchangee, or recipient to execute an acceptable agreement that will:

(i) Identify the Federal origin of the timber;

(ii) Specify domestic processing for the timber involved;

(iii) Require the execution of such agreements between the parties to any subsequent transactions involving the timber;

(iv) Require that all hammer brands and/or yellow paint must remain on logs until they are either legally exported or domestically processed, whichever is applicable; and

(v) Otherwise comply with the requirements of the Act (16 USC 620d).

(g) No later than 10 days following the execution of any such agreement between Purchaser and another party, Purchaser shall furnish to Forest Service a copy of each such agreement. Purchaser shall retain, for 3 years from Termination Date, the records of all sales, exchanges, or dispositions of all Included Timber.

(h) Upon request, all records dealing with origin and disposition of Included Timber shall be made available to Contracting Officer.

(i) For breach of this Section, Forest Service may terminate this contract and take such other action as may be provided by statute or regulation, including the imposition of penalties. When terminated by Forest Service under this Section, Forest Service will not be liable for any Claim submitted by Purchaser relating to the termination.

Sale Name: Bailey Salvage

C8.71 - TRIPARTITE LAND EXCHANGE (04/1999)

Purchaser agrees that timber values for which cash payment is required under B4.0 may be applied to any land exchange transaction authorized by law under which the owner of offered lands agrees to accept the money value of timber sold for the value of land granted to the United States.

C8.72 - BIPARTITE LAND EXCHANGE (04/2004)

Purchaser has offered to exchange land owned by Purchaser, as described in a separate exchange agreement. When title to offered land has been accepted by the United States, Forest Service agrees that the value of the offered land is a land exchange credit and shall be applied to charges for timber in lieu of cash deposits under B4.21. If Purchaser desires to cut timber prior to acceptance of title by the United States, cash deposits shall be refunded when title to an equivalent value of land is accepted, to the extent such deposits are not needed to satisfy other charges.