

**CT6.41# - SPECIFIC REQUIREMENTS.** (1/00) Notwithstanding BT6.41, BT6.411, BT6.5, and BT6.61, felling objectives shall be accomplished by the type of felling methods and equipment listed herein. Methods or equipment other than those specified may be approved. For Payment Units shown in the following table, Purchaser shall submit a cutting plan for Forest Service acceptance, prior to the start of felling operations.

See attached table.

<u>FELLING METHODS</u>	<u>PAYMENT UNITS</u>
Trees should be felled in such a manner as to prevent damage to residual trees	All
Mechanical felling equipment restricted to designated trails	All
If handfelling occurs, skid trails shall be made clearly identifiable to the fallers prior to felling of adjacent timber. Insofar as possible, all timber shall be felled to the lead into the skid trail/corridor system.	1, 3, 5a, 5b
No equipment operation within 12 feet from the edge of the protected site. Listed on map as (ATP) Area To Protect. Red and white candy stripe colored ribbon identifies area on the ground to protect. Trees will be directionally felled away from the protected site.	2
Mechanized felling equipment is restricted to operating on slopes less than than 35 percent.	All
FS road 4240 will be closed for public safety during daily logging operations. Road closure will not interfere with rifle deer and elk hunting seasons. Timing will be approved by Forest Service.	5a, 5b
Whole Tree Yarding (WTY) required.	2, 4
Whole Tree Yarding (WTY) required. Oversize trees 16.0" DBH and over that will be hand felled can have boles bucked on site, but all limbs and tops must remain attached except for normal breakage, and yarded to landings.	1, 3, 5a, 5b