

Sale Name: Yakso

C2.11# - TIMBER SUBJECT TO AGREEMENT (02/1971)

In addition, there is within Sale Area an unestimated quantity of:

Species	Product
<hr/>	
Douglas-fir and Other Conifero	Grn Bio Cv

that shall be Included Timber upon written agreement.

C2.35# (OPTION 1) - INDIVIDUAL TREE DESIGNATION (06/2008)

All see attached table which meet the minimum tree diameter stated on Page 1 are designated for cutting. Additional timber to be cut, if any, will be designated for cutting in accordance with BT2.37.

Leave trees, Marked with orange paint, or identified by see attached table are not to be cut, unless designated by the Forest Service.

C3.47# - ABNORMAL DELAY (09/2004)

Unless otherwise agreed, felled timber meeting Utilization Standards shall be removed by Purchaser pursuant to B2.2 and shall be presented for Scaling within the time period indicated in the following removal schedule. The number of days shown are consecutive calendar days.

Failure to remove and present such timber for Scaling within the required time limits will be considered abnormal delay, subject to B3.47.

**See attached removal schedule.**

DESCRIPTION PURSUANT TO C2.35# (OPTION 1) - INDIVIDUAL TREE  
DESIGNATION (06/2008)

Unit	DxD Spacing <sup>1</sup>	Description of Included Timber
Unit(s)107,114 identified on Sale Area Map as <u>13</u>	13	Cut all Ponderosa pine.  The live Douglas-fir, Western Hemlock or True fir tree with the largest stump diameter <sup>2</sup> in an area will remain standing after logging is complete. All live Douglas-fir, Western Hemlock and True fir within 13 feet of the retained tree will be cut. Ignore all other Coniferous species.
Unit(s)136,140 identified on Sale Area Map as <u>15</u>	15	Cut all Ponderosa pine.  The live Douglas-fir, True fir or Western Hemlock tree with the largest stump diameter <sup>2</sup> in an area will remain standing after logging is complete. All live Douglas-fir, True fir and Western Hemlock within 15 feet of the retained tree will be cut. Leave all minor Coniferous species and factor in DxD.

Unit(s) 100,101,102,103,105,108, 112,116,125,144 identified on Sale Area Map as <span style="border: 1px solid black; padding: 2px;">15</span>	15	Cut all Ponderosa pine.  The live Douglas-fir, Western Hemlock or True fir tree with the largest stump diameter <sup>2</sup> in an area will remain standing after logging is complete. All live Douglas-fir, Western Hemlock, and True fir within 15 feet of the retained tree will be cut. Ignore all other species.
---	----	--

**Definitions:**

DxD: Designation by Description.

<sup>1/</sup> DxD spacing: Is the measured slope distance with a retractable loggers tape. Distances will be measured from the closest point between trees at the 6-inch DxD height. Boundary trees (trees posted with Forest Service boundary tags) will be used as "spacing" trees if they are larger than the surrounding potential harvest trees. **All** boundary trees will remain uncut.

<sup>2/</sup> DxD stump diameter: Measured outside the bark at 6-inches above the ground, on the uphill side of the tree, with a diameter or retractable loggers tape that is perpendicular to the bole of the tree.

<sup>3/</sup> DxD stump height: Identified as the point 6" up from the forest floor on the uphill/high side of the tree bole.

REMOVAL SCHEDULE PURSUANT TO C3.47# - ABNORMAL DELAY (09/2004)

<u>Included Timber</u>	<u>Time Limits</u>	
ALL.	30	days after felling is started.
All timber decked during construction clearing.	30	days after felling on each Specified Road constructed by Purchaser is initiated.
Timber decked during road construction.	30	days after Forest Service authorizes Purchaser to use roads pursuant to B5.2.

C4.211 - DOWNPAYMENT (06/2007)

The downpayment amount shown in A18 may not be applied toward any other payment required under the provisions of this contract, except damages determined pursuant to B9.4, transferred to other timber sales, or refunded until (a) stumpage value representing 25 percent of the total bid value of the timber sale has been charged and paid for, or (b) the estimated value of the unscaled timber is equal to or less than the amount of the downpayment, or (c) if 36 CFR 223.49(e) is applicable, the estimated value of the unscaled timber is equal to or less than the amount of the downpayment.

If Forest Service makes a determination that this contract should not have been included under increased downpayment requirements (36 CFR 223.49(e)), the downpayment shall be revised and applied in accordance with 36 CFR 223.49(f).

C4.212 - TEMPORARY REDUCTION OF DOWNPAYMENT (08/2009)

Notwithstanding B4.211 or C4.211, upon the Purchaser's written request Forest Service may temporarily reduce the downpayment when Purchaser's scheduled operations are delayed or interrupted for 30 or more consecutive days, or the contract term is extended for 30 or more consecutive days for any of the following reasons:

- (1) Forest Service requests or orders Purchaser to delay or interrupt operations for reasons other than breach;
- (2) Purchaser interrupts or delays scheduled operations to work on a sale designated by the Forest Service as in urgent need of harvesting; or
- (3) An adjustment of the contract term authorized upon a determination of substantial overriding public interest, including a market-related contract term addition, or an urgent removal contract term extension under 36 CFR 223.53.

When Purchaser is not cutting or removing timber under contract during a qualifying period of delay, interruption, or extension listed above the downpayment may be reduced to \$1000 or 2 percent of the downpayment amount stated in the contract, whichever is greater. The Purchaser must restore the downpayment to the full amount stated in the contract within 15 days from receipt of the bill for collection and written notice from the Contracting Officer that the basis for temporarily reducing the downpayment no longer exists. Purchaser shall not cut or remove timber on a contract where the downpayment has been temporarily reduced until the downpayment amount stated in the contract is fully restored.

Sale Name: Yakso

C5.1# (OPTION 1) - TEMPORARY ROAD AND LANDING CONSTRUCTION (06/2008)

In addition to the requirements of B5.1 and B6.63, Purchaser and Forest Service will agree to the design, construction, maintenance, closure, and obliteration of all Temporary Roads.

Construction of Temporary Roads in areas shown on Sale Area Map shall be in accordance with the attached plans or criteria.

Unless otherwise agreed, if Purchaser's Operations require more than NA cubic yards of rock for Temporary Roads, landings, or other temporary uses, such rock shall be obtained from commercial sources.

PLANS AND/OR CRITERIA PURSUANT TO C5.1# (OPTION 1) - TEMPORARY ROAD AND LANDING CONSTRUCTION (06/2008). **New and existing temporary roads will be constructed to access skyline landings and to facilitate ground skidding in units 100, 101, 102, 103, 105, 107, 108, 125 and 140. After logging, the temporary roads and landings will be subsoiled to a depth of 20 inches. Shape roadbed to the original slope. Slash and down logs will be placed across the subsoiled roadbed for erosion control, to a depth of not more than 12 inches, ensuring that no vehicle will be able to travel over it. Block beginning of roads with a log/earth berm to prevent vehicle use.**

C5.12# - USE OF ROADS BY PURCHASER (06/1999)

Purchaser's use of existing roads identified on Sale Area Map by the following codes is prohibited or subject to restrictive limitations, unless agreed otherwise:

Code	Use Limitations
X	Hauling prohibited
R	Hauling restricted
U	Unsuitable for hauling prior to completion of agreed reconstruction
P	Use prohibited
A	Public use restriction
W	Regulation waiver

Roads coded A will be signed by the Forest Service to inform the public of use restrictions. Purchaser's use of roads coded R, A, or W shall be in accordance with the following restrictions:

**See Restricted Road List Table.**

**C5.12# – USE OF ROADS BY PURCHASER.** (6/99) Purchaser's use of existing roads identified on Sale Area Map by the following codes is prohibited or subject to restrictive limitations, unless agreed otherwise:

<u>Code</u>	<u>Use Limitations</u>
X	Hauling prohibited
R	Hauling restricted
U	Unsuitable for hauling prior to completion of agreed reconstruction
P	Use prohibited
A	Public use restriction
W	Regulation waiver

Roads coded A will be signed by Forest Service to inform the public of use restrictions. Purchaser's use of roads coded R, A, or W shall be in accordance with the following restrictions:

#### Restricted Road List

Road Number	Road/Bridge Name	Termini		Map Legend	Description of Restrictions
		From	To		
4714	4714	Jct. 4714/970 Rds	Jct. 4714/895 Rds	R	No hauling or equipment use.

The roads authorized for use are subject to the following provisions:

1. The Road Rules in the current Umpqua National Forest Road Rules Document are applicable to all commercial road users. This document title - **COMMERCIAL ROAD RULES** (Umpqua National Forest) is available for inspection at the Umpqua National Forest Supervisor's Offices.
2. State laws governing traffic rules and equipment requirements on State and County highways.
3. Federal Regulations contained in 36 CFR 261.12. These regulations prohibit use of vehicles or equipment in excess of State legal highway loads or posted limits without valid Forest Service overload permits, damaging a road while using it and blocking a road open to use by others, except as may otherwise be provided in the contract. **Submit requests for any proposed overload permit at least 14 days in advance of planned use of overload.**
4. Federal Regulations contained in 36 CFR 261.45 as applied to the area by an order issued under 36 CFR 261.50. These regulations authorize the Forest Service as a sovereign act, to issue additional restrictions and closures any time conditions warrant. Such closures will be in addition to those shown in the current Road Rules Document and will be posted on the road.
5. Unless otherwise provided, the Government will not snow plow roads for the Contractor's use. The Contractor may snow plow any road designated for its use, unless snow plowing of the road is prohibited below, or in, the Road Rules Document. On roads where snow plowing is authorized, a permit defining snow plowing requirements is required. The Contractor will be responsible for repair of any damage to the road structure caused by the snow removal operations. Vehicles, other than conventional over-the-snow vehicles (snowmobiles), will not be permitted to use roads when there is an average un-compacted depth of more than 4 inches of snow unless the road has been snow plowed.

Sale Name: Yakso

C5.13# - ROAD COMPLETION DATE (04/2004)

Construction of Specified Roads shall be completed no later than 10/31/2013; except for earlier construction completion dates for roads listed below:

Road Number	Road Name	Station		Completion Date
		From	To	

---

N/A

Completion date is binding on the party that constructs road, whether Purchaser or Forest Service. Contracting Officer shall modify the completion date in writing to conform to the approved Plan of Operations under B6.311 at the request of Purchaser.

When Purchaser elects Forest Service construction of Specified Roads shown in sale advertisement, Forest Service may adjust construction completion date when road construction is delayed or interrupted for causes that qualify for an adjustment of the completion date of Forest Service's road construction contract. When qualifying delays or interruptions of road construction occur, Forest Service shall evaluate such occurrences and document any findings. The current status of any adjustment shall be available to Purchaser on request. Promptly after the end of Normal Operating Season in which qualifying days occur, Forest Service shall give Purchaser written notice of (a) number of qualifying days claimed, and (b) new construction completion dates. After all road construction is complete, Forest Service shall grant Contract Term Adjustment. Such adjustment shall be limited to road completion date delays that occurred during Normal Operating Season.

If Forest Service is responsible for road construction and the actual date of road completion is 1 year or more after the completion date stated above, Purchaser may request a rate redetermination under B3.3 for remaining volume. Such request must be made within 30 days of notification that road construction has been completed. Upon receipt of such request, Forest Service shall redetermine rates using standard methods in effect on the completion date of road construction. Rates to be established shall apply to all timber removed from Sale Area after the effective date of the rate redetermination.

Forest Service shall in no way be responsible for any delay or damage caused by road contractor in performing the road construction, except such delay as may be the fault or negligence of Forest Service.

When Purchaser constructs Specified Roads and requests Contract Term Adjustment, completion dates shall be adjusted by number of days that qualify for such adjustment, provided such qualifying days occur before specified construction completion date. When Purchaser desires to construct an alternate facility under B5.26, Forest Service and Purchaser shall agree, in writing, on a construction completion date for alternate facility. Contract Term Adjustment as noted above will apply. Completion date shall be adjusted where a Design Change or physical changes necessitate a modification of Specified Road construction work that increases the scope or magnitude of the required work.

If Purchaser fails to complete construction of any or all Specified Roads by applicable completion date, as adjusted, Contract Term Extension shall not be granted.

As used in this Subsection, construction of a road is completed when:

(a) Purchaser constructs Specified Roads and Forest Service furnishes Purchaser with written notice of acceptance under B6.36 or

Sale Name: Yakso

(b) Forest Service constructs road and furnishes Purchaser with written notice authorizing use of road.

Notwithstanding B5.1, Purchaser shall not use a road that Purchaser has elected for Forest Service to construct, until construction is completed and Forest Service furnishes Purchaser with written notice authorizing use of road.

C5.213# - DEPOSIT FOR RECONSTRUCTION ENGINEERING SERVICES (04/2004)

Purchaser shall make a cash deposit for engineering services (preconstruction and construction) provided by Forest Service for reconstruction of National Forest system roads necessary to accommodate Purchaser's use under this contract, pursuant to 16 USC 537.

The total amount to be deposited by Purchaser for reconstruction related engineering services to be completed by Forest Service personnel or by public works contract is \$ \$933.71 . Purchaser shall make this deposit at the end of the first full Normal Operating Season or 12 months from contract award, whichever occurs first. In the event a different deposit schedule is agreed to, such deposit shall be due within 15 days after the date of issue indicated on the initial bill for collection, pursuant to B4.4.

The amount of the required deposit will be shown as an associated charge on Purchaser's Timber Sale Account. Forest Service shall retain any unexpended deposit for reconstruction related engineering services.

The deposit for reconstruction related engineering services shall be commensurate with project need and Purchaser's road use. Forest Service shall complete reconstruction related engineering services on the following schedule unless a different completion schedule is agreed in writing:

Road or Facility No.	Termini		Engineering Services Completion Date
	From	To	
Road-2700441	.3	.31	10/31/2013
Road-2715000	1.48	1.49	10/31/2013

Reconstruction related engineering services may consist of some or all of the engineering work and expense of: preparing, setting out, controlling, inspecting, and measuring the reconstruction of a National Forest system road.

Sale Name: Yakso

C5.221# - MATERIAL SOURCES (04/2004)

Sources of local materials are designated on Drawings and Sale Area Map. Forest Service assumes responsibility for the quality and quantity of material in designated sources. Purchaser shall determine the equipment and work required to produce the specified product, including the selection of acceptable material that is reasonably available in the source that meets specifications. The designation of source includes the rights of Purchaser to use certain area(s) for plant site, stockpiles, and haul roads.

Should the designated source, due to causes beyond the control of Purchaser, contain insufficient acceptable material, Forest Service will provide another source with adjustment in accordance with B5.253.

When Purchaser elects not to use designated sources, Purchaser shall furnish the specified product with no adjustment in unit rates. Quality testing shall be the responsibility of Purchaser. Test results shall be furnished to Forest Service.

When Purchaser elects not to use designated sources and the Schedule of Items lists pit development separately, cost allowance will be reduced under B5.253 when Forest Service determines the work will not be required.

When materials are subject to a weight measurement, the specific gravity or weight/volume relationship used as a basis for determination of estimated quantities shall be:

Source I NA, Source II NA, and Source III NA.

Purchaser may, when agreed in writing, use on the project such suitable stone, gravel, and sand, or other material found in the excavation, and will earn a cost allowance for the excavation of such materials at the corresponding contract unit price and for the pay items for which the excavated material is used. Purchaser shall replace, without additional cost allowance, sufficient suitable materials to complete the portion of the work that was originally contemplated to be constructed with such material. Purchaser shall not excavate or remove any material, except that which is within the excavation limits, without written authorization from Forest Service.

When material is appraised from non-National Forest designated sources, owner charges for the material in terms of unit cost for royalties, purchase of raw materials, or finished products shall be as follows until NA:

**See Material Source Table.**

Should quantity vary from that estimated, payment to owners shall be for units actually obtained. Purchaser shall make arrangements with owner(s) for measurement and payment for royalties, purchase of raw materials, or finished products, as shown above.

Materials produced or processed from National Forest lands in excess of the quantities required for performance of this contract are the property of Forest Service, unless prior written agreement has been obtained to use excess material on other National Forest sales. Forest Service is not obligated to reimburse Purchaser for the cost of their production.

Materials shall be stored to assure the preservation of their quality and fitness for the work. Stored materials shall be located to facilitate their prompt inspection. Sites on Forest Service administered land, approved by Forest Service, may be used for storage purposes and for the placing of Purchaser's plant equipment. All storage sites provided by Forest Service shall be restored at Purchaser's expense. Purchaser

shall be responsible for making arrangements for storage on other than Forest Service administered lands.

When the construction of the portion of the project for which Temporary Roads used for hauling materials is completed, all such Temporary Roads shall be restored as nearly as practicable to their original ground profile, unless otherwise agreed in writing.

**MATERIAL SOURCE TABLE PURSUANT TO C5.221# - MATERIAL SOURCE (04/2004)**

<b>Material</b>	<b>Type of Purchase</b>	<b>Owner(s)</b>	<b>Unit of Measure</b>	<b>Unit Price</b>	<b>Estimated Quantity</b>	<b>Total</b>
		N/A				

Sale Name: Yakso

C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Purchaser shall maintain roads in accordance with the following Contract Road Maintenance Requirements Summary:

**See Contract Road Maintenance Requirements Summary Table.**

TABLE PURSUANT TO C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)  
CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY

Road	Termini		Miles	Applicable <u>PREHAUL</u> Road Maintenance Specifications													
	From	To		T811	T812F	T813	T831F	T832	T834	T835F	T836	T838	T839	T842F	T851	T854	T891
2700000 Seg1	cty 17	2719000	3.1				D		D					D	D	D	
2700000 Seg2	2719000	4714000	8.11	P	D		D		D					D	D	D	
2700000 Seg 3	4714	2700505	3.38	P	P		D		D					D	D	D	
2700220	2700000	4714000	7.1	P		P					P						
2700225	2700220	N unit 103	0.43								P						
2700233	2700220	S unit 136	0.04									P					
2700235	2700220	N unit 136	0.13								P						
2700255	2700220	E unit 140	0.04									P					
2700275	2700275	t rd unit 105	0.16									P				P	
2700276	2700276	Ne unit 105	0.06									P					
2700278	2700275	SE unit 105	0.16									P					
2700441	2700000	N unit 108	0.4									P	P				
2700447	2700000	NW unit 112	0.11									P				P	
2700451	2700000	S unit 112	0.37									P					
2700471	2700000	N unit 125	0.28									P					
2715000	2700000	2715072	2.5	P		P	D		D					D	D	D	
2715070	2715000	S unit 107	0.23									P					
4714000	2700000	N unit 100	1.01	P							P						
4714760	4714000	W unit 101	1.56									P					
4714855	4714000	4714880	0.29									P					
4714865	4714855	t rd W unit 100	0.15									P					
4714880	4714855	EOR t rd unit 100	0.16										P				
4714885	4714760	NW unit 101	0.44										P				
4714895	4714000	Limpy rock pit	0.1										P				
4720005	4714228	N unit 101	0.06														

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

TABLE PURSUANT TO C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)  
CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY

Road	Termini		Miles	Applicable DURING HAUL Road Maintenance													
	From	To		T811	T812F	T813	T831F	T832	T834	T835F	T836	T838	T839	T842F	T851	T854	T891
2700000 Seg1	cty 17	2719000	3.10														
2700000 Seg2	2719000	4714000	8.11														
2700000 Seg 3	4714	2700505	3.38														
2700220	2700000	4714000	7.10							P							
2700225	2700220	N unit 103	0.43								P						
2700233	2700220	S unit 136	0.04									P					
2700235	2700220	N unit 136	0.13								P						
2700255	2700220	E unit 140	0.04									P					
2700275	2700275	t rd unit 105	0.16									P					
2700276	2700276	Ne unit 105	0.06									P					
2700278	2700275	SE unit 105	0.16									P					
2700441	2700000	N unit 108	0.40									P					
2700447	2700000	NW unit 112	0.11									P					
2700451	2700000	S unit 112	0.37									P					
2700471	2700000	N unit 125	0.28									P					
2715000	2700000	2715072	2.50														
2715070	2715000	S unit 107	0.23									P					
4714000	2700000	N unit 100	1.01							P							
4714760	4714000	W unit 101	1.56								P						
4714855	4714000	4714880	0.29								P						
4714865	4714855	t rd W unit 100	0.15								P						
4714880	4714855	EOR t rd unit 100	0.16									P					
4714885	4714760	NW unit 101	0.44									P					
4714895	4714000	Limpy rock pit	0.10									P					
4720005	4714228	N unit 101	0.06														

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

TABLE PURSUANT TO C5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)  
**CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY**

Road	Termini		Miles	Applicable POST HAUL Road Maintenance													
	From	To		T811	T812F	T813	T831F	T832	T834	T835F	T836	T838	T839	T842F	T851	T854	T891
2700000 Seg1	cty 17	2719000	3.10														
2700000 Seg2	2719000	4714000	8.11	P													
2700000 Seg 3	4714	2700505	3.38	P													
2700220	2700000	4714000	7.10	P													
2700225	2700220	N unit 103	0.43									P					
2700233	2700220	S unit 136	0.04									P					
2700235	2700220	N unit 136	0.13									P					
2700255	2700220	E unit 140	0.04									P					
2700275	2700275	t rd unit 105	0.16									P					
2700276	2700276	Ne unit 105	0.06									P					
2700278	2700275	SE unit 105	0.16									P					
2700441	2700000	N unit 108	0.40									P					
2700447	2700000	NW unit 112	0.11									P					
2700451	2700000	S unit 112	0.37									P					
2700471	2700000	N unit 125	0.28									P					
2715000	2700000	2715072	2.50	P													
2715070	2715000	S unit 107	0.23									P					
4714000	2700000	N unit 100	1.01	P							P						
4714760	4714000	W unit 101	1.56									P					
4714855	4714000	4714880	0.29									P					
4714865	4714855	t rd W unit 100	0.15									P					
4714880	4714855	EOR t rd unit 100	0.16									P					
4714885	4714760	NW unit 101	0.44									P					
4714895	4714000	Limpy rock pit	0.10									P					
4720005	4714228	N unit 101	0.06									P					

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party

ROAD LISTING PURSUANT TO

**C5.31# - ROAD MAINTENANCE REQUIREMENTS (7/2001)**

1	2	3			4	5	6			7	8	9					
		Travelway					Brushing & Logout	Surfacing	Dust Abatement			Seasonal Maintenance	Snow Removal	Post Haul			
		Width	X Slope	Comp					Product					App. Rate	Width	Block	Treat
2700000 Seg1	801-1																
2700000 Seg2	801-1, T-811F-1																
2700000 Seg 3	801-1, T-811F-1				Refer to Spec		MgCl	19 tons/mi	12'								
2700220	801-1, T-811F-1, T834-1, T834-4	EX	AI	Compaction Method B	Refer to Spec	Govt. Furnished West Limpy Pit											
2700225	801-1, T834-1, T834-4, 838-1, 838-3, 838-5	EX	AI		Refer to Spec					W							
2700233	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR				
2700235	801-1, T834-1, T834-4, 838-1, 838-3, 838-5	EX	AI		Refer to Spec					W							
2700255	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR				
2700275	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR				
2700276	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR				

2700278	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
2700441	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
2700447	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
2700451	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
2700471	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
2715000	801-1, T-811F-1	EX	AI	Compaction Method B									
2715070	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
4714000	801-1, T-811F-1, T834-1, T834-4	EX	AI	Compaction Method B	Refer to Spec								
4714760	801-1, T834-1, T834-4, 838-1, 838-3, 838-5	EX	AI		Refer to Spec					W			
4714855	801-1, T834-1, T834-4, 838-1, 838-3, 838-5	EX	AI		Refer to Spec					W			

4714865	801-1, T834-1, T834-4, 838-1, 838-3, 838-5	EX	AI		Refer to Spec					W			
4714880	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
4714885	801-1, T834-1, T834-4, 835-1	EX	AI		Refer to Spec					W, B		PR	PR
4714895	801-1, T834-1, T834-4, 835-1	EX	AI							W, B		PR	PR
4720005	801-1, T834-1, T834-4, 835-1	EX	AI							W, B		PR	PR

ROAD LISTING CODES TABLE PURSUANT TO  
C5.31# - ROAD MAINTENANCE REQUIREMENTS (7/2001)

Column No.	Heading	Entry	Explanation
Any		Blank	Except as otherwise described, no entry indicates Purchaser is not authorized or required to perform the work item(s).
Any		RC	This work requirement applies only when haul of sale related construction materials occurs.
2	Drawings	Number	Entry indicates Drawing names or numbers that apply to specifications.
3	Travel	EX Numbers  IS, C, OS, F, or AI	Purchaser shall maintain the traveled way to the width existing upon entry, or Purchaser shall maintain the traveled way to the standard width indicated by the entry, plus curve widening, in accordance with Section T-811. If required, the road template shall be shaped to this width and to the designated cross slope before haul and during recurring maintenance. Cross slopes are designated as:  IS (Inslope), C (Crown), OS (Outslope), F (Flat), AI (As Is). A or B If compaction is required.
4	Brush and Log Out	Numeric & R As Staked  OPT H	Purchaser shall remove brush for specified width on either or both the right (R) side or left (L) side of road.  Limits of brushing are as staked or marked in the field.  Purchaser may use hand or mechanical means of brushing. Only hand brushing may be used.
5	Surfacing	Aggregate Grading	Purchaser shall place surfacing on roads listed according to the grading indicated.
6	Dust abatement	OPT  Product Abbr.  EX Numbers	Product selection is Purchaser's choice from those listed in Section T-812.  Unless otherwise agreed, Purchaser is restricted to product listed corresponding to the abbreviation shown in Section T-812; (i.e., LigS = Lignon Sulfonate) Application rates are estimated amounts. Purchaser shall abate dust on the existing width Purchaser shall abate dust to the width indicated by entry.
7	Seasonal Maintenance	W  B	Waterbars and/or crossditching shall be required prior to expected seasonal precipitation.  Entrance barriers shall be installed by Purchaser prior to nonuse periods.
8	Snow Removal	TS  JU  Blank	Snowplowing authorized for Purchaser's Operations without recreation access being provided per Section T-803 requirements. Snowplowing authorized, but must provide for recreation joint use per Section T-803 requirements. Snowplowing is not authorized. Forest Service may authorize plowing by permit when not in conflict with other uses.
9	Post Haul	PR	PR denotes that work is Purchaser's Responsibility to perform.

Sale Name: Yakso

C5.32# - ROAD MAINTENANCE DEPOSIT SCHEDULE (07/2001)

Other provisions herein notwithstanding, when Forest Service requests payment in lieu of Purchaser's performance of road maintenance, Purchaser shall make Required Deposits (16 USC 537) for current and/or deferred road maintenance. Such deposits are based on the estimated volume and distance hauled and Purchaser's commensurate use of each road listed in the Road Maintenance Plan in C5.31#.

Purchaser and Forest Service may agree in writing on adjustment of such rates. If Purchaser uses roads under jurisdiction of Forest Service other than those listed in the Road Maintenance Plan, Forest Service shall establish rates commensurate with Purchaser's use of such roads.

The Required Deposits for Forest Service work in lieu of Purchaser performance and for deferred maintenance is: \$2.13 per Ton.

The following table lists who Purchaser will make deposits for road maintenance to, and the rate per unit of measure of the deposit. The Road Maintenance Agreement is available for inspection at the Forest Supervisor's office.

<b>Deposit Made To</b>	<b>Rate</b>	<b>Unit of Measure</b>
<b>N/A</b>		

C6.315# - SALE OPERATION SCHEDULE (06/1994)

Unless otherwise agreed to between Purchaser and Forest Service, Purchaser's Operations shall be performed in accordance with the following schedule.

**See attached schedule.**

## SCHEDULE PURSUANT TO C6.315# - SALE OPERATION SCHEDULE (06/1994)

Subdivision	Operating Conditions	Purpose
All	All Felling, Skidding and Yarding is restricted between April 15 and July 1. Protection measures for trees are required for continued logging operations during this period.	Protect Residual trees from bark slippage damage.
All	Temporary road construction activities that may expose new soil are limited to June 1 through October 31.	Protect water quality of affected streams.
All	All new temporary roads will be rocked or blocked for winter wet season by November 1. Additionally, earth-surface roads, including uncompleted roads to be rocked, will be cross drained by October 31.	Protect water quality of affected streams.
All	Surface rock replacement may be done outside June 1 to October 31 as weather and road conditions permit.	Protect water quality of affected streams.
All	Haul vehicles are restricted to all-weather (rocked) roads between November 1 and May 30.	Protect water quality of affected streams.
Units: 108 and 125	No logging operations will occur on weekends and federal holidays from memorial day to labor day	To minimize disturbance to recreation sites.
On the Gravel portion of Road 27.	No hauling will occur on weekends and federal holidays from memorial day to labor day.	To minimize disturbance to recreation sites.

Sale Name: Yakso

C6.405 - ALTERNATE REMOVAL OF INCLUDED TIMBER (05/2005)

Purchaser and Forest Service may agree to alternate removal requirements of Included Timber contained in A2. Alternate removal requirements are to be set forth in an agreement signed by both Purchaser and Contracting Officer. The terms of the agreement binds both parties and becomes part of the timber sale contract.

The development and execution of the agreement is based upon the determination by the Contracting Officer that removal of Included Timber is economically impractical if Purchaser has no ready market for such logs in the tributary area. A tributary area is defined as the area in which the Purchaser and competitors regularly deliver saw logs, or 200 miles from the Sale Area, whichever distance is greater.

The agreement for alternate removal requirements shall be executed prior to removing any timber from the Subdivisions included in the agreement. Alternate removal requirements shall apply only to whole units and not to portions of units. All material meeting alternate removal specifications shall be cut and removed to locations designed in the agreement.

Volumes of material with alternate removal requirements will be determined from the National Cruise report for the sale. Purchaser will be charged for the following:

- a) stumpage value at current contract rates of the alternatively removed timber;
- b) plus the cost of other work required by the Forest Service to dispose of alternatively removed material;
- c) plus the difference between the appraised transportation cost of the Sawtimber and/or Nonsawtimber material involved and the appraised transportation cost of the alternative.
- d) Minus any work required to be completed by the Purchaser associated with alternate removal requirements.

Charges will be debited to the Purchaser's timber sale account.

Upon acceptance of the alternate removal requirements, the Subdivision will be removed from the Sale Area under B6.36.

Title to material included in the alternate removal agreement shall remain with the Forest Service.

C6.41# - SPECIFIC REQUIREMENTS (01/2000)

Notwithstanding B6.41, B6.411, B6.5 and B6.61, felling objectives shall be accomplished by the type of felling methods and equipment listed herein. Methods or equipment other than those specified may be approved. For Subdivisions shown in the following table, Purchaser shall submit a cutting plan for Forest Service acceptance, prior to the start of felling operations.

**See attached table.**

TABLE PURSUANT TO C6.41# - SPECIFIC REQUIREMENTS (01/2000)

<u>FELLING METHODS</u>	<u>SUBDIVISIONS</u>
Felling of all trees to protect residual trees, riparian vegetation, No Cut Areas and facilitate yarding	All
Trees that cannot be reached with the feller/buncher or that are oversized will be conventionally felled using chainsaw and wedges to designated skid trails.	All
All trees shall be felled in a manner so that breakage is minimized and tops remain attached to the bole to facilitate transport of tops to the landing.	All
<u>FELLING EQUIPMENT</u>	<u>SUBDIVISIONS</u>
Mechanized felling equipment will not operate on slopes greater than 25 percent, unless otherwise agreed to in writing.	All
Purchaser and Forest Service shall agree to the skid trail and feller/buncher trail locations prior to felling, unless otherwise agreed to in writing.	All
All felling equipment will be restricted to designated skid trails, or feller/buncher/harvester trails agreed to by Forest Service.	All
To protect residual trees and limit soil disturbance, feller/buncher trails will not be more than 12 feet wide, nor less than 50 feet apart. Skid roads will not be less than 100 feet apart. Feller/buncher trails will be utilized to fell trees back to skid trails for hauling.	All
No equipment entry within 25' of stream buffer boundaries. Hand felling only in these areas.	All

C6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

Purchaser shall submit for Forest Service approval a Yarding/Skidding Plan prior to the start of felling operations. Requirements other than those specified in the following table may be approved. When appropriate, such approval shall include adjustments in Current Contract Rates and revision of the Sale Area Map. In no such case shall the adjustments result in Current Contract Rates less than Base Rates.

Location of all skid roads and trails, tractor roads, skyline corridors, mechanized harvester trails, forwarder roads, and other log skidding facilities, shall be approved prior to their use or construction.

**See attached table for requirements.**

TABLE PURSUANT TO C6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

<u>YARDING/REMOVAL REQUIREMENTS</u>	<u>SUBDIVISIONS</u>
Maintain one end suspension of logs on incoming turns. Has a carriage capable of maintaining a fixed position on the skyline during lateral yarding.	Skyline portion of units: 100,101,102,103,105,107, 108,114,116,125,136, 140, and 146.
Capable of lateral yarding at least 75 feet each side of the skyline. Skyline corridors will average 150 feet apart at the external yarding boundary.	Skyline portion of units: 100,101,102,103,105,107, 108,114,116,125,136, 140, and 146.
Capable of using an intermediate support	Skyline portion of units: 100,101,102,103,105,107, 108,114,116,125,136, 140, and 146.
Skyline corridors will be a maximum of 8 feet wide. Location of all skyline corridors and landings will be agreed to prior to felling operations	Skyline portion of units: 100,101,102,103,105,107, 108,114,116,125,136, 140, and 146.
Multispan may be required.	All
Leave Tops Attached (LTA) when yarding/skidding top log, ensuring that the top and all limbs remain attached. A butt log will be yarded/skidded separately to mitigate damage to residual trees.	All
<u>MECHANIZED HARVESTING REQUIREMENTS</u>	<u>SUBDIVISIONS</u>
Stump height will be a maximum of 6" above ground, on the high side of the tree to facilitate DxD compliance.	Mechanized portion of units: 100,101,103,105,107,108, 112,116,125,136, and 140.
Stumps shall not be grubbed from skid trails, except portions requiring removal for safety, unless agreed to in writing by the Forest Service.	Mechanized portion of units: 100,101,103,105,107,108, 112,116,125,136, and 140.
Purchaser and Forest Service shall agree to the skid trail and other mechanized equipment trail locations prior to felling, unless otherwise agreed to in writing.	Mechanized portion of units: 100,101,103,105,107,108, 112,116,125,136, and 140.
Mechanical equipment restricted to existing skid trails with a minimum spacing of 100 feet when possible. New skid trails will be constructed only when existing skid trails are not available.	Mechanized portion of units: 100,101,103,105,107,108, 112,116,125,136, and 140.
Skid trails will be a maximum of 12 feet wide.	Mechanized portion of units: 100,101,103,105,107,108, 112,116,125,136, and 140.
Maintain one end suspension of logs on incoming turns.	All
No equipment entry within 25' of stream buffer boundaries. Line pulling only in these areas.	All

C6.6# - EROSION CONTROL AND SOIL TREATMENT BY PURCHASER (07/2001)

Erosion prevention and control work required by B6.6, shall be completed within 15 calendar days after yarding/skidding operations related to each landing are substantially completed or after Forest Service designation on the ground of work where such designation is required hereunder. Said time limit shall be exclusive of full days lost in Purchaser's Operations due to causes beyond Purchaser's control. Such on the ground designation shall be done as promptly as feasible unless it is agreed that the location of such work can be established without marking on the ground. After September 15, and as long thereafter as operations continue, the work shall be done as promptly as practicable. Damage resulting from Purchaser's Operations due to failure to perform required work shall be repaired by Purchaser.

On slopes greater than 35 percent, erosion control measures will be done with methods other than mechanized equipment, unless otherwise agreed.

Where soil has been disturbed or displaced on Sale Area by Purchaser's Operations and where measures described in B6.6 will not result in satisfactory erosion control or where subsoiling is shown on Sale Area Map, the following shall be performed. If applicable, timing of the work shall be coordinated with required scarification or subsoiling.

(a) Where staked or otherwise marked on the ground by Forest Service, seed, fertilizer, and mulch will be applied as indicated below in the seeding, fertilizing, and mulching schedule. All applications shall be current and done during the period from May 1 to June 1 to September 15 to October 15 unless otherwise agreed to. Applications shall be done only during favorable conditions. If Purchaser and Forest Service agree, seed can be applied and covered within 10 days of ground disturbance, and may be done outside the required periods.

(b) Where shown on Sale Area Map, landings, Temporary Roads and/or skidtrails/roads shall be scarified to a depth of 20 inches to provide a seedbed for grass seed, fertilizer, and mulch. Seed, fertilizer, and mulch shall be spread evenly at the rates shown in the table. When the seed, fertilizer, and mulch are applied in separate operations, the second or third operations shall be within 10 days of the first or second.

(c) Where shown on Sale Area Map, landings, Temporary Roads, and skid trails/roads used by Purchaser shall be subsoiled to a minimum depth of 20 inches, except that Forest Service may agree to lesser depths. Each subsoiler shank shall be equipped with a shoe and wings which has a total width of at least 18 inches. The design of the shank and wings will be such that the treated, compacted soil is slightly lifted and well-fractured rather than plowed, mixed, or displaced. The distance between subsoiler shank passes shall not exceed 36 inches. Treated areas shall span the total width of compaction. Subsoiling shall be kept reasonably current and shall be done during Normal Operating Season unless otherwise agreed.

(d) When agreed to, Purchaser may use alternate methods of erosion control.

Seed shall meet current Forest Service requirements, with the additional requirement that no seed containing any noxious weed seed in excess of established state limitations as listed in the current "State Noxious Weed Requirements Recognized in the Administration of the Federal Seed Act" publication will be used (commonly referred to as the "all states" noxious weed seed list). Seed shall be furnished separately or in mixture in standard containers clearly marked with: (1) seed name; (2) lot number; (3) net weight; (4) percentages of purity and of germination (in case of legumes, percentage of germination to include hard seed); (5) percentage of weed seed content; and (6) certification that no noxious weed seeds in excess of established state standards are present. The contractor shall furnish the Government duplicate signed copies of a certificate, signed by a Registered Seed Technologist or Seed Analyst (certified through either the Association of Official Seed Analysis or the Society of Commercial Seed Technologists), certifying that each lot of seed has been tested in accordance with the Association of Official Seed Analysts Standards within 12 months prior to date of application. This certificate shall include (1) name and address of laboratory, (2) date of test, (3) lot number for each kind of seed, (4) name of seed, (5) percentage of

*Sale Name: Yakso*

germination, (6) percentage of purity, (7) percentage of weed seed content, and (8) certification that no noxious weed seeds in excess of established state limitations are present in any kind of seed.

Legume seed shall be inoculated with approved cultures in accordance with the instructions of the manufacturer.

No seed may be applied without prior written approval by the government.

**See attached application schedule.**

APPLICATION SCHEDULE PURSUANT TO C6.6# - EROSION CONTROL AND SOIL TREATMENT BY PURCHASER (07/2001)

SUBDIVISION OR UNIT NUMBER	AREAS	SEED		FERTILIZER		MULCH	
	A) SKID TRAILS B) FIRELINES C) TEMP. ROADS D) LANDINGS E) OTHER	APPLICATION		APPLICATION		APPLICATION	
		SPECIES <u>1</u> / MIXTURE	LBS/AC	TYPE <u>2</u> / LBS/AC	LBS/AC	TYPE <u>3</u> / LBS/AC	LBS/AC
All	D	Provided by F.S.	10-15			Straw, Hay, Woodstraw, Slash	

1/ For sales in Oregon, the seed shall meet the State certification specifications. Seed must be packaged in containers carrying official certification labels sewn in, glued to, or printed upon the container, with the following information:

1. Variety (if certified as to variety) and kind.
2. Quantity of seed (pounds or bushels).
3. Class of certified seed (blue tags for certified seed).
4. Inspection or lot number traceable to the certifying agency's records.

For sales in Washington, the seed shall be labeled as "Prohibited and Restricted Noxious Weed Free for the State of Washington." The purchaser shall furnish a copy of the seed analysis.

For state of California lands in Region 6, seed must be certified by the state of California, or by an independent agency or company that is approved by the state of California for "prohibited and restricted noxious weed free for the state of California."

For mixtures of seed, each ingredient in excess of 5 percent must be listed with its percentage by weight and its germination percentage.

Legumes must be inoculated with nitrogen fixing bacteria before planting. The label must show the expiration date of the inoculant.

All seed treated with a fungicide or pesticide must be labeled that it is "treated" giving the name of the chemical used, and an appropriate warning or a caution statement.

2/ Fertilizer shall be a standard commercial fertilizer with guaranteed analysis of contents clearly marked on containers.

3/ Mulch shall meet the appropriate State's certification specifications, with evidence of its certification traceable to the certifying agency's records.

C6.7 - SLASH DISPOSAL (06/2008)

As used in the following Subsections, the term "slash" is vegetative debris including, but not limited to, cull logs, blasted or pushed-out stumps, chunks, broken tops, limbs, branches, rotten wood, damaged brush, damaged or destroyed reproduction, saplings or poles, resulting from Purchaser's Operations.

Any burning of slash or refuse by Purchaser is subject to C7.201.

Forest Service may agree to substitute methods of slash disposal if such substitute methods will give equally satisfactory results.

Forest Service may waive specific slash treatment requirements. Purchaser's Timber Sale Account will be charged for any slash treatment requirements waived or for work taken over by Forest Service. The amount of such charges will be determined by Forest Service if Purchaser has not begun felling operations. If felling operations have begun, charges will be determined by mutual agreement.

Forest Service may enter into a written agreement with the Purchaser for the Purchaser to complete slash disposal work originally scheduled to be done by the Forest Service. The agreement will describe the work to be completed by the Purchaser, and the value of such work. Value of the work to be done will be based upon the slash disposal plan in which the cooperative deposits were calculated, and will include Forest Service overhead. Any deposits paid by the Purchaser for this work will be credited to the Purchaser's timber sale account. This work is in addition to that required by C6.74#.

Forest Service may also enter into a written agreement with Purchaser for the Purchaser to remove slash from landings, subject to B3.41. Brush disposal deposits paid by the Purchaser for the Forest Service to burn landing piles will be credited to the Purchaser's timber sale account in the amount shown in the brush disposal plan, less the amount needed by the Forest Service for final cleanup of the landings following removal of the landing slash piles by the Purchaser. The credit will be made following the final removal by the Purchaser of all Included Timber, and slash piles, from the Sale Area.

C6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Purchaser shall pile, burn, yard, construct firelines or otherwise treat slash defined in C6.7, within designated areas. Work required of Purchaser shall be in accordance with the attached slash plan, specifications, and Sale Area Map.

Unless otherwise agreed, or shown in the attached slash plan or specifications, when Included Timber is removed during Normal Operating Season, required slash work shall be completed within 30 days of removal of approximately three-quarters of the volume in the unit. When Included Timber is removed outside Normal Operating Season, required work will be completed within 30 days of the beginning of the next Normal Operating Season.

**See attached specifications.**

SPECIFICATIONS PURSUANT TO C6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

SLASH PLAN C6.74

Detailed Slash Disposal Plans and Specifications are on attached pages and are numbered to correspond with the work item.

<u>WORK ITEM</u>	<u>MAP SYMBOL</u>	<u>UNIT OF MEASURE</u>	<u>TOTAL UNITS IN SALE</u>	<u>COST PER UNIT (Includes Overhead)</u>
<b>I. <u>PREPARATION OF SLASH</u></b>				
A. Grapple Piling	GP	Acres	<u>110</u>	<u>\$350.00</u>
B. Piling of Landing Slash	PL	Landing	<u>131</u>	<u>*</u>
C. Covering of Piles (all types)	C	Each	<u>110</u>	<u>**</u>
D. Other				
1. Covering of Landing Slash and/or Decks	C	Each	<u>131</u>	<u>\$50.00</u>

\*Included in Logging Cost

\*\* Included in Grapple/Hand Piling Cost

**I. PREPARATION OF SLASH**

A. Grapple Piling

1. Areas of Slash Disposal

Purchaser shall pile all slash meeting minimum specifications in II.B.2. Distribution of acres in sale area shall be as follows: Subdivision(s): 65% of mechanized harvest acres will be mechanically piled, where designated by the Forest Service Fire Management.

2. Slash to be Grapple Piled

All slash greater than 1/2 inch(es) in diameter, up to and including 1 inch(es) in diameter on the large end, having a minimum length of 4 feet. Prior to piling, all pieces greater than 20 feet in length will be bucked.

### 3. Construction and Size of Grapple Piles

All piles shall be compact and free of noncombustible material. Height shall be at least 6 feet and no greater than 12 feet. Width shall be not less than 6 feet nor greater than 12 feet. Piles shall not have a width greater than two times the height.

### 4. Location of Grapple Piles

Piles shall be located at least 15 feet from subdivision boundary. Piles shall be located at least half way between any trees. Piles shall be placed on temporary roads or designated equipment trails when possible.

Piles shall be in a location that will not damage forest improvements. Piles shall not be located on road surfaces (other than temporary roads as stated above), ditch lines, or within 85 feet of live streams, unless approved in writing by Forest Service.

### 5. Acceptable Equipment

Unless otherwise agreed to in writing, slash piling equipment will be restricted to temporary roads or equipment trails that have been approved by Forest Service in advance of operations.

a. Loader/Grapple: The acceptable machine shall be track-mounted (ground pressure will not exceed 7 pounds per square inch), capable of piling logging slash and meet the following specifications: (1) capability of reaching 30 feet; (2) climbing ability up to 25% slope; (3) pivot - operator cab, engine, and arm shall be able to swing 360 degrees while tracks remain stationary; and (4) machine shall be equipped with brush grapple or articulating brush grapple mechanism. Hand piling may be substituted for loader or grapple piling if approved in writing by the Forest Service.

## B. Piling of Landing Slash

### 1. Areas of Slash Disposal

All landing or decking areas, other than specified elsewhere herein, shall be piled by hand, loader/grapple. Landing slash is considered to be the concentrated slash in the landing area caused by the yarding, limbing, and bucking of logs. Purchaser shall pile logging slash on all landings.

### 2. Slash to be Piled

Pile all slash greater than 1 inches in diameter and 3 feet in length. Unless otherwise agreed to in writing, piling shall be done within 30 days after yarding is completed.

### 3. Construction and Size of Landing Piles

Purchaser may hand pile, loader/grapple pile specified slash. Piles must be free of noncombustible material and as compact as possible. Piles shall not have a width greater than two times the height.

### 4. Location of Landing Piles

Outside edge of grapple/loader pile shall be at least 50 feet from base of any trees or adjacent timber. Outside edge of hand piles shall be at least 15 feet from base of any trees or adjacent timber. Pile shall not be located on road surfaces and ditch lines or interfere with functioning of drainage structures, ditches, or stream channels. Piles shall be a minimum of 10 feet from paved road surfaces. Piles located within 50 feet from live streams must be approved in writing by Forest Service.

Exceptions. Specified slash may be spread across the landing in uniform layer after harvest activities, if the landing is not adjacent to a system road. Exceptions must be approved in writing by the Forest Service.

### C. Covering of Piles (all types) and/or Decks

**Covering Material:** All piles shall be covered with black polyethylene plastic 0.004 inch thick or its equivalent as approved by Forest Service.

**Method of Covering:** Covering shall be placed on top of pile and tied down with combustible material. The entire core of the pile will be covered. On all grapple and landing piles, plastic size shall be 100 square feet. All protruding pieces shall be bucked off and placed on piles.

#### 1. Covering of Landing Slash and/or Decks

**Covering Material:** All piles shall be covered with black polyethylene plastic 0.004 inch thick or its equivalent as approved by Forest Service.

**Method of Covering:** Covering shall be placed on top of pile and tied down with combustible material. The entire core of the pile will be covered. On all grapple and landing piles, plastic size shall be 100 square feet. All protruding pieces shall be bucked off and placed on piles.

Sale Name: Yakso

C6.815 - THIRD PARTY SCALING SERVICES (04/2004)

Notwithstanding the requirement for Forest Service or parties under contract to Forest Service to provide Scaling services under B6.81, Scaling designated in A10 shall be conducted by a third party Scaling organization approved by Forest Service. Scaling shall be done in accordance with A9 and Purchaser shall bear costs for Scaling service.

In the event third party Scaling service is suspended for causes such as strikes, termination of third party's approval to Scale National Forest logs by Forest Service, or Purchaser's failure to pay third party Scaling costs, hauling operations shall be suspended until agreed alternate Scaling services are provided or service by third party is resumed.

When an approved alternate Scaling location pursuant to B6.811 does not have an approved third party scaling organization as a commonly used Scaling services provider, Forest Service or parties under contract to Forest Service shall provide Scaling services at the approved alternate location. In such an event, the cost of waived third party Scaling listed in A10 shall be charged to Timber Sale Account.

If Forest Service and Purchaser agree in writing that another party under contract to Forest Service will perform Scaling, the contract will be modified to include C6.816 and Timber Sale Account will be charged for such Scaling.

C6.84 (OPTION 1) - USE OF PAINT BY PURCHASER (05/2005)

Notwithstanding B6.842, use of paint by the Purchaser within the Sale Area in the color(s) used by the Forest Service in the preparation of the sale and administration of the contract will be by written approval of the Forest Service.

C7.1 - PLANS (09/2004)

The plan shall state how Purchaser's representative or alternates will be contacted in a fire emergency, both during periods of operation and at other times such as evenings or weekends. Purchaser shall certify compliance with specific fire precautionary measures included as Subsections under C7.2 - Specific Fire Precautions, before beginning operations during Fire Precautionary Period (closed season) and shall update such certification when operations change.

If helicopter yarding is required, the plan shall include a schedule of rates mutually agreed to for computing Purchaser costs incurred toward meeting Purchaser's obligations under A14, or for paying for helicopters controlled by Purchaser and used under Forest Service direction for suppressing Operations Fires or other fires on Sale Area, excluding Negligent Fires.

C7.11 - ADDITIONAL AREA OF FIRE RESPONSIBILITY (03/1989)

The area within 200 feet slope distance of the center line of any road constructed or reconstructed under this contract on National Forest lands outside of Sale Area shall be considered as a part of Sale Area in connection with responsibilities under B7.3 and B7.4 until the road has been accepted in writing by Forest Service.

C7.2 - SPECIFIC FIRE PRECAUTIONS (09/2002)

When the industrial fire precautions level is I or higher, unless waiver is granted under C7.22, specific required fire precautionary measures are as follows:

## A. Fire Security.

Purchaser will designate in writing a person or persons who shall perform fire security services listed below on Sale Area and vicinity. The designated person will be capable of operating Purchaser's communications and fire fighting equipment specified in the contract, excluding helicopters, and of directing the activities of Purchaser's personnel on Forest fires. Such person must report any fire detected to Forest Service within 15 minutes of detection. In lieu of having the designated person perform the required supervisory duties, Purchaser may provide another person meeting the qualifications stated above to direct the activities of Purchaser's personnel and equipment during all fire fighting activities.

Services described shall be for at least 1 hour from the time Purchaser's Operations are shut down. For the purposes of this provision, personnel servicing equipment, and their vehicles, who are not engaged in cutting or welding metal are excluded.

Fire security services shall consist of moving throughout the operation area or areas constantly looking, reporting, and taking suppression action on any fires detected. Where possible, the designated person shall observe inaccessible portions of helicopter operating areas from vantage points within or adjacent to Sale Area.

Purchaser shall furnish fire security services based on the predicted industrial precaution level, obtained by Purchaser from the appropriate Ranger District Headquarters. If predictions made after 6:00 p.m. local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in fire security services are indicated.

## B. Fire Extinguisher and Equipment (on Trucks, Tractors, Power Saws, etc.).

(a) Each yarder or loader equipped with an internal combustion engine or other spark emitting source shall be equipped with a readily accessible fire extinguisher, with an Underwriter's Laboratory (UL) Rating of at least 5 B,C.

(b) All power-driven equipment operated by Purchaser on National Forest land, except portable fire pumps, shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C and one "D" handled or long handled round point shovel, size 0 or larger. In addition, each motor patrol, truck and passenger-carrying vehicle shall be equipped with a double-bit axe or Pulaski, 3-1/2 pounds or larger.

(c) Equipment required in (a) and (b) shall be kept in a serviceable condition and shall be readily available.

(d) Each gasoline power saw operator shall be equipped with a pressurized chemical fire extinguisher of not less than 8-ounce capacity by weight, and one long handled round point shovel, size 0 or larger, except at a landing where a suitable fire extinguisher and shovel are immediately available. The extinguisher will be kept in possession of the saw operator at all times. The shovel shall be accessible to the operator within 1 minute.

(e) Each helicopter shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C mounted inside the aircraft within reach of the pilot's operating position.

(f) One refill for each type or one extra extinguisher sufficient to replace each size extinguisher required on equipment shall be safely stored in the fire tool box or other agreed upon place on Sale Area that is protected and readily available.

Sale Name: Yakso

(g) At each area where helicopters are being serviced or supplied, a carbon dioxide fire extinguisher with a UL rating of at least 20 B,C will be provided on the site and placed where it is available for immediate use.

#### C. Spark Arrestors and Mufflers.

Each internal combustion engine shall be equipped with a spark arrester qualified and rated under USDA Forest Service Standard 5100-1a as shown in the National Wildfire Coordination Group Spark Arrester Guide, unless it is:

(a) Equipped with a turbine-driven exhaust supercharger such as the turbocharger. There shall be no exhaust bypass.

(b) A multi-position engine, such as on power saws which must meet the performance levels set forth in the Society of Automotive Engineers (SAE) "multi-positioned small engine exhaust fire ignition standard, SAE recommended practice J335B" as now or hereafter amended.

(c) A passenger carrying vehicle or light truck, or medium truck up to 40,000 GVW, used on roads and equipped with a factory designed muffler complete with baffles and an exhaust system in good working condition.

(d) A heavy duty truck, such as a dump or log truck, or other vehicle used for commercial hauling, used only on roads and equipped with a factory designed muffler and with a vertical stack exhaust system extending above the cab.

Exhaust equipment described in this Subsection, including spark arresters and mufflers, shall be properly installed and constantly maintained in serviceable condition.

#### D. Fire Tools.

Purchaser shall furnish serviceable fire fighting tools in a readily accessible fire tool box or compartment of sound construction with a hinged lid and hasp so arranged that the box can be secured or sealed. The box shall be red and marked "Fire Tools" in letters at least 1 inch high. It shall contain a minimum of:

(a) Two axes or Pulaskis with a 32 inch handle.

(b) Three adze eye hoes. One Pulaski may be substituted for one adze eye hoe.

(c) Three long handled, round point shovels, size 0 or larger.

#### E. Tank Truck.

Purchaser shall provide a tank truck or trailer, containing not less than 300 gallons of water, during yarding, skidding, loading, land clearing, right-of-way clearing, mechanical falling, and mechanical treatment of slash. Such tank truck or trailer shall be maintained in a serviceable condition and located within 10 minutes, round trip, from each operating side during Fire Precautionary Period (closed season), except as provided under B7.21.

The tank truck or trailer shall be equipped with a pump capable of discharging 20 gallons of water per minute, using a 1/4 inch nozzle tip, through a 50 foot length of poly or rubber lined hose. In addition, 500 feet of serviceable hard rubber poly or rubber lined or FJRL hose of not less than 1 inch outside diameter, fitted with a nozzle capable of discharging a straight stream of 1/4 inch diameter and a spray pattern shall be immediately available for use. The tank, pump, nozzle and at least 250 feet, of the total 500 feet of hose, shall be connected and ready for use at all times. Synthetic hose may be used by

Sale Name: Yakso

agreement.

If a trailer is used, it shall be equipped with a hitch to facilitate prompt movement. A serviceable tow vehicle shall be immediately available for attachment to the trailer and must meet the time requirements stated above. Such truck or trailer shall be equipped to operate for a minimum of 8 hours.

Where designated on Sale Area Map, Purchaser shall provide a tank trailer or water source and pumping equipment, including accessories, which can be lifted and transported by the yarding system. The component parts shall meet all specifications above. The tank trailer or water supply and pumping accessories shall be deliverable to a fire, in area of operations, within 15 minutes of detection.

In lieu of the above tank trailer or water supply for helicopter operations, Purchaser may provide a suitable helicopter water bucket with a 300 gallon capacity. When Purchaser provides a water bucket, a water source shall be provided within 5 minutes round trip flight time from operating side.

#### F. Communications.

During Purchaser's Operations, excluding powersaw falling and bucking, Purchaser shall provide adequate two-way communication facilities to report a fire to Forest Service within 15 minutes of detection. Citizen Band radios (CB's) are not considered adequate two-way communications because FCC Regulations prohibit commercial use.

#### G. Smoking and Open Fire Restrictions.

Smoking and fires shall be permitted only at the option of Purchaser. Purchaser shall not permit open fires on Sale Area without advance permission in writing from Forest Service.

#### H. Blasting.

Blasting shall be permitted only for road construction purposes unless advance permission is obtained from Forest Service.

Whenever the Industrial Fire Precaution Level is II or greater, a fire security person equipped with a long handled round point No. 0 or larger shovel and a 5 gallon backpack pump can filled with water, will stay at location of blast for 1 hour after blasting is done. Blasting may be suspended by Forest Service, in areas of high rate of spread and resistance to control.

Fuses shall not be used for blasting. Explosive cords shall not be used without permission of Forest Service, which may specify conditions under which such explosives may be used and precautions to be taken.

#### I. Compliance with State Fire Laws.

Listing of specific fire precautionary measures in the foregoing Subsections is not intended to relieve Purchaser in any way from compliance with State fire laws covering fire prevention and suppression equipment, applicable to Purchaser's Operations.

#### J. Aircraft Communications.

Every aircraft used in conjunction with Purchaser's Operations shall be equipped with an operable radio system. The radio system shall be capable of transmitting and receiving on VHF frequency 122.85 Megahertz (MHz) with a minimum output of 5 watts at the transmitter. The system shall be located and installed so that the pilot can operate it while flying. A shielded all-weather broad-band antenna shall be part of the system. Radio and antenna shall be properly installed and maintained.

Upon discovery or notification of a fire on Sale Area, all aircraft pilots controlled by Purchaser shall

monitor VHF frequency 122.85 MHz when within 5 miles of a fire and broadcast their intentions.

K. Logging Block Equipment.

Purchaser shall provide a serviceable 5 gallon backpack pump full of water, one axe, and one long handled round point shovel, size 0 or larger, at each haulback block through which a running line passes.

The area below such blocks must be kept clear of all flammable debris under 4 inches in diameter for a distance of 6 feet in all directions. Material larger than 4 inches that poses a fire risk, such as punky logs, must also be removed.

Purchaser shall avoid line-rub on rocks or woody material which may result in sparks or sufficient heat to cause ignition of fire.

C7.201 - BURNING BY PURCHASER (01/1993)

Notwithstanding the Fire Precautionary Period limitation of B7.2, Purchaser is required to obtain written permission from Forest Service prior to any burning on the National Forest Lands.

C7.22 - EMERGENCY FIRE PRECAUTIONS (09/2004)

Purchaser shall restrict operations in accordance with the Industrial Fire Precaution Levels attached. Forest Service may change the Industrial Fire Precaution Levels to other values upon revision of the National Fire Danger Rating System and may change the specific Industrial Fire Precaution Levels when such changes are necessary for the protection of the National Forest. When sent to Purchaser, the revised Industrial Fire Precaution Levels will supersede the attached levels.

## INDUSTRIAL FIRE PRECAUTIONS SCHEDULE

## LEVEL INDUSTRIAL FIRE PRECAUTION

I. Closed Season - Fire precaution requirements are in effect. A Fire Watch/Fire Security is required at this and all higher levels unless otherwise waived.

II. Partial Hootowl - The following may operate only between The hours of 8 p.m. and 1 p.m. local time:

power saws, except at loading sites;  
cable yarding;  
blasting;  
welding or cutting of metal.

III. Partial shutdown - The following are prohibited:

cable yarding - except that gravity operated logging systems employing non-motorized carriages may be operated between the hours of 8 p.m. and 1 p.m. local time when all blocks and moving lines are 10 feet or more above the ground, excluding the line between the carriage and the choker.

power saws - except at loading sites and on tractor/skidder operations between the hours of 8 p.m. and 1 p.m. local time.

In addition, the following are permitted between the hours of 8 p.m. and 1 p.m. local time:

tractor, skidder, feller-buncher, forwarder, or shovel logging operations where tractors, skidders or other equipment with a blade capable of constructing fireline are immediately available to quickly reach and effectively attack a fire start;  
mechanized loading and hauling;  
blasting;  
welding or cutting of metal;  
any other spark-emitting operation not specifically mentioned.

IV. General shutdown - All operations are prohibited.

The following definitions shall apply to these Industrial Fire Precaution Levels:

Cable yarding systems: A yarding system employing cables and winches in a fixed position.

Closed Season (Fire Precautionary Period): That time period each year when a fire hazard exists as

described in A12.

Hauling: Where hauling involves transit through more than one shutdown zone/regulated use area, the precaution level at the woods site shall govern the level of haul restrictions, unless prohibited by other than the Industrial Fire Precaution Level system.

Loading sites/woods site: A place where any product or material (including but not limited to logs, firewood, slash, soil, rock, poles, posts, etc.) is placed in or upon a truck or other vehicle.

Advance written waiver of the above precautions may be issued by the Contracting Officer or Forest Service Representative.

Such waiver, or substitute precautions under B7.21, shall prescribe measures to be taken by Purchaser to reduce the risk of ignition, and/or the spread of fire. The Contracting Officer or Forest Service Representative shall consider site specific weather factors, fuel conditions, and specific operations that result in less risk of fire ignition and/or spread than contemplated when precaution level was predicted. Consideration shall also be given to measures that reduce the precaution levels above. Purchaser shall assure that all conditions of such waivers or substitute precautions are met.

Purchaser shall obtain the predicted Industrial Fire Precaution Level from the appropriate Ranger District headquarters. If predictions made after 6:00 p.m., local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in restrictions or industrial precautions are indicated.

C8.13 - DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTY (09/2004)

Purchaser and Forest Service hereby agree, acknowledge, and accept that there is no expressed or implied warranty provided by the Forest Service that guarantees the Purchaser will be allowed to complete the removal of products sold under the terms of the contract. Upon execution of the contract, Purchaser hereby acknowledges the acceptance of the risk that this contract is subject to interruption or termination as a result of litigation associated with the environmental analysis process used by the Forest Service in the planning of this timber sale. If such interruption or termination occurs due to litigation, Purchaser agrees to accept as full compensation for such interruption remedies pursuant to B8.33, or for termination remedies pursuant to B8.34.

C8.212 - MARKET-RELATED CONTRACT TERM ADDITION (11/2008)

The term of this contract may be adjusted when a drastic reduction in wood product prices has occurred in accordance with 36 CFR 223.52. The Producer Price Index used to determine when a drastic reduction in price has occurred is stated in A20. Purchaser will be notified whenever the Chief determines that a drastic reduction in wood product prices has occurred. If the drastic reduction criteria specified in 36 CFR 223.52 are met for 2 consecutive calendar quarters, after contract award date, Contracting Officer will add 1 year to the contract term, upon Purchaser's written request. For each additional consecutive quarter such a drastic reduction occurs, Contracting Officer will, upon written request, add an additional 3 months to the term during Normal Operating Season, except that no single 3-month addition shall extend the term of the contract by more than one year. Contracting Officer must receive Purchaser's written request for a market-related contract term addition before the expiration of this contract.

No more than 3 years shall be added to a contract's term by market-related contract term addition unless the following conditions are met:

(i) The sale was awarded after December 31, 2006; and

(ii) A drastic reduction in wood product prices occurred in at least ten of twelve consecutive quarters during the contract term, but not including the quarter in which the contract was awarded.

For each qualifying quarter meeting the criteria in paragraphs (i) and (ii) of this provision, the Forest Service will, upon the Purchaser's written request, add an additional 3 months during the normal operating season to the contract, except no single 3-month addition shall extend the term of a contract by more than 1 year.

In no event shall a revised contract term exceed 10 years as a result of market-related contract term addition.

Additional contract time may not be granted for those portions of the contract that have a required completion date or for those portions of the contract where Contracting Officer determines that the timber is in need of urgent removal or that timber deterioration or resource damage may result from delay.

C8.3# (OPTION 1) - CONTRACT CHANGES (06/2004)

Contract changes involving volumes and/or values will use a weightratio of 3.0668 to convert net CCF cruise volumes to TONS.

## C8.66# (Option 1) - USE OF TIMBER (04/2004)

(a) This contract is subject to the Forest Resources Conservation and Shortage Relief Act of 1990, as amended (16 USC 620, et seq.).

(b) Except for None determined pursuant to public hearing to be surplus, unprocessed Included Timber shall not be exported from the United States nor used in direct or indirect substitution for unprocessed timber exported from private lands by Purchaser or any person as defined in the Act (16 USC 620e).

(c) Timber in the following form will be considered unprocessed:

(i) Trees or portions of trees or other roundwood not processed to standards and specifications suitable for end product use;

(ii) Lumber, construction timbers, or cants intended for remanufacturing not meeting standards defined in the Act (16 USC 620e); and

(iii) Aspen or other pulpwood bolts exceeding 100 inches in length.

(d) Unless otherwise agreed in writing, unprocessed Included Timber shall be delivered to a domestic processing facility and shall not be mixed with logs intended for export.

(e) Prior to award, during the life of this contract, and for a period of 3 years from Termination Date, Purchaser shall furnish to Forest Service, upon request, records showing the volume and geographic origin of unprocessed timber from private lands exported or sold for export by Purchaser or affiliates.

(f) Prior to delivering unprocessed Included Timber to another party, Purchaser shall require each buyer, exchangee, or recipient to execute an acceptable agreement that will:

(i) Identify the Federal origin of the timber;

(ii) Specify domestic processing for the timber involved;

(iii) Require the execution of such agreements between the parties to any subsequent transactions involving the timber;

(iv) Require that all hammer brands and/or yellow paint must remain on logs until they are either legally exported or domestically processed, whichever is applicable; and

(v) Otherwise comply with the requirements of the Act (16 USC 620d).

(g) No later than 10 days following the execution of any such agreement between Purchaser and another party, Purchaser shall furnish to Forest Service a copy of each such agreement. Purchaser shall retain, for 3 years from Termination Date, the records of all sales, exchanges, or dispositions of all Included Timber.

(h) Upon request, all records dealing with origin and disposition of Included Timber shall be made available to Contracting Officer.

(i) For breach of this Section, Forest Service may terminate this contract and take such other action as may be provided by statute or regulation, including the imposition of penalties. When terminated by Forest Service under this Section, Forest Service will not be liable for any Claim submitted by Purchaser relating to the termination.