

## C6.42# - TABLE PURSUANT TO 6.42# - YARDING/SKIDDING REQUIREMENTS (02/2002)

YARDING/SKIDDING REQUIREMENTS	SUBDIVISIONS
Ground based equipment and single span skylineer required, as indicated on the Sale Area and Slash Disposal Map.	All
Dedicated ground based skidtrails/roads shall be no closer than 110 feet apart center to center (except where converging) and will not exceed 12 feet in width.	E1C, E4A, E4B, E6A, E13, E15B, E16A, E16D, E16E, E16F, E17D, E17E, E39B, E62,
Dedicated ground based skidtrails/roads shall be covered with a sufficient layer of slash and tops to prevent excessive rutting as directed by the Forest Service in writing.	E1C, E4A, E4B, E6A, E13, E15B, E16A, E16D, E16E, E16F, E17D, E17E, E39B, E62,
Skyline corridors will be no closer than 120 feet apart center to center and will not exceed 12 feet in width for parallel roads. Skyline corridors will be parallel to each other where feasible.	All
Skyline corridors will be no closer than 150 feet apart center to center at the tailhold or tailtree and will not exceed 12 feet in width for wheel spoked roads.	All
Forest Service Roads 2932 can be closed to traffic during skyline yarding operations.	All
Skidtrails/roads shall minimize disturbance to existing large down logs and felled hazard trees. If such logs are moved, they will be replaced as directed by the Forest Service.	All
Skidtrails/roads/landings shall impact less than 20% of the area.	All
Leading end of logs shall be suspended above ground during yarding and/or loader swing operations.	All
Log lengths shall not exceed 40 feet plus trim and may be reduced if damage occurs to the residual stand. Log lengths may be increased only when approved in writing by the Forest Service.	All
Felling any leave trees to free hung up trees will not be allowed.	All
Severly damaged rub trees shall not be cut until skidding operations are completed. Rub trees shall be designated to be cut unless otherwise directed in writing by the Forest Service.	All
All yarding operations shall result in no more than 15% of the residual trees receiving damage. No more than 10% of the residual trees may have damage exceeding 16 square inches. Damage is defined as exposure or breakage of the cambial layer of the bole or root collar.	All

No trees over the maximum stump diameter, as stated in C2.35#, will be allowed to be cut during skid road construction (ground based), unless designated by the Forest Service.	E1C, E4A, E4B, E6A, E13, E15B, E16A, E16D, E16E, E16F, E17D, E17E, E39B, E62,
Groundbased landings adjacent to any haul roads will be a minimum of 50 feet off the road surface, if feasible, unless otherwise agreed to in writing by the Forest Service.	E1C, E4A, E4B, E6A, E13, E15B, E16A, E16D, E16E, E16F, E17D, E17E, E39B, E62,
Protect all snags. If logging safety is jeopardized, however, snags may be felled and then left in the stand as coarse woody debris	All
Dedicated ground based skidtrails/roads shall terminate no closer than 60 feet from subdivision boundary unless otherwise agreed to by the Forest Service.	All
Ground based yarding operations with tractors will not operate on slopes exceeding 30%, or 50% with feller/bunchers, unless otherwise agreed to by the Forest Service.	E1C, E4A, E4B, E6A, E13, E15B, E16A, E16D, E16E, E16F, E17D, E17E, E39B, E62,
Logging plan maps designed by the Forest Service are for establishing average yarding distances for appraisal purposes only and are not part of this contract.	All
The locations of all skidtrails and skyline corridors will be approved prior to felling operations.	All