

SPECIFICATIONS PURSUANT TO C6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Landing Cleanup, All Units

Purchaser shall pile all slash accumulated at landing that is a minimum of 4 feet in length and 2 inches in diameter. Piles shall be reasonably compact and free of soil and noncombustible material to facilitate grinding or burning. Piles shall be of a size and location which will not impair road use or result in damage to residual timber. All objects which extend more than 6 feet in any direction from the pile profile will be cut off and returned to the pile. A loader, or similar machine equipped with a grapple or tongs may be necessary to accomplish the objectives of this specification.

Slash Cleanup, Unit Machine Pile, Units 3,4,5,8,10,12,& 13.

Purchaser shall treat all slash in the unit that is a minimum of 4 feet in length and 2 inches in diameter by piling with an excavator, or similar machine equipped with a grapple or bucket/thumb. Pile size shall be a minimum of 4 feet in height. No longer than 10 feet. Width of pile shall not exceed 10 feet. Piles shall be located a minimum of 15 feet from residual leave trees and existing snags. A snag is any standing bole 8 inches d.b.h. and 20 feet tall. Do not pile limbs, tops, or other slash within 50 feet of fences, cattle-guards or water troughs.

Tops Yarded, Slash Removal, Units 2, 6, 7, 9, 11, 15, 16, 17, 20, & 21

Purchaser shall leave tops attached to last log and yard to landing.