

Sale Name: Jack SBA

CT2.11# - TIMBER SUBJECT TO AGREEMENT (06/1972)

In addition, there is within Sale Area an unestimated quantity of:

| Species       | Product    |
|---------------|------------|
| Landing Piles | Grn Bio Cv |

that shall be Included Timber upon written agreement.

CT2.35# (OPTION 1) - INDIVIDUAL TREE DESIGNATION (06/2010)

All trees Marked with blue paint above and below stump height in cutting units designated ITM on the Sale Area Map and all trees less than 21.0" DBH, not marked with orange paint in cutting units designated LTM on the Sale Area Map which meet the minimum tree diameter stated in AT2 are designated for cutting. Additional timber to be cut, if any, will be designated for cutting in accordance with BT2.37.

Leave trees, Marked with orange, or identified by N/A are not to be cut, unless designated by the Forest Service.

CT4.211 - DOWNPAYMENT (06/2007)

The downpayment amount shown in AT15 may not be applied toward any other payment required under the provisions of this contract, except damages determined pursuant to BT9.4, transferred to other timber sales, or refunded until (a) stumpage value representing 25 percent of the total bid value of the timber sale is shown on Timber Sale Account to have been cut, removed, and paid for, or (b) the estimated value remaining to be cut and removed, as shown on Timber Sale Account, is equal to or less than the amount of the downpayment, or (c) if 36 CFR 223.49(e) is applicable, the estimated value remaining to be cut and removed, as shown on Timber Sale Account, is equal to or less than the amount of the downpayment. For lump sum timber sales, the downpayment may be applied to payment for release of the single payment unit.

If Forest Service makes a determination that this contract should not have been included under increased downpayment requirements (36 CFR 223.49(e)), the downpayment shall be revised and applied in accordance with 36 CFR 223.49(f).

Sale Name: Jack SBA

CT4.212 - TEMPORARY REDUCTION OF DOWNPAYMENT (08/2009)

Notwithstanding BT4.211 or CT4.211, upon the Purchaser's written request Forest Service may temporarily reduce the downpayment when Purchaser's scheduled operations are delayed or interrupted for 30 or more consecutive days, or the contract term is extended for 30 or more consecutive days for any of the following reasons:

- (1) Forest Service requests or orders Purchaser to delay or interrupt scheduled operations for reasons other than breach;
- (2) Purchaser interrupts or delays scheduled operations to work on a sale designated by the Forest Service as in urgent need of harvesting; or
- (3) An adjustment of the contract term authorized upon a determination of substantial overriding public interest, including a market-related contract term addition, or an urgent removal contract term extension under 36 CFR 223.53.

When Purchaser is not cutting or removing timber under contract during a qualifying period of delay, interruption, or extension listed above the downpayment may be reduced to \$1000 or 2 percent of the downpayment amount stated in the contract, whichever is greater. The Purchaser must restore the downpayment to the full amount stated in the contract within 15 days from receipt of the bill for collection and written notice from the Contracting Officer that the basis for temporarily reducing the downpayment no longer exists. Purchaser shall not cut or remove timber on a contract where the downpayment has been temporarily reduced until the downpayment amount stated in the contract is fully restored.

Sale Name: Jack SBA

CT4.4 - PAYMENTS NOT RECEIVED (08/2012)

(a) Payments are due and payable on the date of issue indicated on the bill for collection. When a payment for timber cut and other charges is not received at the location designated by Forest Service by the date specified in the bill for collection, Contracting Officer will suspend all or any part of Purchaser's Operations until payment or acceptable payment guarantee is received. Other charges include, but are not limited to:

- (i) Slash disposal and road maintenance deposits;
- (ii) Cooperative work at rates established by specific agreement under BT4.218;
- (iii) Damages pursuant to BT9.4;
- (iv) Road use fees;
- (v) Restoration of downpayment pursuant to BT4.22;
- (vi) Periodic payments pursuant to BT4.213;
- (vii) Extension Deposits pursuant to BT4.217; and
- (viii) Other mandatory deposits.

(b) Failure to pay amounts due by the date specified in the bill for collection shall be considered a breach under BT9.3. The 30-day notice period prescribed therein shall begin to run as of the end of business on the date specified for receipt of payments. If the performance or payment is guaranteed by surety bond, the surety will receive a copy of the written notification of breach. Demand will be made on the surety or other institution providing the guarantee or bond instrument for immediate payment 10 days after issuance of written notification of the breach.

(c) Pursuant to the Debt Collection Improvement Act of 1996, as amended, if payment is not received by Forest Service within 15 days after the date of issue indicated on the bill for collection:

(i) Simple interest shall be assessed at the Current Value of Funds Rate as established by the Secretary of the Treasury. Interest will begin to accrue as of the date of issue indicated on the initial bill for collection.

(ii) Debtors will be assessed administrative charges, in addition to the delinquent amount due. Administrative charges are those additional costs incurred by the Government in processing, handling, and collecting delinquent debts.

(iii) A penalty charge of six (6) percent per annum will be assessed on any portion of a debt delinquent more than 90 days. This penalty charge is in addition to interest and administrative charges under paragraphs (c)(i) and (c)(ii). The penalty charge shall accrue from the date of issue indicated on the bill for collection and shall be assessed on all outstanding amounts, including interest and administrative costs assessed under paragraphs (c)(i) and (c)(ii).

(iv) Payments will be credited on the date received by the Federal Depository or Collection Officer designated on the bill for collection.

(d) Forest Service remedies for Purchaser's failure to make payment for timber cut and other charges when due, except for accrual of interest, suspension of all or any part of Purchaser's Operations, and administrative offset, shall be stayed for so long as:

- (i) A bona fide dispute exists as to Purchaser's obligation to make such payment and
- (ii) Purchaser files and prosecutes a timely Claim.

Sale Name: Jack SBA

CT5.12# - USE OF ROADS BY PURCHASER (06/1999)

Purchaser's use of existing roads identified on Sale Area Map by the following codes is prohibited or subject to restrictive limitations, unless agreed otherwise:

| Code | Use Limitations   |
|------|---|
| X    | Hauling prohibited  |
| R    | Hauling restricted  |
| U    | Unsuitable for hauling prior to completion of agreed reconstruction |
| P    | Use prohibited  |
| A    | Public use restriction  |
| W    | Regulation waiver   |

Roads coded A will be signed by the Forest Service to inform the public of use restrictions. Purchaser's use of roads coded R, A, or W shall be in accordance with the following restrictions:

See Restricted Road List Table.

## TABLE PURSUANT TO CT5.12# - USE OF ROADS BY PURCHASER (06/1999)

## Restricted Road List

| Road Number              | Road Name | Termini         |              | Map Legend   | Description of Restrictions   |
|--------------------------|-----------|-----------------|--------------|--------------|---|
| All Roads                |           |                 |              | N/A          | Restrict commercial timber haul on holiday weekends and during the weekends of deer rifle hunting season. Restriction applies from Friday noon through Sunday noon or Monday noon to include the holiday. |
| All Native Surface Roads |           |                 |              | N/A          | Dry season/frozen haul conditions required on native surface roads to reduce road damage. If road surface is rutted 2 inches or deeper or ditch water is muddy, commercial timber haul will be suspended. |
| 12                       |           | Mile Post<br>20 | US HWY<br>26 | Map<br>Notes | Inadequate base and pavement. Use allowed during dry or frozen conditions only.   |
| 30                       |           | Rd 3000-<br>800 | Rd 12        | Map<br>Notes | Inadequate base and surfacing. Use allowed during dry or frozen conditions only.  |
| 4250                     |           | 4258            | RD 12        | Map<br>Notes | Inadequate base and surfacing. Use allowed during dry or frozen conditions only.  |
| All Roads with Bridges   |           |                 |              | N/A          | A USDA Forest Service bridge overload permit is required for all loads over 80,000 lbs.   |
| 4250-530                 |           | 4250            | 4250-531     | P            | Hauling of commercial timber prohibited.  |

Title and Date of Governing Road Rules Document:  
Ochoco National Forest  
Commercial Road Rules

June 2009  
Effective Date

Sale Name: Jack SBA

CT5.13# - ROAD COMPLETION DATE (04/2004)

Construction of Specified Roads shall be completed no later than 10/01/2014; except for earlier construction completion dates for roads listed below:

| Road<br>Number | Road Name | Station |    | Completion<br>Date |
|----------------|-----------|---------|----|--------------------|
|                |           | From    | To |                    |

Completion date is binding on the party that constructs road, whether Purchaser or Forest Service. Contracting Officer shall modify the completion date in writing to conform to the approved Plan of Operations under BT6.311 at the request of Purchaser.

When Purchaser elects Forest Service construction of Specified Roads shown in sale advertisement, Forest Service may adjust construction completion date when road construction is delayed or interrupted for causes that qualify for an adjustment of the completion date of Forest Service's road construction contract. When qualifying delays or interruptions of road construction occur, Forest Service shall evaluate such occurrences and document any findings. The current status of any adjustment shall be available to Purchaser on request. Promptly after the end of Normal Operating Season in which qualifying days occur, Forest Service shall give Purchaser written notice of (a) number of qualifying days claimed, and (b) new construction completion dates. After all road construction is complete, Forest Service shall grant Contract Term Adjustment. Such adjustment shall be limited to road completion date delays that occurred during Normal Operating Season.

If Forest Service is responsible for road construction and the actual date of road completion is 1 year or more after the completion date stated above, Purchaser may request a rate redetermination under BT3.3 for remaining volume. Such request must be made within 30 days of notification that road construction has been completed. Upon receipt of such request, Forest Service shall redetermine rates using standard methods in effect on the completion date of road construction. Rates to be established shall apply to all timber removed from Sale Area after the effective date of the rate redetermination.

Forest Service shall in no way be responsible for any delay or damage caused by road contractor in performing the road construction, except such delay as may be the fault or negligence of Forest Service.

When Purchaser constructs Specified Roads and requests Contract Term Adjustment, completion dates shall be adjusted by number of days that qualify for such adjustment, provided such qualifying days occur before specified construction completion date. When Purchaser desires to construct an alternate facility under BT5.26, Forest Service and Purchaser shall agree, in writing, on a construction completion date for alternate facility. Contract Term Adjustment as noted above will apply. Completion date shall be adjusted where a Design Change or physical changes necessitate a modification of Specified Road construction work that increases the scope or magnitude of the required work.

If Purchaser fails to complete construction of any or all Specified Roads by applicable completion date, as adjusted, Contract Term Extension shall not be granted.

As used in this Subsection, construction of a road is completed when:

(a) Purchaser constructs Specified Roads and Forest Service furnishes Purchaser with written notice of acceptance under BT6.36 or

(b) Forest Service constructs road and furnishes Purchaser with written notice authorizing use of road.

Sale Name: Jack SBA

Notwithstanding BT5.1, Purchaser shall not use a road that Purchaser has elected for Forest Service to construct, until construction is completed and Forest Service furnishes Purchaser with written notice authorizing use of road.

CT5.213# - DEPOSIT FOR RECONSTRUCTION ENGINEERING SERVICES (04/2004)

Purchaser shall make a cash deposit for engineering services (preconstruction and construction) provided by Forest Service for reconstruction of National Forest system roads necessary to accommodate Purchaser's use under this contract, pursuant to 16 USC 537.

The total amount to be deposited by Purchaser for reconstruction related engineering services to be completed by Forest Service personnel or by public works contract is \$6,800.00. Purchaser shall make this deposit at the end of the first full Normal Operating Season or 12 months from contract award, whichever occurs first. In the event a different deposit schedule is agreed to, such deposit shall be due within 15 days after the date of issue indicated on the initial bill for collection, pursuant to BT4.4.

The amount of the required deposit will be shown as an associated charge on Purchaser's Timber Sale Account. Forest Service shall retain any unexpended deposit for reconstruction related engineering services.

The deposit for reconstruction related engineering services shall be commensurate with project need and Purchaser's road use. Forest Service shall complete reconstruction related engineering services on the following schedule unless a different completion schedule is agreed in writing:

| Road or<br>Facility No. | Termini |      | Engineering Services<br>Completion Date |
|-------------------------|---------|------|---|
|                         | From    | To   |   |
| Road-12                 | 4.68    | 8.77 | 06/01/2014                              |

Reconstruction related engineering services may consist of some or all of the engineering work and expense of: preparing, setting out, controlling, inspecting, and measuring the reconstruction of a National Forest system road.

Sale Name: Jack SBA

CT5.221# - MATERIAL SOURCES (04/2004)

Sources of local materials are designated on Plans and Sale Area Map. Forest Service assumes responsibility for the quality and quantity of material in designated sources. Purchaser shall determine the equipment and work required to produce the specified product, including the selection of acceptable material that is reasonably available in the source that meets specifications. The designation of source includes the rights of Purchaser to use certain area(s) for plant site, stockpiles, and haul roads.

Should the designated source, due to causes beyond the control of Purchaser, contain insufficient acceptable material, Forest Service will provide another source with adjustment in accordance with BT5.253.

When Purchaser elects not to use designated sources, Purchaser shall furnish the specified product with no adjustment in unit rates. Quality testing shall be the responsibility of Purchaser. Test results shall be furnished to Forest Service.

When Purchaser elects not to use designated sources and the Schedule of Items lists pit development separately, cost allowance will be reduced under BT5.253 when Forest Service determines the work will not be required.

When materials are subject to a weight measurement, the specific gravity or weight/volume relationship used as a basis for determination of estimated quantities shall be:

Source I N/A, Source II N/A, and Source III N/A.

Purchaser may, when agreed in writing, use on the project such suitable stone, gravel, and sand, or other material found in the excavation, and will earn a cost allowance for the excavation of such materials at the corresponding contract unit price and for the pay items for which the excavated material is used. Purchaser shall replace, without additional cost allowance, sufficient suitable materials to complete the portion of the work, which was originally contemplated to be constructed with such material. Purchaser shall not excavate or remove any material, except that which is within the excavation limits, without written authorization from Forest Service.

When material is appraised from non-National Forest designated sources, owner charges for the material in terms of unit cost for royalties, purchase of raw materials, or finished products shall be as follows until N/A:

See Material Source Table.

Should quantity vary from that estimated, payment to owners shall be for units actually obtained. Purchaser shall make arrangements with owner(s) for measurement and payment for royalties, purchase of raw materials, or finished products, as shown above.

Materials produced or processed from National Forest lands in excess of the quantities required for performance of this contract are the property of Forest Service, unless prior written agreement has been obtained to use excess material on other National Forest sales. Forest Service is not obligated to reimburse Purchaser for the cost of their production.

Materials shall be stored to assure the preservation of their quality and fitness for the work. Stored materials shall be located to facilitate their prompt inspection. Sites on Forest Service administered land, approved by Forest Service, may be used for storage purposes and for the placing of Purchaser's plant equipment. All storage sites provided by Forest Service shall be restored at Purchaser's expense. Purchaser shall be responsible for making arrangements for storage on other than Forest Service adminis-

Sale Name: Jack SBA

tered lands.

When the construction of the portion of the project for which Temporary Roads used for hauling materials is completed, all such Temporary Roads shall be restored as nearly as practicable to their original ground profile, unless otherwise agreed in writing.

MATERIAL SOURCE TABLE PURSUANT TO CT5.221# - MATERIAL SOURCES (04/2004)

| Material | Type of Purchase | Owner (s) | Unit of Measure | Unit Price | Estimated Quantity | Total |
|----------|------------------|-----------|-----------------|------------|--------------------|-------|
| N/A      |                  |           |                 |            |                    |       |
|          |                  |           |                 |            |                    |       |
|          |                  |           |                 |            |                    |       |

Sale Name: Jack SBA

CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

Purchaser shall maintain roads in accordance with the following Contract Road Maintenance Requirements Summary:

See Contract Road Maintenance Requirements Summary Table.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| Road    | Termini |         | Miles | Maint.<br>Level | Applicable Pre-Haul Road Maintenance Specifications |       |       |       |       |       |       |       |       |       |       |
|---------|---------|---------|-------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|         | From    | To      |       |                 | T-803   | T-811 | T-831 | T-832 | T-834 | T-838 | T-839 | T-842 | T-851 | T-854 | T-891 |
| 12      | 1200196 | 2630    | 6.9   | 3               | p   | p     | p     |       | p     |       |       | p     | p     | p     | p     |
| 12      | 2630    | Hwy 26  | 8.75  | 4               | p   |       | p     |       | p     |       |       | p     | p     | p     | p     |
| 1200196 | 12      | 4258100 | 0.8   | 2               | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 1200350 | 12      | 4250600 | 0.2   | 2               | p   |       |       | p     |       | p     |       |       |       |       |       |
| 1200400 | 12      | 1200406 | 0.3   | 2               | p   |       | p     | p     | p     | p     |       |       |       | p     | p     |
| 1200406 | 1200400 | U 90    | 0.1   | 2               | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 1200410 | 4250600 | 1200411 | 0.3   | 2               | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 1200411 | 1200410 | U 93    | 0.1   | 2               | p   |       | p     | p     | p     | p     |       |       |       | p     | p     |
| 1200440 | 12      | 4250700 | 0.1   | 2               | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 1200500 | 12      | 1200501 | 0.2   | 1               | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 1200501 | 1200500 | U 63    | 0.4   | 1               | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 1200502 | 1200520 | U 67    | 0.1   | 1               | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 1200510 | 12      | 1200511 | 0.1   | 1               | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 1200515 | 12      | U 63    | 0.3   | 2               | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 1200520 | 12      | END     | 0.3   | 2               | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 1200600 | 12      | U 53    | 0.7   | 2               | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 1200601 | 1200600 | U 53    | 0.3   | 1               | p   |       | p     |       |       |       | p     |       |       | p     | p     |
| 1200607 | 12      | U 51    | 0.2   | 1               | p   |       | p     |       |       |       | p     |       |       | p     | p     |
| 1200613 | 12      | U 49    | 0.5   | 1               | p   |       | p     |       |       |       | p     |       |       | p     | p     |
| 1200614 | 12      | U 52    | 0.2   | 1               | p   |       | p     |       |       |       | p     |       |       | p     | p     |
| 1200700 | 12      | U 57    | 0.5   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200702 | 12      | U 50    | 0.1   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200704 | 12      | END     | 0.1   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200706 | 1200702 | 1200704 | 0.1   | 1               | p   |       | p     |       |       |       | p     |       |       | p     | p     |
| 1200720 | 12      | END     | 0.3   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200724 | 1200725 | END     | 0.2   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200725 | 12      | 3000900 | 2.58  | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200726 | 1200725 | SEDU 60 | 0.7   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200727 | 1200725 | 3000900 | 0.2   | 2               | p   |       | p     | p     |       | p     |       |       |       |       |       |
| 1200731 | 1200725 | ED U 60 | 0.2   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200737 | 12      | U 43    | 0.3   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 1200740 | 12      | END     | 0.6   | 2               | p   |       | p     | p     |       | p     |       |       |       | p     | p     |
| 22      | 3010150 | 2200602 | 0.9   | 3               | p   | p     | p     |       | p     |       |       | p     | p     | p     | p     |

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,

OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO

CTS\_31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| Road    | Termini |           | Miles | Maint. Level | Applicable Pre-Haul Road Maintenance Specifications |       |       |       |       |       |       |       |       |       |       |
|---------|---------|-----------|-------|--------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|         | From    | To        |       |              | T-803   | T-811 | T-831 | T-832 | T-834 | T-838 | T-839 | T-842 | T-851 | T-854 | T-891 |
| 2630    | 12      | 3000800   | 3.2   | 2            | p   |       | p     | p     | p     | p     |       |       |       | p     | p     |
| 2630810 | 2630    | UNIT 165  | 0.1   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 2630830 | 2630    | SWCORU 44 | 0.2   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 2630840 | 2630    | U 47      | 0.7   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 2630841 | 2630840 | Unit 46   | 0.7   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 2630841 | 30      | Unit 56   | 0.7   | 2            | p   |       |       | p     |       | p     | p     |       |       | p     | p     |
| 2630850 | 2630    | SED U 41  | 0.7   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 2630852 | 2630850 | U 47      | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 2630853 | 2630850 | END       | 0.5   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 2630854 | 2630853 | END       | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 2630860 | 2630    | SED U 48  | 0.3   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 2630861 | 2630860 | UNIT 48   | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 30      | 3010    | 12        | 15    | 3            | p   | p     | p     |       | p     |       |       | p     | p     | p     | p     |
| 3000800 | 2630    | 3000870   | 0.4   | 2            | p   |       | p     | p     | p     | p     |       |       |       |       |       |
| 3000858 | 30      | UNIT 124  | 0.9   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 3000859 | 3000858 | UNIT 124  | 0.4   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 3000870 | 3000800 | UNIT 58   | 0.3   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 3000870 | 30      | Temp RD   | 0.5   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 3000875 | 30      | SEU 154   | 0.7   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 3000885 | 30      | UNIT 69   | 0.4   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 3000900 | 30      | 3000930   | 3.6   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 3000910 | 3000900 | UNIT 173  | 0.2   | 2            | p   |       | p     | p     | p     | p     |       |       |       | p     | p     |
| 3000930 | Temp RD | SE U 94   | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 3000935 | 3000900 | 3000900   | 1.6   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 3010    | 3010150 | 30        | 1.3   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 3010150 | 22      | 3010      | 2.2   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 4250    | 4250600 | 12        | 2.7   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 4250530 | 4250600 | U 87      | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 4250600 | 4250    | UNIT93    | 3.0   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 4250600 | 1200350 | 4250606   | 0.5   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 4250604 | 4250600 | UNIT 93   | 0.2   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 4250606 | 4250600 | Unit 90   | 1.0   | 1            | p   |       |       |       |       |       | p     |       |       | p     | p     |
| 4250610 | Unit 70 | Unit 75   | 1.1   | 2            | p   |       |       | p     |       | p     |       |       |       | p     | p     |
| 4250700 | 1200440 | Unit 129  | 0.1   | 1            | p   |       | p     |       | p     |       | p     |       |       | p     | p     |
| 4258100 | 1200196 | 4258106   | 0.6   | 2            | p   | p     | p     | p     | p     | p     |       | p     | p     | p     | p     |
| 4258106 | 4258100 | U 99      | 0.2   | 2            | p   | p     | p     | p     | p     | p     |       | p     | p     | p     | p     |
| 4276    | 42      | 4276010   | 0.2   | 2            | p   | p     | p     | p     | p     | p     |       | p     | p     | p     | p     |
| 4276010 | 4276    | WELL      | 0.1   | 2            | p   | p     | p     | p     | p     | p     |       |       |       | p     | p     |

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,

OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO  
 CTS 31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| Road    | Termini |          | Miles | Maint.<br>Level | Applicable During-Haul Road Maintenance Specifications |       |       |       |       |       |       |       |       |       |       |
|---------|---------|----------|-------|-----------------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|         | From    | To       |       |                 | T-803  | T-811 | T-812 | T-831 | T-832 | T-834 | T-838 | T-839 | T-851 | T-854 | T-891 |
| 12      | 1200196 | 2630     | 6.9   | 3               | P  | P     | P     | P     |       | P     |       |       | P     | P     | P     |
| 12      | 2630    | Hwy 26   | 8.75  | 4               | P  |       | P     | P     |       | P     |       |       | P     | P     | P     |
| 1200196 | 12      | 4258100  | 0.8   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200350 | 12      | 4250600  | 0.2   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200400 | 12      | 1200406  | 0.3   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200406 | 1200400 | u 90     | 0.1   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200410 | 4250600 | 1200411  | 0.3   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200411 | 1200410 | U 93     | 0.1   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200440 | 12      | 4250700  | 0.1   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200500 | 12      | 1200501  | 0.2   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200501 | 1200501 | U 63     | 0.4   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200502 | 1200520 | U 67     | 0.1   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200510 | 12      | 1200511  | 0.1   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200515 | 12      | U 63     | 0.3   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200520 | 12      | END      | 0.3   | 2               | P  | P     | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200600 | 12      | U 53     | 0.7   | 2               | P  | P     | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200601 | 1200600 | U 53     | 0.3   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200607 | 12      | U 51     | 0.2   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200613 | 12      | U 49     | 0.5   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200614 | 12      | U 52     | 0.2   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200700 | 12      | U 57     | 0.5   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200702 | 12      | U 50     | 0.1   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200704 | 12      | END      | 0.1   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200706 | 1200702 | 1200704  | 0.1   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200720 | 12      | END      | 0.3   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200724 | 1200725 | END      | 0.2   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200725 | 12      | 3000900  | 2.58  | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200726 | 1200725 | SED U 60 | 0.7   | 1               | P  |       | P     | P     |       | P     |       | P     |       | P     | P     |
| 1200727 | 1200725 | 3000900  | 0.2   | 2               | P  |       | P     | P     | P     | P     | P     |       |       |       |       |
| 1200731 | 1200725 | ED U 60  | 0.2   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200737 | 12      | U 43     | 0.3   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 1200740 | 12      | END      | 0.6   | 2               | P  |       | P     | P     | P     | P     | P     |       |       | P     | P     |
| 22      | 3010150 | 2200602  | 0.9   | 3               | P  | P     | P     | P     |       | P     |       |       |       | P     | P     |

CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO  
 CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| Road    | Termini |           | Miles | Maint.<br>Level | Applicable During-Haul Road Maintenance Specifications |       |       |       |       |       |       |       |       |       |       |
|---------|---------|-----------|-------|-----------------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|         | From    | To        |       |                 | T-803  | T-811 | T-812 | T-831 | T-832 | T-834 | T-838 | T-839 | T-851 | T-854 | T-891 |
| 2630    | 12      | 3000800   | 3.2   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 2630810 | 2630    | UNIT 165  | 0.1   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 2630830 | 2630    | SWCORU 44 | 0.2   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 2630840 | 2630    | U 47      | 0.7   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 2630841 | 2630840 | U 46      | 0.7   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 2630841 | 30      | U 56      | 0.7   | 2               | p  |       |       | p     |       | p     | p     |       |       | p     | p     |
| 2630850 | 2630    | SED U 41  | 0.7   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 2630852 | 2630850 | U 47      | 0.2   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 2630853 | 2630850 | END       | 0.5   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 2630854 | 2630853 | END       | 0.2   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 2630860 | 2630    | SED U 48  | 0.3   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 2630861 | 2630860 | U 48      | 0.2   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 30      | 3010    | 12        | 15    | 3               | p  | p     | p     | p     |       | p     |       |       | p     | p     | p     |
| 3000800 | 2630    | 3000870   | 0.4   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000858 | 30      | U 124     | 0.9   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000859 | 3000858 | U 124     | 0.4   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 3000870 | 3000800 | U 58      | 0.3   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000870 | 30      | Temp RD   | 0.5   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000875 | 30      | SEDU 154  | 0.7   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 3000885 | 30      | UNIT 69   | 0.4   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 3000900 | 30      | 3000930   | 3.6   | 2               | p  | p     | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000910 | 3000900 | U 173     | 0.2   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 3000930 | Temp RD | SECOR 94  | 0.2   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 3000935 | 3000900 | 3000900   | 1.6   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 3010    | 3010150 | 30        | 1.3   | 2               | p  | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 3010150 | 22      | 3010      | 2.2   | 2               | p  | p     | p     | p     | p     | p     |       |       |       | p     | p     |
| 4250    | 4250600 | 12        | 2.7   | 2               | p  | p     | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4250530 | 4250600 | U 87      | 0.2   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 4250600 | 4250    | UNIT93    | 3     | 2               | p  | p     | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4250600 | 1200350 | 4250606   | 0.5   | 2               | p  | p     | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4250604 | 4250600 | U 93      | 0.2   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 4250606 | 4250600 | U 90      | 1.0   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 4250610 | U 70    | U 75      | 1.1   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4250700 | 1200440 | U 129     | 0.1   | 1               | p  |       | p     | p     |       | p     |       | p     |       | p     | p     |
| 4258100 | 1200196 | 4258106   | 0.6   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4258106 | 4258100 | U 99      | 0.2   | 2               | p  |       | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4276    | 42      | 4276010   | 0.2   | 2               | p  | p     | p     | p     | p     | p     | p     |       |       | p     | p     |
| 4276010 | 4276    | WELL      | 0.1   |                 |  | p     | p     |       |       |       |       |       |       |       |       |

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,

OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit

Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.



CONTRACT ROAD MAINTENANCE REQUIREMENTS SUMMARY TABLE PURSUANT TO  
 CT5\_31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| Road    | Termini |           | Miles | Maint. Level | Applicable Post-Haul Road Maintenance Specifications |       |       |       |       |       |       |  |  |   |
|---------|---------|-----------|-------|--------------|--|-------|-------|-------|-------|-------|-------|--|--|---|
|         | From    | To        |       |              | T-811  | T-831 | T-834 | T-835 | T-838 | T-839 | T-891 |  |  |   |
| 2630    | 12      | 3000800   | 3.2   | 2            |  | p     | p     |       | p     |       | p     |  |  |   |
| 2630810 | 2630    | UNIT 165  | 0.1   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 2630830 | 2630    | SWCORU 44 | 0.2   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 2630840 | 2630    | U 47      | 0.7   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 2630841 | 2630840 | U 46      | 0.7   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 2630841 | 30      | Unit 56   | 0.7   | 2            |  | p     | p     |       | p     |       | p     |  |  |   |
| 2630850 | 2630    | SED U 41  | 0.7   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 2630852 | 2630850 | U 47      | 0.2   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 2630853 | 2630850 | END       | 0.5   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 2630854 | 2630853 | END       | 0.2   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 2630860 | 2630    | UNIT 48   | 0.3   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 2630861 | 2630860 | U 48      | 0.2   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 30      | 3010    | 12        | 15    | 3            | p  | p     | p     |       |       |       |       |  |  | p |
| 3000800 | 30      | 2630      | 1.9   | 2            |  | p     | p     |       | p     |       | p     |  |  |   |
| 3000858 | 30      | U 124     | 0.9   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 3000859 | 2630860 | UNIT 124  | 0.4   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 3000870 | 3000800 | U 58      | 0.3   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 3000870 | 30      | Temp RD   | 0.5   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 3000875 | 30      | SEDU 154  | 0.7   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 3000885 | 30      | UNIT 69   | 0.4   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 3000900 | 30      | 3000930   | 3.6   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 3000910 | 3000900 | U 173     | 0.2   | 2            |  | p     | p     |       | p     |       | p     |  |  |   |
| 3000930 | Temp RD | SECOR 94  | 0.2   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 3000935 | 3000900 | 3000900   | 1.6   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 3010    | 3010150 | 30        | 1.3   | 2            | p  | p     | p     |       | p     |       |       |  |  |   |
| 3010150 | 22      | 3010      | 2.2   | 2            |  |       |       |       | p     |       |       |  |  |   |
| 4250    | 4250600 | 12        | 2.7   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4250600 | 4250    | UNIT93    | 3     | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4250600 | 1200350 | 4250606   | 0.5   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4250604 | 4250600 | U 93      | 0.2   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 4250606 | 4250600 | Unit 90   | 1     | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 4250610 | U 70    | U 75      | 1.1   | 2            |  |       |       |       | p     |       | p     |  |  |   |
| 4250700 | 1200440 | U 129     | 0.1   | 1            |  |       |       | p     |       | p     | p     |  |  |   |
| 4258100 | 1200196 | 4258106   | 0.6   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4258106 | 4258100 | U 99      | 0.2   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4276    | 42      | 4276010   | 0.2   | 2            | p  | p     | p     |       | p     |       | p     |  |  |   |
| 4276010 | 4276    | WELL      | 0.1   |              | p  |       |       |       |       |       |       |  |  |   |

P = Purchaser Performance Item, D = Deposit to Forest Service, D3 = Deposit to Third Party,  
 OPT = Optional, SPS = Special Project Specification, EOU = End Of Unit  
 Description of work required by the above listed T-specs is shown in the following ROAD MAINTENANCE  
 REQUIREMENTS SPECIFICATION table, and included in the timber sale contract.

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
 CTS.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini              | 2<br>Special<br>Project<br>Specification                      | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing                       | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|--|---|-----------------|------------|------|---------------------------------|--------------------------------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|  |   | Width           | X<br>Slope | Comp |                                 |                                      | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 12<br>1200196<br>to<br>2630                  | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-891-01F              | EX              | AI         | A    | 2' Lt & Rt                      | SRR<br>Deposit<br>See<br>CTS.32#     | OPT                 |                  | EX    |                                  | JU                   |                |       |
| 12<br>2630<br>to<br>Hwy 26                   | T-803-01F<br>T-834-01F  |                 |            |      | 2' Lt & Rt                      | Ashpalt<br>Deposit<br>See<br>CTS.32# |                     |                  |       |                                  | JU                   |                |       |
| 1200196<br>12<br>to<br>4258100               | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200350<br>12<br>to<br>4250600               | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200400<br>12<br>to<br>1200406               | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-838                           |                                      | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 1200406<br>1200400<br>to<br>U 90             | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 1200410<br>4250600<br>TO<br>1200411          | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 1200411<br>1200410<br>TO<br>U 93             | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 1200440<br>12<br>to<br>4250700               | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200500<br>12<br>to<br>1200501               | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200501<br>1200500<br>to<br>U 63             | T-803-01F<br>T-812-01F<br>T-835-01F<br>T-891-01F              |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200502<br>1200520<br>to<br>W.ED.<br>UNIT 67 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini                | 2<br>Special<br>Project<br>Specification                      | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|--|---|-----------------|------------|------|---------------------------------|----------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|  |   | Width           | X<br>Slope | Comp |                                 |                | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 1200510<br>12<br>to<br>1200511                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200515<br>12<br>to<br>unit 63                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200520<br>12<br>to<br>END                     | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-838                           |                | OPT                 |                  | EX    |                                  | TS                   |                |       |
| 1200600<br>12<br>to<br>NE COR.<br>UNIT 53      | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-838                           |                | OPT                 |                  | EX    |                                  | TS                   |                |       |
| 1200601<br>1200600<br>to<br>NW COR.<br>UNIT 53 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    |                                  | TS                   |                |       |
| 1200607<br>12<br>to<br>UNIT 51                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200613<br>12<br>to<br>UNIT 49                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200614<br>12<br>to<br>UNIT 52                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200700<br>12<br>to<br>UNIT 57                 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200702<br>12<br>to<br>N ED.<br>UNIT 50        | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
 CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini             | 2<br>Special<br>Project<br>Specification                      | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|---|---|-----------------|------------|------|---------------------------------|----------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|   |   | Width           | X<br>Slope | Comp |                                 |                | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 1200704<br>12<br>to<br>END                  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200706<br>1200702<br>to<br>1200704         | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200720<br>12<br>TO<br>END                  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200724<br>1200725<br>to<br>END             | T-803-01F<br>T-812-01F<br>T-835-01F<br>T-891-01F              |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200725<br>12<br>to<br>3000900              | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-891-01F              |                 |            |      | T-838                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200726<br>1200725<br>to<br>S ED UNIT<br>60 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 1200727<br>1200725<br>to<br>3000900         | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200731<br>1200725<br>to<br>ED UNIT<br>60   | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200737<br>12<br>to<br>UNIT 43              | T-803-01F<br>T-812-01F<br>T-835-01F<br>T-891-01F              |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 1200740<br>12<br>to<br>END                  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      |                                 |                | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 22<br>3010150<br>to<br>2200602              | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-891-01F              | EX              | AI         | A    | 2' Lt & Rt                      |                | OPT                 |                  | EX    |                                  | JU                   |                |       |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini            | 2<br>Special<br>Project<br>Specification                          | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing                       | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|--|---|-----------------|------------|------|---------------------------------|--------------------------------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|  |   | Width           | X<br>Slope | Comp |                                 |                                      | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 2630<br>12<br>to<br>3000800                | T-803-01F<br><br>T-834-01F  |                 |            |      | 2' Lt & Rt                      | Asphalt<br>Deposit<br>See<br>CT5.32# |                     |                  |       |                                  | TS                   |                |       |
| 2630810<br>2630<br>to<br>S ED Unit<br>165  | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 2630830<br>2630<br>to<br>SW COR<br>UNIT 44 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 2630840<br>2630<br>to<br>UNIT 47           | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 2630841<br>2630840<br>to<br>UNIT 46        | T-803-01F<br>T-812-01F<br>T-835-01F<br>T-891-01F                  |                 |            |      | T-838                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 2630841<br>30<br>TO<br>UNIT 56             | T-803-01F<br>T-812-01F<br>T-835-01F<br>T-891-01F                  |                 |            |      | T-838                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 2630850<br>2630<br>to<br>S ED UNIT<br>41   | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 2630852<br>2630850<br>TO<br>UNIT 47        | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 2630853<br>2630850<br>to<br>END            | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 2630854<br>2630853<br>to<br>END            | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 2630860<br>2630<br>to<br>SW COR<br>UNIT 48 | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                      | OPT                 |                  | EX    | W                                | TS                   |                | PR    |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
 CTS.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini               | 2<br>Special<br>Project<br>Specification                      | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing                   | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|---|---|-----------------|------------|------|---------------------------------|----------------------------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|   |   | Width           | X<br>Slope | Comp |                                 |                                  | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 2630861<br>2630860<br>to<br>S E D UNIT<br>48  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 30<br>3010<br>to<br>12                        | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-891-01F              | EX              | AI         | A    | 2' Lt & Rt                      | SRR<br>Deposit<br>See<br>CTS.32# | OPT                 |                  | EX    |                                  | JU                   |                |       |
| 3000800<br>2630<br>to<br>3000870              | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F |                 |            |      | T-838                           |                                  | OPT                 |                  | EX    |                                  | TS                   |                | PR    |
| 3000858<br>30<br>to<br>E E D UNIT<br>124      | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 3000859<br>2630860<br>to<br>S E D UNIT<br>124 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 3000870<br>3000800<br>to<br>E E D UNIT<br>58  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | T-803-01F            |                | PR    |
| 3000870<br>30<br>TO<br>TEMP<br>ROAD           | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | T-803-01F            |                | PR    |
| 3000875<br>30<br>to<br>S E D UNIT<br>154      | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 3000885<br>30<br>to<br>S E D UNIT<br>69       | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                                  | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 3000900<br>30<br>to<br>3000930                | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F | EX              | AI         | A    | T-838                           | SRR<br>Deposit<br>See<br>CTS.32# | OPT                 |                  | EX    |                                  | TS                   |                |       |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
CTS.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1  | 2   | 3          |         |      | 4                    | 5                                    | 6              |               |       | 7                    | 8            | 9         |       |
|--|---|------------|---------|------|----------------------|--------------------------------------|----------------|---------------|-------|----------------------|--------------|-----------|-------|
| Road No. and Termini                         | Special Project Specification                                     | Travel Way |         |      | Brushing and Log Out | Surfacing                            | Dust Abatement |               |       | Seasonal Maintenance | Snow Removal | Post Haul |       |
|  |   | Width      | X Slope | Comp |                      |                                      | Product        | Applicat Rate | Width |                      |              | Block     | Treat |
| 3000910<br>3000900<br>to<br>S ED UNIT<br>173 | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-834-01F<br>T-891-01F | EX         | AI      | A    | T-838                | SRR<br>Deposit<br>See<br><br>CTS.32# | OPT            |               | EX    |                      | TS           |           |       |
| 3000930<br>TEMP RD<br>to<br>S ED UNIT<br>94  | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-835-01F<br>T-891-01F |            |         |      | T-839                |                                      | OPT            |               | EX    | W                    | TS           | PR        | PR    |
| 3000935<br>3000900<br>to<br>3000900          | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |            |         |      | T-839                |                                      | OPT            |               | EX    | W                    | TS           | PR        | PR    |
| 3010<br>30<br>to<br>3010150                  | T-803-01F<br>T-812-01F<br>T-834-01F<br>T-891-01F                  | EX         | AI      | A    | 2' Lt & Rt           | SRR<br>Deposit<br>See<br>CTS.32#     | OPT            |               | EX    |                      | JU           |           |       |
| 3010150<br>3010<br>to<br>22                  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F     |            |         |      | T-838                |                                      | OPT            |               | EX    |                      | TS           |           | PR    |
| 4250<br>4250600<br>to<br>12                  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F     | EX         | AI      | A    | T-836                | SRR<br>Deposit<br>See<br>CTS.32#     | OPT            |               | EX    |                      | TS           |           |       |
| 4250530<br>4250600<br>TO<br>E ED<br>UNIT 87  | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F     |            |         |      | T-839                |                                      | OPT            |               | EX    | W                    | TS           | PR        | PR    |
| 4250600<br>4250<br>to<br>S ED UNIT<br>93     | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-834-01F<br>T-891-01F | EX         | AI      | A    | T-838                | SRR<br>Deposit<br>See<br><br>CTS.32# | OPT            |               | EX    |                      | TS           |           |       |
| 4250600<br>1200350<br>TO<br>4250606          | T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F                  |            |         |      | T-839                |                                      | OPT            |               | EX    | W                    | TS           | PR        | PR    |
| 4250604<br>4250600<br>to<br>E ED UNIT<br>93  | T-803-01F<br>T-812-01F<br>T-832-01F<br><br>T-835-01F<br>T-891-01F |            |         |      | T-839                |                                      | OPT            |               | EX    | W                    | TS           | PR        | PR    |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (07/2001)

| 1<br>Road No.<br>and<br>Termini               | 2<br>Special<br>Project<br>Specification                      | 3<br>Travel Way |            |      | 4<br>Brushing<br>and<br>Log Out | 5<br>Surfacing | 6<br>Dust Abatement |                  |       | 7<br>Seasonal<br>Mainte<br>nance | 8<br>Snow<br>Removal | 9<br>Post Haul |       |
|---|---|-----------------|------------|------|---------------------------------|----------------|---------------------|------------------|-------|----------------------------------|----------------------|----------------|-------|
|   |   | Width           | X<br>Slope | Comp |                                 |                | Product             | Applicat<br>Rate | Width |                                  |                      | Block          | Treat |
| 4250606<br>4250600<br>to<br>UNIT 90           | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 4250610<br>N END 70<br>to<br>S END<br>UNIT 75 | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 4250700<br>1200440<br>to<br>UNIT 129          | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 4258100<br>1200196<br>TO<br>4258106           | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   |                | PR    |
| 4258106<br>4258100<br>TO<br>Temp<br>RD        | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-835-01F<br>T-891-01F |                 |            |      | T-839                           |                | OPT                 |                  | EX    | W                                | TS                   | PR             | PR    |
| 4276<br>42<br>to<br>4276010                   | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F | EX              | AI         | AI   | T-836                           |                | OPT                 |                  | EX    |                                  |                      |                |       |
| 4276010<br>4276<br>to<br>Morgan<br>Well       | T-803-01F<br>T-812-01F<br>T-832-01F<br>T-834-01F<br>T-891-01F |                 |            |      | T-836                           |                | OPT                 |                  | EX    |                                  |                      |                |       |

ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (7/01)

| Column No. | Heading                       | Entry                | Explanation   |
|------------|-------------------------------|----------------------|---|
|            | Any                           | Blank                | Except as otherwise described, no entry indicates Purchaser is not authorized or required to perform the work item(s).  |
|            | Any                           | RC                   | This work requirement applies only when haul of sale related construction materials occurs.   |
| 2          | Special Project Specification | Number               | Entry indicates Special Project Specification which applies.  |
| 3          | Travel Way                    | EX                   | Purchaser shall maintain the traveled way to the width existing upon entry, or at the completion of Specified Road work.  |
|            |                               | Numbers              | Purchaser shall maintain the traveled way to the standard width indicated by the entry, plus curve widening, in accordance with Section T-811. If required, the road template shall be shaped to this width and to the designated cross slope before haul and during recurring maintenance. |
|            |                               | IS, C, OS, F, or AI  | Cross slopes are designated as:<br>IS (Inslope), C (Crown), OS (Outslope), F (Flat), AI (As Is).  |
|            |                               | A or B               | If compaction is required.  |
| 4          | Brush and Log Out             | Numeric & R and or L | Purchaser shall remove brush for specified width on either or both the right (R) side or left (L) side of road.   |
|            |                               | As Staked            | Limits of brushing are as staked or marked in the field.  |
|            |                               | OPT                  | Purchaser may use hand or mechanical means of brushing.   |
|            |                               | H                    | Only hand brushing may be used.   |


ROAD MAINTENANCE REQUIREMENTS SPECIFICATION CODES TABLE PURSUANT TO  
CT5.31# - ROAD MAINTENANCE REQUIREMENTS (7/01)

| Column No. | Heading              | Entry             | Explanation   |
|------------|----------------------|-------------------|---|
| 5          | Surfacing            | Aggregate Grading | Purchaser shall place surfacing on roads listed according to the grading indicated.   |
| 6          | Dust Abatement       | OPT               | Product selection is Purchaser's choice from those listed in Section T-812.   |
|            |                      | Product Abbr.     | Unless otherwise agreed, Purchaser is restricted to product listed corresponding to the abbreviation shown in Section T-812; (i.e., LigS = Lignon Sulfonate) Application rates are estimated amounts. |
|            |                      | EX                | Purchaser shall abate dust on the existing width  |
|            |                      | Numbers           | Purchaser shall abate dust to the width indicated by entry.   |
| 7          | Seasonal Maintenance | W                 | Waterbars and/or crossditching shall be required prior to expected seasonal precipitation.  |
|            |                      | B                 | Entrance barriers shall be installed by Purchaser prior to nonuse periods.  |
| 8          | Snow Removal         | TS                | Snowplowing authorized for Purchaser's Operations without recreation access being provided per Section T-803 requirements.  |
|            |                      | JU                | Snowplowing authorized, but must provide for recreation joint use per Section T-803 requirements.   |
|            |                      | Blank             | Snowplowing is not authorized. Forest Service may authorize plowing by permit when not in conflict with other uses.   |
| 9          | Post Haul            | PR                | PR denotes that work is Purchaser's Responsibility to perform.  |


Individual T-Specifications listed below and attached are not individually page numbered.

| <b>T-SPECIFICATION LIST</b> |  |                          |
|-----------------------------|--|--------------------------|
|                             |  | Last<br>Revision<br>Date |
| Spec. No.                   | Title  |                          |
| T-803                       | Snow Removal   | 05/07                    |
| T-803-01F                   | SPS Snow Removal                                     | 06/03                    |
| T-811                       | Blading  | 10/07                    |
| T-812                       | Dust Abatement                                       | 05/09                    |
| T-812-01F                   | SPS Dust Abatement                                   | 06/03                    |
| T-831                       | Ditch Maintenance                                    | 10/07                    |
| T-832                       | Remove and End Haul Materials                        | 05/07                    |
| T-832-01F                   | SPS Remove and End Haul Materials                    | 06/03                    |
| T-834                       | Drainage Structure Maintenance                       | 10/07                    |
| T-834-01F                   | SPS Drainage Structure Maintenance                   | 06/03                    |
| T-835                       | Roadway Drainage Maintenance                         | 05/07                    |
| T-835-01F                   | SPS Roadway Drainage Maintenance                     | 06/03                    |
| T-838                       | Maintenance For High Clearance Vehicle Use           | 05/07                    |
| T-839                       | Maintenance For Project Use                          | 05/07                    |
| T-842                       | Cutting Roadway Vegetation                           | 10/07                    |
| T-851                       | Logging Out  | 05/07                    |
| T-854                       | Treatment and Disposal of Danger Trees               | 04/10                    |
| T-891                       | Water Supply and Watering                            | 05/07                    |
| T-891-01F                   | SPS Water Supply and Watering                        | 06/03                    |
|                             |  |                          |
| Drawing No.                 | Title  |                          |
| T-801                       | Road Structure Details                               | 06/03                    |
| T-834                       | Typical Section of Catch Basins and Transition Areas | 06/03                    |
| T-835-02                    | Standard Detail for Water Bar                        | 06/03                    |


# ROAD STRUCTURE DETAILS




## DEFINITIONS BY SURFACING TYPE



### ASPHALT PAVED SURFACING SECTION



### AGGREGATE SURFACING SECTION



### NATIVE MATERIAL SURFACING SECTION

**NOTES**  
TEMPER AND DIMENSIONS WILL VARY WITH LOCAL CONDITIONS

|         |  |          |
|---------|--|----------|
| TITLE   | ILLUSTRATION OF ROAD MAINTENANCE TERMS |          |
| DRAWING | 801-1                                  | APPROVED |

## T-803 - SNOW REMOVAL (05/07)

### 803.01 Description

This Section provides for removal of snow from roads to facilitate logging operations and safe use.

### 803.02 Maintenance Requirements

- (1) Erect signs required by the Sign Plan in the SUPPLEMENTAL SPECIFICATIONS.
- (2) Perform work in a manner to preserve and protect roads and appurtenances, and prevent erosion damage to roads, streams, and other Forest values.
- (3) Do not undercut banks. Do not blade gravel or other surfacing material off the road.
- (4) Keep roadbed drainage ditches, drain dips, and culverts functional when needed during operations and upon completion of operations.
- (5) Control snow removal to identify the usable traveled way having roadbed support. Reshape over-width plowing as necessary to define the usable width.
- (6) Space, construct, and maintain drainage holes in the dike of snow or berm caused by snow removal operations. Place drain holes to obtain surface drainage without discharging on erodible fills.
- (7) Close roads to wheeled vehicles at times and in the manner specified in C(T)5.12 or the Road Rules document.
- (8) Upon seasonal completion of Purchaser's Operations, effectively block the road by a snow barricade, unless otherwise approved by the Contracting Officer.
- (9) Remove snow for either public access or project use as established in the SUPPLEMENTAL SPECIFICATIONS and meet the following requirements:

(a) Removal for Public Access (Method JU) - Remove snow from all of the traveled way, including turnouts, for safe and efficient use for both timber transportation and the public. Remove intruding windfalls, debris, or slough and slide material for the full width of the traveled way and deposit out of drainage's at locations designated by the Contracting Officer.

(b) Removal for Project Use (Method TS) - Remove snow from all or part of the traveled way, including sufficient turnouts for safe and efficient use for timber transportation and to protect the road. Remove intruding windfalls, debris or slough and slide material and dispose of only as necessary to provide passage for timber transportation. Removed materials may be deposited off the traveled way or outside the traveled way at locations designated by the Contracting Officer.

(10) When directed by the Contracting Officer, replace in kind, within sixty (60) days after the start of Normal Operating Season, any surfacing material which has been bladed off the road, unless otherwise agreed. Contracting Officer will notify Purchaser in writing as to the cubic yard equivalent of bladed off material by the start of the normal operating season.

#### 803.03 Equipment

Purchaser may use any type of equipment to remove snow, providing:

- a. Type or use of equipment is not restricted in C(T)5.12 or Road Rules document.
- b. Equipment is of the size and type commonly used to remove snow and will not cause damage to the road.
- c. The use of plows or dozers to remove snow requires written approval by the Contracting Officer. Equip plows or dozers with shoes or runners to keep the dozer blade a minimum of 2 inches above the road surface unless otherwise approved by the Contractor Officer.

#### 803.04 Ice Control

Ice control may be performed by Purchaser when approved by the Contracting Officer in writing. Such approval will include ice control materials, application rates, and any specific requirements of use.

SPECIAL PROJECT SPECIFICATION (6/03)

T-803-01F

SNOW REMOVAL

803.02 Maintenance Requirements

- a. Delete the paragraph and add the following: The Traffic Control Plan specified in B(T)6.33 Safety will be amended as needed for snow removal operations under b. (9) (a) or (b).
  
- b. (1) Delete the sentence and add the following: Erect signs required by the amended Traffic Control Plan and Drawings specified in B(T)6.33 Safety.  
  
(9) Delete the sentence and add the following: Remove snow for either public access or project use as listed in C(T)5.31# Road Maintenance Requirements, and meet the requirements set forth in the amended Traffic Control Plan.

## T-811 BLADING (10/07)

### 811.01 Description

This work consists of surface blading the traveled way to a condition that facilitates traffic and provides proper drainage. Blading includes shaping the crown or slope of travel way, berms, and drainage dips in accordance with this specification. Compaction is required when shown on the ROAD LISTING.

### 811.02 Maintenance Requirements

A. Timing - Perform surface blading during the contract period as often as needed to provide conditions stated for the maintenance level of the road.

#### B. General

1. Blade and shape the existing traveled way and shoulders, including turnouts, to produce a surface which is uniform, consistent to grade, and crowned or cross-sloped as indicated by the character of the existing surface, unless otherwise shown in the ROAD LISTING, to at least  $\frac{1}{2}$  inch per 1 foot of width, but not more than  $\frac{3}{4}$  inch per 1 foot of width. Thoroughly loosen surfacing material to no less than 2 inches depth or the depth of potholes or corrugations. Scarification to facilitate cutting to the full depth of potholes or corrugations may be elected, but will be considered incidental to blading. Do not scarify to a depth that will cause contamination of the surfacing.
2. Apply water during blading when sufficient moisture is not present to prevent segregation. Supply, haul, and apply water in accordance with Section T-891.
3. Shape existing native rock or aggregate surfaced drainage dips to divert surface runoff to existing outlet devices, ditches, or discharge locations.
4. Establish a blading pattern which provides a uniform driving surface, retains the surfacing on the roadbed, and provides a thorough mixing of the materials within the completed surface width. Upon final blading, no disturbed rock shall protrude more than 2 inches above the adjacent surface unless otherwise provided in the contract. Remove and place outside the roadbed, material not meeting this dimension so as not to obstruct drainage ways or structures. This material may be scattered off the roadbed if there is free drainage.

5. Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

| <b>Invasive Species of Concern Prevention Practices</b> |
|---|
| <i>Avoid infestations of invasive species.</i>          |

C. Routine Blading

1. Conform to the dimensions SHOWN ON THE DRAWINGS or designated in the SUPPLEMENTAL SPECIFICATIONS upon completion of blading.
2. Shape roadbed width in excess of the dimensions shown only as needed to provide drainage away from the traveled way. Do not remove established grasses and other vegetation from the excess width except as incidental to providing drainage or unless otherwise provided in the contract.

D. Compaction

Roads requiring compaction will be included in the ROAD LISTING. Unless Compaction Method B is designated in the ROAD LISTING, all traveled ways requiring compaction may be compacted by Method A. Compaction shall commence immediately following blading.

Compaction methods are:

Compaction Method A: Breaking track while operating equipment on the traveled way.

Compaction Method B: 7-10 ton pneumatic, steel, or equivalent vibratory roller, operated to cover the full width two (2) times.

E. Undercutting - Undercutting roadway back slope is not permitted.

## F. Intersections

1. At intersections, blade the roadbeds of side roads which are not closed or restricted from vehicular use to ensure smooth transitions.
2. Signing, cross ditching in the road surface (traveled way), earth berms, or other devices placed to discourage or eliminate use by passenger cars, are field evidence of road closure or restriction. Roads listed for work under Sections T-835, T-836, T-838, or T-839 are considered restricted.
3. Side roads listed for work under this Section are not restricted.

G. Cleaning of Structures - Do not allow materials resulting from work under this Section to remain on or in structures, such as bridges, culverts, cattle guards, or drainage dips.

H. Berms - Maintain existing berms to the condition of adjacent segments. Do not create new berms.

I. Smooth Blading - Smooth blading may be used as an interim measure to remove loose surfacing material from the wheel paths, and store removed materials in a recoverable windrow, until blade processing as described in this section is feasible. Watering will not be required for smooth blading. Accomplish smooth blading without distorting the existing cross-slope or crown of the traveled way.

Move and store loose surfacing materials on the high side of super-elevated curves and sections with uniform inslope or outslope. In crowned sections, store the material on either or both sides as elected. Windrow and place stored materials to provide not less than 12 feet of smooth traveled way on one-lane segments, or 20 feet of smooth traveled way on two-lane segments, or segments with turnouts. Cut holes through windrows, which may collect water on the road, for drainage at least every 500 feet.

## T-812 - DUST ABATEMENT (05/09)

### 812.01 Description

This work consists of applying dust palliatives on roads shown in the Road Listing.

### 812.02 Materials

The dust palliative materials are shown in the Road Listing, unless shown as Optional for Purchaser's election. If Optional is shown then the Purchaser may use any of the products listed below. Dust palliative materials shall meet the following requirements:

- A. Water (H<sub>2</sub>O) will be obtained from sources SHOWN ON THE DRAWINGS or listed in the SUPPLEMENTAL SPECIFICATIONS to Section T-891 Water Supply, unless otherwise approved by the Contracting Officer.
- B. Lignin Sulfonate (LIG S) Provide certification that the material meets the requirements of Subsection 725.20 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP-03)" and the Forest Service Supplemental Specification 725.20.
- C. Magnesium Chloride (MG CL2) Provide certification that that the material meets the requirements of Subsection 725.02 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02.
- D. Calcium Chloride Brine (CA CL2B). Provide certification that the material meets the requirements of Subsection 725.02 of the " Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02.
- E. Calcium Chloride Flake (CA CL2F). Provide certification that that the material meets the requirements of Subsection 725.02 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02.
- F. Bituminous dust palliatives. Manufacture materials specifically for dust abatement purposes which conform to the requirements of Section T-892 for each listed road in the Road Listing.

### 812.03 Methods

As shown in the SUPPLEMENTAL SPECIFICATIONS, Purchaser may utilize a variety of methods to decrease or eliminate the need for dust abatement.

#### 812.04 Equipment

- A. Design, equip, and operate application equipment for spreading dust palliatives so that the material is uniformly applied at the rate and traveled way widths shown in the Road Listing.
- B. For bituminous palliatives provide equipment that heats and applies the bituminous material. Provide a bituminous distributor that is self-powered and mounted on pneumatic tires and equipped with a pump and circulating spray bar, a tachometer, pressure gauges, accurate volume measuring devices such as visual volume dial or gauge calibrated to the tank, and a thermometer. Provide equipment which is a standard commercial type of proven performance.
- C. Accomplish dilution of dust palliatives within the application vehicle with the water source protected from contamination. Circulate the resulting mixture at least five (5) minutes to ensure uniform mixing prior to application.

#### 812.05 Maintenance Requirements

- A. Limit water applications to abatement for hauling vehicles and provide at a frequency and rate which controls dust such that vehicle tail lights and turn signals remain visible. Vary rates of application as needed but remain low enough to avoid forming rivulets. Accomplish the abatement by sufficient frequency of application without saturating and softening the traveled way. Compacted or glazed road surface or wheel tracks may be loosened as needed for water penetration.
- B. Apply all other dust palliatives at the rates and times agreeable to the Contracting Officer. The Road Listing shows the expected average application rate and may be varied to meet field conditions. Lignin Sulfonate, Magnesium Chloride, and Calcium Chloride Brine are listed as gallons per square foot of the undiluted product at fifty (50), thirty-three (33), and thirty-eight (38) percent respectively. Calcium Chloride Flake is listed in pounds per square foot at seventy-seven (77) percent concentration.
- C. Apply bituminous dust palliatives only when the surface to be treated contains sufficient moisture to obtain uniform distribution of the dust palliative unless noted differently in the SUPPLEMENTAL SPECIFICATIONS.
- D. Prior to initial application, when needed, the road will be bladed and shaped under Section T-811, Blading.
- E. Required subsequent applications may be applied to the existing road surface without blading.
- F. Dust palliatives will not be applied in a manner that spatters or mars adjacent structures or trees, or placed on or across cattleguards or bridges. Discharge dust abatement material only on roads approved by the Contracting Officer.

SPECIAL PROJECT SPECIFICATION (6/03)

T-812-01F

DUST ABATEMENT

812.03 Methods

Delete the words "As shown in the SPECIAL PROJECT SPECIFICATIONS" and substitute the following: Roads to be treated with dust abatement are listed in C(T)5.31# Road Maintenance Requirements.

## T-831 DITCH MAINTENANCE (10/07)

### 831.01 Description

This Section provides for routine maintenance of various types of ditches to provide a waterway which is unobstructed, as shown on the ROAD LISTING or DESIGNATED ON THE GROUND.

### 831.02 Maintenance Requirements

- A. Maintain ditches by removing rock, soil, wood, and other materials. Maintained ditches shall function to meet the intent of the original design.
- B. Undercutting backslopes during removal operations is not permitted.
- C. Suitable material up to 4 inches in greatest dimension removed from the ditches may be blended into existing native road surface and shoulder or placed in designated berm.
- D. Do not blend material from ditch cleaning operations into aggregate surfaced roads. Do not blade material across aggregate or bituminous surfaced roads, unless approved in writing by the Contracting Officer.
- E. Haul material in excess of 831.02 D or subject to 831.02 E to a designated waste area under Section T-832. Remove excess materials temporarily stored on the ditch slope or edge of the shoulder daily.
- F. Remove limbs and wood chunks in excess of 12 inches in length or 3 inches in diameter from ditches and place outside the roadway.
- G. Clean paved surfaces of all materials resulting from ditch maintenance work.
- H. Shape lead-off ditches to drain away from the traveled way.
- I. Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

| <b>Invasive Species of Concern Prevention Practices</b> |
|---|
| <i>Avoid infestations of invasive species.</i>          |

## T-832 REMOVE AND END HAUL MATERIALS (05/07)

### 832.01 Description

Work consists of loading, hauling, and placing of slide, slough, or excess materials such as rock, soil, vegetation, and other materials to designated disposal sites.

### 832.02 Maintenance Requirements

A. Remove, end haul, and dispose of excess materials generated by work under other Sections of this contract.

B. Remove the slide and slough materials in the area extending approximately 6 feet vertically above the road surface and not more than 3 feet down slope from the roadbed. Dispose of material at designated sites as SHOWN ON THE DRAWINGS, identified in SUPPLEMENTAL SPECIFICATIONS, or as ordered by the Contracting Officer.

Reshape the slope which generated the slide material as nearly as practical to its original condition by equipment operating from road surface. Reshaping of roadside ditches in slide area shall be in accordance with Section T-831.

C. When approved by the Contracting Officer, fill slumps by compacting selected materials into roadway depressions. Compaction is by Method 2.

D. Place all materials in disposal sites as specified in the SUPPLEMENTAL SPECIFICATIONS, as SHOWN ON THE DRAWINGS, or as ordered by the Contracting Officer.

1. Method 1 - Side Casting and End Dumping. Material may be placed by side casting and end dumping. Where materials include large rocks, provide a solid fill by working smaller pieces and fines into voids. Shape the finished surfaces to drain.

2. Method 2 Layer Placement - Step or roughen surfaces on which materials are to be placed prior to placing any material. Place materials in approximately horizontal layers no more than 12 inches thick. Compact each layer by operating hauling and spreading equipment over the full width of each layer.

E. Repair any damage to existing aggregate or pavement surfaces.

SPECIAL PROJECT SPECIFICATION (6/03)

T-832-01F

REMOVAL AND END HAUL MATERIALS

832.02 Maintenance Requirements

B. Add the following after the first sentence: Disposal of slough material shall be at the Derr material source, T.13S., R.24E. (Road 1200-520), Section 13 on roads listed in C(T)5.31# Road Maintenance Requirements. (See *Forest Geologist for specific waste placement instructions prior to hauling waste material*)

D. Add the following after the first sentence: Specified method shall be Method 1.

## T-834 DRAINAGE STRUCTURE MAINTENANCE (10/07)

### 834.01 Description

This work consists of cleaning and reconditioning culverts and other drainage structures.

### 834.02 Maintenance Requirements

A. Clean drainage structures, inlet structures, culverts, catch basins, and outlet channels specified in the SUPPLEMENTAL SPECIFICATIONS. Clean catch basins by removing the material within the area SHOWN ON THE DRAWINGS.

B. Clean the transition from the ditch line to the catch basin a distance of 10 feet from the catch basin. Clean outlet channels and lead-off ditches a distance of 6 feet. Remove and place debris and vegetation so as to not enter the channel or ditch, or obstruct traffic. Haul debris and vegetation to a designated disposal area in accordance with Section T-832.

C. Hydraulic flushing of drainage structures is not allowed unless provided for in the SUPPLEMENTAL SPECIFICATIONS.

D. Cleaning and reconditioning are limited to the first 3 feet of inlet and outlet, determined along the top of the structure. Recondition culvert inlet and outlet by field methods such as jacking out or cutting away damaged metal which obstructs flow. Treat cut edges with a zinc rich coating, in accordance with AASHTO M 36M and ASTM A 849.

E. Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

| <b>Invasive Species of Concern Prevention Practices</b> |
|---|
| <i>Avoid infestations of invasive species.</i>          |

SPECIAL PROJECT SPECIFICATION (6/03)


T-834-01F

DRAINAGE STRUCTURE MAINTENANCE


834.02 Maintenance Requirements

- A. Delete the words "specified in the SPECIAL PROJECT SPECIFICATIONS" and substitute the following: on those roads listed in C(T)5.31# Road Maintenance Requirements.


# TYPICAL SECTION OF CATCH BASINS AND TRANSITION AREAS



## CROSS SECTION VIEW



## PATH VIEW ALONG DITCH



## SECTION A - A

|         |       |  |
|---------|-------|--|
| TITLE   |       | CLEANING OF DITCH RELIEF<br>CATCH BASIN AND TRANSITION |
| DRAWING | 834-1 | APPROVED   |

## T-835 ROADWAY DRAINAGE MAINTENANCE (05/07)

### 835.01 Description

This work consists of providing post haul drainage on roads.

### 835.02 Maintenance Requirements

#### A. Drainage

1. Upon completion of work, shape the roadway to provide for the removal of surface water. The roadway need not be passable to vehicles. Repair and reinstall water bars, barriers or berms existing prior to the Purchaser's operation. Areas where water is ponded by existing centerline profile sags in through cuts may be left untreated.
2. Continuous blade shaping of the roadbed is not required under this specification.
3. Work to be done at staked locations shall be as indicated on the stake and/or stated in SUPPLEMENTAL SPECIFICATIONS:
4. Any of the following methods are acceptable for use at eroded or rutted locations:
  - Method A: Outsloping the roadbed at not less than  $\frac{1}{2}$  inch per yard of width.
  - Method B: Insloping the roadbed at not less than  $\frac{1}{2}$  inch per yard of width.
  - Method C: Water bar roadbed at locations staked on the ground and construct as SHOWN ON THE DRAWINGS or as included in SUPPLEMENTAL SPECIFICATIONS.
5. Drainage structures located in through fills and natural watercourses shall be fully functional without obstructions, including inlet and outlet channel within 20 feet of the structure.

6. Either clean culverts and other fabricated structures to provide drainage from road ditches and make the ditch functional or provide water bar(s) across the roadbed. Removed structures shall become Purchaser's property to be removed from National Forest System land. Remove and replace any purchaser-installed temporary drainage structures with a water bar.

B. Slides, Slumps and Slough

1. Slides and slough may be left in place, provided they do not potentially impound water or divert water from watercourses. As necessary, reshape the various surfaces to provide drainage.

2. Provide drainage to effectively decrease or eliminate the entry of surface water into slides, slumps, and roadbed surface cracks. Place berms, waterbars or ditches as needed to intercept and remove runoff water from the roadbed. Surface seal cracks by covering over with native soil materials to prevent additional water entry and compact with equipment tires.

C. Entrance Devices

Upon completion of work, replace entrance devices to effectively eliminate access by motorized vehicles having four (4) wheels and a width in excess of 50 inches.

D. Seeding

Seed and fertilize all disturbed areas in accordance with requirements set forth in Section T-841.

SPECIAL PROJECT SPECIFICATION (6/03)  
T-835-01F  
ROADWAY DRAINAGE MAINTENANCE

835.02 Maintenance Requirements

A. Drainage


3. Add the following after the first sentence: Or reestablish existing drainage structures on those roads listed in C(T)5.31# Road Maintenance Requirements.

|             |        |              |
|-------------|--------|--------------|
| FORM NUMBER | SHEETS | TOTAL SHEETS |
|             |        |              |

T-605

DRIVEABLE WATERBARRIER DETAILS


NO SCALE



PROFILE VIEW

PLAN VIEW

T-835  
NO SCALE



NOTES

1. ALL WATER BARS SHALL BEGIN AT THE INTERSECTION OF THE ROADBED AND CUT SLOPE AND RUN ACROSS THE ENTIRE WIDTH OF THE ROADBED.
2. ALL WATER BARS SHALL HAVE FREE FLOWING OUTLETS.
3. WHEN STAKES ARE USED, THEY DESIGNATE THE OUTLET LOCATION.

U.S. DEPARTMENT OF AGRICULTURE  
DESCHUTES/OCHOCO NATIONAL FORESTS

STANDARD DETAIL FOR  
WATER BAR

|                |
|----------------|
| RECOMMENDED BY |
| DESIGNED BY    |
| APPROVED BY    |
| DATE           |
| SCALE          |

Version 1  
5/7/87

WAP00008.DWG

## T-838 MAINTENANCE FOR HIGH CLEARANCE VEHICLE USE (05/07)

### 838.01 Description

This work consists of making limited use roads passable for project use by Purchaser and providing drainage from the traveled way and roadbed.

### 838.02 Maintenance Requirements

#### A. Traveled Way

Purchaser may smooth or fill existing cross ditches and water bars and as approved by the Contracting Officer modify existing road junctions to enable vehicle access. The Purchaser may perform the following work prior to beginning haul and resumption of haul after an extended stoppage:

1. Remove brush, fallen trees, rocks, and other debris from traveled way, including turnouts, turnarounds, and other locations that interfere with needed maintenance as follows:
  - a. No object extending over 4 inches above the road surface shall remain within the 12 feet usable traveled way. Center the usable width on the roadbed or position away from the fill slope.
  - b. Cut and remove standing or down trees, logs, brush, and limbs from within the area described in 1(a). Remove encroaching limbs to a height of 14 feet above the traveled way surface. Scatter material not meeting utilization standards outside and below the roadbed on the fill side. Limb and remove timber that meets utilization standards or deck at locations approved by the Contracting Officer.
  - c. Place all removed materials away from drainages.
  - d. During use, maintain drainage structures including dips, ditches and culverts in a usable condition.
2. Clean and recondition drainage facilities in accordance with Section T-831 and T-834.

#### B. Slough and Slides

1. Slough and slides may be left in place, provided surface drainage is provided and at least 12 feet of width is available for vehicle passage.
2. Purchaser may reposition or ramp over slides and slough when the traveled way width is less than 12 feet providing the material is capable of supporting vehicles. Limit out slope to no more than six percent.

3. Reposition slough or slide materials, which are not capable of supporting a vehicle, on the roadbed to provide the 12 feet width. When directed by the Contracting Officer, slough or slide material will be removed under Section T-832.

#### C. Slumps and Washouts

1. Drain the roadbed immediately upgrade of slumps and longitudinal cracks to prevent water from entering slump area.
2. Slumps and longitudinal cracks at the edge of the roadbed shall not be considered a part of the usable width. Usable width may be reduced to 10 feet in the area of the slump.
3. Unless the Contracting Officer approves material being placed on slumps, ramp the slumps on both ends into undisturbed roadbed to provide at least 10 feet usable width. Use removed materials to guide vehicles to the ramp location or to aid in draining the area.
4. Washouts may be filled with suitable material.

#### D. Post haul

At the end of hauling or prior to entering into seasonal shutdowns or a period of extended inactivity:

1. Shape the traveled way and disturbed roadbed to provide functional drainage.
2. Reinstall removed cross ditches and water bars and provide any additional drainage structures necessary to offset changes caused through use and maintenance.
3. Leave roads useable for high clearance vehicles. Remove or reshape purchaser modifications at road junctions to leave the entrance as it was before use, or as agreed at the time of improvement.

## T-839 MAINTENANCE FOR PROJECT USE (05/07)

### 839.01 Description

Work consists of providing minimum access required for Purchaser's Operations and associated Forest Service contract administration and preventing unacceptable resource or road damage.

### 839.02 Maintenance Requirements

- A. Purchaser is authorized to perform the following maintenance to provide vehicle passage and drainage:
1. Removing log, earth, and rock barriers and/or improving existing road junctions to enable vehicle access as mutually agreed.
  2. Smoothing or filling existing cross ditches and water bars.
  3. Installing Purchaser-furnished culverts or other temporary drainage structures for shallow stream crossings as approved by the Contracting Officer.
  4. Removing brush, fallen trees, rocks, and other materials from the traveled way and other locations that interfere with needed maintenance:
    - a. Place all removed materials away from drainages.
    - b. Limb and remove timber which meets utilization standards or deck at locations approved by the Contracting Officer. Scatter other woody materials, including limbs, off of and below the roadbed without creating concentrations.
  5. Clean and recondition drainage structures in accordance with Section T-831 and Section T-834.
  6. Reposition or ramp over slough and slides to provide adequate width of traveled way material.
  7. Provide traveled way drainage above slumps and seal cracks in slump area. Ramp the slumps on both ends into undisturbed roadbed to provide usable width unless otherwise ordered by the Contracting Officer.
- B. During use, the traveled way shall not channel water along the road. Prior to seasonal periods of anticipated rains and runoff, perform the following work:
1. Shape the traveled way and roadbed to drain.

2. Reinstall removed cross ditches and water bars and provide any additional drainage structures necessary to offset changes through use and maintenance.
3. Perform work outlined in 839.02 A (5), (6), and (7).
4. During periods of non use, replace original barrier or provide and maintain standard MUTCD, Type 3, barricades unless alternate type barriers are approved by the Contracting Officer.

#### 839.03 Post Haul Requirements

- A. Upon completion of project use perform such work as needed to reasonably conform to the character of the existing road prior to Purchaser's maintenance for project use, unless otherwise provided in the SUPPLEMENTAL SPECIFICATIONS or the Road Listing. Work shall be in addition to requirements of 839.02 B and in accordance with 839.03 B and C.
- B. Roads designated in the Road Listing to be blocked shall conform to the requirements of Section T-835. Unless otherwise approved by the Contracting Officer, remove Purchaser-installed temporary structures from National Forest System land. Associated commercially-obtained materials shall remain the property of the Purchaser.
- C. Remove or reshape Purchaser improvements at road junctions, as approved by the Contracting Officer at the time of improvement.

## T-842 CUTTING ROADWAY VEGETATION (10/07)

### 842.01 Description

This work consists of cutting all vegetative growth, including trees and other vegetation less than 4 inches in diameter measured 6 inches above the ground, on roadway surfaces and roadsides.

### 842.02 Maintenance Requirements

#### A. General

1. Cut brush, trees, and other vegetation within each area treated to a maximum height of 6 inches above the ground surface or obstruction such as rocks or existing stumps. When work is performed under this Section, remove all limbs which extend into the treated area, or over the roadbed, to a height of 14 feet above the traveled way surface elevation.
2. Items to remain will be DESIGNATED ON THE GROUND.
3. Work may be performed either by hand or mechanically unless specifically shown in the Road Listing. Self-propelled equipment is not allowed on cut and fill slopes or in ditches.
4. Correct damage to trunks of standing trees caused by Purchaser's operation either by treatment with a commercial nursery sealer or by removing the tree as directed by the Contracting Officer.
5. Limb trees within the cutting limits which are over 4 inches -measured at 6 inches above the ground in lieu of cutting.
6. When trees are limbed, cut limbs within 4 inches of the trunk.

#### B. Cutting Side Vegetation

1. Show the width of vegetation to be removed in the Road Listing.
2. Unless otherwise included in the SUPPLEMENTAL SPECIFICATIONS or DESIGNATED ON THE GROUND:
  - a. Commence work at the edge of the traveled way and proceed away from the road centerline.
  - b. Roads without a defined traveled way: The starting point for cutting will be marked on the ground or defined in the SUPPLEMENTAL SPECIFICATIONS.

3. The points for establishing cutting limits are as follows:

a. Fill and daylighted (wide roadbed) section cutting commences at the edge of the traveled way and proceeds away from the road center line.

b. Drainage ditched section cutting commences at the bottom of the existing ditch and proceeds away from the road center line. Cutting on ditch foreslopes is not required.

c. Unditched cut section cutting commences at the intersection of the cutbank and the roadbed and proceeds away from center line.

4. Provide transitions between differing increments of cutting width. Accomplish transitions in a taper length of not less than 50 feet nor more than 70 feet.

C. Debris

1. Materials resulting from the cutting operation in excess of 12 inches in length or 3 inches in diameter is not allowed to remain on roadway slopes within the treated area, in ditches, or within water courses.

2. Remove limbs and chunks in excess of 3 inches in any dimension from the traveled way and shoulders.

3. Materials may be scattered down slope from the roadbed, outside of the work area and drainages unless otherwise listed in D. Invasive Species of Concern.

D. Invasive Species of Concern

Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

| <b>Invasive Species of Concern Prevention Practices</b> |
|---|
|---|

|  |
|--|
| <i>Avoid infestations of invasive species.</i> |
|--|

## T-851 LOGGING OUT (5/07)

### 851.01 Description

This work consists of removal of fallen trees and snags which encroach into the roadway or the 3 feet of roadside abutting the roadway on the cut side.

### 851.02 Maintenance Requirements

- A. Limb and remove timber which meets Utilization Standards, or deck at locations designated by the Contracting Officer.
- B. Limb other material cut into lengths for handling. Deck outside ditches and drainages, off the traveled way and turnouts or at staked locations. The clearing width is to the edge of the roadway for public use roads, except limited use roads. The clearing width for limited use roads is shown in the specifications.
- C. Notwithstanding B(T)2.3, blowdown timber outside Sale Area required to be removed, which meets Utilization Standards in A(T)2, when designated by the Contracting Officer is Included Timber subject to requirements of B(T)2.2.
- D. Do not leave woody debris and slash in excess of 12 inches in length or 3 inches in diameter, or concentrations which may plug ditches or culverts, in ditches, drainage channels, or on backslopes, traveled way, shoulders, or turnouts.

## T-854 – TREATMENT AND DISPOSAL OF DANGER TREES (04/10)

### 854.01 Description

This work consists of felling and disposal of designated live or dead danger trees sufficiently tall to reach roads used by the Purchaser. Any removal of logs is subject to prior agreement between the Contractor Officer and the Purchaser.

### 854.02 Requirements

#### **A. Designation of danger trees.**

Danger trees to be felled will be designated in advance by the Contracting Officer. Trees to be removed will be Marked.

#### **B. Falling, bucking and treatment for disposal.**

Use controlled felling to ensure the direction of fall and prevent damage to property, structures, roadway, residual trees, and traffic. Stump heights, measured on the side adjacent to the highest ground, must not exceed 12 inches or 1/3 of the stump diameter, whichever is greater. Higher stump heights are permitted when necessary for safety.

Felled snags and trees, which are not Marked for removal, will be left in a stable condition such that they will not roll or slide. Position logs away from standing trees so they will not roll, are not on top of one another, and are located out of roadway and drainage structures.

Fell, limb and, remove trees, which are Marked for removal, that equal or exceed the utilization standards as listed in the Timber Sale contract or SUPPLEMENTAL SPECIFICATIONS. Dispose of merchantable timber designated for removal in accordance with B/BT2.32 Construction Clearing, of the Timber Sale Contract, or as described in SUPPLEMENTAL SPECIFICATIONS.

**C. Slash treatment.**

Within the roadway, remove limbs, chunks, and debris in excess of 12 inches in length and 3 inches in diameter, and concentrations that may plug ditches or culverts, and water courses.

Dispose of slash by scattering outside the roadway limits without damaging trees, or improvements.

Large accumulations of slash may be ordered hauled under T-832.

## T-891 WATER SUPPLY AND WATERING (5/07)

### 891.01 Description

This work consists of providing facilities to furnish an adequate water supply, hauling and applying water.

### 891.02 Materials

If the Purchaser elects to provide water from other than designated sources, the Purchaser is responsible to obtain the right to use the water, including any cost for royalties involved.

Suitable and adequate water sources available for Purchaser's use under this contract are designated as follows:

| <u>Map<br/>Key No.</u> | <u>Location<br/>Road</u>  | <u>Location<br/>Milepost</u> | <u>Use<br/>Restrictions</u> |
|------------------------|---|------------------------------|-----------------------------|
|                        | Morgan Well, Road 4276-010, T.14S., R.24E., Sec. 29, SE 1/4             |                              |                             |
|                        | Younger Well, Road 3000-800, T.13S., R.23E., Sec. 17, NE 1/4            |                              |                             |
|                        | <i>NOTE: Both sites will require a generator and wiring connection.</i> |                              |                             |
|                        | Little Summit Creek Pumper Chance at bridge, junction roads 4254/4270   |                              |                             |
|                        | T.14S., R.23E., Sec. 23, SW 1/4   |                              |                             |

### 891.03 Equipment

A. Positive control of water application is required. Equipment shall provide uniform application of water without ponding or washing.

B. An air gap or positive anti-siphon device shall be provided between the water source and the vehicle being loaded if the vehicle has been used for other than water haul, if the source is a domestic potable water supply, or the water is used for tank mixing with any other materials.

C. The designated water sources may require some work prior to their use. Such work may include cleaning ponded areas, installing temporary weirs or sandbags, pipe repair, pump installation, or other items appropriate to the Purchaser's operations. Flowing streams may be temporarily sandbagged or a weir placed to pond water, provided a minimum flow of 1 cu. ft/sec is maintained. Obtain approval from the Contracting Officer on improvements for sandbags or weirs prior to placement

SPECIAL PROJECT SPECIFICATION (6/03)  
T-891-01F  
WATER SUPPLY AND WATERING

891.03 Equipment

C. Delete the word "Contractor" in the second sentence and substitute the following: Purchaser.

D. Add the following: Watering, juvenile fish protection. All draft hoses being used to withdraw water from any live flowing stream or pond located at various locations in Region Six, the Purchaser shall utilize (1) one of the following methods of screening on any draft hoses used. These roads are listed in C(T)5.31# Road Maintenance Requirements.

(1) Perforated Plate: Screen openings shall not exceed  $3/32$  or 0.0938-inches (2.38 mm).

(2) Profile Bar Screen: The narrowest dimension in the screen openings shall not exceed 0.0689-inches (1.75-mm).

(3) Woven Wire Screen: Screen openings shall not exceed  $3/32$  or 0.0938-inches (2.38 mm).

All screening methods shall be cleaned frequently either with wire brushing, flushing, or any other acceptable method.

Sale Name: Jack SBA

CT5.32# - ROAD MAINTENANCE DEPOSIT SCHEDULE (07/2001)

Other provisions herein notwithstanding, when Forest Service requests payment in lieu of Purchaser's performance of road maintenance, Purchaser shall make Required Deposits (16 USC 537) for current and/or deferred road maintenance. Such deposits are based on the estimated volume and distance hauled and Purchaser's commensurate use of each road listed in the Road Maintenance Plan in CT5.31#.

Purchaser and Forest Service may agree in writing on adjustment of such rates. If Purchaser uses roads under jurisdiction of Forest Service other than those listed in the Road Maintenance Plan, Forest Service shall establish rates commensurate with Purchaser's use of such roads.

The Required Deposits for Forest Service work in lieu of Purchaser performance and for deferred maintenance is: \$4.07 per CCF.

The following table lists who Purchaser will make deposits for road maintenance to, and the rate per unit of measure of the deposit. The Road Maintenance Agreement is available for inspection at the Forest Supervisor's office.

| Deposit Made To | Rate | Unit of Measure |
|-----------------|------|-----------------|
| N/A             |      |                 |

CT6.22# - PROTECTION OF IMPROVEMENTS (07/2001)

Unless otherwise agreed to in writing, Purchaser shall move or relocate the improvements listed in the following table to locations in a manner as specified in drawings or in specifications attached hereto. Improvements shall be returned to their original locations following Purchaser's operations.

See attached table of improvements to be moved.

TABLE PURSUANT TO CT6.22# - PROTECTION OF IMPROVEMENTS (07/2001)

Type of Improvement

Move or Relocate to

Barbed wire fence in  
Cutting Units 39, 42, 48,  
55, 70, 73, 75, 80, 131

Fence may be cut for operations  
where agreed to by Forest  
Service. Fence will be repaired  
by Purchaser following  
operations in each Cutting Unit.

Sale Name: Jack SBA

CT6.315# - SALE OPERATION SCHEDULE (06/1994)

Unless otherwise agreed to in writing between Purchaser and Forest Service, Purchaser's Operations shall be performed in accordance with the following schedule.

See attached schedule.

SCHEDULE PURSUANT TO CT6.315# - SALE OPERATION SCHEDULE  
(06/1994)

| Harvest Unit   | Operating Conditions   | Purpose                             |
|--|--|-------------------------------------|
| Gate in Cutting Unit<br>80 at the<br>3000900/3000935<br>junction | Keep gates closed June 15 to<br>September 30, except to allow<br>vehicles to pass. Gates will be<br>closed immediately after each<br>vehicle passes through. Dates may be<br>extended by the Forest Service. | Grazing<br>Allotment<br>Maintenance |
| 39,48,53,61,62,71,75,<br>91,97,99,127,154                        | No Operations March 1 - August 31<br>See attached matrix   | Protect nesting<br>Goshawk          |
| 80,152   | No Operations March 1 - August 1<br>See attached matrix  | Protect nesting<br>Cooper's Hawk    |
| 61,62  | No Operations March 1 - August 1<br>See attached matrix  | Protect nesting<br>Osprey           |

**Operating Schedule Matrix - Jack SBA Timber Sale**  
 Operations are prohibited during the months a restriction is listed.

| Cutting Unit | JAN | FEB | MAR  | APR  | MAY  | JUNE | JULY | AUG | SEPT | OCT | NOV | DEC |
|--------------|-----|-----|------|------|------|------|------|-----|------|-----|-----|-----|
| 38           |     |     |      |      |      |      |      |     |      |     |     |     |
| 39           |     |     | GH   | GH   | GH   | GH   | GH   | GH  |      |     |     |     |
| 40           |     |     |      |      |      |      |      |     |      |     |     |     |
| 41           |     |     |      |      |      |      |      |     |      |     |     |     |
| 42           |     |     |      |      |      |      |      |     |      |     |     |     |
| 43           |     |     |      |      |      |      |      |     |      |     |     |     |
| 44           |     |     |      |      |      |      |      |     |      |     |     |     |
| 45           |     |     |      |      |      |      |      |     |      |     |     |     |
| 46           |     |     |      |      |      |      |      |     |      |     |     |     |
| 47           |     |     |      |      |      |      |      |     |      |     |     |     |
| 48           |     |     | GH   | GH   | GH   | GH   | GH   | GH  |      |     |     |     |
| 49           |     |     |      |      |      |      |      |     |      |     |     |     |
| 51           |     |     |      |      |      |      |      |     |      |     |     |     |
| 52           |     |     |      |      |      |      |      |     |      |     |     |     |
| 53           |     |     | GH   | GH   | GH   | GH   | GH   | GH  |      |     |     |     |
| 54           |     |     |      |      |      |      |      |     |      |     |     |     |
| 55           |     |     |      |      |      |      |      |     |      |     |     |     |
| 56           |     |     |      |      |      |      |      |     |      |     |     |     |
| 57           |     |     |      |      |      |      |      |     |      |     |     |     |
| 58           |     |     |      |      |      |      |      |     |      |     |     |     |
| 59           |     |     |      |      |      |      |      |     |      |     |     |     |
| 60           |     |     |      |      |      |      |      |     |      |     |     |     |
| 61           |     |     | GH,O | GH,O | GH,O | GH,O | GH,O | GH  |      |     |     |     |
| 61A          |     |     |      |      |      |      |      |     |      |     |     |     |
| 62           |     |     | GH,O | GH,O | GH,O | GH,O | GH,O | GH  |      |     |     |     |
| 63           |     |     |      |      |      |      |      |     |      |     |     |     |

GH = Goshawk - No Operations March 1 - August 31\*\*

CH = Coopers Hawk - No operations March 1 - August 1\*\*

O = Osprey - No operations March 1 - August - 1\*\*

\*\* Unless Forest Service determines nest is unoccupied

Operating Schedule Matrix - Jack SBA Timber Sale  
 Operations are prohibited during the months a restriction is listed.

| Cutting Unit | JAN | FEB | MAR | APR | MAY | JUNE | JULY | AUG | SEPT | OCT | NOV | DEC |
|--------------|-----|-----|-----|-----|-----|------|------|-----|------|-----|-----|-----|
| 64           |     |     |     |     |     |      |      |     |      |     |     |     |
| 65           |     |     |     |     |     |      |      |     |      |     |     |     |
| 67           |     |     |     |     |     |      |      |     |      |     |     |     |
| 69           |     |     |     |     |     |      |      |     |      |     |     |     |
| 70           |     |     |     |     |     |      |      |     |      |     |     |     |
| 71           |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 72           |     |     |     |     |     |      |      |     |      |     |     |     |
| 73           |     |     |     |     |     |      |      |     |      |     |     |     |
| 75           |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 80           |     |     | CH  | CH  | CH  | CH   | CH   |     |      |     |     |     |
| 86           |     |     |     |     |     |      |      |     |      |     |     |     |
| 87           |     |     |     |     |     |      |      |     |      |     |     |     |
| 90           |     |     |     |     |     |      |      |     |      |     |     |     |
| 91           |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 93           |     |     |     |     |     |      |      |     |      |     |     |     |
| 94           |     |     |     |     |     |      |      |     |      |     |     |     |
| 97           |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 99           |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 99A          |     |     |     |     |     |      |      |     |      |     |     |     |
| 124          |     |     |     |     |     |      |      |     |      |     |     |     |
| 127          |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 129          |     |     |     |     |     |      |      |     |      |     |     |     |
| 130          |     |     |     |     |     |      |      |     |      |     |     |     |
| 131          |     |     |     |     |     |      |      |     |      |     |     |     |
| 152          |     |     | CH  | CH  | CH  | CH   | CH   |     |      |     |     |     |
| 154          |     |     | GH  | GH  | GH  | GH   | GH   | GH  |      |     |     |     |
| 165          |     |     |     |     |     |      |      |     |      |     |     |     |
| 166          |     |     |     |     |     |      |      |     |      |     |     |     |
| 173          |     |     |     |     |     |      |      |     |      |     |     |     |

GH = Goshawk - No Operations March 1 to August 31\*\*

CH = Coopers Hawk - No operations March 1 - August 1\*\*

O = Osprey - No operations March 1 August - 1\*\*

\*\* Unless Forest Service determines nest is unoccupied

Sale Name: Jack SBA

CT6.405 - ALTERNATE REMOVAL OF INCLUDED TIMBER (05/2005)

Purchaser and Forest Service may agree to alternate removal requirements of Included Timber contained in AT2. Alternate removal requirements are to be set forth in an agreement signed by both Purchaser and Contracting Officer. The terms of the agreement binds both parties and becomes part of the timber sale contract.

The development and execution of the agreement is based upon the determination by the Contracting Officer that removal of Included Timber is economically impractical if Purchaser has no ready market for such logs in the tributary area. A tributary area is defined as the area in which the Purchaser and competitors regularly deliver saw logs, or 200 miles from the Sale Area, whichever distance is greater.

The agreement for alternate removal requirements shall be executed prior to removing any timber from the Payment Units included in the agreement. Alternate removal requirements shall apply only to whole units and not to portions of units. All material meeting alternate removal specifications shall be cut and removed to locations designed in the agreement.

Volumes of material with alternate removal requirements will be determined from the National Cruise report for the sale. Purchaser will be charged for the following:

- a) stumpage value at current contract rates of the alternatively removed timber;
- b) plus the cost of other work required by the Forest Service to dispose of alternatively removed material;
- c) plus the difference between the appraised transportation cost of the Sawtimber and/or Nonsawtimber material involved and the appraised transportation cost of the alternative.
- d) Minus any work required to be completed by the Purchaser associated with alternate removal requirements.

Charges will be debited to the Purchaser's timber sale account.

Upon acceptance of the alternate removal requirements, the Payment Unit will be removed from the Sale Area under BT6.36.

Title to material included in the alternate removal agreement shall remain with the Forest Service.

CT6.41# - SPECIFIC REQUIREMENTS (01/2000)

Notwithstanding BT6.41, BT6.411, BT6.5, and BT6.61, felling objectives shall be accomplished by the type of felling methods and equipment listed herein. Methods or equipment other than those specified may be approved. For Payment Units shown in the following table, Purchaser shall submit a cutting plan for Forest Service acceptance, prior to the start of felling operations.

See attached table.

TABLE PURSUANT TO CT6.41# - SPECIFIC REQUIREMENTS (01/2000)

| <u>FELLING METHODS</u>   | <u>Cutting Unit</u> |
|--|---------------------|
| Mechanized felling equipment will operate in a manner which will minimize detrimental soil disturbance and residual stand damage.  | All                 |
| Directional felling is required away from fences, roads, streams, private land and other improvements.                             | All                 |
| Mechanized Felling equipment is allowed off the skid trails for a single round trip only except in the streamcourse buffers (50'). | All                 |
| Mechanized felling equipment is prohibited on slopes greater than 35 percent.  | All                 |
| No equipment operation within 50 feet of any seeps, springs, bogs, or ponds.   | All                 |
| Metal tracks and cleats are prohibited on paved roads.   | All                 |
| Vehicles and equipment are prohibited off road in locations of invasive species and ATP on the Sale Area Map.                      | All                 |

FELLING EQUIPMENT

Cutting Unit

|   |     |
|---|-----|
| Mechanized felling equipment will be limited to a boom-mounted shear/saw with a minimum reach of 17 feet from equipment center point or as agreed to by Forest Service. When snow and/or frozen ground conditions exist, other felling methods or equipment may be agreed to. | All |
|---|-----|

Sale Name: Jack SBA

CT6.42# - YARDING/SKIDDING REQUIREMENTS (06/2010)

Purchaser shall submit for Forest Service approval a Yarding/Skidding Plan prior to the start of felling operations. Requirements other than those specified in the following table may be approved. When appropriate, such approval shall include adjustments in Current Contract Rates and revision of the Sale Area Map. In no such case shall the adjustments result in Current Contract Rates less than Base Rates.

Location of all skid roads and trails, tractor roads, skyline corridors, mechanized harvester trails, forwarder roads, and other log skidding facilities, shall be approved prior to felling, construction or use.

See attached table for requirements.

TABLE PURSUANT TO CT6.42# - YARDING/SKIDDING REQUIREMENTS  
(06/2010)

| <u>YARDING/SKIDDING REQUIREMENTS</u>  | <u>CUTTING UNIT</u> |
|---|---------------------|
| Ground based skidding equipment is required. Rubber tired skidders/tractors shall have integral arch/grapple. | All                 |
| Mechanized skidding equipment is prohibited on slopes greater than 35%.                                       | All                 |
| Spacing between skid trails shall be an average of 100 feet.  | All                 |
| Leading end of all logs must be suspended above the ground during tractor skidding.                           | All                 |
| All ground based equipment shall be confined to designated skid trails and landings.                          | All                 |
| No equipment operation within 50 feet of any seeps, springs, bogs, or ponds.                                  | All                 |
| Metal tracks and cleats are prohibited on paved roads.  | All                 |
| Vehicles and equipment are prohibited off road in locations of invasive species and ATP on the Sale Area Map. | All                 |

Sale Name: Jack SBA

CT6.6# - EROSION CONTROL AND SOIL TREATMENT BY THE PURCHASER (07/2001)

Erosion prevention and control work required by BT6.6, shall be completed within 15 calendar days after yarding/skidding operations related to each landing are substantially completed or after Forest Service designation on the ground of work where such designation is required hereunder. Said time limit shall be exclusive of full days lost in Purchaser's Operations due to causes beyond Purchaser's control. Such on the ground designation shall be done as promptly as feasible unless it is agreed that the location of such work can be established without marking on the ground. After September 15, and as long thereafter as operations continue, the work shall be done as promptly as practicable. Damage resulting from Purchaser's Operations due to failure to perform required work shall be repaired by Purchaser.

On slopes greater than 35 percent, erosion control measures will be done with methods other than mechanized equipment, unless otherwise agreed.

Where soil has been disturbed or displaced on Sale Area by Purchaser's Operations and where measures described in BT6.6 will not result in satisfactory erosion control or where subsoiling is shown on Sale Area Map, the following shall be performed. If applicable, timing of the work shall be coordinated with required scarification or subsoiling.

(a) Where staked or otherwise marked on the ground by Forest Service, seed, fertilizer, and mulch will be applied as indicated in the attached seeding, fertilizing, and mulching schedule. All applications shall be current and done during the period from 10/1 to 11/15 unless otherwise agreed to. Applications shall be done only during favorable conditions. If Purchaser and Forest Service agree, seed can be applied and covered within 10 days of ground disturbance, and may be done outside the required periods.

(b) Where shown on Sale Area Map, landings, Temporary Roads and/or skidtrails/roads shall be scarified to a depth of 8 inches to provide a seedbed for grass seed, fertilizer, and mulch. Seed, fertilizer, and mulch shall be spread evenly at the rates shown in the table. When the seed, fertilizer, and mulch are applied in separate operations, the second or third operations shall be within 10 days of the first or second.

(c) Where shown on Sale Area Map, landings, Temporary Roads, and skid trails/roads used by Purchaser shall be subsoiled to a minimum depth of 20 inches, except that Forest Service may agree to lesser depths. Each subsoiler shank shall be equipped with a shoe and wings which has a total width of at least 18 inches. The design of the shank and wings will be such that the treated, compacted soil is slightly lifted and well-fractured rather than plowed, mixed, or displaced. The distance between subsoiler shank passes shall not exceed 36 inches. Treated areas shall span the total width of compaction. Subsoiling shall be kept reasonably current and shall be done during Normal Operating Season unless otherwise agreed.

(d) When agreed to, Purchaser may use alternate methods of erosion control.

Seed shall meet current Forest Service requirements, with the additional requirement that no seed containing any noxious weed seed in excess of established state limitations as listed in the current "State Noxious Weed Requirements Recognized in the Administration of the Federal Seed Act" publication will be used (commonly referred to as the "all states" noxious weed seed list). Seed shall be furnished separately or in mixture in standard containers clearly marked with: (1) seed name; (2) lot number; (3) net weight; (4) percentages of purity and of germination (in case of legumes, percentage of germination to include hard seed); (5) percentage of weed seed content; and (6) certification that no noxious weed seeds in excess of established state standards are present. The contractor shall furnish the Government duplicate signed copies of a certificate, signed by a Registered Seed Technologist or Seed Analyst (certified through either the Association of Official Seed Analysis or the Society of Commercial Seed Technologists), certifying that each lot of seed has been tested in accordance with the Association of Official Seed Analysts Standards within 12 months prior to date of application. This certificate shall include (1) name and address of laboratory, (2) date of test, (3) lot number for each kind of seed, (4) name of seed, (5) percentage of germination, (6) percentage of purity, (7) percentage of weed seed content, and (8) certification that no

Sale Name: Jack SBA

noxious weed seeds in excess of established state limitations are present in any kind of seed.

Legume seed shall be inoculated with approved cultures in accordance with the instructions of the manufacturer.

No seed may be applied without prior written approval by the government.

See attached application schedule.

APPLICATION SCHEDULE PURSUANT TO CT6.6# - EROSION CONTROL AND SOIL TREATMENT  
BY PURCHASER (07/2001)

| PAYMENT<br>UNIT<br>OR UNIT<br>NUMBER | AREAS<br>A) SKID TRAILS<br>B) FIRELINES<br>C) TEMP. ROADS<br>D) LANDINGS<br>E) PERM. ROADS | SEED                         |            | FERTILIZER        |        | MULCH          |        |
|--------------------------------------|--|------------------------------|------------|-------------------|--------|----------------|--------|
|                                      |  | APPLICATION                  |            | APPLICATION       |        | APPLICATION    |        |
|                                      |  | SPECIES <u>1/</u><br>MIXTURE | LBS<br>/AC | TYPE<br><u>2/</u> | LBS/AC | TYPE <u>3/</u> | LBS/AC |
| ALL                                  | A*, C, D   | Idaho Fescue                 | **         |                   |        |                |        |
| ALL                                  | A*, C, D   | Blue<br>Wild Rye             | **         |                   |        |                |        |
| All                                  | A*, C, D   | Red Fescue                   | **         |                   |        |                |        |
| All                                  | A*, C, D   | Bluebunch<br>Wheatgrass      | **         |                   |        |                |        |
| All                                  | A*, C, D   | Yarrow                       | **         |                   |        |                |        |
| ALL                                  | A*, C, D   | Bottlebrush<br>Squirrel Tail | **         |                   |        |                |        |
| All                                  | A*, C, D   | Sandbergs<br>Bluegrass       | **         |                   |        |                |        |

Forest Service will provide premixed seed at no charge to Purchaser.  
 \*\*Seed mixture shall be applied at a rate of 15 pounds per acre plus 10%.  
 \*300 feet of the skid trails from the landings will be seeded.  
 Scarification is required on landings, temporary roads, and 300 feet of the skid trails from the landings .

1/ For sales in Oregon, the seed shall meet the State certification specifications. Seed must be packaged in containers carrying official certification labels sewn in, glued to, or printed upon the container, with the following information:

1. Variety (if certified as to variety) and kind.
2. Quantity of seed (pounds or bushels).
3. Class of certified seed (blue tags for certified seed).
4. Inspection or lot number traceable to the certifying agency's records.

For sales in Washington, the seed shall be labeled as "Prohibited and Restricted Noxious Weed Free for the State of Washington." The purchaser shall furnish a copy of the seed analysis.

For state of California lands in Region 6, seed must be certified by the state of California, or by an independent agency or company that is approved by the state of California for "prohibited and restricted noxious weed free for the state of California."

For mixtures of seed, each ingredient in excess of 5 percent must be listed with its percentage by weight and its germination percentage.

Legumes must be inoculated with nitrogen fixing bacteria before planting. The label must show the expiration date of the inoculant.

Sale Name: Jack SBA

CT6.7 - SLASH DISPOSAL (06/2008)

As used in the following Subsections, the term "slash" is vegetative debris including, but not limited to, cull logs, blasted or pushed-out stumps, chunks, broken tops, limbs, branches, rotten wood, damaged brush, damaged or destroyed reproduction, saplings or poles, resulting from Purchaser's Operations.

Any burning of slash or refuse by Purchaser is subject to CT7.201.

Forest Service may agree to substitute methods of slash disposal if such substitute methods will give equally satisfactory results.

Forest Service may waive specific slash treatment requirements. Purchaser's Timber Sale Account will be charged for any slash treatment requirements waived or for work taken over by Forest Service. The amount of such charges will be determined by Forest Service if Purchaser has not begun felling operations. If felling operations have begun, charges will be determined by mutual agreement.

Forest Service may enter into a written agreement with the Purchaser for the Purchaser to complete slash disposal work originally scheduled to be done by the Forest Service. The agreement will describe the work to be completed by the Purchaser, and the value of such work. Value of the work to be done will be based upon the slash disposal plan in which the cooperative deposits were calculated; and will include Forest Service overhead. Any deposits paid by the Purchaser for this work will be credited to the Purchaser's timber sale account. This work is in addition to that required by CT6.74#.

Forest Service may also enter into a written agreement with Purchaser for the Purchaser to remove slash from landings, subject to BT3.41. Brush disposal deposits paid by the Purchaser for the Forest Service to burn landing piles will be credited to the Purchaser's timber sale account in the amount shown in the brush disposal plan, less the amount needed by the Forest Service for final cleanup of the landings following removal of the landing slash piles by the Purchaser. The credit will be made following the final removal by the Purchaser of all Included Timber, and slash piles, from the Sale Area.

CT6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Purchaser shall pile, burn, yard, construct firelines or otherwise treat slash defined in CT6.7, within designated areas. Work required of Purchaser shall be in accordance with the following slash plan and specifications, and the Sale Area Map.

Unless otherwise agreed, or shown in attached slash plan or specifications, when Included Timber is removed during Normal Operating Season, required slash work shall be completed within 30 days of removal of approximately three-quarters of the volume in the unit. When Included Timber is removed outside Normal Operating Season, required work will be completed within 30 days of the beginning of the next Normal Operating Season.

See following specifications.

SPECIFICATIONS PURSUANT TO CT6.74# - SLASH TREATMENT REQUIREMENTS (02/02)

Slash Plans and Specifications for Piling and/or Decking Slash on Landings  
and  
Temporary Roads (Pursuant to CT6.7 and CT6.74#)

1. Slash to be Piled and/or Decked

- a. Slash resulting from the construction of landings and temporary roads, and slash accumulated on the landings from the logging operation shall be piled and/or decked. Partially pushed out stumps are considered to be included as pushed out stumps in the CT6.7 definition of Slash.

2. Construction and Location of Piles and/or Decks

- a. Slash piles shall be located at least 25 feet from the crown or drip line of any dead or live tree or equal distance between standing dead or live trees, whichever is greater. These piles shall be minimum of 6 feet in height and 12 feet in diameter, if sufficient slash is available.
- b. All piles shall be compact and free of dirt and rocks.
- c. All material extending beyond the general contour of the piled slash shall be trimmed off and added to the pile.

Equipment Requirements

- a. Machines used for piling slash shall be equipped with brush blades, detachable rake fronts or grapples.

SLASH PLANS AND SPECIFICATIONS  
FOR WHOLE TREE YARDING AND LEAVE TOPS ATTACHED YARDING  
(Pursuant to CT6.7 and CT6.74#)

1. Whole Tree Yarding:

All trees meeting Utilization Standards which are less than 60 feet in length are required to be Whole Tree Yarded to the landing. Any portions of live trees required to be removed, which break during falling or yarding, and are 8 feet or more in length shall be yarded to the landing.

2. Leave Top Attached Yarding:

All trees meeting Utilization Standards which are 60 feet in length and greater are required to have tops and limbs attached to the last log while being yarded to the landing. Any portions of live trees required to be removed, which break during felling or yarding, and are 8 feet or more in length shall be yarded to the landing.

3. Applicable Area

Purchaser shall yard tops and dispose of slash, in accordance with specifications, where shown on the Sale Area and Slash Disposal Map in the following Payment Units: All

4. Disposal of Yarded Material

Tops yarded to the landing, as defined in CT6.7, shall be considered landing slash and shall be disposed of as such.

Sale Name: Jack SBA

CT6.8 - MEASURING (08/2000)

The estimated quantity of timber in AT2 was determined in advance of advertisement. Any timber subsequently added or deleted under BT2.13, BT2.14, BT2.15, BT2.31, BT2.32, BT2.33, BT2.34, BT2.35, or BT2.37 will be measured by the Forest Service and formulated using Forest Service Handbook 2409.12, Timber Cruising Handbook Standards, unless otherwise agreed to in writing.

CT6.84 - ACCOUNTABILITY (06/2006)

The following requirements are applicable to product removal permits:

1. Forest Service will issue to Purchaser or designated representative(s) serially numbered Product Removal Permit Books for use only on this sale. Product Removal Permit Books, whether used or unused, shall be returned to issuing Forest Service Office in accordance with instructions contained on cover of each book.

2. All permits shall be completed and attached to load by an individual named in writing, other than the truck driver in accordance with the instructions on the inside cover of the Product Removal Permit Book. Product Removal Permit will be attached prior to removal from the immediate vicinity where loading is done. The permit will remain attached until the load is decked at the delivery point.

When products are manufactured on site and removed as chips, the permit shall be attached to a 12" x 18" vertically mounted board on the front panel on the driver's side of the conveyance unit. The previously validated Product Removal Permit shall be removed from the board before attaching a new permit. The board's texture, density, and thickness shall be such as to accommodate construction type staples and be of durable material for securing the attached permits.

3. Purchaser shall require truck drivers to stop when requested by Forest Service for purposes of monitoring accountability when products are in transit. Methods to be used to alert drivers of an impending stop shall be agreed to in advance of hauling products.

CT6.84 (OPTION 1) - USE OF PAINT BY PURCHASER (05/2005)

Notwithstanding BT6.81, use of paint by the Purchaser within the Sale Area in the color(s) used by the Forest Service in the preparation of the sale and administration of the contract will be by written approval of the Forest Service.

Sale Name: Jack SBA

CT7.1 - PLANS (09/2004)

The plan shall state how Purchaser's representative or alternates will be contacted in a fire emergency, both during periods of operation and at other times such as evenings or weekends. Purchaser shall certify compliance with specific fire precautionary measures included as Subsections under CT7.2 - Specific Fire Precautions, before beginning operations during Fire Precautionary Period (closed season) and shall update such certification when operations change.

If helicopter yarding is required, the plan shall include a schedule of rates mutually agreed to for computing Purchaser costs incurred toward meeting Purchaser's obligations under AT11, or for paying for helicopters controlled by Purchaser and used under Forest Service direction for suppressing Operations Fires or other fires on Sale Area, excluding Negligent Fires.

Sale Name: Jack SBA

CT7.2 - SPECIFIC FIRE PRECAUTIONS (09/2002)

When the industrial fire precautions level is I or higher, unless waiver is granted under CT7.22, specific required fire precautionary measures are as follows:

A. Fire Security.

Purchaser will designate in writing a person or persons who shall perform fire security services listed below on Sale Area and vicinity. The designated person will be capable of operating Purchaser's communications and fire fighting equipment specified in the contract, excluding helicopters, and of directing the activities of Purchaser's personnel on Forest fires. Such person must report any fire detected to Forest Service within 15 minutes of detection. In lieu of having the designated person perform the required supervisory duties, Purchaser may provide another person meeting the qualifications stated above to direct the activities of Purchaser's personnel and equipment during all fire fighting activities.

Services described shall be for at least 1 hour from the time Purchaser's Operations are shut down. For the purposes of this provision, personnel servicing equipment, and their vehicles, who are not engaged in cutting or welding metal are excluded.

Fire security services shall consist of moving throughout the operation area or areas constantly looking, reporting, and taking suppression action on any fires detected. Where possible, the designated person shall observe inaccessible portions of helicopter operating areas from vantage points within or adjacent to Sale Area.

Purchaser shall furnish fire security services based on the predicted industrial precaution level, obtained by Purchaser from the appropriate Ranger District Headquarters. If predictions made after 6:00 p.m. local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in fire security services are indicated.

B. Fire Extinguishers and Equipment (on Trucks, Tractors Power Saws, etc.).

(a) Each yarder or loader equipped with an internal combustion engine or other spark emitting source shall be equipped with a readily accessible fire extinguisher, with an Underwriter's Laboratory (UL) Rating of at least 5 B,C.

(b) All power-driven equipment operated by Purchaser on National Forest land, except portable fire pumps, shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C and one "D" handled or long handled round point shovel, size 0 or larger. In addition, each motor patrol, truck and passenger-carrying vehicle shall be equipped with a double-bit axe or Pulaski, 3-1/2 pounds or larger.

(c) Equipment required in (a) and (b) shall be kept in a serviceable condition and shall be readily available.

(d) Each gasoline power saw operator shall be equipped with a pressurized chemical fire extinguisher of not less than 8-ounce capacity by weight, and one long handled round point shovel, size 0 or larger, except at a landing where a suitable fire extinguisher and shovel are immediately available. The extinguisher will be kept in possession of the saw operator at all times. The shovel shall be accessible to the operator within 1 minute.

(e) Each helicopter shall be equipped with one fire extinguisher having a UL rating of at least 5 B,C mounted inside the aircraft within reach of the pilot's operating position.

(f) One refill for each type or one extra extinguisher sufficient to replace each size extinguisher required on equipment shall be safely stored in the fire tool box or other agreed upon place on Sale Area that is protected and readily available.

Sale Name: Jack SBA

(g) At each area where helicopters are being serviced or supplied, a carbon dioxide fire extinguisher with a UL rating of at least 20 B,C will be provided on the site and placed where it is available for immediate use.

#### C. Spark Arresters and Mufflers.

Each internal combustion engine shall be equipped with a spark arrester qualified and rated under USDA Forest Service Standard 5100-1a as shown in the National Wildfire Coordination Group Spark Arrester Guide, unless it is:

(a) Equipped with a turbine-driven exhaust supercharger such as the turbocharger. There shall be no exhaust bypass.

(b) A multi-position engine, such as on power saws which must meet the performance levels set forth in the Society of Automotive Engineers (SAE) "multi-positioned small engine exhaust fire ignition standard, SAE recommended practice J335B" as now or hereafter amended.

(c) A passenger carrying vehicle or light truck, or medium truck up to 40,000 GVW, used on roads and equipped with a factory designed muffler complete with baffles and an exhaust system in good working condition.

(d) A heavy duty truck, such as a dump or log truck, or other vehicle used for commercial hauling, used only on roads and equipped with a factory designed muffler and with a vertical stack exhaust system extending above the cab.

Exhaust equipment described in this Subsection, including spark arresters and mufflers, shall be properly installed and constantly maintained in serviceable condition.

#### D. Fire Tools.

Purchaser shall furnish serviceable fire fighting tools in a readily accessible fire tool box or compartment of sound construction with a hinged lid and hasp so arranged that the box can be secured or sealed. The box shall be red and marked "Fire Tools" in letters at least 1 inch high. It shall contain a minimum of:

- (a) Two axes or Pulaskis with a 32 inch handle.
- (b) Three adze eye hoes. One Pulaski may be substituted for one adze eye hoe.
- (c) Three long handled, round point shovels, size 0 or larger.

#### E. Tank Truck.

Purchaser shall provide a tank truck or trailer, containing not less than 300 gallons of water, during yarding, skidding, loading, land clearing, right-of-way clearing, mechanical falling, and mechanical treatment of slash. Such tank truck or trailer shall be maintained in a serviceable condition and located within 10 minutes, round trip, from each operating side during Fire Precautionary Period (closed season), except as provided under BT7.21.

The tank truck or trailer shall be equipped with a pump capable of discharging 20 gallons of water per minute, using a 1/4 inch nozzle tip, through a 50 foot length of rubber or poly lined hose. In addition, 500 feet of serviceable hard rubber poly or rubber lined or FJRL hose of not less than 1 inch outside diameter, fitted with a nozzle capable of discharging a straight stream of 1/4 inch diameter and a spray pattern shall be immediately available for use. The tank, pump, nozzle and at least 250 feet, of the total 500 feet of hose, shall be connected and ready for use at all times. Synthetic hoses may be used by

Sale Name: Jack SBA

agreement.

If a trailer is used, it shall be equipped with a hitch to facilitate prompt movement. A serviceable tow vehicle shall be immediately available for attachment to the trailer and must meet the time requirements stated above. Such truck or trailer shall be equipped to operate for a minimum of 8 hours.

Where designated on Sale Area Map, Purchaser shall provide a tank trailer or water source and pumping equipment, including accessories, which can be lifted and transported by the yarding system. The component parts shall meet all specifications above. The tank trailer or water supply and pumping accessories shall be deliverable to a fire, in area of operations, within 15 minutes of detection.

In lieu of the above tank trailer or water supply for helicopter operations, Purchaser may provide a suitable helicopter water bucket with a 300 gallon capacity. When Purchaser provides a water bucket, a water source shall be provided within 5 minutes round trip flight time from operating side.

#### F. Communications.

During Purchaser's Operations, excluding powersaw falling and bucking, Purchaser shall provide adequate two-way communication facilities to report a fire to Forest Service within 15 minutes of detection. Citizen band radios (CB's) are not considered adequate two-way communications because FCC Regulations prohibit commercial use.

G. Smoking and Open Fire Restrictions. Smoking and fires shall be permitted only at the option of Purchaser. Purchaser shall not permit open fires on Sale Area without advance permission in writing from Forest Service.

#### H. Blasting.

Blasting shall be permitted only for road construction purposes unless advance permission is obtained from Forest Service.

Whenever the Industrial Fire Precaution Level is II or greater, a fire security person equipped with a long handled round point No. 0 or larger shovel and a 5 gallon backpack pump can filled with water, will stay at location of blast for 1 hour after blasting is done. Blasting may be suspended by Forest Service, in areas of high rate of spread and resistance to control.

Fuses shall not be used for blasting. Explosive cords shall not be used without permission of Forest Service, which may specify conditions under which such explosives may be used and precautions to be taken.

#### I. Compliance with State Fire Laws.

Listing of specific fire precautionary measures in the foregoing Subsections is not intended to relieve Purchaser in any way from compliance with State fire laws covering fire prevention and suppression equipment, applicable to Purchaser's Operations.

#### J. Aircraft Communications.

Every aircraft used in conjunction with Purchaser's Operations shall be equipped with an operable radio system. The radio system shall be capable of transmitting and receiving on VHF frequency 122.85 Megahertz (MHz) with a minimum output of 5 watts at the transmitter. The system shall be located and installed so that the pilot can operate it while flying. A shielded all-weather broad-band antenna shall be part of the system. Radio and antenna shall be properly installed and maintained.

Upon discovery or notification of a fire on Sale Area, all aircraft pilots controlled by Purchaser shall monitor VHF frequency 122.85 MHz when within 5 miles of a fire and broadcast their intentions.

Sale Name: Jack SBA

K. Logging Block Equipment.

Purchaser shall provide a serviceable 5 gallon backpack pump full of water, one axe, and one long handled round point shovel, size 0 or larger, at each haulback block through which a running line passes.

The area below such blocks must be kept clear of all flammable debris under 4 inches in diameter for a distance of 6 feet in all directions. Material larger than 4 inches that poses a fire risk, such as punky logs, must also be removed.

Purchaser shall avoid line-rub on rocks or woody material which may result in sparks or sufficient heat to cause ignition of fire.

CT7.201 - BURNING BY PURCHASER (01/1993)

Notwithstanding the Fire Precautionary Period limitation of BT7.2, the Purchaser is required to obtain written permission from the Forest Service prior to any burning on the National Forest Lands.

Sale Name: Jack SBA

CT7.22 - EMERGENCY FIRE PRECAUTIONS (09/2004)

Purchaser shall restrict operations in accordance with the Industrial Fire Precaution Levels attached. Forest Service may change the Industrial Fire Precaution Levels to other values upon revision of the National Fire Danger Rating System and may change the specific Industrial Fire Precaution Levels when such changes are necessary for the protection of the National Forest. When sent to Purchaser, the revised Industrial Fire Precaution Levels will supersede the attached levels.

INDUSTRIAL FIRE PRECAUTIONS SCHEDULE

LEVEL INDUSTRIAL FIRE PRECAUTION

I. Closed Season - Fire precaution requirements are in effect. A Fire Watch/Fire Security is required at this and all higher levels unless otherwise waived.

II. Partial Hootowl - The following may operate only between the hours of 8 p.m. and 1 p.m. local time:

power saws, except at loading sites;  
cable yarding;  
blasting;  
welding or cutting of metal.

III. Partial shutdown - The following are prohibited:

cable yarding - except that gravity operated logging systems employing non-motorized carriages may be operated between the hours of 8 p.m. and 1 p.m. local time when all blocks and moving lines are 10 feet or more above the ground, excluding the line between the carriage and the choker.

power saws - except at loading sites and on tractor/skidder operations between the hours of 8 p.m. and 1 p.m. local time.

In addition, the following are permitted between the hours of 8 p.m. and 1 p.m. local time:

tractor, skidder, feller-buncher, forwarder, or shovel logging operations where tractors, skidders or other equipment with a blade capable of constructing fireline are immediately available to quickly reach and effectively attack a fire start;  
mechanized loading and hauling;  
blasting;  
welding or cutting of metal;  
any other spark-emitting operation not specifically mentioned.

IV. General shutdown - All operations are prohibited.

The following definitions shall apply to these Industrial Fire Precaution Levels:

Cable yarding systems: A yarding system employing cables and winches in a fixed position.

Sale Name: Jack SBA

Closed Season (Fire Precautionary Period): That time period each year when a fire hazard exists as described in AT9.

Hauling: Where hauling involves transit through more than one shutdown zone/regulated use area, the precaution level at the woods site shall govern the level of haul restrictions, unless prohibited by other than the Industrial Fire Precaution Level system.

Loading sites/woods site: A place where any product or material (including but not limited to logs, firewood, slash, soil, rock, poles, posts, etc.) is placed in or upon a truck or other vehicle.

Advance written waiver of the above precautions may be issued by the Contracting Officer or Forest Service Representative.

Such waiver, or substitute precautions under BT7.21, shall prescribe measures to be taken by Purchaser to reduce the risk of ignition, and/or the spread of fire. The Contracting Officer or Forest Service Representative shall consider site specific weather factors, fuel conditions, and specific operations that result in less risk of fire ignition and/or spread than contemplated when precaution level was predicted. Consideration shall also be given to measures that reduce the precaution levels above. Purchaser shall assure that all conditions of such waivers or substitute precautions are met.

Purchaser shall obtain the predicted Industrial Fire Precaution Level from the appropriate Ranger District headquarters. If predictions made after 6:00 p.m., local time, are significantly different than originally estimated, Forest Service will inform Purchaser when changes in restrictions or industrial precautions are indicated.

CT8.13 - DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTY (09/2004)

Purchaser and Forest Service hereby agree, acknowledge, and accept that there is no expressed or implied warranty provided by the Forest Service that guarantees the Purchaser will be allowed to complete the removal of products sold under the terms of the contract. Upon execution of the contract, Purchaser hereby acknowledges the acceptance of the risk that this contract is subject to interruption or termination as a result of litigation associated with the environmental analysis process used by the Forest Service in the planning of this timber sale. If such interruption or termination occurs due to litigation, Purchaser agrees to accept as full compensation for such interruption remedies pursuant to BT8.33, or for termination remedies pursuant to BT8.34.

Sale Name: Jack SBA

CT8.212 - MARKET-RELATED CONTRACT TERM ADDITION (11/2008)

The term of this contract may be adjusted when a drastic reduction in wood product prices has occurred in accordance with 36 CFR 223.52. The Producer Price Index used to determine when a drastic reduction in price has occurred is stated in AT17. Purchaser will be notified whenever the Chief determines that a drastic reduction in wood product prices has occurred. If the drastic reduction criteria specified in 36 CFR 223.52 are met for 2 consecutive calendar quarters, after contract award date, Contracting Officer will add 1 year to the contract term, upon Purchaser's written request. For each additional consecutive quarter such a drastic reduction occurs, Contracting Officer will, upon written request, add an additional 3 months to the term during Normal Operating Season, except that no single 3-month addition shall extend the term of the contract by more than one year. Contracting Officer must receive Purchaser's written request for a market-related contract term addition before the expiration of this contract.

No more than 3 years shall be added to a contract's term by market-related contract term addition unless the following conditions are met:

(i) The sale was awarded after December 31, 2006; and

(ii) A drastic reduction in wood product prices occurred in at least ten of twelve consecutive quarters during the contract term, but not including the quarter in which the contract was awarded.

For each qualifying quarter meeting the criteria in paragraphs (i) and (ii) of this provision, the Forest Service will, upon the Purchaser's written request, add an additional 3 months during the normal operating season to the contract, except no single 3-month addition shall extend the term of a contract by more than 1 year.

In no event shall a revised contract term exceed 10 years as a result of market-related contract term addition.

Additional contract time may not be granted for those portions of the contract that have a required completion date or for those portions of the contract where Contracting Officer determines that the timber is in need of urgent removal or that timber deterioration or resource damage may result from delay.

CT8.4 - PERFORMANCE BY OTHER THAN PURCHASER (04/2004)

This provision adds subparagraph (b) (iii) to BT8.4 as follows:

(iii) Specifically assumes in writing the obligations of Purchaser as listed in Small Business Certification executed by Purchaser and attached to and made a part of this contract.

Sale Name: Jack SBA

CT8.66# (Option 1) - USE OF TIMBER (04/2004)

(a) This contract is subject to the Forest Resources Conservation and Shortage Relief Act of 1990, as amended (16 USC 620, et seq.).

(b) Except for None determined pursuant to public hearing to be surplus, unprocessed Included Timber shall not be exported from the United States nor used in direct or indirect substitution for unprocessed timber exported from private lands by Purchaser or any person as defined in the Act (16 USC 620e).

(c) Timber in the following form will be considered unprocessed:

(i) Trees or portions of trees or other roundwood not processed to standards and specifications suitable for end product use;

(ii) Lumber, construction timbers, or cants intended for remanufacturing not meeting standards defined in the Act (16 USC 620e); and

(iii) Aspen or other pulpwood bolts exceeding 100 inches in length.

(d) Unless otherwise agreed in writing, unprocessed Included Timber shall be delivered to a domestic processing facility and shall not be mixed with logs intended for export.

(e) Prior to award, during the life of this contract, and for a period of 3 years from Termination Date, Purchaser shall furnish to Forest Service, upon request, records showing the volume and geographic origin of unprocessed timber from private lands exported or sold for export by Purchaser or affiliates.

(f) Prior to delivering unprocessed Included Timber to another party, Purchaser shall require each buyer, exchangee, or recipient to execute an acceptable agreement that will:

(i) Identify the Federal origin of the timber;

(ii) Specify domestic processing for the timber involved;

(iii) Require the execution of such agreements between the parties to any subsequent transactions involving the timber;

(iv) Require that all hammer brands and/or yellow paint must remain on logs until they are either legally exported or domestically processed, whichever is applicable; and

(v) Otherwise comply with the requirements of the Act (16 USC 620d).

(g) No later than 10 days following the execution of any such agreement between Purchaser and another party, Purchaser shall furnish to Forest Service a copy of each such agreement. Purchaser shall retain, for 3 years from Termination Date, the records of all sales, exchanges, or dispositions of all Included Timber.

(h) Upon request, all records dealing with origin and disposition of Included Timber shall be made available to Contracting Officer.

(i) For breach of this Subsection, Forest Service may terminate this contract and take such other action as may be provided by statute or regulation, including the imposition of penalties. When terminated by Forest Service under this Subsection, Forest Service will not be liable for any Claim submitted by Purchaser relating to the termination.

Sale Name: Jack SBA

CT8.71 - TRIPARTITE LAND EXCHANGE (04/1999)

Purchaser agrees that timber values for which cash payment is required under BT4.0 may be applied to any land exchange transaction authorized by law under which the owner of offered lands agrees to accept the money value of timber sold for the value of land granted to the United States.

CT8.72 - BIPARTITE LAND EXCHANGE (04/2004)

Purchaser has offered to exchange land owned by Purchaser, as described in a separate exchange agreement. When title to offered land has been accepted by the United States, Forest Service agrees that the value of the offered land is a land exchange credit and shall be applied to charges for timber in lieu of cash deposits under BT4.21. If Purchaser desires to cut timber prior to acceptance of title by the United States, cash deposits shall be refunded when title to an equivalent value of land is accepted, to the extent such deposits are not needed to satisfy other charges.

CT8.73 - REQUIREMENT FOR SMALL BUSINESS PROCESSING (04/2004)

To meet the requirements of the small business timber sale set-aside program, Purchaser shall not sell, trade, exchange, or otherwise convey for processing more than 30 percent (50 percent in Alaska) of the advertised sawtimber volume of this sale to a concern that is not a small business within the meaning of the small business size regulations found in 13 CFR 121.507.

Purchaser shall, at the time of execution of this contract, complete the "Small Business Certification" (SBA form 723) and submit it to Contracting Officer. The completed certification together with its provisions pertaining to the disposition, manufacturing, and record keeping requirements of Included Timber by Purchaser and other small business concerns is hereby made a part of this contract.

Upon request of Contracting Officer or an officer of the Small Business Administration, Purchaser shall furnish all records sufficient to verify eligibility and compliance with the requirements of this program. Such records may include employee payroll records, disposition of Included Timber records, and other documents as necessary.

Failure to provide records upon request, filing false information, or making false statements relating to SBA size status or failing to comply with the disposition and manufacturing requirements of Included Timber shall be considered a breach of this Subsection and may result in termination of this contract pursuant to BT9.31.