

# Attachments

**Key to Attachments**

Table of Contents

<u>Attachments Title</u>	<u>PAGES</u>
A. Specification List	3 - 4
B. Supplemental Specifications	5 - 10
C. T-Specifications	11 - 42
<u>List of Mandatory Projects</u>	
D. Pre-commercial Thin and Reduce Fuels to an End Result of 8 to 10 Tons Per Acre.	43 - 45
E. Leave Tree Marking	46 - 47

# **Attachment**

**A**

Contract Name: Voodoo Stewardship

**FOREST SERVICE STANDARD SPECIFICATIONS AND SUPPLEMENTALS FOR CONSTRUCTION OF ROADS  
AND BRIDGES SPECIFICATION LIST**

All specifications not included in the specification listing, but referenced by listed specifications, are applicable. The supplements shown on the specification listed are physically attached. Section 100 through 109 of the Standard Specifications and all other Standard or Supplemental Specifications shown in the specification listing are applicable to this contract.

	Attachment A	ROAD NAME	N/A						
CONTRACT NAME	Voodoo Stewardship	ROAD NUMBER	N/A						
		Miles/Sites	N/A						
DATE PREPARED	06-24-2013	CONST/RECONST	N/A						

157	SOIL EROSION CONTROL	2003							
157.03	General	02/24/05							
157.10(c)	Check Dams	2003							
157.13	Maintenance and Cleanup	2003							
703	AGGREGATE	2003							
703.05	Subbase, Base & Surface Course, and Screened Aggregate	12/07/06							
	T-SPECS								
	(See K-F3.1# & Applicable T-SPECS For Details)								
	PREFACE	01/08							
T-803	SNOW REMOVAL	05/07/07							
T-811	BLADING	10/07/07							
T-812	DUST ABATEMENT	05/07/07							
T-813	SURFACING	10/07/07							
T-831	DITCH MAINTENANCE	10/07/07							
T-832	REMOVE AND END HAUL MATERIALS	05/07/07							
T-834	DRAINAGE STRUCTURE MAINTENANCE	10/07/07							
T-835	ROADWAY DRAINAGE MAINTENANCE	05/07/07							
T-836	MAINTENANCE FOR LIMITED USE	05/07/07							
T-838	MAINTENANCE FOR HIGH CLEARANCE VEHICLE USE	05/07/07							
T-839	MAINTENANCE FOR PROJECT USE	05/07/07							
T-841	VEGETATION ESTABLISHMENT	05/07/07							
T-842	CUTTING ROADWAY VEGETATION	10/07/07							
T-851	LOGGING OUT	05/07/07							
T-854	TREATMENT AND DISPOSAL OF DANGER TREES	05/07/07							
T-891	WATER SUPPLY AND WATERING	05/07/07							
T-892	BITUMINOUS PRODUCTS	05/07/07							

# **Attachment**

## **B**

## Attachments B - Supplemental Specifications

### 157 - Soil Erosion Control

157.03\_nat\_us\_02\_24\_2005

#### 157.03 General

Delete the entire subsection and replace with the following:

Prior to the start of construction, submit a written plan that provides permanent and temporary erosion control measures to minimize erosion and sedimentation during and after construction. Do not begin work until the necessary controls for that particular phase of work have been implemented. Do not modify the type, size, or location of any control. An alternate erosion control plan with all necessary permits may be submitted 30 days before intended use.

Incorporate all permanent erosion control features into the project at the earliest practicable time, as outlined in the approved plan.

When erosion control measures are not functioning as intended, immediately take corrective action.

### 703 - Aggregate

703.05\_nat\_us\_12\_07\_2006

Delete 703.05 and replace with the following:

#### 703.05 Subbase, Base, Surface Course, and Screened Aggregate.

**(a) Subbase or base aggregate.** Furnish hard, durable particles or fragments of crushed stone, crushed slag, or crushed gravel conforming the following:

(1) Gradation	Table 703-2
(2) Liquid limit, AASHTO T 89	25 max.
(3) Plastic limit, AASHTO T 90	Nonplastic
(4) Los Angeles abrasion, AASHTO T 96	40% max.
(5) Sodium sulfate soundness loss (5 cycles), AASHTO T 104	12% max.
(6) Durability index (coarse), AASHTO T 210	35 min.
(7) Durability index (fine), AASHTO T 210	35 min.
(8) Fractured faces, ASTM D 5821	50% min.
(9) Free from organic matter and lumps or balls of clay	

Do not use material that breaks up when alternately frozen and thawed or wetted and dried.

Obtain the aggregate gradation by crushing, screening, and blending processes as necessary. Fine aggregate, material passing the No. 4 sieve, shall consist of natural or crushed sand and fine mineral particles.

**(b) Surface course aggregate.** Furnish hard, durable particles or fragments of crushed stone, crushed slag, or crushed gravel conforming the following:

(1) Gradation	Table 703-3
(2) Liquid limit, AASHTO T 89	35 max.
(3) Plastic Index, AASHTO T 90	
a) If the percent passing the No. 200 sieve is less than 12%	2 to 9
b) If the percent passing the No. 200 sieve is greater than 12%	Less than 2
(4) Los Angeles abrasion, AASHTO T 96	40% max.
(5) Sodium sulfate soundness loss (5 cycles), AASHTO T 104	12% max.
(6) Durability index (coarse), AASHTO T 210	35 min.
(7) Durability index (fine), AASHTO T 210	35 min.
(8) Fractured faces, ASTM D 5821	75% min.
(9) Free from organic matter and lumps or balls of clay	

Do not use material that breaks up when alternately frozen and thawed or wetted and dried.

Do not furnish material that contains asbestos fibers.

Obtain the aggregate gradation by crushing, screening, and blending processes as necessary. Fine aggregate, material passing the No. 4 sieve, shall consist of natural or crushed sand and fine mineral particles.

**(c) Screened aggregate** - Furnish hard, durable particles or fragments of stone, slag, or gravel conforming the following:

- |  |              |
|--|--------------|
| (1) Gradtion   | Table 703-16 |
| (2) Plastic Index, AASHTO T 90                           | Less than 9  |
| (3) Los Angeles abrasion, AASHTO T 96                    | 55% max.     |
| (4) Free from organic matter and lumps or balls of clay. |              |

Do not use material that breaks up when alternately frozen and thawed or wetted and dried.

Obtain the aggregate gradation by crushing, screening, and blending processes as necessary.

**Delete Table 703-2 and replace with the following:**

**Table 703-2  
Target Value Ranges for Subbase and Base Gradation**

Sieve Size	Percent by Mass Passing Designated Sieve (AASHTO T 27 and T 11)					
	Grading Designation					
	A (Subbase)	B (Subbase)	C (Base)	D (Base)	E (Base)	
2½ inch	100					
2 inch	97 - 100	100	100			
1½ inch		97 - 100				
1 inch	65 - 79 (6)		80 - 100 (6)	100		
¾ inch			64 - 94 (6)	86 - 100 (6)	100	
½ inch	45 - 59 (7)					
⅜ inch			40 - 69 (6)	51 - 82 (6)	62 - 90 (6)	
No. 4	28 - 42 (6)	40 - 60 (8)	31 - 54 (6)	36 - 64 (6)	36 - 74 (6)	
No. 40	9 - 17 (4)			12 - 26 (4)	12 - 26 (4)	
No. 200	4.0 - 8.0 (3)	4.0 - 12.0 (4)	4.0 - 7.0 (3)	4.0 - 7.0 (3)	4.0 - 7.0 (3)	

( ) The value in the parentheses is the allowable deviation (±) from the target values..

**Delete Table 703-3 and replace with the following:**

**Table 703-3  
Target Value Ranges for Surface Gradation**

Sieve Size	Percent by Mass Passing Designated Sieve (AASHTO T 27 and T 11)														
	F	G	H	S	T	U	Grading Designation								
1 1/2 inch	100 <sup>(</sup>			100											
1 inch	97-100	100		72 - 92 (6)	100										100
3/4 inch	76-89 (6)	97 - 100	97 - 100							71 - 91 (6)					
1/2 inch															
3/8 inch	56-68 (6)	70 - 80 (6)	80 - 92 (6)	51 - 71 (6)											71 - 90 (6)
No. 4	43-53 (7)	51 - 63 (7)	58 - 70 (7)	36 - 53 (7)	43 - 60 (7)										50 - 68 (7)
No. 8				26 - 40 (6)	30 - 46 (6)										34 - 51 (6)
No. 16	23-32 (6)	28 - 39 (6)	28 - 40 (6)												
No. 40	15-23 (5)	19 - 27 (5)	16 - 26 (5)	14 - 25 (5)	16 - 28 (5)										19 - 30 (5)
No. 200	10.0-16.0 (4)	10.0 - 16.0 (4)	9.0 - 14.0 (4)	8.0 - 15.0 (4)	8.0 - 15.0 (4)										8.0 - 15.0 (4)

( ) The value in the parentheses is the allowable deviation (±) from the target values.  
If the plasticity index (PI) is greater than 0, the TV range for the No. 200 sieve size is 8-12 (4).

**Add Table 703-16:**

**Table 703-16  
Gradation Requirements for Screened Aggregate**

Sieve Size	Percent by Mass Passing Designated Sieve (AASHTO T 27 and T 11)						
	Grading Designation						
	L	M	N	O	P	Q	R
6 inch	100	100					
4 inch			100	100			
3 inch					100	100	
2 inch							100
No. 4		15-45		15-45		15-45	

# **Attachment**

**C**

**Attachment C - T-Specifications**

FOREST SERVICE  
SPECIFICATIONS FOR  
MAINTENANCE OF  
ROADS IN  
STEWARDSHIP CONTRACTS

PACIFIC NORTHWEST REGION

EM 7730-20

01/23/2008

**STEWARDSHIP CONTRACT**

**ROAD MAINTENANCE SPECIFICATIONS**

<u>SPEC#</u>	<u>SUBJECT DESCRIPTION</u>	<u>DATE</u>
T-803	Snow Removal	05/07/2007
T-811	Blading	10/07/2007
T-812	Dust Abatement	05/07/2007
T-813	Surfacing	10/07/2007
T-831	Ditch Maintenance	10/07/2007
T-832	Remove And End Haul Materials	05/07/2007
T-834	Drainage Structure Maintenance	10/07/2007
T-835	Roadway Drainage Maintenance	05/07/2007
T-836	Maintenance for Limited Use	05/07/2007
T-838	Maintenance for High Clearance Vehicle Use	05/07/2007
T-839	Maintenance for Project Use	05/07/2007
T-841	Vegetation Establishment	05/07/2007
T-842	Cutting Roadway Vegetation	10/07/2007
T-851	Logging Out	05/07/2007
T-854	Treatment and Disposal of Danger Trees	05/07/2007
T-891	Water Supply and Watering	05/07/2007
T-892	Bituminous Products	05/07/2007

**SUPPORTING DOCUMENTS FOR MAINTENANCE SPECIFICATIONS**

<u>SUBJECT DESCRIPTION</u>	<u>DATE</u>
Cover Content Preface	01/08
Cover Pages	01/08
Intent Use Guide	01/08

**NO DRAWINGS ACCOMPANY THESE SPECIFICATIONS.**

Contract Name: Voodoo Stewardship

**PREFACE**  
**01/08**

The Pacific Northwest Region of the Forest Service has developed this book for use in the preparation and administration of maintenance requirements included in Stewardship Contracts.

Included are the Standard Specifications (Sections) that commonly apply in Stewardship Contract Contracts. Conditions and requirements specific to individual projects are identified in the Special Project Specifications.

Special Project Specifications, which do not change the intent of the parent section, may be approved by the Forests.

This book is available from the Supervisor's Office of any National Forest in Region 6.

**Maintenance Level Requirements**

**Maintenance Levels** - The following are abbreviated descriptions of maintenance levels.

1. **Maintenance Level II** - Conditions are suitable for high clearance vehicle travel at prudent driving speeds less than 15 mph. Road is maintained in accordance with Section T-836.
2. **Maintenance Level III** - Minimum conditions are provided for passenger car use. Surface provides moderately convenient travel at prudent driving speeds between 15 and 25 mph with corresponding surface roughness tolerated. The surface meets the following conditions.
  - a. Potholes or washboard in wheel tracks normally do not exceed 2 inches in depth, and should not be of such frequency that traffic tends to widen traveled way to avoid the deformities.
  - b. Surface is drained and substantially retains its cross slope or crown.
  - c. Wheel ruts caused by use shall not be in excess of 3 inches in depth on horizontal curves.
3. **Maintenance Level IV** - Higher consideration than in Level III is given to comfort and convenience of the passenger car and commercial user at prudent driving speeds above 25 mph. The surface will meet the following conditions:
  - a. Substantially free of chuckholes, wheel ruts, or washboard corrugations. Surface is drained and retains its cross slope or crown.
  - b. Berms of loose surfacing caused by use do not generally exist, except on horizontal curves berms up to 2 inches in depth may be present.
4. **Maintenance Level V** - the highest degree of consideration is given to user comfort and convenience. Roads are commonly paved or continually dust controlled for travel at speeds of nominally 35 mph. Generally, the surface will meet the following conditions:
  - a. **Level IV plus:** Surface is consolidated except for limited periods immediately preceding maintenance performance.
  - b. Berms are not acceptable.

**T-803 - SNOW REMOVAL (05/07)****803.01 Description**

This Section provides for removal of snow from roads to facilitate logging operations and safe use.

**803.02 Maintenance Requirements**

- (1) Erect signs required by the Sign Plan in the SUPPLEMENTAL SPECIFICATIONS.
- (2) Perform work in a manner to preserve and protect roads and appurtenances, and prevent erosion damage to roads, streams, and other Forest values.
- (3) Do not undercut banks. Do not blade gravel or other surfacing material off the road.
- (4) Keep roadbed drainage ditches, drain dips, and culverts functional when needed during operations and upon completion of operations.
- (5) Control snow removal to identify the usable traveled way having roadbed support. Reshape over-width plowing as necessary to define the usable width.
- (6) Space, construct, and maintain drainage holes in the dike of snow or berm caused by snow removal operations. Place drain holes to obtain surface drainage without discharging on erodible fills.
- (7) Close roads to wheeled vehicles at times and in the manner specified in C(T)5.12 or the Road Rules document.
- (8) Upon seasonal completion of Contractor's Operations, effectively block the road by a snow barricade, unless otherwise approved by the Contracting Officer.
- (9) Remove snow for either public access or project use as established in the SUPPLEMENTAL SPECIFICATIONS and meet the following requirements:
  - (a) Removal for Public Access (Method JU) - Remove snow from all of the traveled way, including turnouts, for safe and efficient use for both timber transportation and the public. Remove intruding windfalls, debris, or slough and slide material for the full width of the traveled way and deposit out of drainage's at locations designated by the Contracting Officer.
  - (b) Removal for Project Use (Method TS) - Remove snow from all or part of the traveled way, including sufficient turnouts for safe and efficient use for timber transportation and to protect the road. Remove intruding windfalls, debris or slough and slide material and dispose of only as necessary to provide passage for timber transportation. Removed materials may be deposited off the traveled way or outside the traveled way at locations designated by the Contracting Officer.
- (10) When directed by the Contracting Officer, replace in kind, within sixty (60) days after the start of Normal Operating Season, any surfacing material which has been bladed off the road, unless otherwise agreed. Contracting Officer will notify Contractor in writing as to the cubic yard equivalent of bladed off material by the start of the normal operating season.

**803.03 Equipment**

Contractor may use any type of equipment to remove snow, providing:

- a. Type or use of equipment is not restricted in C(T)5.12 or Road Rules document.
- b. Equipment is of the size and type commonly used to remove snow and will not cause damage to the road.
- c. The use of plows or dozers to remove snow requires written approval by the Contracting Officer. Equip plows or dozers with shoes or runners to keep the dozer blade a minimum of 2 inches above the road surface unless otherwise approved by the Contractor Officer.

**803.04 Ice Control**

Contract Name: Voodoo Stewardship

Ice control may be performed by Contractor when approved by the Contracting Officer in writing. Such approval will include ice control materials, application rates, and any specific requirements of use.

**T-811 BLADING (10/07)**

**811.01 Description -**

This work consists of surface blading the traveled way to a condition that facilitates traffic and Provides proper drainage. Blading includes shaping the crown or slope of travel traveled way, berms, and drainage dips in accordance with this specification. Compaction is required when shown on the ROAD LISTING.

**811.02 Maintenance Requirements**

**A. Timing-** Perform surface blading during the contract period as often as needed to provide conditions stated for the maintenance level of the road.

**B. General -**

1. Blade and shape the existing traveled way and shoulders, including turnouts , to produce a surface which is uniform, consistent to grade, and crowned or cross-sloped as indicated by the character of the existing surface, unless otherwise shown in the ROAD LISTING, to at least 13 mm (½ inch) per .305 meter (1 foot) of width, but not more than 19 mm (¾ inch) per .305 meter (1 foot) of width. Thoroughly loosen surfacing material to no less than 50 mm ( 2 inches) depth or the depth of potholes or corrugations. Scarification to facilitate cutting to the full depth of potholes or corrugations may be elected, but will be considered incidental to blading. Do not scarify deep enough to cause contamination of the surfacing.

2. Apply water during blading when sufficient moisture is not present to prevent segregation. Supply, haul, and apply water in accordance with Section T-891.

3. Shape existing native rock or aggregate surfaced drainage dips to divert surface runoff to existing outlet devices, ditches, or discharge locations.

4. Establish a blading pattern which provides a uniform driving surface, retains the surfacing on the roadbed, and provides a thorough mixing of the materials within the completed surface width. Upon final blading, no disturbed rock shall protrude more than 50 mm (2 inches) above the adjacent surface unless otherwise provided in the contract. Remove and place outside the roadbed material not meeting this dimension so as not to obstruct drainageways or structures. This material may be scattered off the roadbed if there is free drainage.

Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

<b>Invasive Species of Concern Prevention Practices</b>
<b>Refer to Contract Provision B.6.3.5</b>

**C. Routine Blading -**

1. Conform to the dimensions SHOWN ON THE DRAWINGS or designated in the SUPPLEMENTAL SPECIFICATIONS upon completion of blading.

2. Shape roadbed width in excess of the dimensions shown only as needed to provide drainage away from the traveled way. Do not remove established grasses and other vegetation from the excess width except as incidental to providing drainage or unless otherwise provided in the contract.

**D. Compaction -**

Roads requiring compaction will be included in the ROAD LISTING. Unless Compaction Method B is designated in the ROAD LISTING, all traveled ways requiring compaction may be compacted by Method A. Compaction shall commence immediately following blading.

**Compaction methods are:**

**Compaction Method A:** By breaking track while operating equipment on the traveled way.

**Compaction Method B:** 7--9 metric ton (7-10 ton) pneumatic, steel, or equivalent vibratory roller, operated to cover the full width two (2) times.

**E. Undercutting -**

Undercutting roadway back slope is not permitted.

**F. Intersections**

1. At intersections, blade the roadbeds of side roads which are not closed or restricted from vehicular use to ensure smooth transitions.
2. Signing, cross ditching in the road surface (traveled way), earth berms, or other devices placed to discourage or eliminate use by passenger cars, are field evidence of road closure or restriction. Roads listed for work under Sections T-835, T-836, T-838, or T-839 are considered restricted.
3. Side roads listed for work under this Section are not restricted.

**G. Cleaning of Structures -** Do not allow materials resulting from work under this Section to remain on or in structures, such as bridges, culverts, cattle guards, or drainage dips.

**H. Berms -** Maintain existing berms to the condition of adjacent segments. Do not create new berms (windrows).

**I. Smooth Blading -** Smooth blading may be used as an interim measure to remove loose surfacing material from the wheel paths, and store removed materials in a recoverable windrow, until blade processing as described in this section is feasible. Watering will not be required for smooth blading. Accomplish smooth blading without distorting the existing cross-slope or crown of the traveled way.

Move and store loose surfacing materials on the high side of super-elevated curves and sections with uniform inslope or outslope. In crowned sections, store the material on either or both sides as elected. Windrow and place stored materials to provide not less than 3.6 meters (12 feet) of smooth traveled way on one-lane segments, or 6 meters (20 feet) of smooth traveledway on two-lane segments, or segments with turnouts. Cut holes through windrows, which may collect water on the road, for drainage at least every 150 meters (500 feet).

**T-812 - DUST ABATEMENT (05/07)****812.01 Description**

This work consists of applying dust palliatives on roads shown in the Road Listing.

**812.02 Materials**

The dust palliative materials are shown in the Road Listing, unless shown as Optional for Contractor's election. If Optional is shown then the Contractor may use any of the products listed below. Dust palliative materials shall meet the following requirements:

- A. Water (H2O) will be obtained from sources SHOWN ON THE DRAWINGS or listed in the SUPPLEMENTAL SPECIFICATIONS to Section T-891 Water Supply, unless otherwise approved by the Contracting Officer.
- B. Lignin Sulfonate (LIG S) Provide certification that the material meets the requirements of Subsection 725.20 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP-03)" and the Forest Service Supplemental Specification 725.20.
- C. Magnesium Chloride (MG CL2) Provide certification that that the material meets the requirements of Subsection 725.02 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02.
- D. Calcium Chloride Brine (CA CL2B). Provide certification that the material meets the requirements of Subsection 725.02 of the " Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02..
- E. Calcium Chloride Flake (CA CL2F). Provide certification that that the material meets the requirements of Subsection 725.02 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP03) " and the Forest Service Supplemental Specification 725.02..
- F. Bituminous dust palliatives. Manufacture materials specifically for dust abatement purposes which conform to the requirements of Section T-892 for each listed road in the Road Listing.

**812.03 Methods**

As shown in the SUPPLEMENTAL SPECIFICATIONS, Contractor may utilize a variety of methods to decrease or eliminate the need for dust abatement.

**812.04 Equipment**

- A. Design, equip, and operate application equipment for spreading dust palliatives so that the material is uniformly applied at the rate and traveled way widths shown in the Road Listing.
- B. For bituminous palliatives provide equipment that heats and applies the bituminous material. Provide a bituminous distributor that is self-powered and mounted on pneumatic tires and equipped with a pump and circulating spray bar, a tachometer, pressure gauges, accurate volume measuring devices such as visual volume dial or gauge calibrated to the tank, and a thermometer. Provide equipment which is a standard commercial type of proven performance.
- C. Accomplish dilution of dust palliatives within the application vehicle with the water source protected from contamination. Circulate the resulting mixture at least five (5) minutes to ensure uniform mixing prior to application.

**812.05 Maintenance Requirements**

A. Limit water applications to abatement for hauling vehicles and provide at a frequency and rate which controls dust such that vehicle tail lights and turn signals remain visible. Vary rates of application as needed but remain low enough to avoid forming rivulets. Accomplish the abatement by sufficient frequency of application without saturating and softening the traveled way. Compacted or glazed road surface or wheel tracks may be loosened as needed for water penetration.

B. Apply all other dust palliatives at the rates and times agreeable to the Contracting Officer. The Road Listing shows the expected average application rate and may be varied to meet field conditions. Lignin Sulfonate, Magnesium Chloride, and Calcium Chloride Brine are listed as liters per square meter of the undiluted product at fifty (50), thirty-three (33), and thirty-eight (38) percent respectively. Calcium Chloride Flake is listed in Kilograms per square meter at seventy-seven (77) percent concentration.

C. Apply bituminous dust palliatives only when the surface to be treated contains sufficient moisture to obtain uniform distribution of the dust palliative unless noted differently in the SUPPLEMENTAL SPECIFICATIONS.

D. Prior to initial application, when needed, the road will be bladed and shaped under Section T-811, Blading.

E. Required subsequent applications may be applied to the existing road surface without blading.

F. Dust palliatives will not be applied in a manner that spatters or mars adjacent structures or trees, or placed on or across cattleguards or bridges. Discharge dust abatement material only on roads approved by the Contracting Officer.

**T-813 SURFACING (10/07)**

**813.01 Description**

This work consists of placing surface aggregate as DESIGNATED ON THE GROUND, or as ordered by the Contracting Officer. It includes preparing the area, furnishing, hauling, and placing all necessary materials and other work necessary to blend with the adjacent road cross section.

**813.02 Materials**

- A. Materials will be Government-furnished when stated in the supplemental specifications.
- B. Materials furnished by the Contractor shall conform to the gradation and quality requirements of Section 703 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects FP-03 U.S. Customary Units" and FS supplements to the FP-03.
- C. All materials transported onto National Forest System land shall be free of invasive species of concern. Written documentation of methods used to determine the invasive species of concern free status of any and all materials furnished by the Contractor shall be submitted to the Contracting Officer before transport of any materials onto National Forest System land.

The Contracting Officer shall have 5 days, excluding weekends and Federal holidays, to review the methods and inspect the materials after the required written documentation is provided by the Contractor. After satisfactory review and inspection or after such 5 day period, the Contractor may transport the material onto National Forest System land.

Material or methods appropriate for establishing invasive species of concern free status for the particular invasive species of concern are listed below.

Invasive Species of Concern and Acceptable Methods specific to this project:

Invasive Species of Concern	Acceptable Methods
<i>Centaurea biebersteinii</i> (spotted knapweed) <i>Centaurea diffusa</i> (diffuse knapweed) <i>Centaurea pratensis</i> (meadow knapweed) <i>Cirsium arvense</i> (canada thistle) <i>Cirsium vulgare</i> (bull thistle) <i>Cytisus scoparius</i> (scotch broom) <i>Hypericum perforatum</i> (st. john's-wort) <i>Senecio jacobaea</i> (tansy ragweed)	Documentation of "weed-free" certification of commercial material source

**813.03 Maintenance Requirements**

- A. Thoroughly loosen the area to be surfaced to a minimum depth of 1 inch prior to placement of aggregate.
- B. Mixing and Placing

When scheduled coincidentally with work under Section T-811, and included in the SUPPLEMENTAL SPECIFICATIONS, mix surfacing and existing aggregate with water until a uniform mixture is obtained prior to final shaping and compaction.

Otherwise, spread the material on the prepared area in layers no more than 4 inches in depth. When more than one (1) layer is required, shape and compact each layer before the succeeding layer is placed. Upon completion, the surfacing shall reasonably conform to the adjacent cross section and provide smooth transitions in the road profile.

- C. Compaction Methods

Contract Name: Voodoo Stewardship

**Compaction Method A:** Breaking track while operating equipment on the traveled way.

**Compaction Method B:** 7-10 ton pneumatic, steel, or equivalent vibratory roller, operated to cover the full width two (2) times.

Either Method A or B may be used unless Method B is designated in the ROAD LISTING.

**T-831 DITCH MAINTENANCE (10/07)**

**831.01 Description**

This Section provides for routine maintenance of various types of ditches to provide a waterway which is unobstructed, as shown on the ROAD LISTING or DESIGNATED ON THE GROUND.

**831.02 Maintenance Requirements**

- A. Maintain ditches by removing rock, soil, wood, and other materials. Maintained ditches shall function to meet the intent of the original design.
- B. Undercutting backslopes during removal operations is not permitted.
- C. Suitable material up to 4 inches in greatest dimension removed from the ditches may be blended into existing native road surface and shoulder or placed in designated berm.
- D. Do not blend material from ditch cleaning operations into aggregate surfaced roads. Do not blade material across aggregate or bituminous surfaced roads, unless approved in writing by the Contracting Officer.
- E. Haul material in excess of 831.02 D or subject to 831.02 E to a designated waste area under Section T-832. Remove excess materials temporarily stored on the ditch slope or edge of the shoulder daily.
- F. Remove limbs and wood chunks in excess of 12 inches in length or 3 inches in diameter from ditches and place outside the roadway.
- G. Clean paved surfaces of all materials resulting from ditch maintenance work.
- H. Shape lead-off ditches to drain away from the traveled way.
- I. Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

<b>Invasive Species of Concern Prevention Practices</b>
<b>Refer to Contract Provisions B.6.3.5 and K-G.6.0#</b>

**T-832 REMOVE AND END HAUL MATERIALS (05/07)****832.01 Description**

Work consists of loading, hauling, and placing of slide, slough, or excess materials such as rock, soil, vegetation, and other materials to designated disposal sites.

**832.02 Maintenance Requirements**

**A.** Remove, end haul, and dispose of excess materials generated by work under other Sections of this contract.

**B.** Remove the slide and slough materials in the area extending approximately 6 feet vertically above the road surface and not more than 3 feet down slope from the roadbed. Dispose of material at designated sites as SHOWN ON THE DRAWINGS, identified in SUPPLEMENTAL SPECIFICATIONS, or as ordered by the Contracting Officer.

Reshape the slope which generated the slide material as nearly as practical to its original condition by equipment operating from road surface. Reshaping of roadside ditches in slide area shall be in accordance with Section T-831.

**C.** When approved by the Contracting Officer, fill slumps by compacting selected materials into roadway depressions. Compaction is by Method 2.

**D.** Place all materials in disposal sites as specified in the SUPPLEMENTAL SPECIFICATIONS, as SHOWN ON THE DRAWINGS, or as ordered by the Contracting Officer.

1. Method 1 - Side Casting and End Dumping. Material may be placed by side casting and end dumping. Where materials include large rocks, provide a solid fill by working smaller pieces and fines into voids. Shape the finished surfaces to drain.

2. Method 2 Layer Placement - Step or roughen surfaces on which materials are to be placed prior to placing any material. Place materials in approximately horizontal layers no more than 12 inches thick. Compact each layer by operating hauling and spreading equipment over the full width of each layer.

**E.** Repair any damage to existing aggregate or pavement surfaces.

**T-834 DRAINAGE STRUCTURE MAINTENANCE (10/07)**

**834.01 Description**

This work consists of cleaning and reconditioning culverts and other drainage structures.

**834.02 Maintenance Requirements**

**A.** Clean drainage structures, inlet structures, culverts, catch basins, and outlet channels specified in the SUPPLEMENTAL SPECIFICATIONS. Clean catch basins by removing the material within the area SHOWN ON THE DRAWINGS.

**B.** Clean the transition from the ditch line to the catch basin a distance of 10 feet from the catch basin. Clean outlet channels and lead-off ditches a distance of 6 feet. Remove and place debris and vegetation so as to not enter the channel or ditch, or obstruct traffic. Haul debris and vegetation to a designated disposal area in accordance with Section T-832.

**C.** Hydraulic flushing of drainage structures is not allowed unless provided for in the SUPPLEMENTAL SPECIFICATIONS.

**D.** Cleaning and reconditioning are limited to the first 3 feet of inlet and outlet, determined along the top of the structure. Recondition culvert inlet and outlet by field methods such as jacking out or cutting away damaged metal which obstructs flow. Treat cut edges with a zinc rich coating, in accordance with AASHTO M 36M and ASTM A 849.

**E.** Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

<b>Invasive Species of Concern Prevention Practices</b>
<b>Refer to Contract Provisions B.6.3.5 and K-G.6.0#</b>

**T-835 ROADWAY DRAINAGE MAINTENANCE (05/07)****835.01 Description**

This work consists of providing post haul drainage on roads.

**835.02 Maintenance Requirements****A. Drainage**

1. Upon completion of work, shape the roadway to provide for the removal of surface water. The roadway need not be passable to vehicles. Repair and reinstall water bars, barriers or berms existing prior to the Contractor's operation. Areas where water is ponded by existing centerline profile sags in through cuts may be left untreated.
2. Continuous blade shaping of the roadbed is not required under this specification.
3. Work to be done at staked locations shall be as indicated on the stake and/or stated in SUPPLEMENTAL SPECIFICATIONS:
4. Any of the following methods are acceptable for use at eroded or rutted locations:
  - Method A:** Outsloping the roadbed at not less than  $\frac{1}{2}$  inch per yard of width.
  - Method B:** Insloping the roadbed at not less than  $\frac{1}{2}$  inch per yard of width.
  - Method C:** Water bar roadbed at locations staked on the ground and construct as SHOWN ON THE DRAWINGS or as included in SUPPLEMENTAL SPECIFICATIONS.
5. Drainage structures located in through fills and natural watercourses shall be fully functional without obstructions, including inlet and outlet channel within 20 feet of the structure.
6. Either clean culverts and other fabricated structures to provide drainage from road ditches and make the ditch functional or provide water bar(s) across the roadbed. Removed structures shall become Contractor's property to be removed from National Forest System land. Remove and replace any Contractor-installed temporary drainage structures with a water bar.

**B. Slides, Slumps and Slough**

1. Slides and slough may be left in place, provided they do not potentially impound water or divert water from watercourses. As necessary, reshape the various surfaces to provide drainage.
2. Provide drainage to effectively decrease or eliminate the entry of surface water into slides, slumps, and roadbed surface cracks. Place berms, waterbars or ditches as needed to intercept and remove runoff water from the roadbed. Surface seal cracks by covering over with native soil materials to prevent additional water entry and compact with equipment tires.

**C. Entrance Devices**

Upon completion of work, replace entrance devices to effectively eliminate access by motorized vehicles having four (4) wheels and a width in excess of 50 inches.

**D. Seeding**

Seed and fertilize all disturbed areas in accordance with requirements set forth in Section T-841.

**T-836 - MAINTENANCE FOR LIMITED USE (05/07)****836.01 Description**

This work consists of making limited use roads passable for joint use by Contractor and high clearance vehicles, and providing drainage from the traveled way and roadbed.

**836.02 Maintenance Requirements****A. Traveled Way**

Contractor may smooth or fill existing cross ditches and water bars and by agreement modify existing road junctions to enable vehicle access. Prior to beginning haul and resumption of haul after an extended stoppage:

1. Remove brush, fallen trees, rocks, and other debris from traveled way, including turnouts, turnarounds, and other locations that interfere with needed maintenance as follows:

a. No object extending over 4 inches above the road surface shall remain within the 12 feet usable traveled way and 10 feet turnout widths. Center the usable width on the roadbed or position away from the fill slope.

b. Cut and remove standing or down trees, logs, brush, and limbs from within the area described in 1 a. above. Remove encroaching limbs to a height of 14 feet above the traveled way surface. Scatter material not meeting utilization standards outside and below the roadbed on the fill side. Limb and remove timber which meets utilization standards or deck at agreed locations.

c. Place all removed materials away from drainages.

d. During use, maintain drainage structures, including dips, ditches and culverts in a useable condition.

2. Clean and recondition drainage facilities in accordance with: Section T-831 and T-834.

**B. Slough and Slides**

1. Slough and slides may be left in place, provided surface drainage is provided and at least 12 feet of width is available for vehicle passage.

2. Contractor may reposition or ramp over slides and slough when the traveled way width is less than 12 feet providing the material is capable of supporting vehicles. Limit out slope to no more than six percent.

Contract Name: Voodoo Stewardship

3. Reposition slough or slide materials on the roadbed which are not capable of supporting a vehicle to provide the 12 foot width. When directed by the Contracting Officer, slough or slide material will be removed under Section T-832.

**C. Slumps and Washouts**

1. Drain the roadbed immediately upgrade of slumps and longitudinal cracks to prevent water from entering slump area.
2. Slumps and longitudinal cracks at the edge of the roadbed shall not be considered a part of the usable width. Usable width may be reduced to 10 feet in the area of the slump.
3. Unless the Contractor Officer agrees to material being placed on slumps, ramp the slumps on both ends into undisturbed roadbed to provide at least 10 feet usable width. Use removed materials to guide vehicles to the ramp location or to aid in draining the area.
4. Washouts may be filled with suitable material.

**D. Post haul**

At the end of hauling or prior to entering into seasonal shutdowns or a period of extended inactivity:

1. Shape the traveled way and disturbed roadbed to provide functional drainage.
2. Reinstall removed cross ditches and water bars and provide any additional drainage structures necessary to offset changes caused through use and maintenance.
3. Leave roads useable for high clearance vehicles. Remove or reshape contractor modifications at road junctions to leave the entrance as it was before use, or as agreed at the time of improvement.

Contract Name: Voodoo Stewardship

**T-838 MAINTENANCE FOR HIGH CLEARANCE VEHICLE USE (05/07)**

**838.01 Description**

This work consists of making limited use roads passable for project use by Contractor and providing drainage from the traveled way and roadbed.

**838.02 Maintenance Requirements**

**A. Traveled Way**

Contractor may smooth or fill existing cross ditches and water bars and as approved by the Contracting Officer modify existing road junctions to enable vehicle access. The Contractor may perform the following work prior to beginning haul and resumption of haul after an extended stoppage:

1. Remove brush, fallen trees, rocks, and other debris from traveled way, including turnouts, turnarounds, and other locations that interfere with needed maintenance as follows:
  - a. No object extending over 4 inches above the road surface shall remain within the 12 feet usable traveled way. Center the usable width on the roadbed or position away from the fill slope.
  - b. Cut and remove standing or down trees, logs, brush, and limbs from within the area described in 1(a). Remove encroaching limbs to a height of 14 feet above the traveled way surface. Scatter material not meeting utilization standards outside and below the roadbed on the fill side. Limb and remove timber that meets utilization standards or deck at locations approved by the Contracting Officer.
  - c. Place all removed materials away from drainages.
  - d. During use, maintain drainage structures including dips, ditches and culverts in a usable condition.
2. Clean and recondition drainage facilities in accordance with Section T-831 and T-834.

**B. Slough and Slides**

1. Slough and slides may be left in place, provided surface drainage is provided and at least 12 feet of width is available for vehicle passage.
2. Contractor may reposition or ramp over slides and slough when the traveled way width is less than 12 feet providing the material is capable of supporting vehicles. Limit out slope to no more than six percent.

Contract Name: Voodoo Stewardship

3. Reposition slough or slide materials, which are not capable of supporting a vehicle, on the roadbed to provide the 12 feet width. When directed by the Contracting Officer, slough or slide material will be removed under Section T-832.

**C. Slumps and Washouts**

1. Drain the roadbed immediately upgrade of slumps and longitudinal cracks to prevent water from entering slump area.
2. Slumps and longitudinal cracks at the edge of the roadbed shall not be considered a part of the usable width. Usable width may be reduced to 10 feet in the area of the slump.
3. Unless the Contracting Officer approves material being placed on slumps, ramp the slumps on both ends into undisturbed roadbed to provide at least 10 feet usable width. Use removed materials to guide vehicles to the ramp location or to aid in draining the area.
4. Washouts may be filled with suitable material.

**D. Post haul**

At the end of hauling or prior to entering into seasonal shutdowns or a period of extended inactivity:

1. Shape the traveled way and disturbed roadbed to provide functional drainage.
2. Reinstall removed cross ditches and water bars and provide any additional drainage structures necessary to offset changes caused through use and maintenance.
3. Leave roads useable for high clearance vehicles. Remove or reshape contractor modifications at road junctions to leave the entrance as it was before use, or as agreed at the time of improvement.

Contract Name: Voodoo Stewardship

**T-839 MAINTENANCE FOR PROJECT USE (05/07)**

**839.01 Description**

Work consists of providing minimum access required for Contractor's Operations and associated Forest Service contract administration and preventing unacceptable resource or road damage.

**839.02 Maintenance Requirements**

**A.** Contractor is authorized to perform the following maintenance to provide vehicle passage and drainage:

1. Removing log, earth, and rock barriers and/or improving existing road junctions to enable vehicle access as mutually agreed.
2. Smoothing or filling existing cross ditches and water bars.
3. Installing Contractor-furnished culverts or other temporary drainage structures for shallow stream crossings as approved by the Contracting Officer.
4. Removing brush, fallen trees, rocks, and other materials from the traveled way and other locations that interfere with needed maintenance:
  - a. Place all removed materials away from drainages.
  - b. Limb and remove timber which meets utilization standards or deck at locations approved by the Contracting Officer. Scatter other woody materials, including limbs, off of and below the roadbed without creating concentrations.
5. Clean and recondition drainage structures in accordance with Section T-831 and Section T-834.
6. Reposition or ramp over slough and slides to provide adequate width of traveled way material.
7. Provide traveled way drainage above slumps and seal cracks in slump area. Ramp the slumps on both ends into undisturbed roadbed to provide usable width unless otherwise ordered by the Contracting Officer.

**B.** During use, the traveled way shall not channel water along the road. Prior to seasonal periods of anticipated rains and runoff, perform the following work:

1. Shape the traveled way and roadbed to drain.
2. Reinstall removed cross ditches and water bars and provide any additional drainage structures necessary to offset changes through use and maintenance.
3. Perform work outlined in 839.02 A (5), (6), and (7).
4. During periods of non use, replace original barrier or provide and maintain standard MUTCD, Type 3, barricades unless alternate type barriers are approved by the Contracting Officer.

**839.03 Post Haul Requirements**

**A.** Upon completion of project use perform such work as needed to reasonably conform to the character of the existing road prior to Contractor's maintenance for project use, unless otherwise provided in the SUPPLEMENTAL SPECIFICATIONS or the Road Listing. Work shall be in addition to requirements of 839.02 B and in accordance with 839.03 B and C.

**B.** Roads designated in the Road Listing to be blocked shall conform to the requirements of Section T-835. Unless otherwise approved by the Contracting Officer, remove Contractor-installed temporary structures from National Forest System land. Associated commercially-obtained materials shall remain the property of the Contractor.

**C.** Remove or reshape Contractor improvements at road junctions, as approved by the Contracting Officer at the time of improvement.

**T-841 VEGETATION ESTABLISHMENT (5/07)**

**841.01 Description**

This work consists of applying seed, fertilizer, mulch, and planting containerized or bare root plant stock singularly or in specified combinations to roadways and disposal areas. Work area may be limited to designated portions of the roadway and roadside or include treatment of the entire area bounded by the outer limits of the roadsides.

**841.02 Materials and Application Rates**

Provide the following listed materials:

**A. Fertilizer:** Fertilizer shall be a standard commercial grade and provide the minimum percentage of available nutrients designated.

**% Nitrogen                      % Phosphorus                      % Potassium                      % Sulfur**

**Refer to Contract Provision K-G.6.0#**

Furnish fertilizer in sealed containers with the composition, weight, and guaranteed analysis of contents clearly marked. Apply at the rate of 300 pounds per acre.

**B. Seed:**

1. This work consists of furnishing and placing required seed mix on all areas disturbed under this contract and on any other areas specified.

2. Apply the seed in the following amounts and mixtures:

<u>Species</u>	<u>Application Rate</u>
<b>Refer to Contract Provision K-G.6.0#</b>	<b>Refer to Contract Provision K-G.6.0#</b>

3. Use hand-operated seeding devices, or other devices approved by the Contracting Officer, to apply seed.

4. Furnish weed-free seed, with additional requirement that no seed containing any prohibited noxious weed seed, or any restricted noxious weed seed in excess of current state standards, for those weeds as defined in the current publication commonly referred to as the "All States Noxious Weed List" while the standards for prohibited and restricted noxious weeds are to be found in the appropriate state law or regulations.

Furnish seed separately or in mixture in standard containers with (1) seed name; (2) lot number; (3) net weight; (4) percentages of purity and of germination (in case of legumes, percentage of germination to include hard seed), and (5) percentage of maximum weed seed content clearly marked for each kind of seed; (6) certification that the seed lot meets applicable State and Federal laws with regard to prohibited and restricted noxious weeds clearly marked for each kind of seed. Furnish the Contracting Officer duplicate signed copies of a certificate signed by a Registered Seed Technologist or Seed Analyst (certified through either the Association of Official Seed Analysts or the Society of Commercial Seed Technologists) certifying that each lot of seed has been tested in accordance with the Association of Official Seed Analysts standards within 12 months prior to the date of application. This certification shall include (1) name and address of laboratory, (2) date of test, (3) lot number for each kind of seed, (4) name of seed, (5) percentage of germination, (6) percentage of purity, (7) percentage of weed content, (8) certification that the seed lot meets applicable State and Federal laws with regard to prohibited and restricted noxious weeds, and (9) in the case of a mixture, the proportions of each kind of seed. Legume seed shall be inoculated with approved cultures in accordance with the instructions of the manufacturer. No seed may be applied without prior written approval from the Contracting Officer.

C. **Mulch:** Apply mulch materials as follows:

<u>Mulch Type</u>	<u>Application Rate</u>
Refer to Contract Provision K-G.6.0#	Refer to Contract Provision K-G.6.0#

D. **Plant Stock:** Furnish the following listed plant materials:

<u>Stock</u>	<u>Size</u>	<u>Bare Root</u>	<u>Containerized</u>
N/A			

**841.03 Schedules and Applications**

**A. Schedule**

1. Seeding may not be done until all other ground-disturbing work on the road has been completed and accepted. Complete seeding as soon as other ground-disturbing work is accepted, unless a specific seeding season is listed below.  
Seeding season: April 15 to September 15.
2. Do not apply the treatment when the ground is frozen or excessively wet. Terminate application during periods when there is too much wind to allow consistent treatment rates and control of the treatment area to the designated limits.

**B. Roadside and Slope Treatment**

1. Roadsides will not require advance preparation unless required in the SUPPLEMENTAL SPECIFICATIONS or as SHOWN ON THE DRAWINGS.
2. Apply the designated treatment by hand operated machine. When both roadbed (under 841.03C) and slopes are shown in the SUPPLEMENTAL SPECIFICATIONS for treatment, application may be done at the same time.
3. The Contractor will not be required to operate self-propelled equipment beyond the defined roadbed. Do not apply treatment materials to the foreslope of ditches unless roadbed treatment (841.03C) is also required.

**C. Roadbed Treatment**

1. Scarify portions of the roadbed not previously disturbed and left loose under Section T-835 to a minimum depth of 4 inches unless bedrock is encountered at a lesser depth. The maximum distance between furrows formed by scarification is 12 inches.
2. Treat barrier mounds placed under Section T-835 while in a roughened condition.

**D. Planting**

1. Plant designated woody plant materials at the staked locations or designated spacings.
2. Place containerized plant stock in an appropriately sized hole formed by a dibble or other device to place the roots at the proper depth.
3. Place bare root plant stock in a slotted cut formed by a mattocks, pulaski, or other edged tool. Place the crown at ground level. Do not bend or break the roots.
4. Compress the area adjacent to the hole by foot or special tool to form a depression up and down slope from the stem and force the soil against the container or roots with no air voids.
5. Hold the plantings firmly in place by the soil. When checked by pulling upward on the top 1/2 inch of the plant stem, the planting shall either break at the hold point or the area compressed against the roots show evidence of movement. Remove and replace with fresh stock plantings that are not held firmly by the soil.

**841.04 Government Provided Materials**

Contract Name: Voodoo Stewardship

The Government will provide the following listed materials. At least ten (10) calendar days notice must be given to the Contracting Officer prior to actual date material will be picked up.

Materials will be provided at: **Refer to Contract Provision K-G.6.0#**

**T-842 CUTTING ROADWAY VEGETATION (10/07)****842.01 Description**

This work consists of cutting all vegetative growth, including trees and other vegetation less than 4 inches in diameter measured 6 inches above the ground, on roadway surfaces and roadsides.

**842.02 Maintenance Requirements****A. General**

1. Cut brush, trees, and other vegetation within each area treated to a maximum height of 6 inches above the ground surface or obstruction such as rocks or existing stumps. When work is performed under this Section, remove all limbs which extend into the treated area, or over the roadbed, to a height of 14 feet above the traveled way surface elevation.
2. Items to remain will be DESIGNATED ON THE GROUND.
3. Work may be performed either by hand or mechanically unless specifically shown in the Road Listing. Self-propelled equipment is not allowed on cut and fill slopes or in ditches.
4. Correct damage to trunks of standing trees caused by Contractor's operation either by treatment with a commercial nursery sealer or by removing the tree as directed by the Contracting Officer.
5. Limb trees within the cutting limits which are over 4 inches -measured at 6 inches above the ground in lieu of cutting.
6. When trees are limbed, cut limbs within 4 inches of the trunk.

**B. Cutting Side Vegetation**

1. Show the width of vegetation to be removed in the Road Listing.
2. Unless otherwise included in the SUPPLEMENTAL SPECIFICATIONS or DESIGNATED ON THE GROUND:
  - a. Commence work at the edge of the traveled way and proceed away from the road centerline.
  - b. Roads without a defined traveled way: The starting point for cutting will be marked on the ground or defined in the SUPPLEMENTAL SPECIFICATIONS.
3. The points for establishing cutting limits are as follows:
  - a. Fill and daylighted (wide roadbed) section cutting commences at the edge of the traveled way and proceeds away from the road center line.
  - b. Drainage ditched section cutting commences at the bottom of the existing ditch and proceeds away from the road center line. Cutting on ditch foreslopes is not required.
  - c. Unditched cut section cutting commences at the intersection of the cutbank and the roadbed and proceeds away from center line.
4. Provide transitions between differing increments of cutting width. Accomplish transitions in a taper length of not less than 50 feet nor more than 70 feet.

**C. Debris**

1. Materials resulting from the cutting operation in excess of 12 inches in length or 3 inches in diameter is not allowed to remain on roadway slopes within the treated area, in ditches, or within water courses.
2. Remove limbs and chunks in excess of 3 inches in any dimension from the traveled way and shoulders.
3. Materials may be scattered down slope from the roadbed, outside of the work area and drainages unless otherwise listed in D. Invasive Species of Concern.

**D. Invasive Species of Concern**

Where DESIGNATED ON THE GROUND, included in the ROAD LISTING, SHOWN ON THE DRAWINGS or as ordered by the Contracting Officer invasive species of concern prevention practices shall be followed as listed below.

<b>Invasive Species of Concern Prevention Practices</b>
<b>Refer to Contract Provision B.6.3.5</b>

**T-851 LOGGING OUT (5/07)****851.01 Description**

This work consists of removal of fallen trees and snags which encroach into the roadway or the 3 feet of roadside abutting the roadway on the cut side.

**851.02 Maintenance Requirements**

- A.** Limb and remove timber which meets Utilization Standards, or deck at locations designated by the Contracting Officer.
- B.** Limb other material cut into lengths for handling. Deck outside ditches and drainages, off the traveled way and turnouts or at staked locations. The clearing width is to the edge of the roadway for public use roads, except limited use roads. The clearing width for limited use roads is shown in the specifications.
- C.** Notwithstanding B 2.3, blowdown timber outside Contract Area required to be removed, which meets Utilization Standards in A 2, when designated by the Contracting Officer is Included Timber subject to requirements of B 2.2.
- D.** Do not leave woody debris and slash in excess of 12 inches in length or 3 inches in diameter, or concentrations which may plug ditches or culverts, in ditches, drainage channels, or on backslopes, traveled way, shoulders, or turnouts.

**T-854 - TREATMENT AND DISPOSAL OF DANGER TREES (5/07)****854.01 Description**

This work consists of felling and disposal of designated live or dead danger trees sufficiently tall to reach roads used by the Contractor. Any removal of logs is subject to prior agreement between the Contractor Officer and the Contractor.

**854.02 Requirements****A. Designation of danger trees.**

Danger trees to be felled will be designated in advance by the Contracting Officer. Trees to be removed will be Marked.

**B. Falling, bucking and treatment for disposal.**

Use controlled felling to ensure the direction of fall and prevent damage to property, structures, roadway, residual trees, and traffic. Stump heights, measured on the side adjacent to the highest ground, must not exceed 12 inches or 1/3 of the stump diameter, whichever is greater. Higher stump heights are permitted when necessary for safety.

Felled snags and trees, which are not Marked for removal, will be left in a stable condition such that they will not roll or slide. Position logs away from standing trees so they will not roll, are not on top of one another, and are located out of roadway and drainage structures.

Fell, limb and, remove trees, which are Marked for removal, that equal or exceed the utilization standards as listed in the Stewardship Contract contract or SUPPLEMENTAT SPECIFICATIONS. Dispose of merchantable timber designated for removal in accordance with B/BT2.32 Construction Clearing, of the Stewardship Contract Contract, or as described in SUPPLEMENTAL SPECIFICATIONS.

**C. Slash treatment.**

Within the roadway, remove limbs, chunks, and debris in excess of 12 inches in length and 3 inches in diameter, and concentrations that may plug ditches or culverts, and water courses.

Dispose of slash by scattering outside the roadway limits without damaging trees, or improvements.

Large accumulations of slash may be ordered hauled under T-832.

Contract Name: Voodoo Stewardship

**T-891 WATER SUPPLY AND WATERING (5/07)**

**891.01 Description**

This work consists of providing facilities to furnish an adequate water supply, hauling and applying water.

**891.02 Materials**

If the Contractor elects to provide water from other than designated sources, the Contractor is responsible to obtain the right to use the water, including any cost for royalties involved. Suitable and adequate water sources available for Contractor's use under this contract are designated as follows:

<u>Map</u> <u>Key No.</u>	<u>Location</u> <u>Road</u>	<u>Location</u> <u>Milepost</u>	<u>Use</u> <u>Restrictions</u>
------------------------------	--------------------------------	------------------------------------	-----------------------------------

N/A

**891.03 Equipment**

**A.** Positive control of water application is required. Equipment shall provide uniform application of water without ponding or washing.

**B.** An air gap or positive anti-siphon device shall be provided between the water source and the vehicle being loaded if the vehicle has been used for other than water haul, if the source is a domestic potable water supply, or the water is used for tank mixing with any other materials.

**C.** The designated water sources may require some work prior to their use. Such work may include cleaning ponded areas, installing temporary weirs or sandbags, pipe repair, pump installation, or other items appropriate to the Contractor's operations. Flowing streams may be temporarily sandbagged or a weir placed to pond water, provided a minimum flow of \_\_\_\_\_ cu. ft/sec is maintained. Obtain approval from the Contracting Officer on improvements for sandbags or weirs prior to placement.

Contract Name: Voodoo Stewardship

**T-892 BITUMINOUS PRODUCTS (5/07)**

**892.01 Cutback Asphalt's and Emulsified Asphalt's**

Meet the requirements and application temperatures of Section 702 of the "Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects (FP-03)".

**892.02 Bituminous Dust Palliatives**

Meet the bituminous dust palliatives requirements listed in Table T-892-1 or listed in the SUPPLEMENTAL SPECIFICATIONS.

**892.03 Certificate of Compliance**

Provide a Certificate of Compliance in the following format;

Consignee	<u>                    N/A                    </u>	Designation	_____
Contract Number	_____	Date	_____
Identification (Truck No. Car No., Etc.)	_____		
Type and Grade	_____	With Additive (% , Brand)	_____
Loading Temperature	_____	Net Weight	_____
Net Liters	_____		

The shipment of bituminous material identified above and covered by the bill of lading complies with Government Standard Specification as modified by SUPPLEMENTAL SPECIFICATIONS applicable to this project.

Producer \_\_\_\_\_  
 Signed \_\_\_\_\_  
 (Producer's Representative)

**892.04 Application Temperatures**

Apply bituminous materials within the temperature ranges indicated in Table T-892-2.

TABLE T-892-2 - Application Temperatures

Application Temperature Range (Degrees C)

<u>Type &amp; Grade of Material</u>	<u>Min./Max.</u>	<u>Spray</u> <u>Min./Max.</u>	<u>Mix</u>
MC 30		21-63	16-40
MC 70		40-85	32-68
DO-1-2-3		27-52	
DO-4		27-80	
DO-6-7-8		10-60	

Contract Name: Voodoo Stewardship

TABLE 892-1.- Bituminous dust palliatives.

General Requirements	ASTM Method	DO-1	DO-2	DO-3	DO-4	DO-6	DO-6P	DO-8
Flash Point								
Tag Open-Cup, °C, Min	D 1310	52	52	52	93	66	66	
Cleveland Open-Cup, °C, Min	D 92	-	-	-	-	-	-	100
	-	-	-	-	-	-	-	-
Viscosity:	-	-	-	-	-	-	-	-
Kinematic, @ 38 °C, cSt	D 2170	40-70	90-125	135-200	20-100	-	-	-
Saybolt Furol, @ 25 °C SFS Max.	D 88	-	-	-	-	75-150	25-50	50
Water, % Max.	D 95	0.	0.5	0.5	0.	-	-	-
Asphaltnes, %s	D 2006-70	3-6	4-8	5-10	0-5	5-15	5-15	5-10
Saturates. % Min.	D 2006-70	25	25	25	10	25	25	8
24-Hour Settlement, %	D 244	-	-	-	-	2.0	2.0	2.0
Sieve Test, % Max.	D 244	-	-	-	-	-	-	0.1
Distillation Tests								
Total Distillate to 288 °C, Max. % by Volume	D 244	35	30	30	5	-	-	50
Total Distillate to 360 °C, Max. % by Volume	D 402	-	-	-	-	-	-	-
Oil Distillate, % by Volume	D 244	-	-	-	-	-	10-20	5
Total Residue, % by Weight	D 244	-	-	-	-	60	55	45
Test on Residue from Distillate								
Viscosity, Kenmatic, @ 38 °C ,cST	D 2170	75-250	200-600	500-1500	20-150	-	-	-
Viscosity, Kenmatic, @ 50 °C, cST	D 2170	-	-	-	-	200-600	150-450	250-1200
Solubility in Trichloroethylene, % Min.	D 2042	98	98	98	98	96	96	98
Ductility, CM Min.	D 113	-	-	-	-	-	-	-

# **Attachment**

**D**

Contract Name: Voodoo Stewardship

PROJECT NUMBER 001 - Pre-commercial Thin and Reduce Fuels to an End Result of 8 to 10 Tons Per Acre.

Project Location

This project work will be done within the boundaries of subdivisions shown in the table below for the Voodoo Stewardship Contract.

Subdivision	Acres
33	28
45	10
46	33
50	17
51	24
361	71

Technical Specifications

In identified cutting units, cut and dispose of trees over 12.0 inches in height, and less than 5.0 inches DBH to an a spacing of 24 feet + or - 10 feet leaving the most vigorous, undamaged and healthy trees. Use the following priority when selecting leave trees:

- (1) Western Larch
- (2) Ponderosa Pine
- (3) Western White Pine
- (4) Western Red Cedar
- (5) Western Hemlock
- (6) Douglas-fir
- (7) Grand Fir

All cut trees shall be cut below the lowest live limb, except when prevented by natural obstacles; in which case any live limbs below the cutting point shall be removed. Trees shall be completely severed from the stump. Stump height shall not exceed 6 inches above ground level or 4 inches above natural obstacles.

Cut all brush over 12.0 inches in height to a height not to exceed 8 inches. Herbaceous plants may be ignored.

Treat slash to a fuel loading of 8 to 10 tons per acre. For the purposes of this project slash is defined as vegetative debris including, but not limited to, cull logs, blasted or pushed-out stumps, chunks, broken tops, limbs, branches, rotten wood, damaged or cut brush, damaged, cut or destroyed reproduction, saplings and poles, pre-existing or created by the activity. The process used shall in no way damage or kill existing leave trees. Burning by Contractor will not be approved.

Impact to soils from Contractor's Operations shall be less than 10 percent of the stewardship/cutting unit area. Impact is defined as soils being exposed by the removal of the duff layer or displaced from one place to another as the result of Contractor's Operations.

Not more than 5 percent of the residual stand may be damaged by Contractor's Operations. Scarring of boles that exceed 16 square inches of cambium exposure will be considered damage. Any tree "root sprung" or with a broken top will also be considered damage.

Contractor's Obligations

The Contractor shall furnish materials, labor, supervision, transportation, and all supplies for this project.

Acceptable Quality Level

The Forest Service will visually compare the slash remaining on site with the slash loading photo series on file at the Barlow Ranger Station. The reference photo is on page 42 of USDA GTR PNW 52 (1976). If the fuel loading appears to be within specification the work will be accepted on a completed subdivision.

If the Forest Service and the Contractor do not agree on a visual inspection result, a fixed plot inventory of the down woody material will be completed by the Forest Service using the

PLANAR INTERCEPT FUEL INVENTORY GUIDE (on file at the Barlow Ranger District). Data collected will be entered into the computer model DDWoodyPC to calculate the average tons per acre of down woody material remaining on site. When calculated fuel loadings exceed the high end of

Contract Name: Voodoo Stewardship

the loading objectives, Contractor shall rework to meet specification standards. Contractor's work shall also not go below the low end of the objective range. If this occurs, Contractor may be required redistribute slash to meet the standards.

For pre-commercial thinning, the tree spacing should average a 24 foot spacing. Individual spacing between trees should be no less than or greater than 50 percent the identified spacing where stocking allows. Initial inspection will consist of a review of the trees cut and left to determine if the technical specifications have been met. When work appears satisfactory it will be accepted. When work is unsatisfactory the Contractor will cut additional trees to meet the above technical specifications.

If the Contractor disagrees with the results of the random walk thru by the Forest Service, the Contractor may request a formal systematic sample across the unit. Plots (1/50th acre) will be distributed throughout the area to generate a one percent sample. Each plot examined will record the following findings.

1. Number of leave trees that should have been left.
2. Number of trees that were left.
3. Number of satisfactory leave trees
4. Number of deficient trees
5. Number of excess trees.

Plot centers will be designated on the ground and each plot will be documented if it is satisfactory or unsatisfactory and the reason why. Number of trees deficient + Number of excess trees / trees to be left = x%. 100% - x% = quality. A 90 percent quality rating is acceptable.

If work quality is more than 90 percent, work items will be accepted. Where quality is 90 percent or below, contractor will pay for the costs of the Forest Service formal sampling, and rework the area to meet the required technical specifications.

For ground disturbance, a visual inspection will be made and if there is a concern that disturbance exceeds 10 percent, a soil survey will be conducted by the Forest Service. If found not in compliance with the 10 percent standard, Contractor will pay for the cost of the Forest Service survey and the Contractor will be required to mitigate the damages with methods approved by the Forest Service.

#### Measurement and Stewardship Credit

##### A. Measurement

All acreages are based on the horizontal plane within the established boundaries.

##### B. Re-measurement

1. The Contractor may at any time after award request remeasurement of any treatment type or area. This request must be made in writing to the Forest Service.
2. If remeasurement indicates a variance of 5 percent or less, the Contractor shall pay for the actual cost of remeasurement and no adjustment will be made in the Quantity stated in A.4.3.
3. If remeasurement indicates a variance greater than 5 percent, the Quantity stated in A.4.3 will be modified based on the remeasured amount and the Forest Service will pay for the remeasurement.

##### C. Determining Stewardship Credits

1. Calculation of Stewardship Credits for Accepted Work - Plot Inspection
  - a. After inspection of completed acreage, the Forest Service will calculate the Stewardship Credits.

# Attachment

**E**

Contract Name: Voodoo Stewardship

PROJECT NUMBER 002 - Leave Tree Marking

Project Location

This project work will be done within the boundaries of all subdivision units shown in the table below for the Voodoo Stewardship Contract.

Subdivision	Acres
33	28
45	10
46	33
50	17
51	24
164	16
361	71

Technical Specifications

Leave trees shall be designated as specified in K-C.3.5.7# (Option 1).

Contractor's Obligations

The Contractor shall furnish materials, labor, supervision, transportation, and all supplies not provided by the Forest Service, which are required to complete the project.

Commencement, Prosecution, and Completion of Work

A. The Contractor shall be required to (a) commence work under this contract after a pre-work meeting agreed upon by the Contractor and Forest Service, and (b) prosecute the work diligently. The time stated for completion shall include final cleanup.