

TABLE PURSUANT TO CT6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

<u>YARDING/SKIDDING REQUIREMENTS</u>	<u>CUTTING UNITS</u>
Except during winching, the leading ends of logs must be suspended above the ground during skidding operations.	All
Whole tree skidding, defined as skidding trees with limbs and tops attached until such material reaches the landing, is required.	64,68,123,287,292 297,309,318,356
Over snow harvest for resource protection is required. A minimum of 12 inches of compacted snow and 2 inches of frozen soil in shaded and unshaded areas of the logging site are required. Landings will be designated and approved prior to snowfall.	64,292,490
Equipment shall be restricted to slopes of 35% or less.	All
Ground based skidding equipment is restricted to designated skid trails.	All
Existing skid trails should be used when possible. Skid trails shall not be located down draws, Streamcourses, or swales. Skid trails should be located approximately 120 feet apart.	All
If units are log length yarded, slash will be treated to a maximum of 7 tons per acre. Slash will be pulled back to the dripline of the crowns of the leave trees or 10 feet whichever is greater, pulled back at least 30 feet from private land boundries, and not exceed 18 inches in height. Fuel treatments that may be used include gapple piling, scattering, or other approved methods.	65,125,231,263,275, 278,299,310,328,347, 351,359,362,367,376 378,381,383,391,470, 480,490,494,496,540