

Date: \_\_\_\_\_ Time: \_\_\_\_\_ E # \_\_\_\_\_

Incident Name: \_\_\_\_\_ Incident # \_\_\_\_\_

Company /  
Contractor: \_\_\_\_\_ Equipment ID: \_\_\_\_\_

Agreement # \_\_\_\_\_ Equipment Make: \_\_\_\_\_

VIN/Serial # \_\_\_\_\_ Equipment Model: \_\_\_\_\_

**EQUIPMENT TYPE**
☐ Type 3      ☐ Type 4      ☐ Type 5      ☐ Type 6

MINIMUM STANDARDS FOR TYPES		WILDLAND ENGINES			
		3	4	5	6
<b>Pump Rating</b>	Minimum flow (GPM)	150	50	50	50
	@ Rated pressure (PSI)	250	100	100	100
<b>Tank Capacity (GAL)</b>	MIN	500	750	400	150
	MAX	1500	1500	749	399
<b>Hose (feet)</b>	1 ½"	1000	300	300	300
	1"	500	300	300	300
	¾" Garden Hose	300	300	300	300
	Live Hose Reel ¾" ID	100	100	100	100
<b>Pump and Roll</b>		Yes	Yes	Yes	Yes
<b>Foam Proportioner System</b>		Yes	Yes	Yes	Yes
<b>Maximum GVWR (lbs.)</b>		-	-	26,000	19,500
<b>Personnel Required</b>		3	3	3	3

**MINIMUM EQUIPMENT REQUIREMENTS**

	<i>Not all inclusive; for additional clarification refer to the agreement (SF-1449 section D).</i>		Yes	No
1	<b>Equipment VIN/serial # matches resource order</b> (Schedule of Items)	D.6.3.1		
3	<b>Check-in process completed</b>	D.6.5.3		
4	<b>OF-296 Vehicle/Heavy Equipment Pre-use Inspection Checklist completed</b>	D.17		
5	<b>Vehicle Identification:</b> All equipment shall have the company's name and unique identification number affixed on each side of the vehicle.	D.2.2.3		
6	<b>Agreement:</b> One complete copy	D.8		
7	<b>3 Person Crew:</b> All types must have 3 personnel.	D.2.1.1		
8	<b>Personnel:</b> Full Name & RT-130 Fire Line Refresher Completion Dates	D.3.1.1		
	ENGB: _____ Date: _____			
	FFT1 / FFT2: _____ Date: _____			

9	<b>Boots:</b> All leather, 8" high with lug type sole in good condition.	D.2.1.2		
10	<b>PPE:</b> <i>For ALL personnel</i> Hardhat, Gloves, Hearing Protection, Eye Protection, Headlamp w/batteries	D.2.1.2		
11	<b>Flame resistant clothing:</b> <i>Minimum 2 full sets</i> of flame-resistant shirts and pants certified to NFPA 1977 standard for ALL personnel.	D.2.1.2		
12	<b>Fire shelter:</b> New Generation, <i>for ALL personnel.</i>	D.2.1.2		
13	<b>Line Gear (Day Packs):</b> Minimum of 3 (one per person)	D.2.1.2		
14	<b>Programmable Radios:</b> Minimum of 2 (one must be a handheld), 2 fully charged battery packs per radio, and 1 programming/cloning cable.	D.2.3		
15	<b>Spare Tire:</b> Full size spare tire, securely mounted to vehicle with minimum 4/32 tread.	D.2.2.1.1		
16	<b>All-Wheel / 4-Wheel Drive:</b> Required on T6 (optional on T5, T4, T3)	D.2.1.2		
17	<b>Wheel Chocks:</b> Set of 2	Inventory List		
18	<b>First Aid Kit:</b> 5 person minimum	Inventory List		
19	<b>Fire extinguisher:</b> 2A 10BC, securely mounted to the vehicle, accessible to the operator and with current annual inspection tag.	D.2.1.2		
20	<b>Reflective Triangles:</b> Bi-directional, set of 3	Inventory List		
21	<b>Pump Type</b>	D.2.1.2	Auxiliary	PTO
22	<b>Pump Discharge Pressure Gauge</b>	D.2.1.2		
23	<b>Foam Proportioner System</b>	D.2.1.2	Manual	Auto
24	<b>Foam:</b> Minimum of 5 gallons	D.2.1.2		
25	<b>Compressed Air Foam System CAFS</b> <i>(optional attribute)</i>	D.2.1.2		
MINIMUM INVENTORY				
26	<b>2 – Nozzle, combo fog/straight stream, 1 ½" NH Female</b>	Inventory List		
27	<b>2 – Nozzle, combo fog/straight stream, 1" NPSH Female</b>			
28	<b>2 – Nozzle, Adjustable ¾" Garden Hose</b>			
29	<b>1 – Nozzle, Foam 1 ½" NH</b>			
30	<b>1 – Double Male, 1 ½" NH</b>			
31	<b>1 – Double Female, 1 ½" NH</b>			
32	<b>1 – Double Male, 1" NPSH</b>			
33	<b>1 – Double Female, 1" NPSH</b>			
34	<b>2 – Gated Wye, 1 ½" NH</b>			
35	<b>2 – Gated Wye, 1" NPSH</b>			
36	<b>1 – Gated Wye, ¾" Garden Hose</b>			

## VIPR Fire Equipment Incident Compliance Inspection Checklist

## ENGINE

37	<b>1 – Reducer, 2 ½” NH Female to 1 ½” NH Male</b>		
38	<b>4 – Reducer, 1 ½” NH Female to 1” NPSH Male</b>		
39	<b>1 – Reducer, 1” NPSH Female to ¾” Garden Hose Male</b>		
40	<b>1 – Adapter, 1 ½” NH Female to 1 ½” NPSH Male</b>		
41	<b>1 – Adapter, 1 ½” NPSH Female to 1 ½” NH Male</b>		
42	<b>1 – Mop-Up Wand, ¾” Receptor with ¾” Nozzle Tip</b>		
43	<b>5 – Inline Ball Valve, ¾” Garden Hose</b>		
44	<b>4 – Spanner Wrench, combination 1” &amp; 1 ½”</b>		
45	<b>1 – Fire Hose Clamp, Forestry</b>		
46	<b>1 ½” Hose (see table for min. quantity)</b>		
47	<b>1” Hose (see table for min. quantity)</b>		
48	<b>¾” Hose (see table for min. quantity)</b>		
49	<b>1 – 20’ Suction hose with strainer or screened foot valve</b>		
50	<b>Live Hose Reel – Operational with min. of 100’ of 1” hose (non-collapsible/hardline) with ¾” inside diameter</b>		
51	<b>1 ½” Discharge Valve, full flow with rapid shut off</b>		
52	<b>3 – Shovel, size “0”</b>		
53	<b>3 – Pulaski</b>		
54	<b>2 – Backpack Pump</b>		
55	<b>10 – Fusee (fire starter)</b>		
56	<b>3 – Mill Bastard File</b>		
57	<b>All inventory permanently etched or engraved with company information. <i>Painting or marking the equipment with permanent markers is not acceptable.</i></b>		
58	<b>Vendor maintains a complete inventory list, including any extra items they may be carrying.</b>		
<b>Pump Accessory Kit (if pump is auxiliary)</b>			
59	1 – Wrench, Adjustable 10”	Inventory List	
	1 – Wrench, Spark Plug (Unless adjustable wrench is suitable)		
	1 – Pliers (Slip Joint)		
	1 – Screwdriver (Standard Blade)		
	1 – Screwdriver (Phillips)		
	1 – Spare Starter Rope ( <i>If Required</i> )		
	2 – Quarts Crankcase Oil		
	1 – Grease Gun with Grease		
	Spark Plugs (Sufficient number to replace all plugs on auxiliary pump)		

## CHAINSAW AND CHAINSAW KIT INSPECTION CHECKLIST

<b>Manufacturer:</b>	
<b>Model Number:</b>	
<b>Serial Number:</b>	

<b>CHAINSAW:</b> <i>(Minimum Engine Power required is 3.0 cubic inch or 49cc)</i>	<b>YES</b>	<b>NO</b>
No visible parts broken		
All visible nuts and bolts tight		
Oil in chain oil reservoir		
Proper exhaust system and spark arrester		
Guide bar is a minimum of 18 inches and not bent or damaged		
Pull rope functions properly		
Started and checked that the engine idles evenly, runs smoothly, has satisfactory power, the on/off/kill switch works		
Chain brake works properly		
<b>CHAINSAW KIT:</b>		
1 Chainsaw Kit/Bag/Box to store Compliment		
1 Combination Bar/Spark Plug Wrench (Scrench)		
1 Spare Spark Plug to fit saw		
1 Pint of Spare Engine Oil (2-cycle oil)		
1 Pair of Chaps meeting USFS Specification 6170-4F or later, or certified to NFPA 1977		
1 Extra Chain to fit Saw-Bar Combo		
1 Chain File		
1 Felling Axe		
1 Felling Wedge		
1 OSHA or DOT Approved Fuel Container to hold Chainsaw Fuel and Bar Oil, properly secured on the vehicle		
2 Sets Ear Plugs		

☐ Equipment meets agreement specifications ☐ Equipment does not meet agreement specifications

Inspector: \_\_\_\_\_ Date: \_\_\_\_\_  
*Print Sign*

Operator: \_\_\_\_\_ Date: \_\_\_\_\_  
*Print Sign*

☐ Contractor given the opportunity to correct noted deficiencies (***See Remarks***) ☐ Contactor successfully corrected noted deficiencies

Inspector: \_\_\_\_\_ Date: \_\_\_\_\_  
*Print Sign*

<b>REMARKS:</b> <i>(Note in detail any deficiencies, pertinent information, comments, etc.)</i>