

Date: _____ Time: _____ E # _____

Incident Name: _____ Incident # _____

Company /

Contractor: _____ Equipment ID: _____

Agreement # _____ Equipment Make: _____

VIN/Serial # _____ Equipment Model: _____

License Plate # _____ License Plate State: _____

Operator's Full Name: _____

EQUIPMENT TYPE
☐ **Type 1** – 4,000+ gallons
 ☐ **Type 2** – 2,500 ⇒ 3,999 gallons
 ☐ **Type 3** – 1,000 ⇒ 2,499 gallons
MINIMUM EQUIPMENT REQUIREMENTS

	<i>Not all inclusive; for additional clarification refer to the agreement (SF-1449 section D).</i>		Yes	No
1	Equipment VIN/serial # matches resource order (Schedule of Items)	D.6.3.1		
3	Check-in process completed	D.6.5.3		
4	OF-296 Vehicle/Heavy Equipment Pre-use Inspection Checklist completed	D.17		
5	Agreement: One complete copy	D.8		
6	Vehicle Identification: All equipment shall have the company's name and unique identification number affixed on each side of the vehicle.	D.2.2.3		
7	RT-130 Fire Line Refresher Completion Date:	D.3.1.1		
8	Annual Certification Current: DOT #: _____ or CVSA Inspection: _____	D.2.2		
9	Boots: All leather, 8" high with lug type sole in good condition.	D.2.1.2		
10	PPE: For ALL personnel Hardhat, Gloves, Hearing Protection, Eye Protection, Headlamp w/batteries	D.2.1.2		
11	Flame resistant clothing: Minimum 2 full sets of flame-resistant shirts and pants certified to NFPA 1977 standard for ALL personnel.	D.2.1.2		
12	Fire shelter: New Generation, for ALL personnel.	D.2.1.2		
13	Programmable Radios: Minimum of 1 handheld and 2 fully charged battery packs.	D.2.3		
14	Tire Tread Depth: Minimum 2/32" for rear and 4/32" for steering axle tires.	D.2.2.1		
15	Wheel Chocks: Set of 2	Inventory List		
16	Back-Up Alarm	D.2.1.2		

17	Brakes on all axles.	D.2.1.2		
18	Auxiliary Brakes: All vehicles 36,000 GVWR+ shall be installed with an operator-controlled auxiliary braking system in addition to the service brakes (i.e., engine retarder, transmission retarder, driveline retarder, or exhaust retarder).	D.2.1.2		
19	First Aid Kit: 5 personnel minimum	Inventory List		
20	Fire extinguisher: 2A 10BC, securely mounted to the vehicle, accessible to the operator and with current annual inspection tag.	D.2.1.2		
21	Reflective Triangles: Bi-directional, set of 3	Inventory List		
22	Pump Type	D.2.1.2	Auxiliary	PTO
23	Fuel (if equipped with auxiliary pump): Enough to operate for 12 hours.	D.2.1.2		
24	Pump Discharge Pressure Gauge	D.2.1.2		
25	Tank: Securely attached to the chassis. <i>Fiberglass or plastic tanks must be surrounded by steel to prevent puncture damage.</i>	D.2.1.2		
26	Tank Baffling: <ul style="list-style-type: none"> <input type="checkbox"/> Longitudinal baffle regardless of width and one (1) transverse baffle. <i>The distance between vertical tank walls and baffles, or between parallel baffles, shall not exceed 52".</i> <input type="checkbox"/> Free Floating Baffle System (Baffle Balls) <i>Note: Vendor must have data sheets which validates that the baffling is sufficient to meet the manufacturers recommendation</i> 	D.2.1.2		
27	Spray Bar Head(s): Must be operational. <div style="display: flex; justify-content: space-around;"> Front Rear Both </div>	D.2.1.2 Exhibit J Exhibit M	Gravity	Pressure
MINIMUM INVENTORY				
28	1 – Nozzle, combo fog/straight stream, 1 ½” NH Female	Inventory List		
29	1 – Double Male, 1 ½” NH			
30	1 – Double Female, 1 ½” NH			
31	1 – Gated Wye, 1 ½” NH			
32	2 – Reducer, 2 ½” NH Female to 1 ½” NH Male			
33	1 – Reducer, 1 ½” NH Female to 1” NPSH Male			
34	1 – Adapter, 1 ½” NH Female to 1 ½” NPSH Male			
35	1 – Adapter, 1 ½” NPSH Female to 1 ½” NH Male			
36	1 – Spanner Wrench, combination 1 ½” to 2 ½”			
37	1 – Adjustable Hydrant Wrench			
38	1 – Fire Hose Clamp, 2 ½”			
39	100’ – 1 ½” Hose cotton/synthetic, NH thread			

VIPR Fire Equipment Incident Compliance Inspection Checklist

SUPPORT WATER TENDER

40	50' – 2 ½" Hose cotton/synthetic, NH thread		
41	20' Suction hose with strainer or screened foot valve		
42	1 – 2 ½" Discharge Outlet, NH thread		
43	2 – 1 ½" Discharge Outlet, NH thread		
44	1 – 4" Gravity Dump valve extending past the rear of tank		
45	1 – Shovel – Size 0 or 1		
46	1 – Pulaski		
47	All inventory permanently etched or engraved with company information, <i>painting or marking with permanent markers is not acceptable.</i>		
48	Vendor maintains a complete inventory list, including any extra items they may be carrying.		

☐ Equipment meets agreement specifications ☐ Equipment does not meet agreement specifications

Inspector: _____ Date: _____
Print *Sign*

Operator: _____ Date: _____
Print *Sign*

☐ Contractor given the opportunity to correct noted deficiencies (*See Remarks*) ☐ Contractor successfully corrected noted deficiencies

Inspector: _____ Date: _____
Print *Sign*

REMARKS: (<i>Note in detail any deficiencies, pertinent information, comments, etc.</i>)