

Date: _____ Time: _____ E # _____

Incident Name: _____ Incident # _____

Company /

Contractor: _____ Equipment ID: _____

Agreement # _____ Equipment Make: _____

VIN/Serial # _____ Equipment Model: _____

License Plate # _____ License Plate State: _____

Operator' Full Name: _____

EQUIPMENT TYPE☐**Type 1** – 2,000+ gallons☐**Type 2** – 1,000 ⇒ 1,999 gallons**MINIMUM EQUIPMENT REQUIREMENTS**

	<i>Not all inclusive; for additional clarification refer to the agreement (SF-1449 section D).</i>		Yes	No
1	Equipment VIN/serial # matches resource order (Schedule of Items)	D.6.3.1		
3	Check-in process completed	D.6.5.3		
4	OF-296 Vehicle/Heavy Equipment Pre-use Inspection Checklist completed	D.17		
5	Agreement: One complete copy	D.8		
6	Vehicle Identification: All equipment shall have the company's name and unique identification number affixed on each side of the vehicle.	D.2.2.3		
7	Annual Certification Current: DOT #: _____ or CVSA Inspection: _____	D.2.2		
8	Personnel: Full Name & RT-130 Fire Line Refresher Completion Dates FFT1: _____ Date: _____	D.3.1.1		
	FFT1 / FFT2: _____ Date: _____			
	<i>Additional personnel? If so, see remarks for details.</i>	D.3.1.2		
9	Boots: All leather, 8" high with lug type sole in good condition.	D.2.1.2		
10	PPE: For ALL personnel Hardhat, Gloves, Hearing Protection, Eye Protection, Headlamp w/batteries	D.2.1.2		
11	Flame resistant clothing: Minimum 2 full sets of flame-resistant shirts and pants certified to NFPA 1977 standard for ALL personnel.	D.2.1.2		
12	Fire shelter: New Generation, for ALL personnel.	D.2.1.2		
13	Line Gear (Day Packs): Minimum of 3 (one per person)	D.2.1.2		

14	Programmable Radios: Minimum of 1 handheld and 2 fully charged battery packs.	D.2.3		
15	Spare Tire: Full size spare tire, securely mounted to vehicle with minimum 4/32 tread. Shall be easily accessible.	D.2.2.1.1		
16	Tire Tread Depth: Minimum 2/32" for rear and 4/32" for steering axle tires.	D.2.2.1		
17	Wheel Chocks: Set of 2	Inventory List		
18	Back-Up Alarm	D.2.1.2		
19	Brakes on all axles.	D.2.1.2		
20	Auxiliary Brakes: All vehicles 36,000 GVWR+ shall be installed with an operator-controlled auxiliary braking system in addition to the service brakes (i.e., engine retarder, transmission retarder, driveline retarder, or exhaust retarder).	D.2.1.2		
21	First Aid Kit: 5 personnel minimum	Inventory List		
22	Fire extinguisher: 2A 10BC, securely mounted to the vehicle, accessible to the operator and with current annual inspection tag.	D.2.1.2		
23	Reflective Triangles: Bi-directional, set of 3	Inventory List		
24	Pump Type	D.2.1.2	Auxiliary	PTO
25	Fuel (if equipped with auxiliary pump): Enough to operate for 12 hours.	D.2.1.2		
26	Pump Discharge Pressure Gauge	D.2.1.2		
27	Foam Proportioner System	D.2.1.2	Manual	Auto
28	Foam: Minimum of 5 gallons	D.2.1.2		
29	Monitor None	D.2.1.2	Manual	Remote
30	Tank: Securely attached to the chassis. <i>Fiberglass or plastic tanks must be surrounded by steel to prevent puncture damage.</i>	D.2.1.2		
31	Tank Baffling: <input type="checkbox"/> Longitudinal baffle regardless of width and one (1) transverse baffle. <i>The distance between vertical tank walls and baffles, or between parallel baffles, shall not exceed 52".</i> <input type="checkbox"/> Free Floating Baffle System (Baffle Balls) <i>Note: Vendor must have data sheets which validates that the baffling is sufficient to meet the manufacturers recommendation.</i>	D.2.1.2		
32	Spray Bar Head(s): Must be operational. Front Rear Both	D.2.1.2 Exhibit J Exhibit M	Gravity	Pressure
MINIMUM INVENTORY				
33	1 – Nozzle, combo fog/straight stream, 1 ½" NH Female	Inventory List		
34	1 – Nozzle, 1½-inch NH Female Class A Foam min. 20 GPM at 100 PSI			
35	1 – Double Male, 1 ½" NH			

36	1 – Double Female, 1 ½” NH		
37	1 – Gated Wye, 1 ½” NH		
38	2 – Reducer, 2 ½” NH Female to 1 ½” NH Male		
39	1 – Reducer, 1 ½” NH Female to 1” NPSH Male		
40	2 – Adapter, 1 ½” NH Female to 1 ½” NPSH Male		
41	2 – Adapter, 1 ½” NPSH Female to 1 ½” NH Male		
42	1 – Spanner Wrench, combination 1 ½” to 2 ½”		
43	1 – Adjustable Hydrant Wrench		
44	1 – Fire Hose Clamp, 2 ½”		
45	200’ – 1 ½” Hose cotton/synthetic, NH thread		
46	50’ – 2 ½” Hose cotton/synthetic, NH thread		
47	20’ Suction hose with strainer or screened foot valve		
48	Live Hose Reel, min. of 100’ of 1” hose non-collapsible with 3/4” inside diameter		
49	1 – 2 ½” Discharge Outlet, NH thread		
50	2 – 1 ½” Discharge Outlet, NH thread		
51	1 – 4” Gravity Dump valve on rear of tank		
52	1 – 2½” Valve at bottom of tank with NH threads		
53	10 – Fusee (fire starter)		
54	2 – Shovel – Size 0 or 1		
55	2 - Pulaski		
56	All inventory permanently etched or engraved with company information, <i>painting or marking with permanent markers is not acceptable.</i>		
57	Vendor maintains a complete inventory list, including any extra items they may be carrying.		
OPTIONAL ATTRIBUTES			
58	All-Wheel Drive	D.6.2 Exhibit M	

☐ Equipment meets agreement specifications

☐ Equipment does not meet agreement specifications

Inspector: _____ Date: _____
Print Sign

Operator: _____ Date: _____
Print Sign

☐ Contractor given the opportunity to correct
noted deficiencies (*See Remarks*)

☐ Contactor successfully corrected
noted deficiencies

Inspector: _____ Date: _____
Print Sign

REMARKS: (<i>Note in detail any deficiencies, pertinent information, comments, etc.</i>)