

Reforestation and Nurseries Tech Tips

USDA United States Department of Agriculture
Forest Service



Technology & Development
Program

May 2010

2400

1024-2303P-MTDC

Watering From the Bottom Up: Automating a Subirrigation System for Container Plants

Mary Ann Davies and Ted Etter, Project Leaders



Figure 1—Overhead irrigation is often used to water plants in nurseries.

Highlights...

- When native plants are grown in containers, overhead irrigation may not be effective because the plants' large canopies may intercept much of the water.
- Subirrigation (watering container plants from the bottom up) would be an attractive alternative if watering could be automated, as it is for overhead irrigation systems.
- The Missoula Technology and Development Center developed an automated system that waters container plants from the bottom up when the potting soil dries out.
- This tech tip includes information on assembling and operating an automated system for subirrigating container plants in a nursery.

Native plants grown for restoration projects on national forests are usually started in containers. Forest Service nurseries use overhead irrigation for the container plants because it's inexpensive and relatively simple (figure 1). Overhead irrigation becomes less effective when plants have large canopies that may intercept the water. This is often the case with native plants. To compensate, more overhead irrigation must be applied, which wastes water and has the potential to carry fertilizer (especially nitrates and phosphates) into surface water and groundwater.

Subirrigation is a different approach that waters from the bottom up. This technique relies on the capillary action of potting soil to draw water from a reservoir tray into the containers. Subirrigation can use water more efficiently, reducing fertilizer runoff and watering plants more evenly and accurately. One problem with subirrigation is that employees have to turn the water on and off for each watering. Because employees aren't always available, the plants may dry out and die.



The Forest Service nursery in Moscow, ID, is testing subirrigation for native plants. Researchers proposed that the Missoula Technology and Development Center (MTDC) develop a system to automatically regulate watering intervals based on the moisture content in the potting soil.

The nursery has a 75-gallon water tank beneath the growing bench (figure 2). A submersible pump, wired to a programmable, electronic timer, sits in the water tank. Based on estimates of when the plants might need irrigation, the timer turns the pump on just long enough to fully flood the tray. The tray takes about 20 minutes to drain. The cycle may have to be repeated until the soil reaches the appropriate moisture content.

MTDC designed an automated subirrigation system that includes a soil moisture sensor, a drain assembly, and a controller (figure 3). The controller is set for specific voltages, representing dry and wet soil moisture levels based on the plant's needs. The soil moisture sensor monitors the

water content in the soil. If the soil is too dry, the controller activates the pump. The controller activates the solenoid drain valve before the soil becomes too moist.



Figure 2—The nursery in Moscow, ID, uses a 75-gallon water tank, submersible pump, and programmable timer for subirrigation.




Figure 3—MTDC designed an automated subirrigation system that includes a soil moisture sensor, a drain assembly, and a controller.

Soil Moisture Sensor

The soil moisture sensor, an ECH2O EC-5 manufactured by Decagon Devices, Inc., is inserted into the soil in one of the container plants (figure 4), ideally one of the last to receive water when the tray is filling. The container with the sensor can be up to 15 feet from the controller.



Figure 4—An ECH2O EC-5 soil moisture sensor, manufactured by Decagon Devices, Inc. (inset), is inserted into the potting soil in one of the container plants.

Drain Assembly

The drain assembly includes a solenoid valve, a backflow valve, a water feed nozzle, and additional pipe fittings that connect the water pump hose and drain outlet to the water tank (figure 5). The water feed nozzle attaches the drain assembly to the irrigation tray. The water pump hose connects to the backflow valve side of the assembly. The backflow valve lets water flow into the irrigation tray when the pump is activated, but will not let water flow back into the pump when the pump is turned off. The solenoid valve opens when it is activated by the controller, allowing water in the irrigation tray to drain back into the water tank.




Figure 5—The drain assembly includes a solenoid valve, a backflow valve, a water feed nozzle, and additional nylon pipe fittings.

Because the irrigation trays typically are made from lightweight plastic and the backflow valve and solenoid are both heavy brass fittings, nylon pipe fittings were used to reduce the weight hanging from the irrigation tray. A thin stainless steel plate in the tray helps distribute the weight (figure 6). To prevent leaks, Teflon tape was used on all connections and a butyl rubber gasket was used under the water feed nozzle where it attaches to the irrigation tray.



Figure 6—A thin stainless steel plate under the water feed nozzle helps distribute the weight of the heavy brass fittings.

Controller

The 120-volt controller (figure 7) lets the user set the dry and wet soil moisture voltages. The dry soil moisture voltage activates the water pump and the wet soil moisture voltage activates the solenoid drain valve. The controller also lets the user determine how long to run the water pump and how long to keep the drain valve open.



Figure 7—The automated subirrigation controller.

Controller Settings

Before setting the wet and dry soil voltages, the user should use a voltmeter to measure the voltage coming from the soil moisture sensor for potting soil that ranges from very dry to very wet (saturated). Start with very dry soil (figures 8 and 9) and add a little water, then record the voltage. Repeat until the soil is very wet. Add 25 millivolts to the measured voltage of very dry soil and subtract 25 millivolts from the measured voltage of very wet soil to account for electrical noise.




Figure 8—The user sets the dry soil moisture voltage so the controller will activate the water pump (probe connections shown) and sets the wet soil moisture voltage so the controller will activate the drain valve before the soil becomes too moist.




Figure 9—This example shows that the voltage indicated by a soil moisture sensor in soil increases as potting soil becomes moister. Dry soil may have a voltage of 900 millivolts (activation voltage would be set to 925 millivolts in this example to account for electrical noise). When the potting soil is completely saturated, the voltage will be 2,200 millivolts (the drain activation voltage would be set to 2,175 millivolts to account for electrical noise).

Controller Operation

The water pump's operating time can be programmed in 18-second intervals up to a maximum of 30 minutes. The pump should run long enough to fill the irrigation tray with enough water for all the containers. The drain valve can be programmed to open for 9 or 18 minutes. Every 38 minutes, the drain valve opens for 20 seconds to drain off any water that might have seeped out of the containers.

Materials

Part	Supplier	Part No.	Cost (dollars)
1-inch NPT zero pressure solenoid valve	McMaster-Carr	4711K953	160.14
¾-inch NPT brass threaded tee	McMaster-Carr	4429K254	8.18
1-inch NPT female Buna-S brass piston check valve	McMaster-Carr	7746K83	37.99
¾-inch brass hollow hex head plug	McMaster-Carr	59785K521	8.27
⅛- by ½- by ½-inch Buna-N rubber sheet	McMaster-Carr	8635K564	5.95
¾-inch nylon 90-degree elbow	Dultmeier	TW SE34	2.59
1- by ¾-inch nylon bushing	Dultmeier	TW RB10-34	1.62
¾-inch MPT by ¾-inch barb pipe-to-hose nylon fitting	Dultmeier	TW A3434	0.52
¾-inch nylon hex nipple	Dultmeier	TW M3400	0.50

Suppliers

Dultmeier Sales

P.O. Box 45565
Omaha, NE 69145–0565
Phone: 888–677–5054
<http://www.dultmeier.com>

McMaster-Carr

P.O. Box 54960
Los Angeles, CA 90054–0960
Phone: 562–463–4277
<http://www.mcmaster.com>

Conclusions

Anyone interested in building a subirrigation controller can call Ted Etter (406–329–3980) at MTDC to request electronic drawings. In the future, Decagon Devices, Inc., may start building controllers for their soil moisture sensors if customers express enough interest.



Acknowledgments

MTDC would like to thank Kas Dumroese, Anthony Davis, Jeremy Pinto, and the nursery technicians at the Moscow nursery for testing the controller and helping us refine it until it met their needs.

About the Authors

Mary Ann Davies received a bachelor's degree in mechanical engineering with a minor in industrial and management engineering from Montana State University. She worked in the Pacific Northwest Region as a facility engineer and as a tramway engineer. Davies has worked in fire management as a crewmember and as a crewboss. She worked for 5 years with the Rocky Mountain Research Station in the fire chemistry and fire behavior groups before coming to MTDC in 1999.

Ted Etter joined MTDC in 2002 as an electronics engineer and project leader. He has 20 years of experience designing test equipment, display devices, and medical instrumentation for private industry. For 6 years before joining MTDC, Etter taught courses in electronics at the University of Montana College of Technology, Missoula. His work at MTDC includes projects in wireless communications, alternative energy sources, instrumentation, and process control. Etter received a bachelor's degree in mathematics from the University of Oregon and a master's degree in teacher education from Eastern Oregon State University.

Library Card

Davies, Mary Ann; Etter, Ted. 2010. Watering from the bottom up: automating a subirrigation system for container plants. Tech Tip 1024–2303P–MTDC. Missoula, MT: U.S. Department of Agriculture, Forest Service, Missoula Technology and Development Center. 6 p.

When native plants are grown in containers, overhead irrigation may not be effective because the plants' large canopies may intercept much of the water. Subirrigation (watering containers from the bottom up) would be an attractive alternative if watering could be automated, as it is for overhead irrigation systems. The Missoula Technology and Development Center developed an automated system that waters containers from the bottom up when the potting soil dries out and allows water to drain from the containers before the soil becomes too moist. This tech tip includes information on assembling and operating an automated system for subirrigating container plants in a nursery.

Keywords: automation, controllers, electronics, equipment development, irrigation, nurseries, restoration, soil moisture sensors



For additional information about subirrigation controllers, contact MTDC:

USDA Forest Service
Missoula Technology and Development Center
5785 Hwy. 10 West
Missoula, MT 59808-9361
Phone: 406–329–3900
Fax: 406–329–3719

Forest Service and Bureau of Land Management employees can search a more complete collection of MTDC's documents, CDs, DVDs, and videos on their internal computer networks at:

<http://fsweb.mtdc.wo.fs.fed.us/search/>

Electronic copies of MTDC's documents are available on the Internet at:

<http://www.fs.fed.us/eng/pubs>



The Forest Service, United States Department of Agriculture (USDA), has developed this information for the guidance of its employees, its contractors, and its cooperating Federal and State agencies and is not responsible for the interpretation or use of this information by anyone except its own employees. The use of trade, firm, or corporation names in this document is for the information and convenience of the reader and does not constitute an endorsement by the Department of any product or service to the exclusion of others that may be suitable.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410, or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.