









Harry's Ridge Tunnel Alternatives			
 <p>Alternative 2 Full Repair of Existing Tunnel</p> <p>P R</p>	 <p>Alternative 3 Minor Repair of Existing Tunnel</p> <p>P R</p>	 <p>Alternative 4 Convert Existing Tunnel to Pressure System</p> <p>P</p>	 <p>Alternative 5 New Pressurized Tunnel</p> <p>P</p>
Pumice Plain Outlet Alternatives			Lake Storage Alternative
 <p>Alternative 6 Mechanically Excavated Open Channel</p> <p>P</p>	 <p>Alternative 7 Facilitate Natural Channel Formation</p> <p>P R</p>	 <p>Alternative 8 Buried Conduit within the Debris Blockage</p> <p>R</p>	 <p>Alternative 9 Lake Storage</p> <p>R</p>

P = Primary Outflow Measure **R** = Redundant Outflow Measure

Icons for Spirit Lake Alternatives: A table that shows the icons for each of the Action Alternatives for managing Spirit Lake water levels for the Spirit Lake Outflow Safety Improvement Project. Icons are a cartoon picture meant to capture the unique aspects of each alternative. The name of each alternative is provided beneath the icon. Whether the alternative can serve as a primary outflow measure, a redundant outflow measure, or both is indicated by a "P" or an "R" below the icon and Alternative name.