

SKIDDER INCIDENT INSPECTION CHECKLIST**Date:** _____ **Time:** _____

INCIDENT NAME: _____ INCIDENT NUMBER: _____ RESOURCE #: E-_____

COMPANY/CONTRACTOR: _____

AGREEMENT NUMBER: _____

EQUIPMENT MAKE: _____ MODEL: _____

VIN/SERIAL #: _____

OPERATOR NAME: _____

EQUIPMENT and OPERATOR REQUIREMENTS – SKIDDER Type 1: 176+ HP Type 2: 100-175 HP Type 3: 60-99 HP

#	Minimum Requirements	Yes	No
---	<i>Not all inclusive; for additional clarification refer to agreement (SF-1449 section D)</i>	-----	-----
1	Agreement: One complete copy. Note, must have arrived at incident with at least 1 complete copy (May verify with Finance/Equipment Times)	(D.8) (D.21.9.1)	
2	Check-In Process: Completed (Note: Also includes; Finance, and Plans)	(D.6.5.3)	
3	VIN # on Skidder matches Resource Order (may also have to verify on DPL):	(D.6.2) (D.6.3.1)	
4	Incident Pre-Use Inspection (OF-296 Vehicle/Heavy Equipment Mechanical Inspection)	(D.17) (D.17.1)	
5	RT-130 Fire Line Refresher including Fire Shelter (current): DATE: _____	(D.3.1_1)	
6	ROPS/FOPS/OPS: Shall be equipped with falling object protective structure (FOPS) and/or rollover protective structure (ROPS). Meet all applicable Federal OSHA requirements	(D.2.1.1)	
7	Protective Canopy: Shall be constructed to protect the operator from injury due to falling trees, limbs, saplings or branches which might enter the compartment side areas and from snapping winch lines or other objects	(D.2.1.1)	
8	Cab: The lower portion of the cab shall be fully enclosed with solid material, except at entrances, to prevent the operator from being injured from obstacles entering the cab	(D.2.1.1)	
9	Cab: The upper rear portion of the cab shall be fully enclosed with open mesh material with openings of such size as to reject the entrance of an object larger than 2 inches in diameter.	(D.2.1.1)	
10	Cab: Each machine cab shall have a second means of egress.	(D.2.1.1)	
11	Deflectors: Shall be installed in front of each cab to deflect whipping saplings and branches.	(D.2.1.1)	
12	Radiator Protection: (applicable for heavy equipment)	(D.2.1.1)	
13	Seat Belt	(D.2.1.1)	
14	Lighting: Minimum 2 rear, 2 forward	(D.2.1.1)	
15	Back Up Alarm: Backup alarm that meets the Type D (87 decibels, dBA)	(D.2.2)	
16	Shovel	(D.2.1.1)	
17	Fire Extinguisher: 2A 10BC, that is securely mounted to the vehicle and accessible by the operator. The fire extinguisher shall have a current annual inspection tag	(D.2.1.1)	
18	Tire Chains: Not required to be mounted but must be available for use within the next operational period.	(D.2.1.1)	
19	Programmable Radio: One (1) handheld programmable radio.	(D.2.1.1)	
20	Fire Shelter: New Generation	(D.2.1.1)	

---	Minimum Requirements...cont.	Yes	No
21	PPE: <input type="checkbox"/> Boots <input type="checkbox"/> Hard Had (Hardhat meeting NFPA Standard 1977) <input type="checkbox"/> Gloves <input type="checkbox"/> Headlamp with batteries <input type="checkbox"/> Hearing Protection <input type="checkbox"/> Eye Protection <input type="checkbox"/> (D.2.1.1)		
22	Flame Resistant Clothing (Shirt and Pants). A minimum of two full sets	(D.2.1.1)	
23	<input type="checkbox"/> Grapple <input type="checkbox"/> Winch	(D.2.1.1)	

Equipment meets agreement specifications Equipment does not meet agreement specifications

Inspector: _____ Date: _____
(Print and sign)

Contractor: _____ Date: _____
(Print and sign)

- Contractor given the opportunity to correct noted deficiencies (*See Remarks*)
- Contractor successfully corrected noted deficiencies

Inspector: _____ Date: _____

REMARKS: _____