

**AUTO/TRUCK MECHANIC WITH SERVICE TRUCK  
INCIDENT COMPLIANCE INSPECTION****Date:** \_\_\_\_\_ **Time:** \_\_\_\_\_**INCIDENT NAME:** \_\_\_\_\_ **INCIDENT NUMBER:** \_\_\_\_\_ **RESOURCE #:** E-\_\_\_\_\_**COMPANY/CONTRACTOR:** \_\_\_\_\_**AGREEMENT NUMBER:** \_\_\_\_\_**MECHANIC NAME:** \_\_\_\_\_**EQUIPMENT and OPERATOR REQUIREMENTS  
AUTO/TRUCK MECHANIC WITH SERVICE TRUCK****Minimum Requirements***Not all inclusive; for additional clarification refer to agreement (SF-1449 section D)***Yes No**

|   |  |         |  |  |
|---|--|---------|--|--|
| 1 | <b>Equipment VIN/serial # matches resource order</b> (Schedule of Items)     | D.6.3.1 |  |  |
| 2 | <b>Check-in process completed</b>  | D.6.5.3 |  |  |
| 3 | <b>OF-296 Vehicle/Heavy Equipment Pre-use Inspection Checklist completed</b> | D.17    |  |  |
| 4 | <b>Agreement:</b> One complete copy  | D.8     |  |  |

**Equipment Required (D.2.3)**

|    |  |  |  |
|----|--|--|--|
| 5  | <b>Charging/Starting System Analyzer</b>   |  |  |
| 6  | <b>Arc Welder:</b> Minimum 225 amp with air arc capability and industry-acceptable repair electrodes   |  |  |
| 7  | <b>Code Reader:</b> Ability to read models from 1995-present, ability to accept software upgrades, ability to diagnose ABS (brakes)/SRS (Air bags)/Engine Symptoms, must be a self-sustained device with built-in screen, buttons, and software. Must have universal compatibility with many makes/models. |  |  |
| 8  | <b>Oxy / Acetylene Torch Set:</b> With appropriate cutting and welding tips  |  |  |
| 9  | <b>Air Compressor:</b> Min. of 120 psi. @ 20 CFM with tank and accessories   |  |  |
| 10 | <b>Impact Wrenches:</b> 1/2, 3/4 and 1-inch impact wrenches and impact sockets to 3 inch   |  |  |
| 11 | <b>Hand tool set:</b> to accomplish normal field repairs on equipment  |  |  |
| 12 | <b>Jack Stands:</b> two 12-ton capacity  |  |  |
| 13 | <b>Hydraulic Jacks:</b> one 12-ton and one 20-ton  |  |  |
| 14 | <b>Portable Lighting:</b> Auxiliary or vehicle powered for fieldwork   |  |  |
| 15 | <b>Jumper Cables:</b> 20-foot heavy-duty, minimum 2 gauge  |  |  |
| 16 | <b>Hazardous Material Spill Kit:</b> Minimum 10-gallon spill containment capability  |  |  |
| 17 | <b>Misc. Drain Pans</b>  |  |  |
| 18 | <b>Combination Vice:</b> Min. 4 ½ inch jaw   |  |  |
| 19 | <b>Battery Tester</b>  |  |  |

**Minimum Requirements – continued (D.2.3)****Yes No**

|    |  |  |  |
|----|--|--|--|
| 20 | <b>Volt / Ohm Meter</b>  |  |  |
| 21 | <b>Drill with Bits:</b> 3/8 and 1/2 inch drill, with drill bits from 1/16 to 3/4 inch    |  |  |
| 22 | <b>Fuel Pressure Testing Kit</b>   |  |  |
| 23 | <b>Tap and Die Set:</b> 1/8 to 1 inch fine and coarse thread                             |  |  |
| 24 | <b>Tap and Die Set:</b> 1/8 to 1 inch pipe thread  |  |  |
| 25 | <b>Grinder:</b> 4 inch minimum   |  |  |
| 26 | <b>Self-contained brake and clutch bleeder system</b>                                    |  |  |
| 27 | <b>Knowledge and skills to perform hydraulic system repairs</b>                          |  |  |
| 28 | <b>Onboard A/C power generator for operating electric equipment on the service truck</b> |  |  |

**Consumable Goods (D.2.4)**

|    |  |  |  |
|----|--|--|--|
| 29 | <b>Commonly used SAE and Metric Nuts and Bolts:</b> up to 1/2 inch X 3 inch                  |  |  |
| 30 | <b>Assorted electrical connections:</b> for commonly used wire sizes on all equipment        |  |  |
| 31 | <b>Assorted electrical wire:</b> Sizes commonly found on all types of equipment              |  |  |
| 32 | <b>Assorted common electrical fuses and bulbs</b>  |  |  |
| 33 | <b>Assorted lubricants and cleaners used by field mechanics</b>                              |  |  |
| 34 | <b>Assorted metal fasteners, machine screws, self-tapping screws:</b> up to #12 x 1 1/2 inch |  |  |
| 35 | <b>Air Brake Fittings:</b> Commonly used, up to 5/8 inch                                     |  |  |
| 36 | <b>Shop Towels</b>   |  |  |
| 37 | <b>Misc. funnels</b>   |  |  |

**Additional Requirements**

|    |   |         |  |  |
|----|---|---------|--|--|
| 38 | <b>Boots:</b> All leather, 8" high with lug type sole in good condition   | D.2.2.1 |  |  |
| 39 | <b>PPE:</b> <input type="checkbox"/> Hard Hat <input type="checkbox"/> Gloves <input type="checkbox"/> Eye Protection <input type="checkbox"/> Hearing Protection<br><input type="checkbox"/> Headlamp with batteries | D.2.2.1 |  |  |
| 40 | <b>Flame resistant clothing:</b> A minimum of two full sets of flame-resistant shirts and pants certified to NFPA 1977 standard   | D.2.2.1 |  |  |
| 41 | <b>Fire shelter</b>   | D.2.2.1 |  |  |
| 42 | <b>Chaps:</b> One pair, welding   | D.2.2.1 |  |  |
| 43 | <b>Welding Jacket</b>   | D.2.1.1 |  |  |
| 44 | <b>Fire extinguisher:</b> 2A 10BC, securely mounted to the vehicle, accessible to the operator and with current annual inspection tag   | D.2.3.2 |  |  |
| 45 | <b>Back-Up Alarm:</b> Meets the Type D (87 decibels, dBA) requirements of SAE J994  | D.2.3.2 |  |  |
| 46 | <b>Reflectors:</b> Triangles, bi-directional, 1 set of 3  | D.2.3.2 |  |  |
| 47 | <b>Wheel Chocks:</b> (minimum one pair)   | D.2.3.2 |  |  |
| 48 | <b>Shovel</b>   | D.2.3.2 |  |  |

[illegible]