

## Florida National Scenic Trail Design Parameters

Design Parameters are technical guidelines for the survey, design, construction, maintenance, and assessment of the FNST. Local deviations from any Design Parameter may be established based on trail-specific conditions, topography, or other factors, provided that the deviations are consistent with the general intent of the applicable Trail Class and National Scenic Trail experience.

D : III ENCE		T - 'I Cl 1 -	T -: I Cl 2	T :1 Cl =2	T 'I Cl	T : CL -E
Designed Use FNST		Trail Class 1	Trail Class 2	Trail Class 3	Trail Class 4	Trail Class 5
Design Tread Width	Wilderness (Single Lane)	0" - 12"	6" - 18"	12" - 24" Exception: may be 36" - 48" at steep side slopes	18" - 24" Exception: may be 36" - 48" at steep side slopes	Not applicable
	Non-Wilder- ness (Single Lane)	6" - 12"	12" - 24"	18" - 36"	24" - 60"	36" - 72"
	Non-Wilder- ness (Double Lane)	36" - 48"	36" - 48"	36" - 60"	48" - 72"	72" - 120"
	Structures (Minimum Width)	18"	18"	36"	48"	60"
Design Surface	Туре	Native, ungrad- ed May be contin- uously rough	Native, limited grading May be contin- uously rough	Native with some on-site borrow or imported material where needed for stabilization, occasional grading Intermittently rough	Native with im- proved sections of borrow or imported ma- terial,. routine grading Stable, with mi- nor roughness	Likely imported materials, rou- tine grading Uniform, firm, and stable
	Protrusions	≤ 24" Likely common and continuous	≤ 6" May be com- mon and con- tinuous	≤3" May be com- mon, not continuous	≤3" Uncommon, not continuous	No protrusions
	Obstacles (Maximum Height)	24"	12"	10"	8"	No obstacles
Design Grade	Target Grade	5% - 20%	5% - 12%	3% - 10%	2% - 8%	2% - 5%
	Short Pitch Max	30%	25%	15%	10%	5% - 8%
	Maximum Pitch Density	20% - 30% of trail	10% - 30% of trail	10% - 20% of trail	5% - 10% of trail	0% - 5% of trail
Design Cross Slope	Target Cross Slope	Natural side slope	5% - 20%	5% - 10%	3% - 7%	2% - 3%
	Maximum Cross Slope	Natural side slope	20%	10%	8%	5%
Design	Height	6"	6" - 8"	8"	8" - 10"	8" - 10"
Clearing	Width	≥ 24" Some veg- etation may encroach into clearing area	24" - 48" Some light vegetation may encroach into clearing area	36" - 60"	48" - 72"	72" - 96"
	Shoulder Clearance	3" - 6"	6" - 12"	12" - 18"	12" - 18"	12" - 24"
Design Turn	Radius	2' - 3'	3' - 6'	4' - 8'	8' - 10'	8' - 12'

