

## Chapter 7

# How To Use *Aquarius*

---

This chapter describes how to use *Aquarius* including how to: 1) build a flow network using the graphical user interface, 2) enter the necessary physical and economic data, 3) solve the water allocation problem, and 4) view model outputs. We assume that the user is familiar with basic procedures for running applications in a Windows environment such as choosing commands and resizing windows. *Aquarius* requires a personal computer with a Pentium-type processor and a 32-bit operating system (Microsoft Windows 98, NT, 2000, XP). Enhanced performance is attained using a system with a high number crunching capability.

## Exploring the Network Worksheet Screen

As described in Chapter 6, *Aquarius* was written using an object-oriented programming language. Each water system component is an object of the model, and each tool is a function that operates on an object. Although the object terminology is not repeated in this chapter, remember that the object structure of the model is what allows users to easily create a unique flow network composed of a set of water system components (WSC).

### Network Worksheet (NWS) Screen

Once the *Aquarius* software is loaded in the computer, the application is launched by double-clicking the *Aquarius* icon. Initially a shortened menu selection is displayed with options for creating a new flow network or for opening an existing one by selecting the *File* menu. Then, the *Aquarius* screen and NWS appear (figure 7.1).

The NWS can be resized and scrolled. Several flow networks can be displayed simultaneously, although only one NWS at a time is active. The title bar at the top of the NWS indicates the name of the flow network, which should have the file extension “.nwk”. The menu bar at the top of the screen provides access to the various *Aquarius* commands. The two palettes contain the WSCs (upper side) and tools (left side) used to create the flow networks, as described later. At the bottom of the screen is the status line, which provides information on the currently selected object or procedure.

### Menu Bar

Pull-down menus are arranged at the top of the screen as shown in figure 7.1. Each menu has sub-menus that allow the user to access the functions available in the model once a NWS is loaded. The complete layout of the pull-down menu bar is in figure 7.2. The command functions are explained throughout this chapter.




Figure 7.1 *Aquarius* (V05) network worksheet screen .

## Water System Components (WSC) Palette

The WSC that make up a flow network are a series of nodes and links. All WSC are in a palette that is automatically displayed on the upper side of the screen. The user can move the WSC palette any place on the screen including the four boundaries. The WSC palette can be removed from the screen by disabling the palette from the *View* menu. Choosing the WSC palette again returns it to its default position. The icons, names, and functions of the WSC are in table 7.1.




















Figure 7.2 *Aquarius* (V05) pull-down menus.

Table 7.1 The water system components palette.

Button	Name and function
	<i>Surface Water</i> : creates a surface water supply source (catchment) contributing uncontrolled flows.
	<i>Ground Water</i> : creates a subsurface water supply source (aquifer) contributing controlled flows <b>by pumping</b> .
	<i>Storage Reservoir</i> : creates a water storage capacity for flow regulation.
	<i>Release-to-downstream-demand</i> : creates a pseudo-system component to help satisfy downstream demands.
	<i>Spill Controller</i> : creates a pseudo-system component that helps minimize reservoir spillages.
	<i>Hydropower</i> : creates a powerplant (with variable or fixed-head) for hydroelectric generation.
	<i>Irrigation Water Supply</i> : creates an offstream water demand area of agricultural irrigation.
	<i>Urban Water Supply</i> : creates an offstream water demand area for municipal and industrial water supply.
	<i>Instream Recreation</i> : creates a river reach with water based recreation activities in the area.
	<i>Storage Reservoir with Recreation</i> : creates a storage capacity with added lake recreation activities.
	<i>Instream Flow Protection</i> : creates a river reach designated for fish/wildlife habitat protection.
	<i>Flood Control</i> : creates a river reach prone to overbank flooding to assess possible damages.
	<i>River Reach</i> : creates a natural channel to convey flows between system components.
	<i>Canal/Pipeline</i> : creates a water conveyance structure such as a canal or pipeline.
	<i>Left-bank Diversion</i> : creates a diversion point for diverting water over the left-bank.
	<i>Right-bank Diversion</i> : creates a diversion point for diverting water over the right-bank.



*Left-bank Junction:* creates an inflow point to the waterway from its left-bank.



*Right-bank Junction:* creates an inflow point to the waterway from its right-bank.











---

---

## Tools Palette

The tools palette gives quick access to a group of functions that operate the WSCs. All tools are in a palette that is automatically displayed on the left side of the screen. The user can move the tools palette to any of the four sides of the screen. The tools palette can be removed from the screen by disabling tools palette from the *View* menu. Choosing tools palette again returns it to its default position. The icons, names, and functions of the tools are in table 7.2.

Table 7.2 The tools palette.

Button	Name and function
	<i>Select:</i> selects one or more system components from a flow network.
	<i>Move:</i> moves a system component within the network worksheet.
	<i>Rotate:</i> rotates the direction of flow in a system component.
	<i>Delete:</i> deletes a system component from the network worksheet.
	<i>Physical Connectivity:</i> displays categories of in/outflows from a system component.
	<i>Physical Input:</i> accesses the physical data structure of a system component.
	<i>Economic Input:</i> accesses the economic data structure of a system component.
	<i>Output Graph:</i> accesses the list of output variables of a system component.
	<i>Graphical Folder:</i> opens a folder that creates a list of variables for output in graphical format.
	<i>Tabular Folder:</i> opens a folder that creates a list of variables for output in tabular format (ASCII).



*Select Output Variables*: moves the output variables into the *Graphical /Tabular Folder*.

---

---

## Creating a Flow Network

The user interacts with the model through a graphical user interface to create a flow network. The graphical user interface consists of the four elements of the model introduced earlier: i) the network worksheet (NWS), ii) the menus, iii) the water system components (WSC) palette, and iv) the tools palette.

In the NWS, each system component corresponds to a graphical node or link of the flow network. The components are represented by icons in the WSC palette, based on a pictorial representation of the component's function. By selecting (left clicking) an icon from the WSC palette and then left clicking again in the NWS, the model creates an instance of the component. In this manner, all the necessary components that simulate the topology of the actual river system are created.

To assemble a flow network, place two or more nodes (water sources, reservoirs, powerplants, demand areas, diversions, or junctions) in the NWS. Next, link the nodes using river reaches and/or canal/pipelines, also selected from the WSC palette. Once a link is selected, place it in the NWS by clicking first on an outgoing terminal of the upstream node and then on an incoming terminal of the downstream node, always in that order. Additional nodes and links can be added to a network, but links can only be placed between existing nodes.

There is no limit to the number of components that can be added to a network, but doing so increases the mathematical dimension of the water allocation problem and the computation time needed to find the optimal solution (see reference to computation times at the end of Chapter 8). In placing links, the model prevents most absurd connections such as routing water released from a reservoir back as an inflow to the same reservoir. Moreover, the model will automatically disallow connections that are hydraulically unsound or not allowed by the model.

Components can be moved anywhere in the NWS by clicking the *Move* button from the tools palette, clicking on the component, and dragging and dropping it to its new position. A component can be removed from the NWS by clicking the *Delete* button of the tools palette and then clicking on the component in the NWS. *Delete* removes the icon from the screen and eliminates that instance of the component from the model.

The creation and alteration of flow networks is expedited by copying and inserting portions of an existing network onto the same or a new NWS. To do this, click the *Select* button of the tools palette and select the part of the existing network to copy to the Windows clipboard. Select the desired part by dragging a rubber-band box around it. The starting point is the upper-left corner of the box, which

is anchored by left-clicking at the location. The box is enlarged by dragging the pointer to its final position. The screen colors are reversed within the box (figure 7.3). To copy the information in the box into the Windows clipboard, choose *Copy WSC* under the *Edit* menu. To place the information from the clipboard to a NWS, select the command *Paste WSC* from the *Edit* menu and click at the desired location within the NWS. The *Paste WSC* command is available whenever the Windows clipboard has information that can be brought into a NWS.

Because *Copy/Paste* creates new instances in the NWS of the components stored on the clipboard




Figure 7.3 Copy and paste of network components.

and duplicates their data structure, we call the duplicated objects clones. After pasting new components in a NWS, amend the data associated with the new components if they require different data from that brought in with the pasting operation. Information on the clipboard can be placed into numerous worksheet locations as long as it remains in the clipboard. *Copy/Paste* also provides the opportunity to build a library of individual components (e.g., reservoirs, irrigation areas) or small networks, which can be easily incorporated onto a NWS when necessary.


## Entering Input Data

The model uses physical and economic groups of input data. The physical data consist largely of the dimensions and operational characteristics of the system components such as maximum reservoir storage capacity, powerplant efficiency, the return flow coefficient from an irrigation zone. The economic data consist mainly of the demand functions of the various water uses competing for water within the river system. The input data entered for any system component is a property of the object, even when stored on a disk for future use. When the network is reloaded from the disk to the NWS, all data saved from the previous session for each component are retrieved in exactly the same form.

We recommend that every time a flow network has had its physical input data modified, particularly when WSCs have been added or deleted, the new version of the network should be saved, closed and reopened before any further analysis can take place.

### Physical Input Data

Physical data are entered into the model using a series of dialog boxes specifically designed for each system component. The data entry procedure is selected by clicking the *Physical Input* button from the tools palette and clicking the component of interest. A data entry dialog box opens with multiple tabs that group the input data by categories (as an example see figure 7.4). Table 7.3 lists the data required for each system component.



The image shows a software dialog box titled "RESERVOIR" with a close button (X) in the top right corner. The dialog has three main tabs: "Operational Characteristics", "Operational Constraints", and "Outlet Works". The "Operational Characteristics" tab is active and contains two sub-sections: "Physical Characteristics" and "Evaporation". Under "Physical Characteristics", there is a text field for "Name of Reservoir" containing the text "East\_Lake". Below this, there are two groups of input fields. The first group, "Elevation vs. Storage function parameters :", contains two fields: "c1" with the value "1.860" and "d1" with the value "0.440". The second group, "Area vs. Storage function parameters :", contains two fields: "c2" with the value "1.280" and "d2" with the value "0.590". At the bottom of the dialog, there are two buttons: "Read" and "Cancel".

Figure 7.4 Physical data input dialog box for a reservoir.



Table 7.3 Physical inputs for the following system components.

WSC	Input Data	Page of Reference
<i>Surface Water</i> .....	Physical Characteristics Name of river/basin Input file name	3-2
<i>Ground Water</i> .....	Physical Characteristics Name of well or aquifer Pumping Capacity Monthly values ...	3-2
<i>Storage Reservoir</i> .....	Physical Characteristics Name of reservoir Parameters of Elevation vs. Storage function Parameters of Area vs. Storage function Evaporation Monthly evaporation rates Operational Characteristics Initial storage Final storage Minimum storage Maximum storage Operational Constraints (check-box) <input checked="" type="checkbox"/> Minimum storage <input checked="" type="checkbox"/> Maximum storage <input checked="" type="checkbox"/> Final storage Outlet Works Several entries ...	3-3, 5-14
<i>Release-to-downstream-demand</i> .....	Physical Characteristics Name of pseudo-object Operational Characteristics Minimum flows ... Maximum flows ... Operational Constraints (check-box) <input type="checkbox"/> Minimum flow <input type="checkbox"/> Maximum flow	3-5
<i>Spill Controller</i> .....	Physical Characteristics Name	3-6
<i>Hydropower</i> .....	Physical Characteristics Name of hydropower plant Installed capacity Design discharge Turbine-generator efficiency	3-8, 5-14

Parameters of the Energy Rate vs. Storage function	
Maintenance Schedule	
Monthly index of availability of the hydropower units ...	
Maximum Release	
Monthly values ...	
Minimum Release	
Monthly values ...	
Operational Constraints (check-box)	
<input checked="" type="checkbox"/> Minimum release	
<input checked="" type="checkbox"/> Maximum release	
<i>Irrigation Water Supply</i> .....	3-11, 5-14
Physical Characteristics	
Name of irrigation area	
Coefficient of return flow	
Annual firm water	
Annual trend	
Maximum Flow	
Monthly values ...	
Minimum Flow	
Monthly values ...	
Seasonal Pattern	
Monthly values ...	
Operational Constraints (check-box)	
<input type="checkbox"/> Minimum flow	
<input type="checkbox"/> Maximum flow	
<input type="checkbox"/> Seasonal Pattern	
<input type="checkbox"/> Annual firm water	
<i>Urban Water Supply</i> .....	3-13, 5-14
Physical Characteristics .	
Name of municipal and industrial area	
Coefficient of return flow	
Annual firm water	
Annual trend	
Maximum Flow	
Seasonal values ...	
Minimum Flow ...	
Seasonal values ...	
Seasonal Pattern	
Monthly values ...	
Operational Constraints (check-box)	
<input type="checkbox"/> Minimum flow	
<input type="checkbox"/> Maximum flow	
<input type="checkbox"/> Seasonal pattern	
<input type="checkbox"/> Annual firm water	
<i>Instream Recreation</i> .....	3-14, 5-14
Physical Characteristics	
Name of instream recreation area	
Maximum Flow	
Monthly values ...	
Minimum Flow	
Monthly values ...	

Operational Constraints (check-box)	
<input type="checkbox"/> Minimum flow	
<input type="checkbox"/> Maximum flow	
<i>Storage Reservoir with Recreation</i> .....	3-3, 3-17, 5-14
Physical Characteristics	
Name of reservoir	
Parameters of Elevation vs. Storage function	
Parameters of Area vs. Storage function	
Evaporation	
Monthly evaporation rates	
Operational Characteristics	
Initial storage	
Final storage	
Minimum storage	
Maximum storage	
Minimum storage for recreation	
Maximum storage for recreation	
Operational Constraints (check-box)	
<input checked="" type="checkbox"/> Minimum storage	
<input checked="" type="checkbox"/> Maximum storage	
<input checked="" type="checkbox"/> Final storage	
Outlet Works	
<i>Instream Flow Protection</i> .....	3-17
Physical Characteristics	
Name of instream flow protection area	
Maximum Flow	
Seasonal values ...	
Minimum Flow	
Seasonal values ...	
Operational Constraints (check-box)	
<input type="checkbox"/> Minimum flow	
<input type="checkbox"/> Maximum flow	
<i>Flood Control</i> .....	3-19
Physical Characteristics	
Name of flood control area	
Bankfull discharge	
Monthly values ...	
<i>River Reach</i> (no input data required)	
<i>Canal/Pipeline</i> (no input data required)	
<i>Diversion and Junction</i> (no input data required)	

---

Note: An option is enabled when a check mark appears in the check box; disabled when the check box is empty.  
Variables in shaded font are not available yet

## Economic Input Data

The economic data are the parameters necessary to specify the demand curves (i.e., the marginal prices that users are willing to pay) for water during each season of the optimization horizon. The data entry procedure is selected by clicking the *Economic Input* button from the tools palette and clicking the object of interest. In some cases the user has the option to choose among exponential, linear or constant prices, after which a data entry dialog box opens for user interaction (as an example see figure 7.5). Table 7.4 lists the economic data required for each competing water use.

Table 7.4 Economic inputs for the following system components.

System Component	Input Data	Eq. of Reference
<i>Hydropower</i>	Average annual and seasonal energy price: $P, P_s$ .....	(4.3)
	Parameters of the seasonal demand function: $a_2, b_2$	
	Exponential decaying price .....	(4.3)
	Constant price .....	(4.10)
<i>Irrigation Water Supply</i>	Parameters of the seasonal demand function: $a_3, b_3$	
	Exponential decaying price .....	(4.20)
	Constant price .....	(4.25)
<i>Urban Water Supply</i>	Parameters of the seasonal demand function: $a_4, b_4$	
	Exponential decaying price .....	(4.28)
	Constant price .....	(4.33)
<i>Instream Recreation</i>	Parameters of the seasonal demand function: $a_5, b_5$	
	Linear price .....	(4.36)
	Constant price .....	(4.41)
<i>Storage Reservoir with Recreation</i>	Parameters of the seasonal demand function: $a_6, b_6, c_6$	
	Hyperbolic tangent price .....	(4.44)
<i>Flood Control</i>	Parameters of the flood damage curve: $a_7, b_7$	
	Exponential increasing cost .....	(4.45)
<i>Ground Water Pumping</i>	Parameter of the seasonal pumping supply function	
	Constant cost: $a_8$ .....	(4.50)




Figure 7.5 Economic data input dialog box for an irrigation area.

## Network Connectivity

Once the flow network is assembled, the model conducts a series of validation steps before proceeding to solve the water allocation problem. These procedures are launched by choosing the command *Update Network Connectivity* from the *Connectivity* menu. Among the various validation steps, the model checks that:

- ✓ all WSCs are named;
- ✓ all WSCs that compete for water have marginal prices different from zero;
- ✓ instream water users (IRA, IFP, FCA) are placed in the flow network as such;
- ✓ offstream water uses (M&I, IRR, HPW) are placed in the flow network as such;
- ✓ reservoirs have a waterway available for releasing uncontrolled spills (at the central terminal);
- ✓ component connections are hydraulically sound.

Warning messages are displayed for violations of preestablished network connectivity rules. If all steps are successfully completed, the network status changes from connectivity *..unchecked* to connectivity *..checked* on the title bar of the NWS.

System components competing for water are framed by a red line on the screen. Similarly, links conveying controlled flows (i.e., links leaving a node where a decision is made) are turned red. The number of sets of decision variables is equal to the number of red links. The WSC frame and the links turn red after updating network connectivity.

An additional operation performed during this stage is defining the hydraulic connectivity of the network objects. This information is used by the model to generate the mathematical connectivity of the system components based on the requirements of the optimization technique selected. Details on the mathematical connectivity of the system elements are found in Chapter 6.

If Names on Network is chosen from the View menu, next to each component in the NWS the model displays the name assigned to the component by the user and the number assigned by the model to links (i.e., river reaches and conveyance structures) and to diversion and junction nodes. The user can also look at and print a table summarizing the network nodes (figure 7.6 top) and another one summarizing network links (figure 7.6 bottom). These tables are accessed by the commands List Network Nodes and List Network Links in the Connectivity menu.

## Selecting the Optimization Technique

*Aquarius* uses a sequential optimization technique, Sequential Quadratic Programming (SQP), for solving the water allocation problem. Details of the algorithm are in Chapter 5. The algorithm is (automatically) selected from the *Techniques* menu. This command opens a dialog box containing a series of parameters, specified by the user, that control the sequential process and the accuracy of the computations (figure 7.7). Parameters are divided into two groups, those that control the sequential approximation algorithm, named Sequences Parameters, the purpose of each is:

**Number of Sequences:** this defines the maximum number of QP sequential problems to be solved (see Figure 5.1). The default for this parameter is 50, which is a reasonable number for a medium size networks as the one presented in Chapter 8.

**Number of Sequences using QPinit:** after an initial feasible solution is found, **a few number of sequences** are specified to approximate the solution to a near-optimal level. The recommended value is between 1 and 5. The default value for any new run is set equal to 3.

**Max. Number of Iterations per Sequence:** this parameter is intrinsic to the general differential algorithm used by QPTHOR to solve the QP problem. The user should explore values ranging from 5 to 50 iterations per sequence. In general, the larger the value adopted, the smaller the number of sequences necessary to reach the optimal solution.

And the Accuracy Parameters, to control the accuracy of the calculations. The purpose of each parameter is:

The figure consists of two screenshots from a software application. The top screenshot is titled "Table of Nodes for: Example00.nwk" and displays a table with the following data:

No.	Name	Type	Price	Function	Connections	
					Upstream	DownStream
1	Native_Fish	CONSERVATION	No		East_Lake	Jct_4
2	East_Fork	NATURALFLOW	No		-	East_Lake
3	Mid_Valley	IRRIGATION	Yes		Div_1	Jct_5
4	Whitewater	RECREATION	Yes		Jct_6	Jct_4
5	West_Lake	RESERVOIR	No		West_Fork	Plant_B Jct_6
6	East_Lake	RESERVOIR	No		East_Fork - -	Plant_A Upper_Valley Native_Fish

The bottom screenshot is titled "Table of Links for: Example00.nwk" and displays a table with the following data:

No.	Name	From	To	Description
1	L1	Plant_C	Jct_3	routing
2	L3	Upper_Valley	Jct_4	return
3	L2	Native_Fish	Jct_4	routing
4	L4	East_Lake	Plant_A	decision
5	L6	East_Lake	Upper_Valley	decision

Figure 7.6 Table of network nodes and connectivity links.

Change of Objective-Value between Sequences: is the main stop criterion. Five consecutive solutions (sequences) of the nonlinear problem with an objective function change less than the specified dollar amount will cause the application to stop (\$1000 in the example).

Change of Objective-value Between Iterations: this is the stop criterion for each sequence of the differential algorithm (QPTHOR), similar to the criterion above (\$0.05 in the example).

Computational Accuracy Requirement: used extensively during optimization. A quantity  $q$  is set equal to zero when its value is less than its order of magnitude  $\bar{q}$  times a selected accuracy (e.g.,  $q < \Delta \bar{q}$ ,  $\Delta = 0.1$  in the example).

Computational Accuracy for Evaporation: this parameter is used during the reconciliation procedure implemented for the "Implicit" modeling of reservoir evaporation (0.0001 in the example).




Figure 7.7 Control parameters dialog box.

The final solution to the water allocation problem found by the model is generally sensitive to the values assigned to the parameters listed above. The proper values for the parameters will depend on the topology of the network, the number of water users competing for water, and the length of the optimization horizon. Given the difficulty of preestablishing the proper value for all these parameters, the user should begin running the model with the default values and then experiment with different values for the parameters to find the most appropriate set of numbers for the problem at hand.

## Specifying the Simulation Time Interval

The time interval for the analysis is specified by selecting the *Uniform Time Intervals* from the *Time Interval* menu. This opens a submenu for selecting the periodic time interval: *Monthly*, *Weekly*, *Daily*. The monthly time interval is the only option active at the present (automatically selected). Once the periodic time interval is selected, a window opens to enter the four items listed in the dialog box in figure 7.8. Although the model was conceived to operate at any of the uniform time steps offered in the menu (monthly, weekly, daily), present limitations in the graphical user interfaces allow for only monthly time intervals.

The first entry in figure 7.8, Period of Analysis, specifies the length, in number of periods for which



the model will determine the system operation. Inflow data should be provided for at least the same segment of time. The next entry, Optimization Horizon, also in number of time periods, specifies how far into future the model should look to build the optimal operational policies. The optimization horizon defines the actual size of the optimization problem(s) being solved.

If the Optimization Horizon is set equal to the Period of Analysis (Overlapping Period = 0), the quasi-continuous optimization scheme is disabled (see Chapter 5, Time Intervals of Analysis); hence, the optimal operational policies identified by the model will extend for the full number of periods indicated by the optimization horizon. However, when the period of analysis is longer than the optimization horizon, which enables the quasi-continuous optimization procedure, the user must also specify the number of Overlapping Periods. The model allows the user to prescribe any number of overlapping periods for monthly simulation.

The last input in the dialog box in figure 7.8, Starting Month, indicates the period within the annual cycle for the start of the system operation. For instance, 1 for January, 2 for February, . . . 12 for December (for a monthly time step). In this manner, time series data, such as inflows, evaporation rates, etc., are properly considered.

The dialog box is titled "Uniform Time Intervals : Monthly". It features four rows of input fields, each followed by the word "months". The first row is "Period of Analysis" with a text box containing "120". The second row is "Optimization Horizon" with a text box containing "36". The third row is "Overlapping Period" with a text box containing "12". The fourth row is "Starting Month (1,2..12)" with a text box containing "1". At the bottom of the dialog box, there are two buttons: "OK" on the left and "Cancel" on the right.

Figure 7.8 Period of analysis and optimization horizon dialog box.

## Solving the Water Allocation Problem

Once the network is assembled, including input of all the physical and economic data, and the network connectivity is verified, *Aquarius* is ready to find the optimal water allocation. This is accomplished by selecting the command *Start Water Allocation* from the *Solve Network* menu.

The problem is solved in two steps. First, an initial feasible solution (IFS) to the water allocation problem must be found. The IFS that the model finds will generally be far from the optimal solution (see Chapter 5, Search for an Initial Feasible Solution), but serves as the starting point for the sequential optimization procedure that follows. The IFS is obtained automatically by the model (the search for an IFS is invisible to the user), and only for a network in the *..checked* condition.

By specifying zero (0) number of sequences, the user can make the model to stop after finding the IFS. The graphical output capabilities of the model, introduced next, can be used to render the state of the system that corresponds to the IFS found by the model.

The second step, actual optimization, consists of running the optimization algorithm to find the optimal solution of the water allocation problem. As explained in Chapter 5, sequential algorithms go through a succession of quadratic approximations of the nonlinear global objective function until the optimal solution is reached. The maximum number of QP sequences allowed is indicated in the corresponding dialog box (figure 7.7). As the solutions of the QP problems progress, the status bar at the bottom of the screen displays the sequence number. Once the optimal solution is found, or the maximum number of sequences is reached, the optimization stops (indicated in the status bar). The sequential optimization process can be interrupted by selecting *Stop Water Allocation* from the *Solve Network* menu. The user can track the sequential changes in system state and decision variables during the optimization by using the graphical output capabilities presented next.

## Graphical and Tabular Output

Flow networks generally contain many state, decision, and economic variables that an analyst should consider. *Aquarius* facilitates the interpretation and analysis of all information through readily accessible graphical and tabular output display formats. The user can display output variables on the screen by selecting *Display Output Graphs* from the *Outputs* Menu or by pressing the corresponding icon in the tools palette and clicking on the component of interest in the NWS. This opens a dialog box that lists all physical and economic output variables available for that component. Figure 7.9 shows a dialog box for a reservoir. A graph window is created when a check mark is inserted (enabled) in the corresponding check box and is deleted (disabled) when the check box is empty.

If instead of clicking on a WSC in the NWS, the user clicks any place in the worksheet, a graph window opens showing the evolution of the global objective function value as the sequential algorithm (SQP) completes optimization. This is possible because the flow network as a whole is also an object.

Single-variable graph windows allow the user to visualize the sequential changes in the




Figure 7.9 Selecting graphical display output variables for a reservoir.

state, decision, and economic output variables as the system reaches its optimal state. Visualizing sequential changes is only possible if the output graph windows were opened either before launching optimization or during the optimization.

Several graph windows can be open simultaneously, the only limitation is the number of windows visible on the screen at one time. As they are opened, the graph windows appear on the screen in a cascade format. The user may choose *Tile* from the *Window* menu to display all graph windows at once. The model maintains a register of all graph windows opened during a working session. The same graph windows can be reactivated any time by choosing *Reactivate Screen Graphs* from the *Outputs* menu. The continuous refreshing of the graphical output windows after each sequence of optimization increases slightly the execution time of the model. Table 7.5 presents the output variables available for graphical display, listed by type of water system component.

Table 7.5 Output variables for the following system components

<i>Surface Water</i>	<input type="checkbox"/> Natural Flows [Mcm]
<i>Ground Water</i>	<input type="checkbox"/> Pumping Flows [Mcm] <input type="checkbox"/> Pumping Cost [Mill.\$]
<i>Storage Reservoir</i>	<input type="checkbox"/> Total inflows [Mcm] <input type="checkbox"/> Releases (up to 3 outlets) [Mcm] <input type="checkbox"/> Storage [Mcm] <input type="checkbox"/> Evaporation losses [Mcm]
<i>Hydropower</i>	<input type="checkbox"/> Powerplant releases [Mcm] <input type="checkbox"/> Plant generation [GWh] <input type="checkbox"/> Benefits [Mill.\$] <input type="checkbox"/> Marginal prices [\$/Mcm]
<i>Irrigation Water Supply</i>	<input type="checkbox"/> Allocated Flows [Mcm] <input type="checkbox"/> Return flows [Mcm] <input type="checkbox"/> Benefits [Mill.\$] <input type="checkbox"/> Marginal Prices [\$/Mcm]
<i>Urban Water Supply</i>	<input type="checkbox"/> Allocated Flows [Mcm] <input type="checkbox"/> Return flows [Mcm] <input type="checkbox"/> Benefits [Mill.\$] <input type="checkbox"/> Marginal prices [\$/Mcm]
<i>Instream Recreation</i>	<input type="checkbox"/> Instream flows [Mcm] <input type="checkbox"/> Benefits [Mill.\$] <input type="checkbox"/> Marginal prices [\$/Mcm]
<i>Storage Reservoir with Recreation</i>	<input type="checkbox"/> Total inflows [Mcm] <input type="checkbox"/> Reservoir releases (up to 3 outlets) [Mcm] <input type="checkbox"/> Storage [Mcm] <input type="checkbox"/> Evaporation losses [Mcm] <input type="checkbox"/> Benefits [Mill.\$]

	<input type="checkbox"/> Marginal prices [\$/Mcm]
<i>Instream Flow Protection</i>	<input type="checkbox"/> Instream flows [Mcm]
<i>Flood Control</i>	<input type="checkbox"/> Flood discharge [Mcm]
	<input type="checkbox"/> Flows over bankfull discharge [Mcm]
	<input type="checkbox"/> Flood damages [Mill.\$]
	<input type="checkbox"/> Marginal cost [\$/Mcm]
<i>River System</i>	<input type="checkbox"/> Global Objective Function [Mill.\$]

---

In addition to single-variable graphs, the user can create graphical and tabular outputs containing one or more physical or economic variables. This is useful for displaying, in the same graph, output variables of the same class generated at different locations in a flow network. For instance, the user may want to compare energy generated at different powerplants, instream versus offstream water allocations, or storage trajectories for all reservoirs. Similarly, this option can be used to generate tabular outputs (in ASCII format) that can be printed or automatically imported into an Excel spreadsheet. This is done by selecting *Create Output Folder* from the *Outputs* menu. This opens a submenu from which to choose either a *Graphical* or a *Tabular Output Folder*. Folders can also be opened from the tools palette. Both choices open a new window, the folder, that will list all output variables. Once the folder window is visible, the procedure for selecting the variables starts by clicking the *Select Output Variables* button of the tools palette and clicking the component of interest in the NWS. This opens another window that lists all output variables for that specific component (table 7.5 and figure 7.10). Select the output variables of interest by dragging each one from the Select Output Variable window and dropping it into the Output Folder window (figure 7.10). Once all variables are selected, create an output product (i.e., graph or file) by clicking on the *Create Graph (File)* button.




Figure 7.10 Specifying a list of variables for the tabular output folder.

In contrast to single-variable graph windows where information is updated during the sequential optimization process, graphs and tables created by the output folder reflect the state of the system at the moment the output is created (i.e., a static view). If only the optimal state of the network is of interest, the output folder should be created after the water allocation finishes. Printouts of any of the windows, including the NWS, can be obtained by making the window of interest the active window and selecting *Print* from the *File* Menu. The *Print* command also provides most of the customary Windows print settings.

*Chapter 8*  
**Model Applications**

This chapter presents two hypothetical river systems modeled at a monthly time step. The first, of average complexity, is used to demonstrate various features of Aquarius, including the study of alternative price functions for offstream and hydroelectric demands, and of the effect of improving efficiency of irrigation water use. The second, of minimal complexity, is used to illustrate the concept of economic efficiency that drives the water allocation.

**Description of the River Basin System**

The first hypothetical river basin is represented by the flow network in figure 8.1, in which the water flows from left to right. The basin comprises three water source subbasins, East Fork, West Fork, and Lower Fork. Two of the subbasins are headwater catchments, at high elevations (left portion of the graph). The third catchment area (Lower Fork) delivers unregulated inflows to the downstream portion of the main water course. Inflows for a real case would typically be based on flow data from the study site. Flows for this hypothetical river basin were taken from rivers of the western United States. The long-term mean-annual discharges of the three catchments are 9,600 Mcm (East Fork), 6,700 Mcm (West Fork), and 6,500 Mcm (Lower Fork). The flow regime is characterized by highly peaked hydrographs, typical of mountainous regions where runoff is dominated by snowmelt. Flows are relatively low during the winter and very high during the spring and early summer months (i.e., April through July).

The natural flows in are regulated by four reservoirs: East Lake, West Lake, Mid Lake, and Lower Lake (figure 8.1). Table 8.1 lists the operational characteristics of the reservoirs. The upper reservoirs (East and West Lakes) have relatively limited capacity to regulate inflows, with active storage/inflow ratios of about 0.3. The third reservoir, Mid Lake, which impounds water from the two upstream river forks, has a storage capacity equal to 70% of the mean-annual discharge at that site. The most downstream reservoir also has limited capacity (storage to natural inflow ratio equal to 0.26), but around 2/3 of its inflows are pre-regulated. When considering the whole basin, the ratio of active storage to natural flows is approximately 1.0.

Table 8.1 Operational characteristics of four hypothetical reservoirs.

Reservoir	Storage [Mcm]			Sto./Inf. Ratio	Elev. vs. Stor.		Area vs. Stor.		Constraints		
	Min.	Max.	Init=Fin.		$c_1$	$d_1$	$c_2$	$d_2$	Min.	Max.	Final
East	2,000.	5,000.	3,500.	0.31	1.86	0.44	1.28	0.59	y	y	y
West	2,000.	4,000.	3,000.	0.30	2.77	0.48	0.26	0.75	y	y	y
Mid	6,000.	17,500.	14,000.	0.70	3.03	0.38	0.30	0.73	y	y	y
Lower	14,000.	20,000.	17,500.	0.26	0.79	0.44	1.00	0.68	y	y	y




Figure 8.1 Flow network of an hypothetical river basin system.

Thus, the system contains enough active storage to accommodate the total amount of water generated by the three catchments during an average hydrologic year.

Table 8.1 also provides information about the elevation-storage and area-storage relations for the four reservoirs (equations (3.4a) and (3.4b)). Monthly evaporation rates (which would typically, in a real case, be estimated from data gathered at nearby meteorological stations) were set equal to 30, 35, 40, 50, 65, 70, 85, 70, 60, 50, 40, and 35 mm/month, from January through December, respectively for all reservoirs. Data pertinent to the spillways are set to zero (not used for operation at monthly time intervals). The three operational constraints for reservoirs, minimum, maximum, and final storage, are enforced according to table 8.1.

Hydropower is generated using releases from the four reservoirs. Due to existing topographical conditions, the two high elevation reservoirs, East Lake and West Lake, are connected to run-of-river powerplants, A and B, by canals that run parallel to the river at an almost constant elevation. It is reasonable to assume that the two power facilities operate under fixed-head conditions (see figure 3.4, right side). The remaining two powerplants, C and D, are located in the intermediate and lower portions of the system, operate directly connected to the reservoir, and are subject to variable hydraulic heads (see figure 3.4, left side). Table 8.2 describes the power facilities.

Table 8.2 Characteristics of four hypothetical hydropower facilities.

Utility	Installed	Design	Group	Scheduled	-- Energy Rate --		Plant Release		Constraints		
	Capacity [Mw]	Discharge [m3/s]			Efficiency [ - ]	Maint.	$a_I$	$b_I$	Min.	Max.	Min.
						[Mwh/Mcm]		[Mcm]			
Plant A		350	920	0.90	no	97.15	0.00	100	≈2,400.	yes	yes
Plant B	300	600	0.90	no	164.13	0.00	100	≈1,600.	yes	yes	
Plant C	450	800	0.90	no	163.76	0.04	100	≈2,100.	yes	yes	
Plant D	250	1,600	0.90	no	89.66	0.02	250	≈4,200.	yes	yes	

We assume uninterrupted service for maintenance or repairs of the generation groups (all monthly coefficients are equal to one). Moreover, minimum powerplant releases (discharge per month) are entered as indicated in table 8.2. Maximum releases are automatically computed by the model from the specified powerplant design discharge and maintenance schedule coefficient (by clicking the Reset button in the Maximum Releases dialog box). Maximum and minimum powerplant releases are enforced in the formulation of the problem by enabling the corresponding constraints in the Operational Constraint box.

Two separate outlet works in East Lake Dam control releases from the reservoir, one on each bank. The left-bank reservoir outlet conveys water into the run-of-river hydroelectric Plant A. Characteristics of the powerplant are in table 8.2. The right-bank outlet discharges into a canal that conveys water to the Upper Valley agricultural area. Fifty percent of the irrigation withdrawals are assumed to return to the natural channel via ground water accretion, far downstream from the dam. Minimum and maximum water



allocations for the Upper Valley zone are listed in table 8.3. However, all the operational constraints for the Upper Valley demand area (minimum, maximum, seasonal and firm water) are disabled for this exercise.

Table 8.3 Offstream and instream demand areas for the hypothetical system.

Demand Area	Monthly Demand		Return Flow Coefficient [ - ]	----- Constraints -----			
	Min. [Mcm]	Max.		Min.	Max.	Seas.	Firm
Upper Valley	0	1,000.	0.5	no	no	no	no
Mid Valley	0	2,000.	0.3	no	no	yes	no
Big City	0	1,000.	0.0	no	no	yes	yes
Native Fish	var.	4,000.		yes	no	no	no
Whitewater	var.	4,000.		no	no	no	no

The central link extending downstream from East Lake reservoir (figure 8.1, link 27), represents the natural riverbed. This portion of the river is assumed to have native fish species whose populations have declined since reservoir construction, thus becoming an environmentally sensitive area. Flow requirements were determined using a flow-habitat model as part of a fish recovery program. The recommended mean-monthly flows for the fish habitat protection area (figure 8.1, Native Fish) are 40, 40, 40, 60, 80, 120, 140, 100, 60, 40, 40, and 40 Mcm for the months of January through December, respectively. The recommended minimum releases are aimed at reestablishing some of the natural variability of the flow regime.

The West Lake reservoir regulates natural flows contributed by the West Fork subbasin. The reservoir supplies water for the run-of-river Powerplant B, located on the right-bank of the river. Characteristics of the plant are in table 8.2. The river reach downstream from West Lake but upstream of the junction with the East Fork (Jct 6) is used extensively for recreational purposes, mostly rafting and kayaking. This water use is represented in the flow network by the instream Whitewater user (figure 8.1). Operation of the commercial recreational activities is from May through September.

Regulated flows from the East and West Fork Rivers enter Mid Lake reservoir, where they are regulated again. Releases from Mid Lake Dam are used to generate power at Plant C, which is a variable-head powerplant. Characteristics of Plant C are in table 8.2. Turbine flows are returned to the river at the toe of the dam. Further downstream, water is diverted to an irrigation demand zone named the Mid Valley agricultural area. Thirty percent of the diverted water returns to the stream (table 8.3), which implies a 70% consumptive use. Maximum and minimum diversion channel capacity are indicated in table 8.3, though they are not enforced in the example. However, whatever annual volume of water the model delivers to this region must match the seasonal demand of the crops grown there, which is distributed among months January through December as follows: 0.0, 0.0, 0.0, 0.05, 0.10, 0.15, 0.25, 0.25, 0.15, 0.05, 0.0, 0.0.

Controlled releases from Mid Lake (minus Mid Valley consumptive use) and inflows from the Lower Fork tributary enter Lower Lake. There are two controlled releases from Lower Lake Dam: into Plant D, which is a variable-head powerplant (table 8.2), and into a canal that conveys water to a municipal and industrial demand area named Big City. Big City is a transbasin diversion from which no return flows are possible, as evidenced by the lack of a return link. Big City has a firm contract for 7,000 Mcm per year, which implies that at least that amount of water should be delivered every year. Moreover, the water to be delivered must match the following seasonal distribution (from January through December): 0.07, 0.07, 0.075, 0.08, 0.09, 0.10, 0.10, 0.10, 0.09, 0.08, 0.075 0.07.

Figure 8.1 shows the names of the system components as entered by the user, and the numbers assigned automatically by the model to links and nodes (shown only for junctions and diversions). The model may randomly change the numbering of links and nodes every time the connectivity of the network is checked. A change in the numbering of nodes and links implies a possible change in the mathematical arrangement of the system components when the optimization problem is formulated (Chapter 6, Mathematical Connectivity of System Components). Slightly different optimal solutions should be expected from different mathematical network arrangements due to limitations of numerical precision. Also, as mentioned in Chapter 7, changes in the prescribed maximum number of iterations per QP sequence and the value of the accuracy parameters may also cause slight changes in the final optimal solution.

Once network connectivity is updated (indicated by *...connectivity checked*) at the top of figure 8.1), eight links turn from blue to red. Red links indicate the location in the network where decision variables are created by the model to solve the water allocation problem. Similarly, red lines framing eight water users indicate that they economically compete for water.

## Defining Demand Functions

The demand functions used in this example reflect the general structure of prices in Chapter 4, Benefit Functions. Monthly prices for energy are assumed equal for all months and for all power facilities. This is a reasonable assumption considering that all powerplants sell their energy to the same electrical grid system. Furthermore, downward sloping demand curves, equation (4.3), reflect the difference in energy prices from on-peak to off-peak hours; the rate of decay is constant for all months. Table 8.4 has information on hydropower economics.

The only instream user economically competing for water is the water-based recreation area Whitewater. This highly seasonal activity, running from May through September, is represented by linear demand functions, equation (4.25). The seasonality can be inferred from the values of the coefficients of the price functions in table 8.5, which shows values different from zero only for May through September.

Price functions are seasonal for the Upper Valley irrigation area (growing seasons from April through October) and seasonality for Mid Valley. The coefficients of the exponential decreasing price functions, equation (4.15), are shown in table 8.5. Prices are equal to zero for the nonirrigation months. For the transbasin urban demand zone, Big City, prices also decay exponentially with quantity supplied, equation (4.20), although, in contrast to the agricultural zone, municipalities and industries consume water all year around. This is indicated in table 8.5 by the nonzero values of demand function coefficients for all months of the year.

Table 8.4 Information on hydropower economics.

Hydroplant	Avg. Energy Price		Price Function	
	$P$	$P_s$	$a_2$	$b_2$
	[\$/MWh]		[\$/MWh]	
Plant A	30.	30.	46.75	1,712.
Plant B	30.	30.	46.75	2,085.
Plant C	30.	30.	46.75	2,917.
Plant D		30.	30.	46.75
		800.		

Table 8.5 Economic information on instream and offshore demand areas.

Month	Whitewater		Upper Valley		Mid Valley		Big City	
	$a_5$	$b_5$	$a_3$	$b_3$	$a_3$	$b_3$	$a_4$	$b_4$
	[\$/Mcm]		[\$/Mcm]		[\$/Mcm]		[\$/Mcm]	
Jan	0.	0.	0.	0.	0.	0.	38,700.	78.
Feb	0.	0.	0.	0.	0.	0.	49,800.	92.
Mar	0.	0.	0.	0.	0.	0.	65,200.	118.
Apr	0.	0.	40,000.	662.	16,000.	485.	71,200.	134.
May	2000.	2.0	40,000.	749.	16,000.	485.	76,000.	145.
Jun	2000.	2.0	40,000.	814.	16,000.	485.	79,600.	155.
Jul	2000.	2.0	40,000.	857.	16,000.	485.	85,000.	164.
Aug	2000.	2.0	40,000.	890.	16,000.	485.	83,100.	160.
Sep	2000.	2.0	40,000.	749.	16,000.	485.	73,400.	141.
Oct	0.	0.	40,000.	543.	16,000.	485.	67,800.	115.
Nov	0.	0.	0.	0.	0.	0.	56,700.	88.
Dec	0.	0.	0.	0.	0.	0.	41,500.	71.

Note: parameters  $b$  cannot assumed the value zero, hence enter a small number (e.g.,  $b=1$ )

## Finding an Efficient Water Allocation

This section describes the water allocation for the hypothetical river basin in figure 8.1 given the water prices and operational constraints described earlier. The problem was solved over a two-year period using monthly time intervals. The optimization horizon was also set equal to 24 months, making the quasi-continuous optimization procedure unnecessary. Because only a small number of operational constraints was specified for the network, the model finds a water allocation based mostly on the water value. After this baseline case is solved, conditions are modified for different portions of the network to illustrate specific model capabilities.

## Initial Feasible Solution

The flow cascading algorithm (Chapter 5) provides the initial feasible solution (IFS) for this problem. The approach consists of simply cascading flows through the reservoirs, avoiding storage regulation when possible, and assigning water to instream and offstream users provided that reservoirs' and water users' operational constraints are not violated. The analyst can force the model to stop immediately after finding an IFS by entering “0” (zero) *Number of Sequences* in the corresponding dialog box (see figure 7.7). Figure 8.2 displays some selected graphical outputs, created by the model, that illustrate the state of the river-reservoir system after the IFS was found.

The storage trajectories for the reservoirs indicate constant reservoir levels for two of the four reservoirs. Figure 8.2 shows monthly releases from East Lake Dam to Plant A, Rare Fish and Upper Valley. The IFS algorithm satisfies minimum required flows at the Native Fish river reach and then arbitrarily chooses any competing water user (Plant A in this example) to which to allocate the remaining flows. For months in which the powerplant capacity was exceeded (months 5, 6, and 16), the extra reservoir inflows were directed toward the Upper Valley irrigation area. Reservoir evaporation is also satisfied. Release conditions from Mid Lake are different from those at East Lake in that a single user (Plant C) is directly linked to the reservoir. Because the maximum capacity of the powerplant is at times exceeded, the reservoir is forced to regulate its inflows to avoid spillages.

When encountering offstream demand areas that claim water directly from the natural channel, rather than from a storage reservoir as Upper Valley does, and when no minimum flows are enforced, the IFS algorithm maintains water in the river rather than diverting it. Figure 8.2 shows no water allocated to Mid Valley agricultural zone. Note that zero flows is a feasible solution when seasonality is required.

The value of the total benefits from this arbitrary pattern of water allocation over two years of operation was calculated by the model as \$1,103.529 million. Although this initial solution is feasible, it is far from being an efficient allocation of water, as demonstrated next. The set of parameters chosen to control the optimization sequential process and the accuracy of the computations for this example network coincide with those shown in figure 7.7. The water allocation problem is solved using the “implicit” approach for modeling reservoir evaporation.




Figure 8.2 Selected graphical outputs from the initial feasible solution.

## Final Solution

A crucial element during the allocation process is the monotonic decrease in the marginal price of allocated water with the increasing availability of flows. Reservoirs are also important components during the allocation of water in the basin because flow regulation allows for releases that efficiently satisfy instream and offstream demands. Figure 8.3 shows the high contrast between the uncontrolled inflows and the controlled outflows from the West Lake reservoir.




Figure 8.3 Uncontrolled inflows and controlled outflows from West Lake.

Figure 8.4 shows selected graphs of the result of the optimization. The two headwater reservoirs absorb most of the variability of the natural inflows, creating favorable conditions for the rest of the basin to generate hydropower and distribute water during the seasons in which it is needed. Water levels in East and West Lake reservoirs oscillate from empty to full to avoid spilling the large volumes of inflow associated with snowmelt. Because Plants A and B are run-of-river plants (i.e., their energy generation is not a function of reservoir storage levels), they impose no limitations in the oscillation of the water levels in the two headwater reservoirs. Contrarily, at Mid Lake Dam, with a variable-head powerplant, almost constant and maximum water levels are maintained during the whole optimization horizon to maximize hydropower production. High reservoir levels are also maintained at Lower Lake, which besides receiving the regulated inflows from the upstream portion of the basin, also captures uncontrolled inflows from Lower Fork Basin, forcing an appreciable degree of regulation at the reservoir.




Figure 8.4 Selected graphical outputs from the final optimization solution.

Releases from East Lake are shown in figure 8.4 (upper-right graph, stacked bars). Water diversions into the Upper Valley irrigation area (middle bars) display the classical seasonality of irrigation demand, in this case controlled exclusively by the monthly price functions, since no seasonality constraint was enforced for Upper Valley. Water is diverted during the growing season, with zero flows during months outside the irrigation season (zero economic benefits for those months, see table 8.5). Optimal releases for Plant A satisfy on-peak energy demand throughout the entire optimization horizon, assigning extra releases (to generate lower value energy) only during the first few months of every year. Link 27, the river reach where the fish protection area was established, received no more flows than the ones enforced by the user via the minimum flow constraint. This is expected since the optimization algorithm gives preference for releases to users generating revenue, and Native Fish has no economic benefits attached to it.

Releases from West Lake, after passing through Plant B, become instream flows in the West Fork River where the Whitewater recreation area is located. As indicated in figure 8.4, the model releases relatively larger flows from West Dam during periods 5 through 8 and 17 through 20, the months of economically valuable rafting and kayaking use.

Optimal diversion for irrigation at Mid Valley also display the classical seasonal pattern, but this time they are due to the enforcement of the seasonal pattern constraint (the price functions are all equal). The volumes of water allocated each irrigation season are very similar but not identical, with 30 percent of the diverted flow returning to the stream during the same month in which is diverted ( $r=0.3$ ).

Optimal releases from Lower Lake are displayed by the stacked bar diagram in the lower right-graph of figure 8.4. The lower bars correspond to water supplied to the Big City M&I demand area; the upper bars represent water released for hydropower to Plant D. Optimal flows allocated to Big City follow the seasonal pattern indicated on page 137. Releases to Plant D tend to follow the storage fluctuations in the reservoir, being small as the reservoir builds up storage and largest during those months with the highest water levels at the reservoir.

Evaporation losses represent, on average, a relatively small amount of water when compared to the total inflows to the reservoirs, 2.3% for headwater reservoirs and 3.8% for Lower Lake, but with important monthly variations. Evaporation losses do not influence the storage patterns significantly, thus justifying using the implicit model for reservoir evaporation. Moreover, reservoir spills do not occur for the period of record analyzed in this exercise.

As illustrated in figure 5.1, the optimization algorithm SQP searches for the optimal allocation of water by successively solving quadratic programming problems. Figure 8.5 shows the evolution of the value of the global objective function as it progresses toward the optimal solution for this example. There is a substantial improvement in the water allocation during the first few sequences, accompanied by a drastic increase in revenues, followed by a relatively flat portion of the revenue curve where only small changes occur during the remaining sequences. The search

for the optimum stops when:  
 a) the maximum number of sequences is reached (40 in this example); b) the change of global return between two consecutive QP sequences becomes less than \$1000 (see figure 7.7); or c) the solution runs into some infeasibilities (detected by the third accuracy parameter in figure 7.7). In this example network, the second termination criterion stopped the calculations at sequence 29. At this point, revenues for the two-year period computed by the model totaled \$1,649.414 million.





Figure 8.5 Evolution of the global objective function.

If the third criterion stops the optimization, a warning message alerts the user to either keep the solution obtained that far, or consider increasing the constraint infeasibility accuracy parameter and resume the optimization process. This situation may happen only when the implicit approach for modeling reservoir evaporation is adopted.



## Changes in Offstream Water Demand

We now introduce a change in the demand of water from an offstream zone to demonstrate how the new problem can be solved with minimum computational effort, and discuss the implications of the change. The allocation of water to the Upper Valley irrigation area for the baseline case relied exclusively on the demand curves specified for each time period. Note that the optimal allocation displays a seasonal variability consistent with the monthly demand functions in table 8.5 (see figure 8.4). We now assume that flows are also required for the nonirrigation month January at Upper Valley. The new use will be incorporated into the model by altering the economic conditions in the network rather than by imposing a minimum flow level constraint. For the baseline case the demand function had null parameters for January (table 8.5); now they are set equal to those for July ( $a_3=40,000$  and  $b_3=857$ ). The user can solve the new water allocation problem by altering the marginal price of water at Upper Valley for January, validating the network connectivity, and solving the optimization problem to find the efficient water allocation policies under the new economic condition.



However, because changes in the price structure do not invalidate feasibility in the network, the user can proceed from the last optimal solution, in this case the baseline solution, to the new optimal condition. Changes in marginal prices can be introduced any time during the execution of the optimization or at the end of the sequences. If the change is introduced as the application is executing, the graphical outputs will indicate how the model immediately starts redirecting the allocation of water to accommodate the new economic conditions. If the change is introduced after AQUARIUS has reached an optimum, the model will adopt the last optimal solution as the IFS for the new round of optimization. For a minor change in price, the model will find the new optimum very quickly. Figure 8.6 shows the results of the above outlined procedure. The water allocation at Upper Valley shows positive flows for January (note that months 1, 2, 3, 11 and 12 have zero flow allocation in the baseline solution, figure 8.4). The allocation of flows to Upper Valley during January reflects the willingness of the irrigation area to compensate other users for the extra water demanded for that month. In other words, a new potential Pareto optimal arrangement was found.




Figure 8.6 Change in offstream water demand.

As an additional example of a change in offstream water demand, consider an improvement in irrigation efficiency, a change that can be characterized in terms of physical rather than economic factors. Either by structural measures or conservation practices, the water duty for irrigation often can be decreased. Although this may imply several modifications to the original baseline case, we will simply increase the amount of return flow that originates from the Upper Valley irrigation area from 0.5 to 0.7. This has practically the same effect on the network of reducing the water duty, since more water will be left in the river for use by other system components downstream.

After solving the network with the new Upper Valley return flow (note that when a physical variable is changed a completely new run is required), the benefit from the network operation increases from \$1,649.414 million to \$1,700.151 million, a \$50.7 million (3.1%) change over the two-year period. Additional information can be extracted to identify the downstream water uses who benefit from this improved economic condition. The increase in benefit provides economic incentive for negotiations among the multiple users in the basin to finance the structural improvements necessary to conserve water in the basin.

## Change in Energy Price

Although unit revenues for hydroenergy are variable according to the type of energy being generated, on-peak vs. off-peak (figure 4.2), some power systems are compensated economically for the energy generated using a single rate, regardless of the time of the day in which the energy is delivered. The purpose of this exercise is to demonstrate how this case can be modeled by AQUARIUS and to show the operational consequences of such an assumption.

Within the AQUARIUS formulation, adopting a constant unit price for energy is equivalent to replacing the exponential curve in equation (4.3) by the single step function (i.e., a constant value for all plant utilization factors) in equation (4.31). Then, the value assigned to the parameter  $a_2$  will represent the constant rate paid for hydroenergy. A constant price specified by  $a_2=15$  \$/Mwh was adopted for one of the powerplants, Plant D, while maintaining the rest of the hypothetical system at levels of the baseline case described above. The system operation was reoptimized under these new conditions. The values of the old and new powerplant releases from Plant D are shown in figure 8.7.




Figure 8.7 Hydropower releases with decreasing and constant energy price.

The model for the exponential price function (left graph) shows power releases covering the on-peak volumes for all time steps (since on-peak releases have a higher price) plus releases during off-peak periods. When interpreting the series of releases from Plant D, remember that the upper portion of the basin is holding most of its inflows during the first months to build up storage in the reservoirs. In contrast, when the energy price function for Plant D is a constant (figure 8.7, right graph), the powerplant is not compelled to satisfy on-peak releases as before. Although power releases occur in a more random pattern, they contribute more to total system revenue, which depends as well on other reservoir functions that encourage gains in storage whenever possible to maximize the amount of energy generated with the same amount of water and to satisfy the demand from Big City). Of course, this series of power releases would be unacceptable in a real system where, typically, minimum power releases would be imposed to ensure that a minimum amount of energy is generated each month (imposing such minimums is also a viable option using AQUARIUS).

## Economic Efficiency for a Simple Case

In this exercise, we use a simple flow network to illustrate the basic concept of economic efficiency used in the model to drive the allocation of water in a river basin. This network consists of a single reservoir with two offshore demand areas, The Farm and The City, which withdraw water directly from the reservoir (figure 8.8, upper-left). The irrigation and urban zones have completely different demands regarding the amount and seasonal distribution of water required. The Farm receives water only during the growing season, April through October, whereas The City receives water all year. Monthly price curves were provided for the two water uses according to their seasonal demands. Furthermore, no minimum or maximum limits on releases are enforced. The only constraints are upper and lower bounds on reservoir storage, set equal to 5,000 and 2,000 Mcm, respectively, as indicated by the dashed lines in the upper right graph of figure 8.8.




Figure 8.8 Conditions of economic efficiency in water allocation.

Figure 8.8 shows the most significant outputs from the optimal solution: the reservoir storage trajectory, the optimal releases, and the marginal prices of water for the two uses computed at the point of optimality. As stated in Chapter 2, the model will allocate releases at a constant marginal price, provided that an unbounded solution to the water allocation problem is obtained.

Figure 8.8 shows that the model reached the optimum when marginal prices were equalized for the two demands (compare the two marginal price bar graphs). Once the optimal solution has been reached, the value of water for each user, at the margin, is the same. This is not to say that the optimally allocated flows are equal for the two users. In fact, one can observe that the two users receive very different amounts of releases.

Under optimal conditions, the model keeps the marginal prices constant in time provided that the solution of the problem is unbounded. Figure 8.8 shows that once the storage in the reservoir reaches the upper or lower bound, the solution becomes bounded (i.e., it is no longer an interior solution) and the marginal price changes. The solution of the reservoir problem is interior from time period 1 through 6; thus, the marginal prices remain constant during those 6 months. Similar behavior can be observed for other periods with interior solutions (e.g., 7-10, 12-17, 19-24). This demonstrates, as discussed in Chapter 2, that the marginal benefit of the release remains constant in time if the allocation is optimal.

## Software Performance

The time of execution of an application depends on many factors. Among them are: the size of the flow network (the number of decision sets); the topology of the network (the type of water uses and how they interconnect); the number and type of operational constraints (whether the problem is mostly constrained or unconstrained); the formulation selected for calculating reservoir evaporation (implicit or explicit); the length of the period of study (including the period of analysis, the optimization horizon and the overlapping period); the value of the parameters controlling the QP sequential process (maximum number of QP sequences allowed and number of iterations per sequence); the value of the parameters controlling accuracy (for general calculations and for checking the feasibility of the solution); and the value of the parameters controlling when to stop the optimization (minimum allowed change between consecutive values of the objective function).

Definitively, the size of the flow network and the length of the period of analysis are the two main factors determining the execution time. For a given network, the execution time increases exponentially with the optimization horizon. For instance, the Example network is solved in 8 seconds for a 12 month optimization horizon, 57 seconds for 24 months, and 183 seconds for 36 months. The model was run in a personal computer with a 500 MHz Intel Pentium III processor (the execution times do not include graphical output display between sequences).



## Literature Cited

---

- Abdalla, C. W., B. A. Roach, and D. J. Epp. 1992. Valuing environmental quality changes using averting expenditures: an application to groundwater contamination. *Land Economics* 68(2):163-169.
- Allen, D. S., R. S. Jackson, and A. L. Perr. 1998. Alabama-Coosa-Tallapoosa and Apalachicola-Chattahoochee-Flint comprehensive study: recreation demand element. Final report to U.S. Army Corps of Engineers, Waterways Experiment Station, Vicksburg, MS.
- Andersen, J.E. Keith, and C.G. Clyde. 1973. The demand for agricultural water in Utah. Report PRWG100-4, Utah Water Research Laboratory, Utah State University, Logan.
- Ayer, H.W., and P.G. Hoyt. 1981. Crop-water production functions: economic implications for Arizona. Technical Bulletin 242, Agricultural Experiment Station, University of Arizona, Tucson.
- Arrow, K., R. Solow, P. R. Portney, E. E. Leamer, R. Radner, and H. Schuman. 1993. Report of the NOAA Panel on Contingent Valuation. *Federal Register* 58(10):4602-4614.
- Baumol, W. J. 1977. *Economic theory and operations analysis*. Prentice-Hall, Englewood Cliffs, NJ.
- Bazzara M.S., and J.J. Jarris, 1977. *Linear Programming and Network Flows*. John Willey & Sons, 565p.
- Bernardo, D.J., N.K. Whittlesey, K.E. Saxton, and D.L. Bassett. 1987. An irrigation model for management of limited water supplies. *Western Journal of Agricultural Economics* 12(2):164-173.
- Billings, R.B. 1990. Demand-based benefit-cost model of participation in water project. *Journal of Water Resources Planning and Management* 116(5):593-609.
- Bishop, R., K. Boyle, M. Welsh, R. Baumgartner, and P. Rathbun. 1987. Glen Canyon Dam releases and downstream recreation: an analysis of user preferences and economic values. Heberlein-Baumgartner Research Services, Madison, Wisconsin, 188 pp.
- Booch, G., 1994. *Object Oriented Analysis and design with Applications*. Second Edition.
- Bovee K. D., 1982. A guide to stream habitat analysis using the Instream Flow Incremental Methodology. Instream Flow Information Paper No.12. FWS/OBS-82/26. U.S. Fish and Wildlife Service, Washington DC. [14.4].
- Bowen, R.L., and R.A. Young. 1985. Financial and economic irrigation net benefit functions for Egypt's Northern Delta. *Water Resources Research* 21(9):1329-1335.
- Bower, B.T. 1966. The economics of industrial water utilization. In: *Water research*, A.V. Kneese and S.C. Smith, editors, Johns Hopkins Press, Baltimore, pp. 143-173.
- Booker, J.F., and R.A. Young. 1994. Modeling intrastate and interstate markets for Colorado River water resources. *Journal of Environmental Economics and Management* 26:66-87.
- Brown, T. C. 1993. Measuring nonuse value: a comparison of recent contingent valuation studies. In *Benefits and Costs in natural resource planning, sixth interim report, W-133*. Department of Agricultural and Applied Economics, University of Georgia, Athens, pp. 163-203.
- Brown, T. C., and J. W. Duffield. 1995. Testing part-whole valuation effects in contingent valuation of instream flow protection. *Water Resources Research* 31(9):2341-2351.
- Brown, T.C., and T.C. Daniel. 1991. Landscape aesthetics of riparian environments: relationship of flow quantity to scenic quality along a wild and scenic river. *Water Res. Research* 27(8):1787-1795.
- Brown, T.C., J.G. Taylor, and B. Shelby. 1991. Assessing the direct effects of streamflow on recreation: a literature review. *Water Resources Bulletin* 27(6):979-989.
- Cheslak, E.F., and A.S. Jacobson. 1990. Integrating the instream flow incremental methodology with a population response model. *Rivers* 1(4):264-288.

- Colby, G. B. 1990. Enhancing Instream Flow benefits in an Era of Water Marketing. *Water Resources Research* 26(6):1113-1120.
- Danielson, L.E. 1979. An analysis of residential demand for water using micro time-series data. *Water Resources Research* 15(4):763-767.
- Daubert, J. and R. Young. 1981. Recreational demands for maintaining instream flows: a contingent valuation approach. *American Journal of Agricultural Economics* 63(4):666-675.
- Díaz, G.E. and D.G. Fontane, "Hydropower Optimization via Sequential Quadratic Programming", *Journal of Water Resources Planning and Management*, ASCE, December 1989.
- Díaz, G.E., T.C. Brown, and H.J. Morel-Seytoux, 1992. The marginal economic value of streamflows: A systems approach", at Proc. 12<sup>th</sup> Annual AGU Hydrology Days at Colorado State University. Public., 57 Selby Lane, Atherton, CA 94027.
- Duffield, J.W., C.J. Neher, and T.C. Brown. 1992. Recreation benefits of instream flow: application to Montana's Big Hole and Bitterroot Rivers. *Water Resources Research* 28(9):2169-2181.
- De Rooy, J. 1974. Price responsiveness of the industrial demand for water. *Water Resources Research* 10(3):403-406.
- El-Hawary, M. E. and G. S. Christensen, 1979. Optimal Economic Operation of Electric Power Systems. Vol.142 in *Mathematics in Science and Engineering Series*. Academic Press.
- Elliott, R.D. 1973. Economic study of the effect of municipal sewer surcharges on industrial wastes and water usage. *Water Resources Research* 9(5):1121-1131
- Foster, H.S., Jr., and B.R. Beattie. 1979. Urban residential demand for water in the United States. *Land Economics* 55(1):43-58.
- Frank, M.D., and B.R. Beattie. 1979. The economic value of irrigation water in the Western United States: an application of ridge regression. Technical Report 99, Texas Water Resources Institute, Texas A&M University, College Park.
- Gibbons, D.C. 1986. The economic value of water. *Resources for the Future*, Washington, D.C.
- Gillilan, D.M., and T.C. Brown. 1997 (in press). Keeping water in streams: instream flow protection in the American West. Island Press, Washington, D.C.
- Gisser, M. 1970. Linear programming models for estimating the agricultural demand functions for imported water in the Pecos River basin. *Water Resources Research* 6(4):1025-1032.
- Gisser, M., R.R. Lansford, W.D. Gorman, B.J. Creel, and M. Evans. 1979. Water trade-off between electric energy and agriculture in the Four Corners area. *Water Res. Research* 15(3):529-538.
- Gouevsky, I.V., and D.R. Maidment. 1984. Agricultural water demands. In *Modeling water demands*, edited by J. Kindler and C.S. Russell, Academic Press, New York, pp. 101-219.
- Grebenstein, C.R., and B.C. Field. 1979. Substituting for water inputs in U.S. manufacturing. *Water Resources Research* 15(2):228-232.
- Griffin, R.C. 1990. Valuing urban water acquisitions. *Water Resources Bulletin* 26(2):219-225.
- Griffin, R.C., and C. Chang. 1990. Pretest analyses of water demand in thirty communities. *Water Resources Research* 26(10):2251-2255.
- Grima, A.P.L. 1973. The impact of policy variables on residential water demand and related investment requirements. *Water Resources Bulletin* 9(4):703-710.
- Hall W. A. and J. A. Dracup, 1970. *Water Resources Systems Engineering*. McGraw-Hill Book Company.
- Hanke, S.H., and L. de Mare. 1984. Municipal water demands. In *Modeling water demands*, edited by J. Kindler and C.S. Russell, Academic Press, London, pp. 149-169.
- Hansen, L.T., and A. Hallam. 1991. National estimates of the recreational value of streamflow. *Water Resources Research* 27(2):167-175.
- Harpman, D.A., E.W. Sparling, and T.J. Waddle. 1993. A methodology for quantifying and valuing the impacts of flow changes on a fishery. *Water Resources Research* 29(3):575-582.

- Hartman, L.M., and R.L. Anderson. 1962. Estimating the value of irrigation water from farm sales in Northeastern Colorado. *Journal of Farm Economics* 44(1):207-213.
- Heady, E.O., H.C. Madsen, K.J. Nicol, and S.H. Hargrove. 1973. National and interregional models of water demand, land use, and agricultural policies. *Water Resources Research* 9(4):777-791.
- HEC-U.S. Army Corps of Engineers, (1982). HEC-5 Simulation of Flood Control and Conservation Systems. The Hydrologic Engineering Center. Users Manual Computer Program 723-X6-L2500
- Howe, C.W. 1982. The impact of price on residential water demand: some new insights. *Water Resources Research* 18(4):713-716.
- Howitt, R.E., W.D. Watson, and R.M. Adams. 1980. A reevaluation of price elasticities for irrigation water. *Water Resources Research* 16(4):623-628.
- James L.D., and R.R. Lee, 1971. *Economics of Water Resources Planning*. McGraw-Hill, 615p.
- Johnson, N.S. and R.M. Adams. 1988. Benefits of increased streamflow: the case of the John Day River steelhead fishery. *Water Resources Research* 24(11):1839-1846.
- Jones, C.V., and J.R. Morris. 1984. Instrumental price estimates and residential water demand. *Water Resources Research* 20(2):197-202.
- Kelly, S., and H. Ayer. 1982. Water conservation alternatives for California agriculture: a microeconomic analysis. ERS Staff Report AGES820417, Natural Resource Economics Division, Economic Research Service, USDA, Washington, D.C.
- Kelso, M.W., W.E. Martin, and L.E. Mack. 1973. Water supplies and economic growth in an arid environment: an Arizona case study. University of Arizona Press, Tucson.
- Knetsch, J.L. 1964. The influence of reservoir projects on land values. *Journal of Farm Economics* 46(1):231-243.
- Kulshreshtha, S.N., and D.D. Tewari. 1991. Value of water in irrigated crop production using derived demand functions: a case study of South Saskatchewan River Irrigation District. *Water Resources Bulletin* 27(2):227-236.
- Lamb, B. L., 1995. Criteria for evaluating state instream-flow programs: deciding what works. *Journal of Water Resources Planning and Management*, May-June.
- Laufer, F. and H. J. Morel-Seytoux, 1979. Optimal weekly releases from a seasonal reservoir, I. Deterministic future. *Water Resources Research*, Vol 15, No.2, pp
- Laughland, A. S., L. M. Musser, W. N. Musser, and J. S. Shortle. 1993. The opportunity cost of time and averting expenditures for safe drinking water. *Water Resources Bulletin* 29(2):291-299.
- Leifson, T. and H. J. Morel-Seytoux, 1981. User's manual for QPTHOR: A FORTRAN quadratic programming routine. CER81-82TL-HJM37, Hydrowar Program, Colorado State University, Fort Collins, CO.
- Lyman, R.A. 1992. Peak and off-peak residential water demand. *Water Res. Research* 28(9):2159-2167.
- Lynne, G.D., W.G. Luppold, and C. Kiker. 1978. Water price responsiveness of commercial establishments. *Water Resources Bulletin* 14(3):719-729.
- Loomis, J. 1987. Balancing public trust resources of Mono Lake and Los Angeles' water right: an economic approach. *Water Resources Research* 23:1449-1456.
- Loucks D.P., J. Stedinger and D. Haith, (1981). *Water Resource Systems Planning and Analysis*. Prentice Hall, Inc. Englewood Cliffs, New Jersey 07632, 559 p
- Martin, W.E., and J.F. Thomas. 1986. Policy relevance in studies of urban residential water demand. *Water Resources Research* 22(13):1735-1741.
- Madariaga, B., and K.E. McConnell. 1984. Value of irrigation water in the Middle Atlantic states: an econometric approach. *Southern Journal of Agricultural Economics* 16(2):91-98.
- Milliman, J.W. 1959. Land values as measures of primary irrigation benefits. *Journal of Farm Economics* 41(2):234-243.



- Moore, M.R., N.R. Gollehon, and M.B. Carey. 1994. Multicrop production decisions in Western irrigated agriculture: the role of water price. *American Journal of Agricultural Economics* 76:859-874.
- Morel-Seytoux H.J., C-M Zhang and M. Flug, 1995. An Optimization Computation Technique for Management of Reservoirs for Recreation. Proc. 15<sup>th</sup> Annual AGU Hydrology Days at Colorado State University. Public., 57 Selby Lane, Atherton, CA 94027, pp.185-194.
- Narayanan, R. 1986. Evaluation of recreational benefits of instream flows. *Journal of Leisure Research* 18(2):116-128.
- Nieswiadomy, M. 1985. The demand for irrigation water in the High Plains of Texas, 1957-80. *American Journal of Agricultural Economics* 67(3):619-626.
- Nieswiadomy, M.L. 1992. Estimating urban residential water demand: effects of price structure, conservation, and education. *Water Resources Research* 28(3):609-615.
- Office of Technology Assessment. 1983. Water related technology for sustainable agriculture in U.S. arid/semiarid lands. U.S. Government Printing Office, Washington, D.C.
- Ogg, C.W., and N.R. Gollehon. 1989. Western irrigation response to pumping costs: a water demand analysis using climatic regions. *Water Resources Research* 25(5):767-773.
- Palacios Gomez, F., Lasdon, L., and Engquist, M. (1982). Nonlinear optimization by successive linear programming. *Management Science*, 28(10), 1106-1120.
- Portney, P.R. 1994. The contingent valuation debate: why economists should care. *Journal of Economic Perspectives* 8(4):, 3-17.
- Renzetti, S. 1992a. Evaluating the welfare effects of reforming municipal water prices. *Journal of Environmental Economics and Management* 22:147-163.
- Renzetti, S. 1992b. Estimating the structure of industrial water demands: the case of Canadian manufacturing. *Land Economics* 68(4):396-404.
- Renzetti, S. 1993. Examining the differences in self- and publicly supplied firms' water demands. *Land Economics* 69(2):181-188.
- Rizaiza, O.S.A. 1991. Residential water usage: a case study of the major cities of the western region of Saudi Arabia. *Water Resources Research* 27(5):667-671.
- Russell, C.S. 1970. Industrial water use. Report to the National Water Commission, section 2, Washington, D.C.
- Sanders, L.D., R.G. Walsh, and J.R. McKean. 1991. Comparable estimates of the recreational value of rivers. *Water Resources Research* 27(7):1387-1394.
- Schneider, M.L., and E.E. Whitlatch. 1991. User-specific water demand elasticities. *Journal of Water Resources Planning and Management* 117(1):52-73.
- Shelby, B., T.C. Brown, and R. Baumgartner. 1992. Effects of streamflows on river trips on the Colorado River in Grand Canyon, Arizona. *Rivers* 3(3):191-201.
- Shelby, B., T.C. Brown, and J.G. Taylor. 1992. Streamflow and recreation. USDA Forest Service General Technical Report RM-209, Rocky Mountain Forest and Range Experiment Station, Fort Collins, CO., 27 pages.
- Solley, W.B., C.F. Merk, and R.R. Pierce. 1988. Estimated water use in the United States in 1985. U.S. Geological Survey Circular 1004, Washington, D.C.
- Stalnaker, C. B., 1994. Evolution of Instream Flow Habitat Modeling. In *The Rivers Handbook*, Vol 2. p.276-286. Edited by P. Calow and G. E. Petts. Blackwell Scientific Publications.
- Stanford, J. A., 1994. Instream flows to assist the recovery of endangered fishes of the upper Colorado River Basin. USDI - National Biological Survey, Biological Report 24, July.
- Stevens, T.H., J. Miller, and C. Willis. Effect of price structure on residential water demand. *Water Resources Bulletin* 28(4):681-685.

- Taylor, R.G., and R.A. Young. 1995. Rural-to-urban water transfers: measuring direct foregone benefits of irrigation water under uncertain water supplies. *Journal of Agricultural and Resource Economics* 20(2):247-262.
- Torell, L.A., J.D. Libbin, and M.D. Miller. 1990. The market value of water in the Ogalalla Aquifer. *Land Economics* 66(3):163-175.
- Turnovsky, S.J. 1969. The demand for water: some empirical evidence on consumers response to a commodity uncertain in supply. *Water Resources Research* 5(2):350-361.
- U.S. Army Corps of Engineers, (1986). Engineering and Design - Management of water control systems. Engineer manual No. 1110-2-3600.
- U.S. Bureau of Reclamation. 1986. Depletion schedule, Colorado River simulation system (CRSS) demand input data. Denver, Colorado.
- U.S. Water Resources Council. 1983. Economic and environmental principles for water and related land resources implementation studies. U.S. Government Printing Office, Washington, D.C.
- van der Leeden, F., F.L. Troise, and D.K. Todd. 1990. The water encyclopedia. Lewis Publishers, Chelsea, Michigan.
- Vaux, H.J., Jr., and R.E. Howitt. 1984. Managing water scarcity: an evaluation of interregional transfers. *Water Resources Research* 20(7):785-792.
- Walsh, R., R. Ericson, D. Arosteguy, and M. Hansen. 1980. An empirical application of a model for estimating the recreation value of instream flow. Colorado Water Resources Research Institute, Completion Report No. 101, Colorado State University, Fort Collins, 66 pp.
- Ward, F.A. 1987. Economics of water allocation to instream uses in a fully appropriated river basin: evidence from a New Mexico wild river. *Water Resources Research* 23(3):381-392.
- Wilde, D. J. and C. S. Beightler, 1967. *Foundations of Optimization*. Prentice Hall, Englewood Cliffs, N.J First edition, 480p
- Williams, M., and B. Suh. 1986. The demand for urban water by customer class. *Applied Economics* 18(2):213-225.
- Willig, R.D. 1976. Consumer's surplus without apology. *American Economic Review* 66(4):589-597.
- Young, R.A., and S.L. Gray. 1972. Economic value of water: concepts and empirical estimates. Technical Report to the National Water Commission, NTIS number PB210356, National Technical Information Service, Springfield, Virginia.
- Young, R. A. 1996. Measuring economic benefits for water investments and policies. World Bank Technical Paper No. 338. Washington, D.C. 118 pages.
- Young, C.E., K.R. Kinsley, and W.E. Sharpe. 1983. Impact on residential water consumption of an increasing rate structure. *Water Resources Research* 19(1):81-86.

