


READ INSTRUCTIONS BEFORE USING THIS FILE



Materials List				
Item	Quantity	Description	Part #	Supplier
1	1	20' (L) x 8' (W) x 8'-6" (H) ISO Shipping container		*Martin Container-container.com
2		Partition Wall-4 x 8-1/4" plywood (see sheet 2 for complete list)		Local hardware store
3-6	4	100 gallon "Poly Processing poly tank	44000115	*Core-Rosion Products
7	1	1 1/2" ABS pipe fittings.		Local hardware store
8	4	1 1/2" Valterra valve		*valterra.com
9	1	Anti-siphon valve		Local hardware store
10	1	1.5 HP *Dayton Centrifugal pump	2ZWU6	*grainer.com
11	1	*Ruwac main vacuum- ATV wash Down System SO#8094	#USFORESTSERVICE	*ruwac.com
12	1	Diaphragm pump (Primary Pump)	4300-043A	*pumpbiz.com
13	1	1" flex hose		Local hardware store
14	2	50 micron filters and housing	X100B	*sifilters.com
15	1	2" Valterra gate valve		*valterra.com
16	1	Flex coupling		Local hardware store
17	1	Centrifugal-Action Separators	ILB	*Lakos.com
18	1	High pressure pump-Hand carry pressure washer kit	1500A	*Ultimatewasher.com
19		High pressure hose included with pump kit (see #18)		
20	1	30 gallon drum with pump see detail 1 sheet 12		ruwac.com
21		Discharge outlet (see notes)		
22	1	1 1/2" diam. stainless steel elbow, see sheet 13.		Local hardware store
23	1	1 1/2" diam. Sch. 80 PVC pipe		Local hardware store

Note: * Or approved equal.

Notes: (1)

- 20 foot ISO shipping container L-20', W-8', H-8'-6".
- Partition wall. Plywood paneling on all interior walls in wash bay.
- 100 gallon fresh water tank on 24" support rings. Water tank pumps located beneath tank stand. (See sheet 8) Tank #1
- 100 gallon fresh water tank on 24" support rings. Water tank pumps located beneath tank stand. (See sheet 8) Tank #2.
- 100 gallon water settling tank on 24" support rings. Water tank pumps located beneath tank stand. (See sheet 8) Tank #3.
- 100 gallon water tank (sump flushing) on 24" support rings. Tank pumps located beneath tank stand. (See sheet 8) Tank #4.
- 1 1/2" ABS pipe fittings.
- Discharge valve, typ.
- Anti-siphon valve.
- 1 1/2 hp stainless steel flush pump.
- Ruwac main vacuum
- Primary pump.
- 1" flex hose.
- 50 micron filter.
- 2" Valterra gate valve.
- Flex coupling.
- Centrifugal-Action Separator
- High pressure pump.
- High pressure hose.
- 30 gallon drum with pump see detail 1 sheet 12.
- Winterizing discharge outlet.
- Sump return 1 1/2" diam. pipe see sheet 13.
- Flush water pipe, 1 1/2" Sch. 80 PVC

NOT TO SCALE