Notes: 1

- 1. Gate valve, 1 1/2" size typ.
 2. 100 gallon polypropylene water tank.
 3. Jim Buoy life preserver Install see detail 2-sheet 8.
 4. PVC pipe schedule 40, 1 1/2", typ.
 5. Flexible PVC coupling, Install with stainless clamps per manufacturer
- specs. typ. 6. PVC Tee, 1 1/2" typ.
- 7. Vinyl 90N Ell, 1/2" barbed type, typ.
 8. Check valve, 1/2" brass swing type line size, install typ.
- Female coupling, typ.
 Vinyl tubing-,1/2" typ.

- 11. Support rod, typ.12. Float switch- tanks 2-4 N.O., Locate FS2, FS3 & FS4 to close when tank water level $\,$ is 30" from top of tank. Attach to support rod (11) with zip ties. Locate FS1 to open when water level is 2" below top of tank 4.
- Transfer pump, typ. Locate at center of tank
 Bulkhead fitting, 1 1/2" female thread typ.
 Half-nipple, 1 1/2" x3" galvanized, typ.
 Barbed PVC fitting, 1/2".
 PVC tubing schedule 40, 1/2" diam. x 4' L

- 18. Brass nipple 1/2*x6" L


 19. Bulkhead fitting, 1/2" female threaded.


 20. PVC Cap threaded connect to male adapter.

 21. PVC male threaded adapter,1 1/2"

Note: Use 1/2" barbed nylon fittings & 1/2" vinyl tubing between tanks.

Materials List				
Item	Quantity	Description	Part #	Supplier
1	6	1 1/2" gate valve		*Valterra
2	4	100 gallon Polypropylene vertical tank.	44000115	*Core-Rosion Products
3	4	*Jim Bouy life preserver, 24" diam.	JBW-24	*jimbuoy.com
4		PVC schedule 40 pipe, 1 1/2" diam.		Local hardware store
5	6	Flexible PVC coupling with stainless steel clamps, line size		*Ferenco.com
6	4	PVC Tee-1 1/2"		Local hardware store
7	6	Vinyl 90N Ell, 1/2" barbed type		Local hardware store
8	3	Check valve-1/2" brass swing type		Local hardware store
9	4	Female coupling-1/2" SCH 40 PVC		Local hardware store
10		Vinyl tubing 1/2"		Local hardware store
11	4	Support rod-1/2" SCH 40 PVC pipe (tanks 1-3=3" L, tank 4=1'L)		Local hardware store
12	4	Float switch- tanks 1-3 N.O., tank 4 N.C.		manufacturer?
13	3	Transfer pump-Little Giant	2E-38N-WG	*Blowerwheel.com
14	6	Bulkhead fittings 1 1/2" female thread	TF5	Aquatic Eco
15	4	Half-nipple-1 1/2" x 3" galvanized		Local hardware store
16	1	Barb to thread PVC fitting, 1/2"		Local hardware store
17		PVC tubing 40, 1/2" diam.x @ 4' L		Local hardware store
18	1	Nipple-1/2" x 6" brass		Local hardware store
19	1	Bulkhead fittings 1/2" female thread	TF1	*Aquatic Eco
20	1	PVC threaded cap, 1 1/2"		Local hardware store
21	1	PVC male threaded adapter, 1 1/2"		Local hardware store
		Note: * Or approved equal.		





Elevation Tanks 1,2,3,4

Elevation

NOT TO SCALE

U.S. DEPARTMENT OF AGRICULTURE FOREST SERVICE **RECREATION FACILITIES DESIGN CATALOG**

DRAWING NAME

ATV WASHER

TANK LAYOUT

BUILT ENVIRONMENT IMAGE GUIDE PROVINCE(S) (BEIG)

▼ SEMI-PRIMITIVE NON-MOTORIZED

□ NORTHEAST ☐ SOUTHEAST COASTAL

☐ GREAT PLAINS □ NORTH PACIFIC ☐ SOUTHEAST MOUNTAIN ☐ ROCKY MOUNTAIN ☐ SOUTHWEST

SHEET

11 of 14

RECREATION OPPORTUNITY SPECTRUM (ROS) **X** PRIMITIVE