

USDA Forest Service

4/5/10

LONG-TERM RETARDANT

Qualified by USDA Forest Service In Accordance with Forest Service Specification 5100-304b, As Amended

These products are evaluated and qualified only at the specified mix ratio and only for use with the indicated application Consult individual agencies for specific policies relating to long-term retardant use.

<u>Chemical</u>	Mix Ratio (Pounds concentrate Per gallon water)	Qualified Applications ¹				
		Fixed-Wing Airtanker	SEATS	Helicopter		Ground
				Fixed-Tank	Bucket	Engine
Dry Concentrate - Gum-thickened	d; Permanent or Temporary Ba	se				
Phos-Chek D75-R	1.20 lb/gal	•	•		•	
Phos-Chek D75-F	1.20 lb/gal	•	•		•	
Phos-Chek P100-F	1.0 lb/gal	0	0		0	
Dry Concentrate - Gum-thickened	d; Temporary Base					
Phos-Chek 259-F	1.14 – 1.60 lb/gal	•	•	•	•	•
Phos-Chek G75-F	1.12 lb/gal	•	•		•	•
Phos-Chek G75-W	1.12 lb/gal				•	•
Wet Concentrate - Gum-thickene	d; Permanent or Temporary Ba	se				
Phos-Chek LC-95A-R	5.5:1	•	•		•	•
	complies with all requirements of a l (Product complies with all require	· · · ·	n for laboratory eval	uation; a field evaluation	is required for full	qualification).