

United States Department of Agriculture Forest Service



Technology & Development Program

December 2008

2300/5100

0823-2347P-MTDC

Improving the Pulaski Sheath

Mary Ann Davies, Project Leader, and John Smith, Equipment Specialist

he existing Pulaski sheath has two plastic covers, one for the ax and one for the hoe. The covers are pulled tight onto the toolheads with a plastic strap and slotted buckle (figure 1). Since the 1980s, the orange plastic Pulaski sheath has been used by trail maintenance and firefighting employees. In the late 1990s, rivets were added to the sheath for safety, tightening the covers on the ax and hoe heads.



Figure 1—The existing Pulaski sheath has been used by trail maintenance and firefighting employees since the 1980s. The strap (inset) tends to slip through the buckle, allowing the toolhead covers to fall off.

• The orange plastic Pulaski sheath tends to loosen, allowing the covers to fall off the sharp ax and hoe toolheads.

 A section of the plastic strap can be replaced with 1-inch-wide nylon webbing with a double bar metal buckle that will keep the covers tight on the toolheads.

The Problem

The strap tends to slip through the buckle, allowing the covers to loosen or fall off the toolheads. The Missoula Technology and Development Center (MTDC) was asked to retrofit the strap to keep the plastic covers on the toolheads.

The Solution

A section of the plastic strap and the old buckle can be cut off and replaced with 1-inch-wide nylon webbing with a metal buckle.

Cut the existing strap and buckle from the toolhead covers, leaving about 2 inches of plastic on each end.

Either:

- A. Use a 1-inch slot punch to create a slot in each side of the toolhead covers. Thread the webbing through each slot and sew a double bar metal buckle to one end of the webbing (figure 2).
- B. Sew 1-inch-wide webbing to the ends of the plastic strap using six to eight stitches per inch of heavy duty nylon thread (figure 3). Sew a metal buckle to one end of the webbing.
- C. Rivet 1-inch-wide webbing to the remaining 2 inches of the plastic strap using 1/8-inch blind rivets (figure 4).Sew a metal buckle to one end of the webbing.

Table 1 lists parts and suppliers.




Figure 2—The plastic Pulaski sheath's strap can be improved by replacing the plastic strap and buckle with 1-inch-wide nylon webbing and a double bar metal buckle. This design shows the webbing looped through a slot (inset) made into one side of each toolhead cover.

Table 1—Parts and suppliers for the improved strap for the Pulaski sheath.

A, B, C	1-inch x 0.045-inch	http://www.LOWYUSA.com
	nylon webbing MIL-	Phone: 310-763-1111
	W-17337 or commercial	Style No. WBN6/100
	equivalent	backpack webbing
A, B, C	1-inch double-bar metal	http://www.LOWYUSA.com
	buckle	TBC 3739-Tabler buckle with
		lip under tongue
С	1/8-inch diameter blind	McMaster-Carr
	rivet	Part No. 97447A020
С	1/8-inch round hole	McMaster-Carr
	washer	Part No. 90183A212



Figure 3—Sew 1-inch-wide webbing to the plastic strap, using six to eight stitches (inset) of heavy duty nylon thread per inch. The stitches in the larger photo were digitally enhanced so they could be seen clearly.



Figure 4—Rivet (inset) the 1-inch-wide webbing to the plastic strap.

Conclusions

Replacing the plastic strap and slotted buckle on the existing Pulaski sheath with 1-inch-wide webbing and a metal buckle keeps the covers tight on the sharp ax and hoe toolheads. The webbing strap keeps the toolhead covers together, preventing them from becoming separated or lost. This low-cost improvement allows existing covers to be used safely.



Acknowledgments

Thanks to Bill Goslin, Stevensville Ranger District of the Bitterroot National Forest, for submitting this project proposal. Goslin and his trail crew field tested various prototypes, providing comments and improvements until we found a simple, easy fix.

About the Authors

Mary Ann Davies is a project leader at the Forest Service's Missoula Technology and Development Center (MTDC). She received a bachelor's degree in mechanical engineering with a minor in industrial and management engineering from Montana State University. She worked in the Forest Service's Pacific Northwest Region with facilities, tramways, recreation, and fire. Before coming to MTDC in 1998, she worked 5 years with the Rocky Mountain Research Station's fire chemistry and the fire behavior groups in Missoula, MT. Davies works on projects in the nurseries, fire, and recreation programs and in the watershed, soil, and air program.

John Smith joined MTDC in 2005 as an equipment specialist. He graduated from the University of Montana with a bachelor's degree in education and taught elementary school in Ovando, MT. He began his Forest Service career in 1974 as a wildland firefighter working for the Superior District of the Lolo National Forest. A Missoula smokejumper for more than two decades, Smith's experience as assistant loadmaster foreman, master parachute rigger, and safety program manager is applied to fire equipment development.

Library Card

Davies, Mary Ann; Smith, John. 2008. Improving the Pulaski Sheath. Tech Tip 0823-2347P-MTDC. Missoula, MT: U.S. Department of Agriculture Forest Service, Missoula Technology and Development Center. 4 p.

Covers on the orange plastic Pulaski sheath protect users from the sharp ax and hoe toolheads. The strap on the sheath tends to slip through the buckle, allowing the covers to loosen or fall off the toolheads. A section of the plastic strap and the buckle can be cut from the sheath and replaced by 1-inch-wide nylon webbing and a metal buckle that will keep the covers tight on the toolheads.

Keywords: equipment development, fire fighting, firefighting, handtools, retrofits, safety at work, tools



Mary Ann Davies or John Smith at MTDC:

Missoula Technology and Development Center 5785 Hwy. 10 West

Missoula, MT 59808-9361

Fax: 406-329-3719

Mary Ann Davies Phone: 406-329-3981 E-mail: mdavies@fs.fed.us

John Smith

Phone: 406-829-6793 E-mail: jrsmith01@fs.fed.us

the Internet at:

http://www.fs.fed.us/eng/t-d.php

Forest Service and Bureau of Land Management employees can search a more complete collection of MTDC's documents, CDs, DVDs, and videos on their internal computer networks at:

http://fsweb.mtdc.wo.fs.fed.us/search/

The Forest Service, United States Department of Agriculture (USDA), has developed this information for the guidance of its employees, its contractors, and its cooperating Federal and State agencies, and is not responsible for the interpretation or use of this information by anyone except its own employees. The use of trade, firm, or corporation names in this document is for the information and convenience of the reader, and does not constitute an endorsement by the Department of any product or service to the exclusion of others that may be suitable.